

FCC TEST REPORT
for
Square Connect, Inc.

SQ Home Controller
Model No.: SQB003-C-US

Prepared for : Square Connect, Inc.
Address : 46 S 12th St., San Jose, CA 95112, USA

Prepared By : Anbotek Compliance Laboratory Limited
Address : 1/F, 1 /Building, SEC Industrial Park, No. 4 Qianhai Road,
Nanshan District, Shenzhen, 518054, China
Tel: (86) 755-26014771
Fax: (86) 755-26014772

Report Number : 201202772F
Date of Test : Feb. 23~29, 2012
Date of Report : Feb. 29, 2012

TABLE OF CONTENT

Description	Page
Test Report	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty.....	5
2. MEASURING DEVICE AND TEST EQUIPMENT.....	6
3. TEST PROCEDURE	7
4. CONDUCTED LIMITS	8
4.1. Block Diagram of Test Setup	8
4.2. Power Line Conducted Emission Measurement Limits (15.207).....	8
4.3. Configuration of EUT on Measurement	8
4.4. Operating Condition of EUT	8
4.5. Test Procedure	9
4.6. Power Line Conducted Emission Measurement Results	9
5. RADIATION INTERFERENCE.....	12
5.1. Requirements (15.249, 15.209):	12
5.2 Test Procedure	12
5.3 Test Results.....	12
6. OCCUPIED BANDWIDTH.....	15
6.1. Requirements (15.249):	15
6.2 Test Results.....	15
7. PHOTOGRAPH.....	18
7.1. Photo of Power Line Conducted Emission Measurement	18
7.2. Photo of Radiation Emission Test	18
 Appendix I (2 Pages)	
Appendix II (2 Pages)	

TEST REPORT

Applicant : Square Connect, Inc.
 Manufacturer : Square Connect, Inc.
 EUT : SQ Home Controller
 Model No. : SQB003-C-US
 Serial No. : N/A
 Rating : DC 5V, 1A
 Trade Mark : N/A

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.207, 15.209&15.249

The device described above is tested by Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Anbotek Compliance Laboratory Limited

Date of Test :

Feb. 23~29, 2012

Andy chen

Prepared by :

(Tested Engineer / Andy Chen)

Jerry Du

Reviewer :

(Project Manager / Jerry Du)

Henry. Yang.

Approved & Authorized Signer :

(Manager / Henry Yang)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : SQ Home Controller

Model Number : SQB003-C-US

Test Power Supply : 120V~, 60Hz for Adapter

Adapter : Power Supply
Model: SAW-0502000
Input: 100-240V~, 50-60Hz, 0.5A
Output: 5V $\overline{---}$, 2000mA

RF Transmission Frequency : 908.40MHz-908.42MHz

Channels : 2

Antenna Type : RPSMA-J Port
(It is a unique coupling to the interntional radiator, which considered sufficient to comply with the provisions of 15.203)

Antenna Gain : 2dBi

Applicant : Square Connect, Inc.
Address : 46 S 12th St., San Jose, CA 95112, USA

Manufacturer : Square Connect, Inc.
Address : 46 S 12th St., San Jose, CA 95112, USA

Date of receiver : Feb. 16, 2012
Date of Test : Feb. 16~28, 2012

1.2. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503

Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 752021

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, August 20, 2010.

IC-Registration No.: 8058A-1

Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, August 30, 2010.

Test Location

All Emissions tests were performed at
Anbotek Compliance Laboratory Limited. at 1/F, 1 /Building, SEC Industrial Park,
No. 4 Qianhai Road, Nanshan District, Shenzhen, 518054, China

1.3. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB

Conduction Uncertainty : Uc = 3.4dB

2. MEASURING DEVICE AND TEST EQUIPMENT

The following test equipments were used during test:

Equipment	Manufacturer	Model #	Serial #	Data of Cal.	Due Data
EMI Test Receiver	Rohde & Schwarz	ESCI	100119	May.03, 2011	May.02, 2012
EMI Test Receiver	Rohde & Schwarz	ESIB26	100249	Sep.22, 2011	Sep.21, 2012
EMI Test Software	SHURPLE	ESK1	N/A	N/A	N/A
Spectrum Analyzer	Agilent	E7405A	MY45114970	Jun.21, 2011	Jun.20, 2012
Signal Generator	Rohde & Schwarz	SMR27	100124	Jul.06, 2010	Jul.05, 2012
Signal Generator	Rohde & Schwarz	SML03	102319	Aug.01, 2010	Aug.01, 2012
AC Power Source	Sepcial power system	YF650	N/A	N/A	N/A
Absorbing Clamp	Rohde & Schwarz	MDS21	100218	Apr.30, 2010	Apr.29, 2012
Power Meter	Rohde & Schwarz	NRVD	101287	Jul.19, 2011	Jul.18, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Universal radio Communication tester	Rohde & Schwarz	CMU200	101724	Sep.08, 2011	Sep.07, 2012
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
BiConilog Antenna	ETS-LINDGREN	3142C	00042670	Mar.03, 2011	Mar.02, 2012
BiConilog Antenna	ETS-LINDGREN	3142C	00042673	Mar.03, 2011	Mar.02, 2012
Loop Antenna	ETS-LINGREN	6502	00071730	Mar.03, 2011	Mar.02, 2012
Double-ridged Waveguide horn	ETS-LINDGREN	3117	00035926	Dec.30, 2011	Dec.29, 2012
Double-ridged Waveguide horn	ETS-LINDGREN	3117	00041545	Dec.30, 2011	Dec.29, 2012
Pre-amplifier	CD	PAM0203	804203	Jun.21, 2011	Jun.20, 2012
RF Switch	CD	RSU-M3	706543	Jun.21, 2011	Jun.20, 2012
Thermo-/Hygrometer	N/A	TH01	N/A	May.03, 2011	May.02, 2012
Shielding Room	Zhong Yu Electronic	N/A	N/A	N/A	N/A
3m Anechoic Chamber	Zhong Yu Electronic	N/A	N/A	Apr.28, 2010	Apr.27, 2012

3. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2009 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:


Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2009 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

4. Conducted Limits

4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: SQ Home Controller)

4.2. Power Line Conducted Emission Measurement Limits (15.207)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

4.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

EUT : SQ Home Controller
 Model Number : SQB003-C-US
 Applicant : Square Connect, Inc.

4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in test mode (On) and measure it.

4.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.4-2003 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 4.6.

4.6. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150KHz to 30 MHz is investigated.

The test curves Please refer the following pages.


FCC ID: CGO- SQB003

CONDUCTED EMISSION TEST DATA

EUT: SQ Home Controller M/N: SQB003-C-US
 Operating Condition: Full Load
 Test Site: 1# Shielded Room
 Operator: Well.Wang
 Test Specification: AC 120V/60Hz
 Comment: Live Line
 Tem:25°C Hum:50%

SCAN TABLE: "Voltage (150K~30M) FIN"

Short Description: 150K-30M Disturbance Voltages



MEASUREMENT RESULT: "AT1202712101_fin"

3/1/2012 9:20AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.357000	28.20	10.1	59	30.6	QP	L1	GND
0.375000	34.40	10.1	58	24.0	QP	L1	GND
0.523500	21.20	10.1	56	34.8	QP	L1	GND
1.045000	15.70	10.2	56	40.3	QP	L1	GND
1.301500	17.70	10.2	56	38.3	QP	L1	GND
1.607500	17.20	10.3	56	38.8	QP	L1	GND

MEASUREMENT RESULT: "AT1202712101_fin2"

3/1/2012 9:20AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.361500	21.60	10.1	49	27.1	AV	L1	GND
0.379500	24.60	10.1	48	23.7	AV	L1	GND
0.888000	10.20	10.1	46	35.8	AV	L1	GND
2.390500	7.00	10.3	46	39.0	AV	L1	GND
5.288500	2.70	10.5	50	47.3	AV	L1	GND
15.580000	-0.50	10.7	50	50.5	AV	L1	GND


FCC ID: CGO- SQB003

CONDUCTED EMISSION TEST DATA

EUT: SQ Home Controller M/N: SQB003-C-US
 Operating Condition: Full Load
 Test Site: 1# Shielded Room
 Operator: Well.Wang
 Test Specification: AC 120V/60Hz
 Comment: Neutral Line
 Tem:25°C Hum:50%

SCAN TABLE: "Voltage (150K~30M) FIN"

Short Description: 150K-30M Disturbance Voltages



MEASUREMENT RESULT: "AT1202712102_fin"

3/1/2012 9:23AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.267000	21.80	10.1	61	39.4	QP	N	GND
0.339000	21.20	10.1	59	38.0	QP	N	GND
0.465000	19.40	10.1	57	37.2	QP	N	GND
0.901500	14.90	10.1	56	41.1	QP	N	GND
1.049500	12.10	10.2	56	43.9	QP	N	GND
1.337500	12.70	10.2	56	43.3	QP	N	GND

MEASUREMENT RESULT: "AT1202712102_fin2"

3/1/2012 9:23AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.361500	17.30	10.1	49	31.4	AV	N	GND
0.366000	18.50	10.1	49	30.1	AV	N	GND
0.906000	8.40	10.1	46	37.6	AV	N	GND
1.643500	7.10	10.3	46	38.9	AV	N	GND
2.350000	6.40	10.3	46	39.6	AV	N	GND
22.253500	5.80	10.8	50	44.2	AV	N	GND

5. Radiation Interference

5.1. Requirements (15.249, 15.209):

FIELD STRENGTH of Fundamental: 902-928 MHZ 2.4-2.4835 GHz 94 dB μ V/m @3m	FIELD STRENGTH of Harmonics 54 dB μ V/m @3m	S15.209 30 - 88 MHz 88 - 216 MHz 216 - 960 MHz ABOVE 960 MHz	40 dBuV/m @3M 43.5 46 54dBuV/m
---	---	--	---

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

5.2 Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 5.3.

5.3 Test Results

PASS.

The test curves Please refer the following pages.

FCC ID: CGO- SQB003

Data: (Frequency=908.40MHz)

Horizontal Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
85.87	0.63	8.43	38.79	58.24	28.51	40.00	-11.49	QP
171.97	0.72	10.31	39.40	59.51	31.14	43.50	-12.36	QP
908.40	1.51	29.00	38.52	98.36	90.35	94.0	-3.65	Peak
1,816.80	1.82	28.02	39.21	55.17	45.80	54.0	-8.20	Peak
2,725.20	2.28	33.16	35.16	43.50	43.78	54.0	-10.22	Peak
3,633.60	2.50	33.31	35.02	39.0	39.79	54.0	-14.21	Peak
4,542.00	2.65	34.40	34.77	33.72	36.0	54.0	-18.00	Peak
5,450.40	---	---	---	---	---	---	---	---
6,358.80	---	---	---	---	---	---	---	---
7,267.20	---	---	---	---	---	---	---	---
8,175.60	---	---	---	---	---	---	---	---
9,084.00	---	---	---	---	---	---	---	---

Vertical Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
135.96	0.68	9.19	39.0	57.50	28.77	43.10	-15.13	QP
416.16	0.74	11.95	40.09	55.13	27.73	46.00	-18.27	QP
908.40	1.51	29.00	38.52	97.04	89.03	94.0	-4.97	Peak
1,816.80	1.82	28.02	39.21	55.28	45.91	54.0	-8.09	Peak
2,725.20	2.28	33.16	35.16	42.58	42.86	54.0	-11.14	Peak
3,633.60	2.50	33.31	35.02	38.04	38.83	54.0	-15.17	Peak
4,542.00	2.65	34.40	34.77	32.52	34.80	54.0	-19.20	Peak
5,450.40	---	---	---	---	---	---	---	---
6,358.80	---	---	---	---	---	---	---	---
7,267.20	---	---	---	---	---	---	---	---
8,175.60	---	---	---	---	---	---	---	---
9,084.00	---	---	---	---	---	---	---	---

FCC ID: CGO- SQB003

Data: (Frequency=908.42MHz)

Horizontal Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
85.87	0.63	8.43	38.79	59.34	29.61	40.00	-10.39	QP
171.97	0.72	10.31	39.40	59.61	31.24	43.50	-12.26	QP
908.40	1.51	29.00	38.52	98.82	90.81	94.0	-3.19	Peak
1,816.80	1.82	28.02	39.21	55.18	45.81	54.0	-8.19	Peak
2,725.20	2.28	33.16	35.16	43.50	43.78	54.0	-10.22	Peak
3,633.60	2.50	33.31	35.02	39.0	39.79	54.0	-14.21	Peak
4,542.00	2.65	34.40	34.77	33.72	36.0	54.0	-18.00	Peak
5,450.40	---	---	---	---	---	---	---	---
6,358.80	---	---	---	---	---	---	---	---
7,267.20	---	---	---	---	---	---	---	---
8,175.60	---	---	---	---	---	---	---	---
9,084.00	---	---	---	---	---	---	---	---

Vertical Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dB μ V	Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
135.96	0.68	9.19	39.0	57.13	28.00	43.50	-15.5	QP
416.16	0.74	11.95	40.09	55.34	27.94	46.00	-18.06	QP
908.40	1.51	29.00	38.52	97.04	89.03	94.0	-4.97	Peak
1,816.80	1.82	28.02	39.21	55.28	45.91	54.0	-8.09	Peak
2,725.20	2.28	33.16	35.16	42.58	42.86	54.0	-11.14	Peak
3,633.60	2.50	33.31	35.02	38.04	38.83	54.0	-15.17	Peak
4,542.00	2.65	34.40	34.77	32.52	34.80	54.0	-19.20	Peak
5,450.40	---	---	---	---	---	---	---	---
6,358.80	---	---	---	---	---	---	---	---
7,267.20	---	---	---	---	---	---	---	---
8,175.60	---	---	---	---	---	---	---	---
9,084.00	---	---	---	---	---	---	---	---

NOTE: “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

NOTE: “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6. Occupied Bandwidth

6.1. Requirements (15.249):

The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.


6.2 Test Results

Pass.

Please refer the following plot.

FCC ID: CGO-SQB003


Left Side (908.40MHz)



SES-908.40-Bandedge-L

Date: 28.02.2012 11:43:04

Right Side (908.40MHz)




SES-908.40-Bandedge-H

Date: 28.02.2012 11:41:20

FCC ID: CGO-SQB003


Left Side (908.42MHz)



SES-908.42-Bandedge-L

Date: 28.02.2012 11:14:24

Right Side (908.42MHz)



SES-908.42-Bandedge-H

Date: 28.02.2012 11:16:18