

Technical Description

Model : WUBB-181G

Wireless USB Network Adapter,

Overview

The Wireless LNA USB Network Adapter, model WUBB-181G is a USB Network Adapter, compliant with IEEE Std 802.11bg – 2002. This device operates in the 2.4GHz unlicensed Industrial, Scientific and Medical band and used Direct Sequence Spread Spectrum and OFDM communication techniques. WUBB-181G is compatible with the USB 1.1 and USB 2.0 specification. To achieve maximum networking speeds (54Mbps), this device must be connection of this device to a USB 2.0 host port on a PC. Connection of this device to a USB 1.1 host port will yield a maximum of 11Mbps networking speed.

Maximum power consumption is limited to less than 500mA (max). In some countries power and available bandwidth may be further reduced to meet regulatory requirements.

The 2.4 GHz antenna is internal to the EUT and it is not readily available to be modified by the end user. Therefore it meets the 15.203 Requirement. The antenna is connected to the EUT with a unique adaptor not available to the general public.

Functional Description

The WUBB-181G is based on Broadcom's two chip CMOS based 802.11b/g solution, namely the BCM4320 Baseband/MAC & System Interface and the BCM2050 Radio chipsets..

The BCM2050 zero IF Radio is an integrated transceiver device that has been optimized for use in 2.4-GHz wireless systems. It has been designed to provide low-power, low-cost, and robust communications for applications operating in the globally available 2.4-GHz unlicensed ISM band. It is fully compliant with the 802.11b and draft 802.11g specifications and meets or exceeds the requirements where appropriate to provide the highest communication link quality of service.

The BCM2050 features a simple, innovative shared LO architecture that allows a high-performance radio implementation in a single CMOS chip. A proprietary PLL design generates quadrature LO signals in the 2.4-GHz band for both the transmitter and receiver. The PLL is locked to a 12-MHz free running crystal oscillator. A proprietary self-calibrating VCO is fully integrated frequency agile LO, ensures the lowest phase noise performance and covers the full 2.4-GHz ISM band.

The receiver front end consists a low noise amplifier, a single side band mixer and on-chip low pass filter, which provide good performance without a costly external IF band pass filter. Because the entire receive channel is one chip, all sensitive components are eliminated from the board design and this leads to the most robust and noise-immune design, optimal for integration in laptop computers and embedded applications.

The internal lowpass filter structure also features DC cancellation loop and self-calibration circuitry, which automatically adjusts circuit elements to compensate for any process variation. This eliminates tuning and ensures that the devices are uniform across process variation and temperature. An RSSI signal is also generated in these amplifiers for the system to determine signal strength. The output is a stable I/Q output for direct interface to the BCM43X X series of baseband/MAC components.

The transmit signal is input through the I/Q input from the baseband. It is then filtered and upconverted to RF using the quadrature LO signals. The signal is then boosted to a minimum 1-mW output power level by an internal power amplifier. The output signal is optimized to enable easy integration with widely available power amplifiers and minimizes the linearity requirements for these devices. Output power control is digitally programmable from full power to low power in 4-dB steps.

Technical Description

Model : WUBB-181G

Wireless USB Network Adapter,

The BCM2050 is controlled directly from the baseband and MAC through a fully digital control interface. This interface provides control for the various sections of the chip, defines data transfers and allows access to the various internal registers of the device.

The BCM2050 is in a 64-pin LPCC package.

The BCM4320 provides IEEE 802.11b/g MAC and baseband functions and interfaces to the BCM2050 to provide wireless LAN connectivity supporting data rates from 1 Mbps to 54Mbps. Broadcom's direct conversion architecture virtually eliminates the additional external components typically required for 802.11b/g implementations, resulting in significant cost, power, and footprint savings. Additionally, industry-standardized WEP and WEP2 encryption coupled with IEEE 802.1x support is provided to ensure the security of transmitted data.

Product Features

- WHQL certifies drivers for Windows XP, Windows Millennium Edition, Windows 2000, and Windows 98SE.
- Meets PCI power management interface v1.1 (ACPI)
- IEEE 802.11b/g compliant MAC and baseband
- WECA Wi-Fi November 2001 compliant
- 24-bit IV and 40-bit key WEP encryption support
- 24-bit IV and 104-bit key WEP encryption support
- 128-bit IV and 128-bit key WEP2 encryption support
- Software support for 128-bit OCB mode AES
- IEEE 802.1x and LEAP support