

ELECTRONICS TESTING CENTER, TAIWAN

NO. 8, LANE 29, WEN-MING RD.,
LO-SHAN TSUN. KUI-SHAN
HSIANG, TAoyUAN HSIEN
333, TAIWAN, R. O. C.

Tel:(03)3280026
Fax:(03)3280034

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0$

The max. average power of channel, including tune-up tolerance(mW) is **0.00010095 mW @ 303.856 MHz** (With Tune-up tolerance),

The min. test separation distance (mm) is **5 mm**,

So, $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] = 0.000036 < 3.0$ (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.

Signature _____



Name: Neo Lao/Title: Section Manager, EMC Testing Department II

TEL: +886-2-2602-3052

Email: neo.lao@etc.org.tw