



## MEASUREMENT REPORT

### FCC PART 15.231(b)/ RSS 210

---

**FCC ID:** CHQ7245T  
**IC:** 2968A-7245T  
**APPLICANT:** RHINE ELECTRONIC CO., LTD.  
**Application Type:** Certification  
**Product:** Transmitter  
**Model No.:** UC7245T  
**Brand Name:** RHINE  
**FCC Classification:** FCC Part 15 Security/Remote Control Transmitter (DSC)  
**FCC Rule Part(s):** Part 15.231(b)  
**IC Rule Part(s):** RSS 210 Issue 9  
**Test Procedure(s):** ANSI C63.10-2013  
**Received Date:** November 8, 2019  
**Test Date:** November 11 ~ 13, 2019

**Tested By** : *Peter Syu*  
( Peter Syu )  
**Reviewed By** : *Paddy Chen*  
( Paddy Chen )  
**Approved By** : *Chenz Ker*  
( Chenz Ker )



The test results only relate to the tested sample.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
1911TW5404-U1	1.0	Original Report	2019-11-20	

---

# CONTENTS

Description	Page
<b>1. INTRODUCTION .....</b>	<b>6</b>
1.1. Scope .....	6
1.2. MRT Test Location .....	6
<b>2. PRODUCT INFORMATION .....</b>	<b>7</b>
2.1. Equipment Description.....	7
2.2. Test Standards .....	7
2.3. Test Methodology .....	7
2.4. EUT Setup and Test Mode .....	8
<b>3. ANTENNA REQUIREMENTS.....</b>	<b>9</b>
<b>4. TEST EQUIPMENT CALIBRATION DATE .....</b>	<b>10</b>
<b>5. MEASUREMENT UNCERTAINTY.....</b>	<b>11</b>
<b>6. TEST RESULT .....</b>	<b>12</b>
6.1. Summary .....	12
6.2. Radiated Emissions .....	13
6.2.1. Standard Applicable .....	13
6.2.2. Test Procedure.....	13
6.2.3. Test Setup.....	14
6.2.4. Test Results .....	15
6.3. 20dB Bandwidth / 99% Bandwidth .....	22
6.3.1. Standard Applicable .....	22
6.3.2. Test Procedure.....	22
6.3.3. Test Setup.....	22
6.3.4. Test Result.....	23
6.4. Transmission Time.....	24
6.4.1. Standard Applicable .....	24
6.4.2. Test Procedure.....	24
6.4.3. Test Setup.....	24
6.4.4. Test Result.....	25
6.5. Duty Cycle .....	26
6.5.1. Standard Applicable .....	26
6.5.2. Test Procedure.....	26
6.5.3. Test Setup.....	26
6.5.4. Test Result.....	27
6.6. AC Conducted Emissions Measurement.....	29

---

6.6.1.	Test Limit .....	29
6.6.2.	Test Setup.....	29
6.6.3.	Test Result.....	30
<b>7.</b>	<b>CONCLUSION.....</b>	<b>31</b>

## §2.1033 General Information

<b>Applicant</b>	RHINE ELECTRONIC CO., LTD.
<b>Applicant Address</b>	NO. 29, AN HE ROAD, TAN-ZI SHIANG, TAICHUNG COUNTY, 427 Taiwan
<b>Manufacturer</b>	RHINE ELECTRONIC CO., LTD.
<b>Manufacturer Address</b>	NO. 29, AN HE ROAD, TAN-ZI SHIANG, TAICHUNG COUNTY, 427 Taiwan
<b>Factory</b>	KAM SHING ELECTRONIC CO., LTD
<b>Factory Address</b>	The Youth Industrial Administration Park, Chengjing Town, Huiyang city, Guangdong Province China
<b>Test Site</b>	MRT Technology (Taiwan) Co., Ltd
<b>Test Site Address</b>	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
<b>MRT Registration No.</b>	291082
<b>FCC Rule Part(s)</b>	Part 15.231(b)
<b>Model No.</b>	UC7245T
<b>Test Device Serial No.</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
<b>FCC Classification</b>	FCC Part 15 Security/Remote Control Transmitter(DSC)

### Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


## 1. INTRODUCTION

### 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	Transmitter
Model No.	UC7245T
Frequency Range	433.98 MHz
Type of modulation	ASK
Antenna Type	Integral Antenna

### 2.2. Test Standards

The following report is prepared on behalf of the **RHINE ELECTRONIC CO., LTD.** in accordance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commission rules/ IC RSS-Gen 8.8,8.9,8.10 and RSS-210 AnnexA

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

### 2.3. Test Methodology

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013).

**Deviation from measurement procedure.....None**

## 2.4. EUT Setup and Test Mode

The EUT was operated at continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode	
Mode 1	Transmitting by 433.98MHz



### 3. ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **Transmitter** is permanently attached.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The Transmitter unit complies with the requirement of §15.203.

## 4. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2020/3/25
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2020/6/18
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25

### Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2020/6/4
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2020/4/29
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2020/4/22
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2020/4/23
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2020/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2020/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2020/4/22
Cable	Rosnol	K1K50-UP0264- K1K50-4M	MRTTWE00012	1 year	2020/6/18

### Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/2
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2020/7/11
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2020/3/26

### Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

## 5. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement – SR2</b>	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ):	
150kHz~30MHz:	2.42dB
<b>Conducted Measurement– SR1</b>	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.3dB	
<b>Radiated Emission Measurement – AC1</b>	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ):	
Horizontal:	9K~30MHz: 4.14dB
	30MHz~1GHz: 4.22dB
	1GHz~40GHz: 4.05dB
Vertical:	9K~30MHz: 4.14dB
	30MHz~1GHz: 3.37dB
	1GHz~40GHz: 4.08dB

## 6. TEST RESULT

### 6.1. Summary

Company Name: RHINE ELECTRONIC CO., LTD.

FCC/IC Part Section(s)	Test Description	Test Condition	Test Result
15.203	ANTENNA REQUIREMENTS	--	Pass
15.205,15.209,15.231(b)/ RSS Gen 8.9,8.10 RSS-210 Annex A	Radiated Spurious Emissions	Radiated	Pass
15.231(c)/ RSS-210 Annex A.1.3	20dB Bandwidth / 99% Bandwidth		Pass
15.231(a)/ RSS-210 Annex A.1.1(a)	Transmission Time		Pass
15.231(a)/ RSS-210 Annex A.1.1(a)	Duty Cycle		Pass
15.207 / RSS Gen 8.8	AC Conducted Emissions 150kHz - 30MHz		Line Conducted

#### Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 3) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 4) The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
- 5) The EUT Power by Battery, so do not need to test Conducted Emissions.

## 6.2. Radiated Emissions

### 6.2.1. Standard Applicable

According to §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750	125 to 375
174-260	3,750	375
260-470	13,750 to 12,500	1375 to 1,250
Above 470	12,500	1,250

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements start below or at the lowest crystal frequency.

Compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.


### 6.2.2. Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.231(b) and FCC Part 15.209 Limit / RSS-Gen 8.9 and RSS-210 Annex A.1.2.


### 6.2.3. Test Setup

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.231(b) and FCC Part 15.209 Limit/ RSS-Gen 8.9 and RSS-210 Annex A.1.2.

#### 30MHz ~ 1GHz Test Setup:




#### 1GHz ~ 5GHz Test Setup:



### 6.2.4. Test Results

EUT	Transmitter	Date of Test	2019-11-11
Factor	VULB 9162	Temp. / Humidity	26°C /51%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	TX_433.98MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	433.979	50.81	24.66	75.46	-25.37	100.83	200	0	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Transmitter	Date of Test	2019-11-11
Factor	VULB 9162	Temp. / Humidity	26°C /51%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	TX_433.98MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)	
1	*	433.983	39.42	24.66	64.08	-36.75	100.83	240	280	Peak

Note:

1. "\*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



EUT	Transmitter	Date of Test	2019-11-12
Factor	VULB 9162	Temp. / Humidity	26°C /51%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	TX_433.98MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	48.430	10.38	21.57	31.95	-48.87	80.82	100	400	Peak
2	103.720	10.69	19.32	30.01	-50.81	80.82	100	400	Peak
3	243.400	12.33	20.32	32.65	-13.35	46.00	100	400	Peak
4	* 324.880	17.16	22.41	39.57	-6.43	46.00	100	400	Peak
5	763.320	12.95	29.94	42.89	-37.93	80.82	100	400	Peak
6	868.080	16.40	31.35	47.75	-33.07	80.82	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Transmitter	Date of Test	2019-11-12
Factor	VULB 9162	Temp. / Humidity	26°C /51%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	TX_433.98MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	49.400	10.94	21.62	32.56	-48.26	80.82	100	400	Peak
2	103.720	10.82	19.32	30.14	-50.68	80.82	100	400	Peak
3	* 243.400	12.34	20.32	32.66	-13.34	46.00	100	400	Peak
4	296.750	12.85	21.36	34.21	-46.61	80.82	100	400	Peak
5	731.310	13.41	29.59	43.00	-37.82	80.82	100	400	Peak
6	848.680	12.78	31.26	44.04	-36.78	80.82	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Transmitter	Date of Test	2019-11-12
Factor	BBHA 9120D	Temp. / Humidity	26°C /51%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	TX_433.98MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1302.000	53.72	-6.41	47.31	-26.69	74.00	100	400	Peak
2	1735.625	66.07	-5.16	60.91	-19.91	80.82	100	155	Peak
3	1735.625	N/A	N/A	52.45	-8.37	60.82	100	155	Average
4	2169.750	64.09	-3.74	60.35	-20.47	80.82	100	400	Peak
5 *	2602.875	69.48	-2.37	67.11	-13.71	80.82	100	-40	Peak
6 *	2602.875	N/A	N/A	58.65	-2.17	60.82	100	-40	Average
7	3038.125	65.97	-2.80	63.17	-17.65	80.82	100	175	Peak
8	3038.125	N/A	N/A	54.71	-6.11	60.82	100	175	Average
9	3471.625	55.50	-1.34	54.16	-26.66	80.82	100	400	Peak
10	3906.750	56.62	-0.17	56.46	-17.54	74.00	100	255	Peak
11	3906.750	51.12	-0.17	50.95	-3.05	54.00	100	255	Average
12	4341.125	47.84	1.77	49.60	-24.40	74.00	100	400	Peak
13	4773.000	45.84	3.10	48.94	-25.06	74.00	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Average factor (20Log(1/Duty Cycle)) is 8.46dB (For No3, No6)
6. Average Measurement = Peak Measurement - Average factor.

EUT	Transmitter	Date of Test	2019-11-12
Factor	BBHA 9120D	Temp. / Humidity	26°C /51%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	TX_433.98MHz	Test Voltage	By Battery



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1302.375	45.19	-6.41	38.78	-35.22	74.00	100	400	Peak
2	1734.875	54.71	-5.16	49.55	-31.27	80.82	100	400	Peak
3	2170.125	53.16	-3.74	49.43	-31.39	80.82	100	400	Peak
4	* 2604.000	56.15	-2.37	53.78	-27.04	80.82	100	400	Peak
5	3038.375	54.90	-2.80	52.10	-28.72	80.82	100	400	Peak
6	3471.375	42.17	-1.34	40.84	-39.98	80.82	100	400	Peak
7	3906.000	42.85	-0.17	42.68	-31.32	74.00	100	400	Peak
8	4773.750	39.37	3.10	42.47	-31.53	74.00	100	400	Peak

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

### 6.3. 20dB Bandwidth / 99% Bandwidth


#### 6.3.1. Standard Applicable

According to FCC Part 15.231(c), the bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

#### 6.3.2. Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT's operation band.


#### 6.3.3. Test Setup



### 6.3.4. Test Result

Test Frequency (MHz)	Modulation Type	20dB Bandwidth (KHz)	99% Bandwidth (KHz)	Limit (KHz)	Result
433.98	ASK	8.766	29.626	≤ 1085	Pass

Limit = Fundamental Frequency \* 0.25%, 433.98 MHz \* 0.25% = 1.085 MHz,  
 1.085MHz \* 1000 = 1085KHz



## 6.4. Transmission Time


### 6.4.1. Standard Applicable

According to FCC 15.231(a)(1), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

### 6.4.2. Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 434MHz, then set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.


### 6.4.3. Test Setup





6.4.4. Test Result

Test Item	Frequency (MHz)	Measurement (s)	Limit (s)	Result
Transmission Time ( $T_{on}$ )	433.98	0.96	< 5	Pass



## 6.5. Duty Cycle


### 6.5.1. Standard Applicable

According to FCC Part 15.231(b) and 15.35(c), for pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.

### 6.5.2. Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 434MHz, then set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

### 6.5.3. Test Setup




### 6.5.4. Test Result

Modulation Type	Total Time (T <sub>on</sub> ) (ms)	The duration of one cycle (ms)	Duty Cycle (ms)	Average Factor (dB)
ASK	13.6	36	0.38	8.46


Note 1: Duty Cycle = Total Time (T<sub>on</sub>) / (T<sub>on</sub> + T<sub>off</sub>).

$$(((640\mu s * 19) + (240\mu s * 6)) / (36\text{ms})) = 13.6\text{ms}$$


Note 2: Average Factor = 20 \* Log\*(1/Duty Cycle).



### 433.98MHz (T<sub>on</sub>-Long)



### 433.98MHz (T<sub>on</sub>-Short)



## 6.6. AC Conducted Emissions Measurement


### 6.6.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits		
Frequency (MHz)	QP (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 6.6.2. Test Setup



### **6.6.3. Test Result**

Note: The EUT Power by Battery, so do not need to test Conducted Emissions.

## 7. CONCLUSION

The data collected relate only the item(s) tested and show that the **Transmitter** is in compliance with FCC Rules/ IC RSS 210 Annex A1.1.

————— The End —————