



## RF Exposure Evaluation

---

**FCC ID** : CHQGTX751  
**APPLICANT** : RHINE ELECTRONIC CO., LTD.  
**Application Type** : Certification  
**Product** : Transmitter  
**Model No.** : G-TX751  
**Brand Name** : RHINE  
**FCC Rule Part(s)** : Part 2.1093 (Portable)  
**Received Date** : July 24, 2023

**Tested By** : *Kaunaz Lee*  
( Kaunaz Lee )  
**Reviewed By** : *Paddy Chen*  
( Paddy Chen )  
**Approved By** : *Chenz Ker*  
( Chenz Ker )



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
2307TW5404-U2	1.0	Original Report	2024-02-05	

## 1. PRODUCT INFORMATION

### 1.1. Equipment Description

Product Name	Transmitter
Model No.	G-TX751
Brand Name	RHINE
Frequency Range	390 MHz

## 2. RF Exposure Evaluation

### 2.1. FCC Limits

According to FCC KDB 447498 D04V01 - SAR-Based Exemption

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula .

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The example values shown as below are for illustration only.

Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
300	39	65	88	110	129	148	166	184	201	217	
450	22	44	67	89	112	135	158	180	203	226	
835	9	25	44	66	90	116	145	175	207	240	
1900	3	12	26	44	66	92	122	157	195	236	
2450	3	10	22	38	59	83	111	143	179	219	
3600	2	8	18	32	49	71	96	125	158	195	
5800	1	6	14	25	40	58	80	106	136	169	

Note: when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

## 2.2. Test Result of RF Exposure Evaluation

Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	EIRP (mW)	FCC SAR Test Exclusion Threshold (mW)
Sub-1G	390	-24.95	-54.95	28.8

So, this device can complies the SAR test exclusion.

\_\_\_\_\_ The End \_\_\_\_\_