

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM140700352501

Email: ee.shenzhen@sgs.com Page: 1 of 22

1 Cover Page

FCC REPORT

Application No.: SZEM1407003525RF

Applicant: Crimestopper Security Products, Inc.

Manufacturer: DONGGUAN PORTMAN ELECTRONIC SCIENCE AND

TECHNOLOGY CO.,LTD

Factory: DONGGUAN PORTMAN ELECTRONIC SCIENCE AND

TECHNOLOGY CO.,LTD

Product Name: Car alarm –RS2-G3

Model No.(EUT): T34A-1

FCC ID: CHXT34A-1W433
Trade Mark: Crime stopper

Standards: 47 CFR Part 15, Subpart C (2013)

Date of Receipt: 2014-07-09

Date of Test: 2014-07-14 to 2014-08-18

Date of Issue: 2014-08-21

Test Result: PASS *

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM140700352501

Page: 2 of 22

2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2014-08-21		Original	

Authorized for issue by:		
Tested By	Chris-3hong	2014-08-18
	(Chris Zhong) /Project Engineer	Date
Prepared By	Lintin Lu	2014-08-21
	(Linlin Lv) /Clerk	Date
Checked By	Owen 2hon	2014-08-27
	(Owen Zhou) /Reviewer	Date



Report No.: SZEM140700352501

Page: 3 of 22

3 Test Summary

Test Item	Test Requirement	Test method	Result	
Antenna Requirement	47 CFR Part 15, Subpart C Section	ANSI C63.10(2009)	PASS	
Antenna nequirement	15.203	ANSI C63.10(2009)	PASS	
Field Strength of the	47 CFR Part 15, Subpart C Section	ANSI Cea 10(2000)	PASS	
Fundamental Signal	15.231 (b)	ANSI C63.10(2009)	rass	
Spurious Emissions	47 CFR Part 15, Subpart C Section	ANSI C63.10(2009)	PASS	
Spurious Emissions	15.231 (b)/15.209	ANSI C63.10(2009)		
20dP Rondwidth	47 CFR Part 15, Subpart C Section	ANSI C63.10(2009)	PASS	
20dB Bandwidth	15.231 (c)	ANSI C63.10(2009)		
Dwell Time	47 CFR Part 15, Subpart C Section	ANCI Cea 10/2000)	DACC	
Dwell Time 15.231 (a)		ANSI C63.10(2009)	PASS	



Report No.: SZEM140700352501

Page: 4 of 22

4 Contents

		Page
CO/	VER PAGE	1
VEF	RSION	
TES	ST SUMMARY	3
	_	
GEN	NERAL INFORMATION	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF EUT	5
5.3		
5.4	DESCRIPTION OF SUPPORT UNITS	
5.5	TEST LOCATION	6
5.6	TEST FACILITY	7
5.7	DEVIATION FROM STANDARDS	7
5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
5.10	EQUIPMENT LIST	8
TES	ST RESULTS AND MEASUREMENT DATA	10
6.1	ANTENNA REQUIREMENT	10
•		
_		
_		
6.3	20DB BANDWIDTH	
6.4	DWELL TIME	
	VEI TES CO GEI 5.1 5.2 5.3 5.4 5.5 5.6 5.7 5.8 5.9 5.10 TES 6.1 6.2 6.2. 6.2. 6.2.	5.2 GENERAL DESCRIPTION OF EUT 5.3 TEST ENVIRONMENT AND MODE 5.4 DESCRIPTION OF SUPPORT UNITS 5.5 TEST LOCATION. 5.6 TEST FACILITY. 5.7 DEVIATION FROM STANDARDS 5.8 ABNORMALITIES FROM STANDARD CONDITIONS. 5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER. 5.10 EQUIPMENT LIST TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT 6.2 SPURIOUS EMISSIONS 6.2.1 Duty Cycle. 6.2.2 Spurious Emissions. 6.3 20DB BANDWIDTH.



Report No.: SZEM140700352501

Page: 5 of 22

5 General Information

5.1 Client Information

Applicant:	Crimestopper Security Products, Inc.
Address of Applicant:	1770 South Tapo St., Simi Valley, CA93063
Manufacturer:	DONGGUAN PORTMAN ELECTRONIC SCIENCE AND
	TECHNOLOGY CO.,LTD
Address of Manufacturer:	NO.10, LUYI 2 ROAD, TANGXIA TOWN, DONGGUAN CITY,
	GUANGDONG PROVINCE CHINA
Factory:	DONGGUAN PORTMAN ELECTRONIC SCIENCE AND
	TECHNOLOGY CO.,LTD
Address of Factory:	NO.10, LUYI 2 ROAD, TANGXIA TOWN, DONGGUAN CITY, GUANGDONG PROVINCE CHINA

5.2 General Description of EUT

Product Name:	Car alarm –RS2-G3
Mode No.:	T34A-1
Trade Mark:	Crime stopper
Sample Type:	Portable production
Operation Frequency:	433.88MHz
Modulation Type:	FSK
Antenna Type:	Integral
Antenna Gain:	-1.3dBi
Power Supply:	3.0V DC (3.0V x 1 "CR2") for Tx



Report No.: SZEM140700352501

Page: 6 of 22

5.3 Test Environment and Mode

Operating Environment:	Operating Environment:		
Temperature:	23.0 °C		
Humidity:	50 % RH		
Atmospheric Pressure:	1005 mbar		
Test mode:			
Transmitting mode: Keep the EUT in transmitting mode.			

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in dull, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140700352501

Page: 7 of 22

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM140700352501

Page: 8 of 22

5.10 Equipment List

	RE in Chamber				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2015-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
6	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
7	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
8	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24
9	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24
10	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
11	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24
12	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
13	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
14	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24
15	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24
16	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
17	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04



Report No.: SZEM140700352501

Page: 9 of 22

	RF connected test				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
2	Humidity/ Temperature Indicator	HYGRO ZJ1-2B		SEL0033	2014-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2014-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R&S	NRVS	SEL0144	2014-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2014-10-24

Note: The calibration interval is one year, all the instruments are valid.



Report No.: SZEM140700352501

Page: 10 of 22

6 Test results and Measurement Data


6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -1.3dBi.




Report No.: SZEM140700352501

Page: 11 of 22

6.2 Spurious Emissions

6.2.1 Duty Cycle




[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140700352501

Page: 12 of 22

Test plot as follows: Duty cycle numbers



[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140700352501

Page: 13 of 22

6.2.2 Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.231(b) and 15.209							
Test Method:	ANSI C63.10: 2009							
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Receiver Setup:	Frequency	Detector	I	RBW	VBW	R	emark	
	0.009MHz-0.090MHz	Peak	1	0kHz	30kHz		Peak	
	0.009MHz-0.090MHz	Average	1	0kHz	30kHz	A۱	verage	
	0.090MHz-0.110MHz	Quasi-peak	1	0kHz	30kHz	Qua	asi-peak	
	0.110MHz-0.490MHz	Peak	1	0kHz	30kHz		Peak	
	0.110MHz-0.490MHz	Average	1	0kHz	30kHz	A۱	verage	
	0.490MHz -30MHz	Quasi-peak	1	0kHz	30kHz	Qua	asi-peak	
	30MHz-1GHz	Quasi-peak	10	00 kHz	300kHz	Qua	asi-peak	
	Above 1GHz	Peak	1	MHz	3MHz	l	Peak	
	Above Tariz	Peak	1	MHz	10Hz	A۱	verage	
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/me	ter)	Limit (dBuV/n	n) Re	mark	Measurer distance	
	0.009MHz-0.490MHz	2400/F(kHz))	-		-	300	
	0.490MHz-1.705MHz	24000/F(kHz	<u>'</u>)	-		-	30	
	1.705MHz-30MHz	30		-		-	30	
	30MHz-88MHz	100		40.0	Quas	i-peak	3	
	88MHz-216MHz	150		43.5	Quas	i-peak	3	
	216MHz-960MHz	200		46.0	Quas	i-peak	3	
	960MHz-1GHz	500		54.0	Quas	i-peak	3	
	Above 1GHz	500		54.0	Ave	rage	3	
	Note: 15.35(b), Unless of emissions is 20dB applicable to the peak emission level rad	above the max	kimu der t	m permit est. This	ted avera	ge emis	ssion limit	total
Limit:	Frequency	Limit (dB			Re	emark		
(Field strength of the		,	80.83		Average Value		ue	
fundamental signal)	433.92MHz		00.83			Peak Value		



Report No.: SZEM140700352501

Page: 14 of 22

Test Procedure:	 a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
	c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
	e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
	f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning.
	And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Setup:	








Figure 2. 30MHz to 1GHz



Report No.: SZEM140700352501

Page: 15 of 22




Figure 3. Above 1 GHz

Test Mode:	Transmitting mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Measurement Data

6.2.2.1 Field Strength Of The Fundamental Signal

Peak value:									
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization	
433.920	2.35	16.58	27.33	89.58	81.18	100.83	-19.65	Horizontal	
433.920	2.35	16.58	27.33	94.37	85.97	100.83	-14.86	Vertical	

Average value:										
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization		
433.920	2.35	16.58	27.33	89.58	60.72	80.83	-20.11	Horizontal		
433.920	2.35	16.58	27.33	94.37	65.51	80.83	-15.32	Vertical		

Remark:

Duty cycle=0.0948

PDCF=20*log (Duty Cycle)

Average value= Peak value+ PDCF



Report No.: SZEM140700352501


Page: 16 of 22

6.2.2.2Spurious Emissions

Below 1GHz

QP value:

Horizontal:



Condition: FCC15.231(B) 433MHZ 3m 3142C HORIZONTAL

Job No. : 3525RF Mode : TX • T344_1


	Freq	CableA		Preamp Factor			Limit Line	Over Limit	Remark
	MHz	d₿	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	dB	
1 2 3 4 5 6	406.09	2.90	21.59	27.22	31.99 32.80 39.55 34.55	30.93 31.63	40.00 46.00 46.00 46.00	-25. 93 -26. 22 -15. 07 -14. 37	



Report No.: SZEM140700352501

Page: 17 of 22

Vertical:



Condition: FCC15.231(B) 433MHZ 3m 3142C VERTICAL

Job No. : 3525RF Mode : TX : T34A-1

	Freq	CableA		Preamp Factor				Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	dBuV/m	dB	
1 2 3 4 5 6	32. 41 107. 89 274. 19 378. 58 462. 35 798. 98	2.46	8.71 12.78 16.04 17.34	26. 47 26. 99	31.34 32.22 41.32 41.84	14.12 20.32 32.51 34.12	43.50 46.00 46.00 46.00	-29.38 -25.68 -13.49 -11.88	



Report No.: SZEM140700352501

Page: 18 of 22

Above 1GHz

Peak value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1300.000	2.53	27.71	38.35	48.92	40.81	74	-33.19	Vertical
2170.000	3.19	31.15	38.44	52.94	48.84	74	-25.16	Vertical
2605.000	3.60	32.47	38.47	53.71	51.31	74	-22.69	Vertical
3040.000	3.76	31.89	38.52	55.15	52.28	74	-21.72	Vertical
3472.000	3.89	32.86	38.73	55.68	53.70	74	-20.30	Vertical
3907.000	4.14	33.34	38.91	54.82	53.39	74	-20.61	Vertical
1300.000	2.53	27.71	38.35	43.40	35.29	74	-38.71	Horizontal
1807.000	2.88	30.16	38.41	44.61	39.24	74	-34.76	Horizontal
2389.000	3.36	32.34	38.46	44.87	42.11	74	-31.89	Horizontal
3040.000	3.76	31.89	38.52	51.70	48.83	74	-25.17	Horizontal
3472.000	3.89	32.86	38.73	55.41	53.43	74	-20.57	Horizontal
3907.000	4.14	33.34	38.91	54.65	53.22	74	-20.78	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.






Report No.: SZEM140700352501

Page: 19 of 22

6.3 20dB Bandwidth



Measurement Data


20dB bandwidth (MHz)	Limit (MHz)	Results
0.271	1.0848	PASS



Report No.: SZEM140700352501

Page: 20 of 22

Test plot as follows:




[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140700352501

Page: 21 of 22

6.4 Dwell Time



Measurement Data


Test item	Limit (MHz)	Results
Transmitting time	≤5S	PASS



Report No.: SZEM140700352501

Page: 22 of 22

Test plot as follows:



[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."