

Test report no. : 96081-6

Item tested : LivingColors – Luminaire

Type of equipment: Low Power Transceiver

Client : Silicon & Software Systems Polska Sp. z O. O.

FCC Part 15.249

Low Power Transceiver
2400 – 2483.5 MHz Band

RSS210 Issue 6 & RSS Gen Issue 2

Low-Power Licence-exempt Radiocommunications devices
2400 – 2483.5 MHz Band

28 March 2008

Authorized by :



Egil Hauger
Technical Verificator

CONTENTS

1	GENERAL INFORMATION	3
1.1	Testhouse Info	3
1.2	Client Information	3
1.3	Manufacturer (if other than client)	3
2	Test Information	4
2.1	Test Item	4
2.2	Test Environment	5
2.2.1	Normal test condition	5
2.3	Test Period	5
3	TEST REPORT SUMMARY	6
3.1	General	6
3.2	Test Summary	7
3.3	Description of modification for Modification Filing	7
3.4	Comments	7
3.5	Family List Rational	7
4	TEST RESULTS	8
4.1	Power-Line Conducted Emissions	8
4.2	Transmitter Frequency Stability	9
4.3	6 dB bandwidth	10
4.4	Peak Power Output	11
4.5	Band Edge Emissions	12
4.6	Spurious Emissions (Radiated)	13
4.7	Receiver Spurious Emissions (Radiated)	16
5	LIST OF TEST EQUIPMENT	38
6	BLOCK DIAGRAM	39
6.1	System set up	39
6.2	Test Site Radiated Emission	40

1 GENERAL INFORMATION

1.1 Testhouse Info

Name : Nemko Comlab
Address : Gåsevikveien 8, Box 96
N-2027 Kjeller, NORWAY
Telephone : +47 64 84 57 00
Fax : +47 64 84 57 05
E-mail: post@comlab.no
FCC test firm registration # : 994405
Industry Canada OATS registration # : 4443

1.2 Client Information

Name : Silicon & Software Systems Polska Sp.Z O.O.
Address : ul. Nyska 83/85, 50-505 Wroclaw, Poland
Telephone : +48 71 3348177

Contact:

Name : Sebastian Roslan
Telephone : +48 71 3348177
E-mail : Sebastian.roslan@s3group.com

1.3 Manufacturer (if other than client)

Name : Philips Lighting
Address : BU Consumer Lamps, Mathildelaan 1, 5611 BD, Eindhoven , The Netherlands
Telephone : +31 40 2755531
Fax : -

Contact:

Name : Bao Trinh
Telephone : +31 40 2755531
E-mail : bao.trinh@philips.com

2 Test Information

2.1 Test Item

Name :	Luminaire
Model/version :	LivingColors Luminaire
Serial number :	TX: 53(23) , RX: 39
Hardware identity and/or version:	2.1
Software identity and/or version :	Test specific
Operating frequency:	2433 MHz
Transmitter data rate:	250kbit/s
Tuneable Bands :	None
Emissions Designator :	/
Number of Channels :	1
Operating Modes :	Transceiver
Channel spacing:	None
Channel bandwidth:	200kHz (TX) , 540kHz (RX)
Type of Modulation :	MSK
User Frequency Adjustment :	None
Rated Output Power :	-4dBm (0.4 mW) @ 50 ohm
Type of Power Supply :	AC mains 120V /60Hz
Antenna gain:	Between 3.3 – 1.1 dBi
Antenna Connector :	Integral
Antenna Diversity Supported :	None

¹ The tested equipment has integrated antenna only

Theory of Operation

The Luminaire is a transceiver. It is a single channel AC operated unit.

Description of Test Item

The required frequencies, modulation and modes are selected by preprogrammed software on the EUT.

The measurements were done with the EUT powered by 120 V AC. It was checked that power variations between 85% and 115% did not have any influence on the measurements. And measurements were performed only at normal conditions.

All radiated measurements were performed on three axes.

2.2 Test Environment

2.2.1 Normal test condition

Temperature: 20 - 22 °C
Relative humidity: 30 - 40 %
Normal test voltage: AC/DC converter, 120V 60Hz

The values are the limit registered during the test period.

2.3 Test Period

Item received date: 2007-11-30
Test period : 2007-12-05 to 2007-12-07

3 TEST REPORT SUMMARY

3.1 General

Manufacturer: Philips Lighting

Model No.: Luminaire

Serial No.: /

All measurements are traceable to national standards.

The tests were conducted for the purpose of demonstrating compliance with FCC CFR 47 Part 15.249 and Industry Canada RSS-210 Issue 7.

Radiated tests were conducted in accordance with ANSI C63.4-2003. The radiated tests were made in a semi-anechoic chamber at measuring distances of 3 and 10 metres.

☒ New Submission

☐ Production Unit

☐ Class II Permissive Change

☒ Pre-production Unit

DXT Equipment Code

☐ Family Listing

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".



TEST REPORT #: 96081-6

TESTED BY: 
G.Suwanthakumar, Test engineer

DATE: 28.03.2008

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

3.2 Test Summary

Name of test	FCC Part 15 reference	RSS210 Issue 7 / RSS Gen Issue 2	Result
Supply Voltage Variations	15.31(e)	4.5	Complies ²
Transmitter frequency stability	15.31(m)	7.2.4	Complies
Antenna Requirement	15.203	7.1.4	Integral ¹
Power-Line Conducted Emission	15.207(C)	7.2.2	Complies
6 dB bandwidth	15.215(c)	-	Complies
Peak Power Output	15.249(a)(c)	A2.9	Complies
Band edge Emissions	15.249(d)	A.2.9	Complies
Spurious Emissions (Radiated)	15.249 (e)	A2.9 & 4.3	Complies
Spurious Emissions (Antenna Conducted)	15.249	7.2.3.1	N/A ¹
Receiver Spurious Emissions (Radiated)	N/A	6	Complies

¹ The EUT has only integral antenna.

² Power supply varied according to the standard

RSS Gen issue 2 covers section 6 & 7

RSS 210 issue 7 covers section A2.9

3.3 Description of modification for Modification Filing

Not applicable.

3.4 Comments

The EUT is delivered with pre-programmed 1 channel to operate in TX or RX mode.

The LC7 has integral antenna only.

3.5 Family List Rational

Not Applicable.

4 TEST RESULTS

4.1 Power-Line Conducted Emissions

Para. No.: 15.207 (a)

Test Performed By: G.Suwanthakumar

Date of Test: 05.12.2007

Measurement procedure: ANSI C63.4-2003 using 50 μ H/50 ohms LISN.

Test Results: **Complies**

Measured both in standby mode and operating mode.

Highest measured value (L1 and N):

Frequency	Detector	Measured value	Limit	Margin
MHz	QP/AV	dB μ V	dB μ V	dB
0.172	QP	43	64,9	> 20
0.172	AV	20	54,9	> 20
0.28	QP	44	60,9	> 20
0.28	AV	34	50,9	> 20
0.5	QP	41	56	> 20
0.5	AV	31	46	> 20
0.78	QP	34	56	>20
0.78	AV	20	46	>20
29.71	QP	11	60	>20
29.71	AV	3	50	>20

See the attached graphs for peak scan. The measured peak values are also within the requirements.

4.2 Transmitter Frequency Stability

Para. No.: /

Test Performed By: G.Suwanthakumar

Date of Test: 07.12.07

Measurement Data:

Temperature	Channel nr.	Given Frequency (MHz)	Measured value (MHz)	Deviation (Hz)
20 ° C	-	2433	2433	0

Comment:

For information only:

There are no requirements to frequency tolerance for low power devices in the 2400 – 2483.5 MHz band according to 15.249 or RSS 210

4.3 6 dB bandwidth

Para. No.: 15.215(c)

Test Performed By: G.Suwanthakumar

Date of Test: 07.12.2007

Test Results: Complies

Measurement Data:

	2433 MHz
Measured 6 dB bandwidth (kHz)	360.72

See the attached graphs

4.4 Peak Power Output

Para. No.: 15.249 (a)

Test Performed By: G.Suwanthakumar

Date of Test: 07.12.2007

Test Results: Complies

Measurement Data:

Maximum field strength: 93.3 dB μ V/m

RF channel	2433 MHz
Measured maximum field strength – Vertical polarization	87.39 dB μ V/m
Measured maximum field strength – Horizontal polarization	93.34 dB μ V/m

The used instrument settings are : RBW/VBW: 1MHz , Peak detector.

The measured eirp is: 0.57mW at nominal temperature, the given power at 50hm is 0.4mW

The calculated antenna gain: 1.53 dBi

See attached graphs for field strength measurements

Detachable antenna?

☐ Yes ☒ No

If detachable, is the antenna connector non-standard?

☐ Yes ☐ No

The tested equipments have integral antenna only.

Requirements:

The maximum peak output power shall be ≤ 94 dB μ V/m

4.5 Band Edge Emissions

Para. No.: 15.249 (d)

Test Performed By: G.Suwanthakumar	Date of Test: 07.12.2007
------------------------------------	--------------------------

Test Results: Complies

Measurement Data:

RF channel	2433
Measured maximum dBc	> 50

The operating frequency is well away from 2400 MHz (lower band edge) & well within 2483.5 MHz (upper band edge).

Requirements:

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental.

4.6 Spurious Emissions (Radiated)

Para. No.: 15.249 (e)

Test Performed By: G.Suwanthakumar

Date of Test: 06.12.2007

Test Results: Complies

Measurement Data:

Radiated emission 9 kHz - 25 GHz, see attached table

Highest value: Peak 42.83dB μ V/m, average 33.93 dB μ V/m, at 4.8 GHz

The worst case is obtained at vertical polarization .Measured Peak values are lower than 48 dB μ V/m

In RX mode no spurious emission detected in the frequency range 9kHz – 25 GHz.

Duty Cycle Correction Factor Calculation:

RF duty cycle Correction Factor: Calculation according to RF burst Para 15.35 (c):

Measured duty cycle: on time 811.62 μ s , ON+OFF time: 2.27ms (see attached graphs)

$$-20 \cdot \log (0.811/2.27) = 8.9 \text{ dB}$$

Maximum duty cycle according to Para 15.35 (b): **20 dB**

This value is used for calculating the Peak limit for spurious emissions and for calculating the Spurious Emissions value with Average Detector when measuring with Peak Detector above 1 GHz.

Radiated spurious emissions are performed from 9kHz to 25 GHz .

Example of frequency graph of radiated emission is also attached.

Antenna factor, amplifier gain and cable loss are included in spectrum analyzer "Transducer factor".

No components above 4.8 GHz were detected

Radiated Emission 1 – 25 GHz, Peak , Luminaire

Measured with Peak Detector

The maximum emission is obtained at vertical polarization (worst case).

Frequency	RF channel	Dist. corr. factor	Field strength, Peak, 3 metres	DC Corr. Factor	Limit	Margin
GHz		dB	dB μ V/m	dB	dB μ V/m	dB
4.8	2433	0	42.83	-	74	31.2
Above 2 nd	2433	0	None detected	-	74	-

Radiated emission 1- 25 GHz, Average, Luminaire

Measured with Peak Detector

Frequency	RF channel	Dist. corr. factor	Field strength, Peak, 3 metres	DC Corr. Factor	Limit	Margin
GHz		dB	dB μ V/m	dB	dB μ V/m	dB
4.8	2433	0	42.83	8.9	54	20.1
Above 2 nd	2433	0	None detected	8.9	54	-

Radiated Emission 30 – 1000 MHz, Luminaire

Measured with Q-Peak Detector

The maximum emission is obtained at vertical polarization (worst case).

Frequency	Operational condition	Field strength	Measuring distance	Limit FCC15.209	Margin
MHz		dB μ V/m	metres	dB μ V/m	dB
42.25	TX on/VP	29	3	40	11
64.05	TX on/VP	23	3	40	17
71.6	TX on/VP	23	3	40	17
79.65	TX on/VP	15	3	40	25
108.8	TX on/VP	15	3	43.5	28,5
134.65	TX on/VP	18	3	43,5	25,5

4.7 Receiver Spurious Emissions (Radiated)

Para. No.: 6

Test Performed By: G.Suwanthakumar

Date of Test: 07.12.2007

Test Results: Complies

Measurement Data:

Radiated emission 9 kHz - 25 GHz, see attached table

In RX mode no spurious emission detected in the frequency range 9kHz – 25 GHz. Except at 4.8 GHz. The measured value with peak dectector is 47.97 dBuV/m. The calculated average value is 39.1 dBuV/m

This value is used for calculating the Peak limit for spurious emissions and for calculating the Spurious Emissions value with Average Detector when measuring with Peak Detector above 1 GHz.

Example of frequency graph of radiated emission is also attached.

NEMKO COMLAB

Peak

06. Dec 07 11:22

Operator:

Comment:

gns

SABER

Luminarie

Standby mode


115V ac 60Hz

FCC part 15

L1 pol

Scan Settings (1 Range)

Frequencies				Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
150k	30M	4.5k	9k	PK	50ms	AUTO LN OFF	60dB



Luminaire - Conducted emission – In standby mode - L1 Polarity

NEMKO COMLAB


06. Dec 07 11:04

Peak

Operator: gns
 Comment: SABER
 Luminaire
 Standby mode
 115V ac 60Hz
 FCC part 15

Scan Settings (1 Range)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
150k	30M	4.5k	9k	PK	50ms	AUTO	LN OFF 60dB



Luminaire - Conducted emission – In standby mode – N Polarity

NEMKO COMLAB

Peak

06. Dec 07 11:22

Operator:

Comment:

gns

SABER

Luminarie

Standby mode


115V ac 60Hz

FCC part 15

L1 pol

Scan Settings (1 Range)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
150k	30M	4.5k	9k	PK	50ms	AUTO LN OFF	60dB



Luminaire - Conducted emission – In Active mode – L1 Polarity

NEMKO COMLAB
Peak

06. Dec 07 11:49

Operator:


gns

Comment:


SABER
 Luminarie
 Active mode
 115V ac 60Hz
 FCC part 15
 N pol

Scan Settings (1 Range)


Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
150k	30M	4.5k	9k	PK	50ms	AUTO LN OFF	60dB




Luminaire - Conducted emission – In active mode – N Polarity



Luminaire- Maximum field strength – 87.39 dB μ V/m - Vertical polarization




Luminaire- Maximum field strength – 93.34 dB μ V/m - Horizontal polarization




Date: 7.DEC.2007 13:04:27

6 dB bandwidth



Date: 3.DEC.2007 21:03:49

Duty cycle ON time



Date: 3.DEC.2007 21:05:48

Duty cycle ON+OFF time

Radiated emission 10 kHz-30 MHz.

Measuring distance 10 m, measured with Peak detector.

No component detected, see attached graph.

Limit is converted to 10 m using 40 dB/decade according to 15.31 (f) (2).

NEMKO COMLAB

Peak

07. Dec 07 14:58

Operator:

Comment:

gns

SABER

Luminarie

TX mode

115V ac 60Hz

FCC part 15

Scan Settings (4 Ranges)

Frequencies				Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
10k	100k	1k	1k	PK	20ms	0dB	LN OFF	60dB
20k	20k	5k	9k	PK	20ms	AUTO	LN ON	60dB
20k	10M	5k	9k	PK	20ms	AUTO	LN OFF	60dB
10M	30M	5k	9k	PK	20ms	AUTO	LN OFF	60dB

Transducer No.

Start

Stop


Name

13

10k

30M

HFH2Z2



Luminaire - 10 kHz – 30MHz –radiated emission - (TX/RX mode)

Measuring distance 3 m .

No component detected, see attached graphs.

Nemko Comlab

07. Dec 07 09:55

Peak

EUT: SABER

Manuf: S3 Group

Op Cond: 4m HP

Operator: gns

Test Spec: FCCpart 15

Comment: TX mode

Scan Settings (1 Range)

Frequencies					Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
30M	200M	50k	120k	PK	50ms	0dBLN	ON	60dB	

Transducer No.

20

Start


30M

Stop

200M

Name

HK116



TX mode: Luminaire - Radiated emission 30 –200MHz, Horizontal polarization

Nemko Comlab

Peak

07. Dec 07 09:47

EUT:

Manuf:

Op Cond:

Operator:

Test Spec:

Comment:

SABER

S3 Group

1m VP

gns

FCCpart 15

TX mode

Scan Settings (1 Range)

Frequencies				Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
30M	200M	50k	120k	PK	50ms	0dBLN ON	60dB

Transducer No.

Start

Stop


Name

20

30M

200M

HK116



TX mode: Luminaire- Radiated emission 30 –200MHz, Vertical polarization

Nemko Comlab
Peak

07. Dec 07 10:07

EUT:

SABER

Manuf:

S3 Group

Op Cond:

1m vp

Operator:

gns

Test Spec:

FCCpart 15

Comment:

TX mode

Scan Settings (1 Range)

----- Frequencies -----				----- Receiver Settings -----			
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
200M	1000M	50k	120k	PK	50ms	AUTO	LN ON 60dB

Transducer No.

Start

Stop


Name

21

200M

1000M

HL223



TX mode: Luminaire- Radiated emission 200 – 1000 MHz, Vertical polarization


Nemko Comlab
Peak

07. Dec 07 10:22

EUT: SABER
Manuf: S3 Group
Op Cond: 4m HP
Operator: gns
Test Spec: FCCpart 15
Comment: TX mode

Scan Settings (1 Range)					Receiver Settings				
Frequencies									
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
200M	1000M	50k	120k	PK	50ms	AUTO	LN ON	60dB	

Transducer No.	Start	Stop	Name
21	200M	1000M	HL223



TX mode: Luminaire - Radiated emission 200 –1000 MHz, Horizontal polarization

Nemko Comlab

Peak

07. Dec 07 08:54

EUT:

Manuf:

Op Cond:

Operator:

Test Spec:

Comment:

SABER

S3 Group

1 m VP

gns

FCCpart 15

RX mode

Scan Settings (1 Range)

----- Frequencies -----||----- Receiver Settings -----|

Start

Stop

Step

IF BW

Detector

M-Time

Atten

Preamp

OpRge

30M

200M

50k

120k

PK

50ms

0dBLN

ON

60dB

Transducer No.

Start

Stop


Name

20

30M

200M

HK116



RX mode: Luminaire - Radiated emission 30 - 200 MHz, Vertical polarization

Nemko Comlab

Peak

07. Dec 07 09:03

EUT:

Manuf:

Op Cond:

Operator:

Test Spec:

Comment:

SABER

S3 Group

4 m HP

gns

FCCpart 15

RX mode

Scan Settings (1 Range)

Frequencies					Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
30M	200M	50k	120k	PK	50ms	0dB	LN ON	60dB	

Transducer No.

Start

Stop


Name

20

30M

200M

HK116



RX mode: Luminaire - Radiated emission 30 - 200 MHz, Horizontal polarization

Nemko Comlab

Peak

07. Dec 07 10:57

EUT:

Manuf:

Op Cond:

Operator:

Test Spec:

Comment:

SABER

S3 Group

1m vp

gns

FCCpart 15

RX mode

Scan Settings (1 Range)

Frequencies					Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
200M	1000M	50k	120k	PK	50ms	AUTO	LN ON	60dB	

Transducer No.

Start

Stop


Name

21

200M

1000M

HL223



RX mode: Luminaire - Radiated emission 200 - 1000MHz, Vertical polarization

Nemko Comlab

Peak

07. Dec 07 10:22

EUT:

Manuf:

Op Cond:

Operator:

Test Spec:

Comment:

SABER

S3 Group

4m HP

gns

FCCpart 15

IRX mode

Scan Settings (1 Range)

Frequencies				Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
200M	1000M	50k	120k	PK	50ms	AUTO	LN ON	60dB

Transducer No.

Start

Stop


Name

21


200M

1000M

HL223




RX mode: Luminaire - Radiated emission 200 - 1000MHz, Horizontal polarization




Date: 7.DEC.2007 11:00:28


2nd harmonic – Horizontal Polarization - TX



TX mode: Spurious scan 1 - 10 GHz (peak detector)




Spurious scan 10 - 18 GHz (peak detector)




Date: 7.DEC.2007 14:35:36

Spurious scan 18 - 25 GHz (peak detector)



Date: 3.DEC.2007 20:24:02

RX mode: Spurious scan 1 - 10 GHz (peak detector)



Date: 7.DEC.2007 10:43:32

RX mode: LO (peak detector)


5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

No.	Instrument/ancillary	Type of instrument/ancillary	Manufacturer	Ref. no.
1	FSEK30	Spectrum Analyzer	Rohde & Schwarz	LR 1337
2	ESN	EMI Reciever	Rohde & Schwarz	LR 1237
3	3115	Antenna horn	EMCO	LR 1330
4	643	Antenna horn	Narda	LR 093
5	642	Antenna horn	Narda	LR 220
6	PM7320X	Antenna horn	Siverts lab	LR 103
7	DBF-520-20	Antenna horn	Systron Donner	LR 101
8	638	Antenna horn	Narda	LR 098
9	5VF1000/2000	BP filter	Trilithic	LR 1174
10	5VF2000/4000	BP filter	Texscan	LR 42
11	ESH3-Z3	LISN	Rohde & Schwarz	LR 1076
12	8449B	Amplifier	Hewlett Packard	LR 1322
13	-	Shielded room	ETS	LR 1410
14	HFH2-Z2	Antenna loop	Rohde and Schwarz	LR 285
15	10855A	Amplifier	Hewlett Packard	LR 1445
16	HL223	Antenna log.per	Rohde & Schwarz	LR 1261
17	HK116	Antenna biconic	Rohde & Schwarz	LR 1260
18	ESVS 30	Test Receiver	Rohde & Schwarz	LR 1101
19	R3271	Spectrum Analyser	Advantest	LR 1123

6 BLOCK DIAGRAM

6.1 System set up



Luminaire

6.2 Test Site Radiated Emission

