



**Accredited EMC-Test-Laboratory**

**DAR-No.: TTI-P-G-166/98-30**

Listed by  
**FEDERAL COMMUNICATIONS COMMISSION (FCC )**  
**Registration Number: 90462**  
**FCC Website: WWW.FCC.GOV**

**Test report no.: 4-0541a-1-1/02**  
**Type identification : W-LAN card 'PA3171U-1MPC' in**  
**TOSHIBA Notebook 'Portege 2000'**  
**FCC id: CJ6PA3171WL**

**Table of Content**

1 General Information.....3

    1.1 Notes..... 3

    1.2 Statement of Compliance ..... 3

    1.3 Testing laboratory..... 4

    1.4 Details of applicant ..... 4

    1.5 Application details ..... 4

    1.6 Test item ..... 5

    1.7 Test specifications..... 6

        1.7.1 RF exposure limits ..... 6

2 Technical test ..... 7

    2.1. Summary of test results ..... 7

    2.2 Test environment ..... 7

    2.3 Test equipment used ..... 7

    2.4 Test results (Body SAR)..... 8

    2.5 Tissue dielectric properties..... 9

    2.6 Tissue parameters..... 9

    2.7 Measurement uncertainties ..... 10

    2.8 System validation..... 11

Appendix 1: System performance verification ..... 12

Appendix 2: Measurement results (printout from DASY<sup>TM</sup>)..... 13

Appendix 3: Photo documentation ..... 18

Appendix 4: Calibration parameters of E-field probe ..... 27

## 1 General Information

### 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.6. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

### 1.2 Statement of Compliance

The SAR values found for the TOSHIBA laptop 'Portege 2000' with WLAN card 'PA3171U-1MPC' are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1 g tissue according the FCC rule §2.1093, the ANSI/IEEE C 95.1:1999 and the NCRP Report Number 86 for uncontrolled environment.

#### Tester operator:



2002-02-05

Fabien Coulet

---

Date

Name

Signature

#### Technical responsibility for area of testing:



2002-02-05

Bernd Rebmann

---

Date

Name

Signature

### 1.3 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6-10, D-66117 Saarbrücken

Germany

Telephone: +49 681 598 - 0

Fax: + 49 681 598 - 8475

e-mail: info@ict.cetecom.de

Internet: <http://www.cetecom.com>

State of accreditation: The Test laboratory SAR is accredited according to DIN EN ISO / IEC 17025 45001.

DAR-No.:TTI-P-G-166/98-30

Test location, if different from CETECOM ICT Services GmbH

Name: ---

Street: ---

Town: ---

Country: ---

Phone: ---

Fax: ---

### 1.4 Details of applicant

Name: TOSHIBA Corporation Digital Media Network Company

Ome Operations-Digital Media Equipment

Street: 2-9, SUEHIRO-CHO, OME

Town: TOKYO, 198-8710

Country: Japan

Contact: Mr. KOICHI KAJI

Phone: +81-428-30-7432

Fax: +81-428-34-1445

### 1.5 Application details

Date of receipt of application: 2002-02-04

Date of receipt of test item: 2002-02-04

Date of test: 2002-02-04

Person who have been present during the test: ---

## 1.6 Test item

Description of test item:


EUT Type: Laptop with integrated miniPCI WLAN card  
 Trade Name: Toshiba  
 Model: Portege 2000  
 SW: --  
 Frequency: 2402-2483.5 MHz here 2412-2462 MHz  
 Modulation: 22M0P7D (DSSS) ch steps: 5 MHz  
 Number of channels: 11  
 Max RF output power: 19.2 dBm cond.  
 Antenna Type: integral **notebook** antenna  
 Power supply: 15V DC

### 1.6.1 Antenna data

Model Name: HTL-007-P\*\*\*  
 Frequency Range: 2.4 – 2.5 GHz  
 Bandwidth: Over 200MHz ( VSWR :under 2 )

Gain (Average): Antenna fixed beside of keyboard of Portege2000

Antenna	X-Y PLANE (dBi)		Y-Z PLANE (dBi)	
	Horizontal	Vertical	Horizontal	Vertical
Wireless LAN Main	-7.8	-3.9	-0.0	-2.9
Wireless LAN Sub	-14.0	-7.5	-13.4	-5.1



## 1.7 Test specifications

**Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01)  
Draft IEEE Std 1528-200X: Version 6.4:July 2001**

### 1.7.1 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Table 1: RF exposure limits

**Notes:**

- \* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time
- \*\* The Spatial Average value of the SAR averaged over the whole body.
- \*\*\* The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

## 2 Technical test

### 2.1. Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

The deviations as specified in 2.4 were ascertained in the course of the tests performed.

### 2.2 Test environment

Ambient temperature: 21°C – 23°C

Tissue simulating liquid: 21°C – 23°C

### 2.3 Test equipment used

Manufacturer	Device	Type	Serial number	Date of last calibration
Schmid & Partner Engineering AG	Dosimetric E-Fiel Probe	ET3DV6	1558	February 20, 2001
Schmid & Partner Engineering AG	Dosimetric E-Fiel Probe	ET3DV6	1559	February 20, 2001
Schmid & Partner Engineering AG	900 MHz System Validation Dipole	D900V2	102	February 13, 2001
Schmid & Partner Engineering AG	1800 MHz System Validation Dipol	D1800V2	287	February 13, 2001
Schmid & Partner Engineering AG	Data acquisition electronics	DAE3V1	413	January 15, 2001
Schmid & Partner Engineering AG	Software	DASY 3 V3.1c	---	Calibration isn't necessary
Schmid & Partner Engineering AG	Phantom	Pre SAM	---	Calibration isn't necessary
Rohde & Schwarz	Universal Radio Communication Tester	CMU 200	U-972406/000	August 30, 2001
Hewlett Packard	Network Analyser 300 kHz to 3 GHz	HP 8753C	2936A00872	Mai 11, 1998
Agilent	Dielectric Probe Kit	Agilent 85070C	US99360146	March 8, 2001

## 2.4 Test results (Body SAR)

The table contain the measured SAR values averaged over a mass of 1 g			
Frequency	Position	Touch on the flat phantom	Limit
Ch 7 2442 MHz	Touch right (see photo 2)	0.985 W/kg	1.6 W/kg
Ch 7 2442 MHz	Touch left (see photo 3)	0.0023 W/kg	1.6 W/kg
Ch 7 2442 MHz	under –right side- (see photo 4)	0.0747 W/kg	1.6 W/kg
Ch 7 2442 MHz	under –left side- (see photo 5)	0.0019 W/kg	1.6 W/kg

Table 3: Test results (Body SAR)

Note 1: Upper and lower frequencies were not measured because the values at the middle frequency did not exceed 1.27 W/kg (1.60 W/kg reduced of 2 dB)

Note 2: The used conversion factor during the measurement was 5.56 at 1800MHz, this value was not extrapolated to a frequency of 2400 MHz since use of a conversion of 5.40 is the worst case condition. From the supplied calibration for the probe S/N1559, it can be seen that the ConvF is inversely related to frequency (see page 27), that means that when the frequency increases the ConvF decreases. Since the ConvF factor for the DASY system appears in the numerator, the calculated SAR value will decrease with lower ConvF factors.



## 2.5 Tissue dielectric properties

The dielectric properties have been measured by the contact probe method at 22-24°C. The following materials are used for producing the tissue-equivalent materials:

Ingredients (% by weight)	Frequency (MHz)									
	<input type="checkbox"/> 450		<input type="checkbox"/> 835		<input type="checkbox"/> 915		<input type="checkbox"/> 1900		<input checked="" type="checkbox"/> 2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	70.0	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.40	1.35	0.76	0.18	0.3	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	0.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	0.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.0	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	29.7	0.0	26.7

Table 4: Tissue dielectric properties

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16MΩ+ resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

## 2.6 Tissue parameters

Used Target Frequency	Target Head Tissue		Target Body Tissue		Measured Head Tissue		Measured Body Tissue		Measured Date	
	[MHz]	$\epsilon_r$	$\sigma$ [S/m]	$\epsilon_r$	$\sigma$ [S/m]	$\epsilon_r$	$\sigma$ [S/m]	$\epsilon_r$		$\sigma$ [S/m]
<input type="checkbox"/> 450		43.5	0.87	56.7	0.94	---	---	---	---	---
<input type="checkbox"/> 835		41.5	0.90	55.2	0.97	---	---	---	---	---
<input type="checkbox"/> 900		41.5	0.97	55.0	1.05	---	---	---	---	---
<input type="checkbox"/> 915		41.5	0.98	55.0	1.06	---	---	---	---	---
<input type="checkbox"/> 1800 - 2000		40.0	1.40	53.3	1.52	---	---	---	---	---
<input checked="" type="checkbox"/> 2450		39.2	1.80	52.7	1.95	---	---	52.4	2.05	4 <sup>th</sup> February 02

Table 5: Parameter of the tissue simulating liquid

## 2.7 Measurement uncertainties

The overall combined measurement uncertainty of the measurement system is  $\pm 12,1\%$  (K=1). The breakdown of the individual uncertainties is as follows:

<b>Calibration Error:</b>					
	<b>Probability Distribution</b>	<b>Standard Uncertainty</b>			
		<b>900 MHz</b>	<b>1500 MHz</b>	<b>1800 MHz</b>	
Incident power	Rectangular	$\pm 1,2\%$	$\pm 1,2\%$	$\pm 1,2\%$	
Mismatch uncertainty	Rectangular	$\pm 0,6\%$	$\pm 0,6\%$	$\pm 0,6\%$	
Exp. fitting error (95% confidence)	Normal	$\pm 0,4\%$	$\pm 0,2\%$	$\pm 0,2\%$	
Liquid permittivity	Rectangular	$\pm 2,3\%$	$\pm 2,8\%$	$\pm 2,9\%$	
Probe positioning	Normal	$\pm 0,5\%$	$\pm 0,8\%$	$\pm 1,0\%$	
Field homogeneity	Rectangular	$\pm 0,6\%$	$\pm 1,2\%$	$\pm 1,4\%$	
<b>Combined Standard Uncertainty</b>		<b><math>\pm 2,8\%</math></b>	<b><math>\pm 3,4\%</math></b>	<b><math>\pm 3,6\%</math></b>	
<b>E-Field Probe Error:</b>					
<b>Error Description</b>	<b>Error</b>	<b>Probability Distribution</b>	<b>Weight</b>	<b>Standard Uncertainty</b>	
Isotropy around axis	$\pm 0,2$ dB	U-shape	0,5	$\pm 2,4\%$	
Spherical Isotropy	$\pm 0,4$ dB	U-shape	0,5	$\pm 4,8\%$	
Isotropy from gradient	$\pm 0,5$ dB	U-shape	0		
Spatial resolution	$\pm 0,5\%$	normal	1	$\pm 0,5\%$	
Linearity error	$\pm 0,2$ dB	rectangular	1	$\pm 2,5\%$	
Calibration error	$\pm 3,6\%$	normal	1	$\pm 3,6\%$	
<b>Combined Standard Uncertainty:</b>				<b><math>\pm 6,9\%</math></b>	
<b>Source Uncertainty:</b>					
<b>Error Description</b>	<b>Error</b>	<b>Probability Distribution</b>	<b>Weight</b>	<b>Standard Uncertainty</b>	
Device positioning	$\pm 6\%$	normal	1	$\pm 6\%$	
Laboratory set-up	$\pm 3\%$	normal	1	$\pm 3\%$	
<b>Combined Standard Uncertainty:</b>				<b><math>\pm 6,7\%</math></b>	
<b>SAR Evaluation Error</b>					
<b>Error Description</b>	<b>Error</b>	<b>Probability Distribution</b>	<b>Weight</b>	<b>Standard Uncertainty</b>	<b>Offset</b>
Data acquisition error	$\pm 1\%$	rectangular	1	$\pm 0,6\%$	
ELF and RF disturbances	$\pm 0,25\%$	normal	1	$\pm 0,25\%$	
Conductivity assessment	$\pm 10\%$	rectangular	1	$\pm 5,8\%$	
Extrapolation and boundary effects	$\pm 3\%$	normal	1	$\pm 3\%$	+ 5 %
Probe positioning	$\pm 0,1$ mm	normal	1	$\pm 1\%$	
Integration and cube orientation	$\pm 3\%$	normal	1	$\pm 3\%$	
Cube shape inaccuracies	$\pm 2\%$	rectangular	1	$\pm 1,2\%$	
<b>Combined Standard Uncertainty:</b>				<b><math>\pm 7,4\%</math></b>	

<b>Combined Uncertainties</b>		
<b>Error Description</b>	<b>Standard Uncertainty</b>	<b>Offset</b>
E-field probe errors	± 6.9 %	
SAR evaluation error	± 7.4 %	± 5 %
Source uncertainty	± 6,7 %	
<b>Combined Standard Uncertainty:</b>	<b>± 12.1 %</b>	
<b>Expanded Uncertainty (k=2):</b>	<b>± 24,2 %</b>	

Table 6: Measurement uncertainties

The measurement uncertainties were performed by Schmid & Partner Engineering AG.


## 2.8 System validation

The system validation is used for verifying the accuracy of the complete measurement system and performance of the software. The system validation is performed with 1800 MHz head tissue equivalent material according IEEE Std 1528-200X: 2001. (graphics plots attached).


<b>Validation Kit</b>	<b>Frequency</b>	<b>Target SAR<sub>1g</sub></b>	<b>Target SAR<sub>10g</sub></b>	<b>Measured SAR<sub>1g</sub></b>	<b>Measured SAR<sub>10g</sub></b>	<b>Measured date</b>
D1800V2, S/N:287	1800 MHz	1.905 mW/g	0.99 mW/g	1.93 mW/g	1.00 mW/g	2002-02-04


Table 7: Test results (system validation)


## Appendix 1: System performance verification




## Appendix 2: Measurement results (printout from DASYS™)














### Appendix 3: Photo documentation



Photo 1: Measurement System DASY 3




Photo 2: Touch position right side




Photo 3: Touch position left side





Photo 4: EUT under side (right position)



Photo 5: EUT under side (left position)



Photo 6: EUT



Photo 7: EUT upper side





Photo 8: EUT rear side




Photo 8: EUT under side

## Appendix 4: Calibration parameters of E-field probe

### Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

## Calibration Certificate

### Dosimetric E-Field Probe

Type:	ET3DV6
Serial Number:	1559
Place of Calibration:	Zurich
Date of Calibration:	Feb. 20, 2001
Calibration Interval:	12 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

Approved by:

ET3DV6 SN:1559

### DASY3 - Parameters of Probe: ET3DV6 SN:1559

#### Sensitivity in Free Space

NormX	<b>1.51</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	<b>1.54</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	<b>1.51</b> $\mu\text{V}/(\text{V}/\text{m})^2$

#### Diode Compression

DCP X	<b>102</b> mV
DCP Y	<b>102</b> mV
DCP Z	<b>102</b> mV

#### Sensitivity in Tissue Simulating Liquid

<b>Head</b>	<b>450 MHz</b>	$\epsilon_r = 43.5 \pm 5\%$	$\sigma = 0.87 \pm 10\%$ mho/m
ConvF X	<b>7.27</b> extrapolated		Boundary effect:
ConvF Y	<b>7.27</b> extrapolated		Alpha <b>0.22</b>
ConvF Z	<b>7.27</b> extrapolated		Depth <b>3.41</b>
<b>Head</b>	<b>900 MHz</b>	$\epsilon_r = 42 \pm 5\%$	$\sigma = 0.97 \pm 10\%$ mho/m
ConvF X	<b>6.70</b> $\pm 7\%$ (k=2)		Boundary effect:
ConvF Y	<b>6.70</b> $\pm 7\%$ (k=2)		Alpha <b>0.30</b>
ConvF Z	<b>6.70</b> $\pm 7\%$ (k=2)		Depth <b>3.03</b>
<b>Head</b>	<b>1500 MHz</b>	$\epsilon_r = 40.4 \pm 5\%$	$\sigma = 1.23 \pm 10\%$ mho/m
ConvF X	<b>5.94</b> interpolated		Boundary effect:
ConvF Y	<b>5.94</b> interpolated		Alpha <b>0.42</b>
ConvF Z	<b>5.94</b> interpolated		Depth <b>2.53</b>
<b>Head</b>	<b>1800 MHz</b>	$\epsilon_r = 40 \pm 5\%$	$\sigma = 1.40 \pm 10\%$ mho/m
ConvF X	<b>5.56</b> $\pm 7\%$ (k=2)		Boundary effect:
ConvF Y	<b>5.56</b> $\pm 7\%$ (k=2)		Alpha <b>0.48</b>
ConvF Z	<b>5.56</b> $\pm 7\%$ (k=2)		Depth <b>2.27</b>

#### Sensor Offset

Probe Tip to Sensor Center	<b>2.7</b>	mm
Optical Surface Detection	<b>2.3 <math>\pm</math> 0.2</b>	mm