FCC CFR47 PART 15 SUBPART C CERTIFICATION TEST REPORT

#### FOR

802.11 B/G/N HALF MINICARD

MODEL NUMBER: PA3724U-1MPC

FCC ID: CJ6UPA3724WL IC: 248H-DPA3724W

REPORT NUMBER: 09U12485-1

ISSUE DATE: MARCH 26, 2009

Prepared for TOSHIBA CORPORATION OME COMPLEX, 2-9, SUEHIRO-CHO TOKYO 198-8710, JAPAN

Prepared by COMPLIANCE CERTIFICATION SERVICES 47173 BENICIA STREET FREMONT, CA 94538, U.S.A. TEL: (510) 771-1000 FAX: (510) 661-0888



#### **Revision History**

Rev.	lssue Date	Revisions	Revised By
	03/25/09	Initial Issue	T. Chan

## TABLE OF CONTENTS

1.	AT	TESTATION OF TEST RESULTS	4
2.	TES	ST METHODOLOGY	5
3.	FAC	CILITIES AND ACCREDITATION	5
4.	REI	FERENCES	5
5.	CA	LIBRATION AND UNCERTAINTY	6
5	.1.	MEASURING INSTRUMENT CALIBRATION	6
5	.2.	MEASUREMENT UNCERTAINTY	6
6.	EQ	UIPMENT UNDER TEST	7
6	.1.	DESCRIPTION OF EUT	7
6	.2.	RADIO MODULE APPROVAL CONDITIONS	7
7.	LIN	AITS AND RESULTS	8
7	.1.	CO-LOCATED MAXIMUM PERMISSIBLE EXPOSURE	8

Page 3 of 8

### **1. ATTESTATION OF TEST RESULTS**

COMPANY NAME:	TOSHIBA COPORATION OME COMPLEX, 2-9, SUEHIRO-CHO TOKYO 198-8710, JAPAN
EUT DESCRIPTION:	802.11bgn Half MiniCard and Dual Band 800/1900 Universal Data Modem Platform
MODEL:	PA3724U-1MPC AND UNDP-1

APPLICABLE STANDARDS			
STANDARD	TEST RESULTS		
FCC CFR 47 PARTS 1 AND 2	Pass		
OET BULLETIN 65	Pass		
Industry Canada RSS-102	Pass		

Compliance Certification Services, Inc. (CCS) calculated the MPE of the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note**: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:

Tested By:

THU CHAN EMC MANAGER COMPLIANCE CERTIFICATION SERVICES

Chin Pany

CHIN PANG EMC ENGINEER COMPLIANCE CERTIFICATION SERVICES

Page 4 of 8

## 2. TEST METHODOLOGY

The calculations documented in this report were performed in accordance with FCC CFR 47 Parts 1, and 2, OET Bulletin 65, and RSS-102.

### 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <u>http://www.ccsemc.com</u>.

### 4. REFERENCES

All 800 MHz Cell band and 1900 MHz PCS bands were made as documented in Qualcomm test report.

All 2.4 GHz band measurement was made as documented in Realtek test report.

Duty cycle data is excerpted from the applicable test report.

Antenna gain data is excerpted from product documentation provided by the applicant.

## 5. CALIBRATION AND UNCERTAINTY

#### 5.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

#### 5.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY		
Power Line Conducted Emission	+/- 2.3 dB		
Radiated Emission	+/- 3.4 dB		

Uncertainty figures are valid to a confidence level of 95%.

Page 6 of 8

### 6. EQUIPMENT UNDER TEST

#### 6.1. DESCRIPTION OF EUT

The EUT is an 802.11 b/g/n RTL8192E half miniCard radio module that is manufactured by Realtek Semiconductor Corp.

The WWAM module is a dual band, 800/1900MHz, operates in GSM/GPRS mode. The module manufactured by Qualcomm.

### 6.2. RADIO MODULE APPROVAL CONDITIONS

The Cellular / PCS radio module is manufactured by Qualcomm with original FCC ID: J9CUNDP-1 grant on January 18, 2008.

The WLAN radio module is manufactured by Realtek Semiconductor Corp. with original FCC ID: TX2-TL8192EHMC grant on November 03, 2008.

The Bluetooth module is manufactured by Yuden CSR with original FCC ID: RYYEYTFXCS grant on Jane 15, 2007 or manufactured by Askey Computer Corp. with original FCC ID: H8N-BTU1030 grant on March 02, 2009.

Page 7 of 8

### 7. LIMITS AND RESULTS

### 7.1. CO-LOCATED MAXIMUM PERMISSIBLE EXPOSURE

#### <u>LIMITS</u>

Per OTE Bulletin 65, for frequency bands with the same MPE limits, the Power Densities produced by each transmitter are summed. The summation must be under the limit for the band.

Per OTE Bulletin 65, for frequency bands with different limits the Power Densities are calculated separately for each band, divided by the limit for the band and the results are then summed. The summation must be less than 1.

#### **RESULTS**

Mode	MPE	Output	Antenna	FCC Power	FCC	FCC Fraction	FCC
	Distance	Power	Gain	Density	Limit	of Limit	Limit
	(cm)	(dBm)	(dBi)	(mW/cm^2)	(mW/cm^2)	Dimensionless	(mW/cm^2)
2.4GHz	20.0	24.90	-2.84	0.03	1.00	0.03	
800 MHz	20.0	32.98	-3.16	0.19	0.55	0.35	
Colocated						0.38	1.00
Mode	MPE	Output	Antenna	FCC Power	FCC	FCC Fraction	FCC
	Distance	Power	Gain	Density	Limit	of Limit	Limit
	(cm)	(dBm)	(dBi)	(mW/cm^2)	(mW/cm^2)	Dimensionless	(mW/cm^2)
2.4GHz	20.0	24.90	-2.84	0.03	1.00	0.03	
1900 MHz	20.0	29.47	-3.25	0.08	1.00	0.08	
Colocated						0.12	1.00

# **END OF REPORT**

Page 8 of 8