



NOTE:
1. SEPARATE PIN FROM 82-97 CONNECTOR BEFORE ASSEMBLY. ATTACH PINS TO CENTER CONDUCTOR USING PLIERS. PINS MUST BE FULLY SEATED AND TIGHT. REPLACE 82-97 CONNECTORS OVER PINS. PUSH WITH A CLOCKWISE MOTION. A GAP OF .150" TO .170" MUST BE MAINTAINED FROM END OF PIN TO END OF CONNECTOR.

REMOVED CUTOUT VIEW AT TOP VIEW. ADDED ITEM 24 BALLOON (F.H. SCREWS). ADDED H-REF DIMS 2.62 & 2.10. ADDED V-REF DIMS 1.77 & 2.05. (SAK)

A0	20002342	3/31/99	PWK
----	----------	---------	-----

2.50 DIM WAS 2.45. 3.37 DIM WAS 3.36. DELETED NOTE 2. (RFB)

ALL DIMENSIONS IN INCHES UNLESS OTHERWISE NOTED.				THIS PRINT IS THE PROPERTY OF ADC, IT SHALL NOT BE COPIED WITHOUT PERMISSION.				TITLE A/D, 2 WAY COMBINER/SPLITTER 2.5-2.7 GHz			
TOLERANCES UNLESS OTHERWISE NOTED.				MATERIAL				DWG. NO.			
.XX ±.02 FRAC ±1/64				FINISH				2111-5008		REV	
.XXX ±.005 ANG ±0° 30'				DO NOT SCALE DRAWING				A0		A0	
REV				DATE				SCALE 1=1		SHEET 1 OF 1	
ECO				REL				C		1	
APV				REL				C		1	
APV				REL				C		1	