

1. GENERAL

1.1 Outlines

The NAVTEX NCR-333 function receives and displays the various types of information broadcast at frequencies of 518 kHz, 490 kHz and 4209.5 kHz, such as: navigational warning, meteorological warning, search and rescue information, and other types of information. NCR-333 also provides the function that selects information type and coast station for intended uses.

1.2 Features

● Receiving NAVTEX broadcasts

NCR-333 receives NAVTEX broadcasts automatically on 518 kHz, 490 kHz, and 4209.5 kHz.

● Large screen allows comfortable visibility

NCR-333 has a 5.7-inch LCD screen display with clear visibility. It also provides three different character sizes of display, and can be selected at your convenience.

● Message saving function

NCR-333 can store up to 200 message identification codes for 70 hours. Moreover, the stored message of each channel can be saved up to 50 messages permanently.

● Automatically receiving station setting function

NCR-333 can select receiving stations automatically on GPS position data is valid.

● Permanent storage of data settings

NCR-333 can set and store the message type and seashore station that receive to internal memory. The data, therefore, does not need to be re-set, even after power has been turned off.

● Dual voltage supply input

NCR-333 can be used on wither 24 V_{DC} or 12 V_{DC} vessels.

● Self-diagnosis Function

NCR-333 has automatic self-diagnosis function. This function allows easy maintenance and high system reliability.

● Connection to external equipment

NCR-333 can be used with the JRC Total Navigator (ECDIS) and external serial printers.