



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE ! BALTIMORE, MARYLAND 21230-3432 ! PHONE (410) 354-3300 ! FAX (410) 354-3313

August 13, 2008

Japan Radio Co., Ltd.
2-1-4 Fukuoka, Kamifukuoka-shi
Saitama, 356-0011, Japan

Dear Karim Ghodbane,

Enclosed is the EMC test report for compliance testing of the JRC FWA System - Type W <XL0> Wireless Terminal as tested to the requirements of Title 47 of the CFR, Part 101.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
MET LABORATORIES, INC.

Jennifer Sanchez
Documentation Department

Reference: (\\Japan Radio Company\Type W <XL0> \ EMC80940A-FCC101)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc. While use of the National Voluntary Laboratory Accreditation Program (NVLAP) letters or the NVLAP Logo, the Standards Council of Canada Logo, A2LA, or the Nationally Recognized Testing Laboratory (NRTL) Letters in this report reflects MET Accreditation under these programs, these letters, logo, or statements do not claim product endorsement by these organizations or any Agency of the U.S. Government. This letter of transmittal is not a part of the attached report.

DOC-EMC702 2/26/2004



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*
914 WEST PATAPSCO AVENUE ! BALTIMORE, MARYLAND 21230-3432 ! PHONE (410) 354-3300 ! FAX (410) 354-3313

**Electromagnetic Compatibility Criteria
Test Report**

For the

**JRC FWA System - Type W <XL0>
Wireless Terminal**

Tested under

**FCC Certification Rules
Title 47 of the CFR, Part 101**

MET Report: EMC80940A-FCC101

August 13, 2008

Prepared For:

**Japan Radio Co., Ltd.
2-1-4 Fukuoka, Kamifukuoka-shi
Saitama, 356-0011, Japan**

Prepared By:
MET Laboratories, Inc.
914 W. Patapsco Ave
Baltimore, MD 21230




Electromagnetic Compatibility Criteria Test Report

For the


**JRC FWA System - Type W <XL0>
Wireless Terminal**

Tested Under

**FCC Certification Rules
Title 47 of the CFR, Part 101, for Intentional Radiators**



Liming Xu
Electromagnetic Compatibility Lab



Jennifer Sanchez
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of Part §101 of the FCC Rules under normal use and maintenance.



Shawn McMillen
Electromagnetic Compatibility Lab



Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	September 12, 2008	Final Issue.
1	November 24, 2008	Revision 1
2	December 11, 2008	Revision 2



Table of Contents

1	Requirements Summary	1
2	Equipment Configuration	2
2.1	Overview	2
2.2	Test Site	3
2.3	Description of Test Sample	3
2.4	Equipment Configuration.....	5
2.5	Support Equipment	5
2.6	Ports and Cabling Information	5
2.7	Mode of Operation	6
2.8	Method of Monitoring EUT Operation	6
2.9	Modifications	6
2.9.1	Modifications to EUT	6
2.9.2	Modifications to Test Standard	6
2.10	Disposition of EUT	6
3	Electromagnetic Compatibility Criteria for Intentional Radiators	7
3.1	Emission and Bandwidth.....	7
3.2	Emission Limitations, Conducted and Spurious Emissions	11
3.3	Transmitter Power Limitations.....	24
3.4	Modulation	26
3.5	Frequency Stability	28
3.6	Directional Antenna	30
3.7	MPE Calculation	31
4	Test Equipment	32



List of Tables

Table 1. Requirements Summary of EMC Part 15.101 Compliance Testing	1
Table 2. Equipment Configuration	5
Table 3. Ports and Cabling Information	5
Table 4. Radiated Emissions Test Results	17
Table 5. Transmission Power Limitation Test Results	25
Table 6. Carrier Frequency Deviations due to Temperature Instability	28
Table 7. Carrier Frequency Deviations Due to Voltage Variations	29
Table 8. Directional Antenna Test Results	30
Table 9. Test Equipment List	32

List of Graphs

Graph 1. Bandwidth Test Results - QPSK	9
Graph 2. Bandwidth Test Results – 16 QAM	10
Graph 3. Emissions Limitation Test Result, QPSK	12
Graph 4. Emissions Limitation Test Result, QPSK	12
Graph 5. Emissions Limitation Test Result, 16 QAM	13
Graph 6. Emissions Limitation Test Result, 16 QAM	13
Graph 7. Conducted Spurious Emissions Test Results, 1 GHz to 2.9 GHz	14
Graph 8. Conducted Spurious Emissions Test Results, 9 GHz to 12 GHz	14
Graph 9. Conducted Spurious Emissions Test Results, 12 GHz to 26.5 GHz	15
Graph 10. Radiated Spurious Emissions Test Results, 1 GHz to 2.9 GHz	18
Graph 11. Radiated Spurious Emissions Test Results, 2.9 GHz to 12 GHz	18
Graph 12. Radiated Spurious Emissions Test Results, 12 GHz to 26.5 GHz	19
Graph 13. Radiated Spurious Emissions Test Results, 26.5 GHz to 40 GHz	19
Graph 14. Radiated Spurious Emissions Test Results, 33 GHz to 50 GHz	20
Graph 15. Radiated Spurious Emissions Test Results, 50 GHz to 75 GHz	20
Graph 16. Radiated Spurious Emissions Test Results, 75 GHz to 110 GHz	21
Graph 17. Radiated Spurious Emissions Test Results, 110 GHz to 170 GHz	21
Graph 18. Radiated Spurious Emissions Test Results, 170 GHz to 260 GHz	22
Graph 19. Modulation Test Results, QPSK	27
Graph 20. Modulation Test Results, 16 QAM	27

List of Figures

Figure 1. Block Diagram of Test Configuration	4
---	---

List of Photographs

Photograph 1. Conducted Spurious Emissions Test Setup	16
Photograph 2. Radiated Spurious Emissions Test Setup	23



List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
d	Measurement Distance
dB	Deci Bels
dBμV	Deci-Bels above one micro Volt
dBμV/m	Deci-Bels above one micro Volt per meter
DC	Direct Current
DCF	Distance Correction Factor
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
f	Frequency
FCC	Federal Communications Commission
H	Magnetic Field
GHz	Giga Hertz
Hz	Hertz
ICES	Interference-Causing Equipment Standard
kHz	kilohertz
kPa	kilopascal
kV	kilo Volt
LISN	Line Impedance Stabilization Network
MHz	MegaHertz
μH	micro Henry
μF	micro Farad
μs	micro seconds
RF	Radio Frequency
RMS	Root-Mean-Square



1.0 Requirements Summary

Reference	Description	Compliance
Title 47 of the CFR, Part 101, Subpart C & G, §101.107 , 101.507	Frequency Stability	Complies
Title 47 of the CFR, Part 101, Subpart C, §101.109	Emission & Bandwidth	Complies
Title 47 of the CFR, Part 101, Subpart C, §101.111	Emission Limitations	Complies
Title 47 of the CFR, Part 15, Subpart G, §101.111	Spurious Emissions - Conducted	Complies
Title 47 of the CFR, Part 15, Subpart G, §101.111	Spurious Emissions - Radiated	Complies
Title 47 of the CFR, Part 101, Subpart C & G, §101.113, 101.513	Transmitter Power Limitations	Complies
Title 47 of the CFR, Part 15, Subpart G, §101.141	Modulation	Complies
Title 47 of the CFR, Part 15, Subpart C & G, §101.115, 101.517	Directional Antenna	Complies

Table 1. Requirements Summary of EMC Part 101 Compliance Testing



2.0 Equipment Configuration

2.1 Overview

An EMC evaluation to determine compliance of the JRC FWA System - Type W <XL0> Wireless Terminal with the requirements of Part §15.101 was performed. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the JRC FWA System - Type W <XL0> Wireless terminal. Japan Radio Co., Ltd., should retain a copy of this document, which should be kept on file for at least two years after the manufacturing of the JRC FWA System - Type W <XL0> Wireless Terminal has been **permanently** discontinued.

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part §15.101, in accordance with purchase order number AT04201118. All tests were conducted using measurement procedure EIA/TIA 603B.

Model(s) Tested:	JRC FWA System - Type W <XL0> Wireless Terminal
Model(s) Covered:	JRC FWA System - Type W <XL0> Wireless Terminal
EUT Specifications:	Primary Power: 110 VAC 50/60 Hz
	FCC ID: CKENTG337-XL0
	Equipment Code: TNB
	RF Power Output: EIRP = 61.1dBm (QPSK) and 58.55dBm(16QAM)
	Equipment Frequency Range: 24.264GHz-24.535GHz
	Modulation Type: QPSK and 16 QAM
Analysis:	The results obtained relate only to the item(s) tested.
Evaluated by:	Liming Xu
Date(s):	04/22/2005 – 07/06/2005



2.2 Test Site

All testing was performed at MET Laboratories, Inc., 914 W. Patapsco Ave., Baltimore, MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a semi-anechoic chamber. In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories. In accordance with §2.948(d), MET Laboratories has been accredited by the National Voluntary Laboratory Accreditation Program (Lab Code: 100273-0).

2.3 Description of Test Sample

The JRC FWA System - Type W <XL0>, Equipment Under Test (EUT) is a broadband wireless point-to-multipoint (PTMP) and point-to-point (PTP) communication system operating at 24-26 GHz that provides high-speed IP access using time division duplex (TDD), and adaptive modulation.




Figure 1. Block Diagram of Test Configuration



2.4 Equipment Configuration

The EUT was set up as outlined in Figure 1. All equipment incorporated as part of the EUT is included in the following list.

Ref. ID	Name / Description	Model Number	Serial Number
3	TYPEW-WT	NTG-337-XL0	NJJW000001T
4	WT-ADAPTER	NQD-2049	N/A
5	AC-ADAPTER	NBG-317	N/A

Table 2. Equipment Configuration

2.5 Support Equipment

Ref. ID	Name / Description	Model Number	Serial Number
1	TYPEW-AP-RFU	NTG-335-XL0	NJVW000001T
2	TYPEW-AP-IFU	NTJ-111	NJVW000001T

2.6 Ports and Cabling Information

Ref. ID	Port name on EUT	Cable Description or reason for no cable	Qty.	Length (m)	Shielded?
1	ANT	COAXIAL CABLE	1	3	YES
2	ANT	COAXIAL CABLE	1	3	YES
2	DC-48V	POWER SUPPLY CABLE	1	2	NO
2	ETHER	ETHERNET CABLE	1	10	NO
3	ETHER	ETHERNET CABLE	1	2	NO
4	ANT	ETHERNET CABLE	1	2	NO
4	PC	ETHERNET CABLE	1	10	NO
4	DC	POWER SUPPLY CABLE(DC)	1	1.8	NO
5	DC	POWER SUPPLY CABLE(DC)	1	1.8	NO
5	AC	POWER SUPPLY CABLE(AC)	1	1.8	NO

Table 3. Ports and Cabling Information



2.7 Mode of Operation

The Point-to-multipoint (PTMP) system is comprised of two sub-systems; the Access Point (AP) serves as the hub unit connects to a wide area network, and the Wireless Terminal serves as the remote unit and connects to a local network.

Modulation types are QPSK and 16QAM. The modulation rate may be fixed or adaptive.

In normal operating mode the connections to the equipment are Ethernet. Management interfaces are available for management purposes.

2.8 Method of Monitoring EUT Operation

Visual indication of link status is given by LEDs on the WT Interface Unit. A flashing green “ETHER” LED and absence of a red “ALM” LED indicate that an RF is established and traffic is passing between the WT and associated AP.

If appropriately connected to Ethernet-enabled network devices (i.e. PCs) the connection state can be determined by a number of methods including using the PING command.

Remote monitoring is available through a management application.

2.9 Modifications

2.9.1 Modifications to EUT

No modifications were made to the EUT.

2.9.2 Modifications to Test Standard

No modifications were made to the test standard.

2.10 Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Japan Radio Co., Ltd. upon completion of testing.



3.0 Electromagnetic Compatibility Criteria for Intentional Radiators

3.1 Emission and Bandwidth

Test Requirement: § 101.109: (c) The maximum bandwidth which will be authorized per frequency assigned is set out in the table that follows.

Frequency band (MHz)	Maximum authorized band-width
928 to 929	25 kHz 156
932 to 932.5, 941 to 941.5	12.5 kHz 156
932.5 to 935, 941.5 to 944	200 kHz 1
952 to 960	200 KHz 156
1,850 to 1,990	10 MHz 1
2,110 to 2,130	3.5 MHz
2,130 to 2,150	800 or 1600 KHz 1
2,150 to 2,160	10 MHz
2,160 to 2,180	3.5 MHz
2,180 to 2,200	800 or 1600 KHz 1
2,450 to 2,483.5	625 KHz 2
2,483.5 to 2,500	800 KHz
3,700 to 4,200	20 MHz
5,925 to 6,425	30 MHz 1
6,425 to 6,525	25 MHz
6,525 to 6,875	10 MHz 1
10,550 to 10,680	5 MHz 1
10,700 to 11,700	40 MHz 1
12,200 to 12,7008	500 megahertz
13,200 to 13,250	25 MHz
17,700 to 18,140	220 MHz 1
18,140 to 18,142	2 MHz
18,142 to 18,580	6 MHz
18,580 to 18,820	20 MHz 1
18,820 to 18,920	10 MHz



Frequency band (MHz)	Maximum authorized band-width
18,920 to 19,160	20 MHz 1
19,160 to 19,260	10 MHz
19,260 to 19,700	220 MHz 1
21,200 to 23,600	50 MHz 14
24,250 to 25,250	40 MHz 7
27,500 to 28,350	850 MHz
29,100 to 29,250	150 MHz
31,000 to 31,075	75 MHz
31,075 to 31,225	150 MHz
31,225 to 31,300	75 MHz
38,600 to 40,000	50 MHz 7
Above 40,000	(3)

1 The maximum bandwidth that will be authorized for each particular frequency in this band is detailed in the appropriate frequency table in § 101.147. If contiguous channels are aggregated in the 928–928.85/952–952.85/956.25–956.45 MHz, the 928.85–929/959.85–960 MHz, or the 932–932.5/941–941.5 MHz bands, then the bandwidth may exceed that which is listed in the table.


Results: The EUT was found compliant with the requirement(s) of this section. The occupied bandwidth was tested at 24.227 GHz. All channels selected by the EUT are symmetrical across the band of 24.050-24.549 GHz for each modulation. Therefore, the occupied bandwidth limits would be satisfied by the same channel operating in the 24.264 – 24.535 GHz band.

Test Engineer(s): Liming Xu


Test Date(s): 04/22/05



Bandwidth Test Results



Graph 1. Bandwidth Test Results - QPSK



Graph 2. Bandwidth Test Results – 16 QAM



3.2 Emission Limitations, Conducted and Radiated Spurious Emissions

Test Requirement(s): §101.111(a): The mean power of emissions must be attenuated below the mean output power of the transmitter in accordance with (a)(2)(iv).

Test Procedure: The emission mask for LMDS and the 24 GHz Service shall use the equation in paragraph (a)(2)(iv) of this section and apply it only to the band edge of each block of spectrum, but not to subchannels established by licensees. The value of P in the equation is the percentage removed from the carrier frequency and assumes that the carrier frequency is the center of the actual bandwidth used. The emission mask can be satisfied by locating a carrier of the subchannel sufficiently far from the channel edges so that the emission levels of the mask are satisfied. The LMDS or 24 GHz emission mask shall use a value B (bandwidth) of 40 MHz, for all cases even in the case where a narrower subchannel is used (for instance the actual bandwidth is 10 MHz) and the mean output power used in the calculation is the sum of the output power of a fully populated channel. For block assigned channels, the out-of-band emission limits apply only outside the assigned band of operation and not within the band.


Results: The EUT was found compliant with the requirement(s) of this section. There are no detectable emissions up to 260 GHz. The emissions bandwidth was tested at 24.064 GHz for QPSK and 16QAM. All channels selected by the EUT are symmetrical across the band of 24.050-24.549 GHz for each modulation. Therefore, the emissions bandwidth limits would be satisfied by the same channel operating at 24.264 GHz band.

Test Engineer(s): Liming Xu


Test Date(s): 04/27/05




Emission Limitation Test Results




Graph 3. Emissions Limitation Test Result, QPSK



Graph 4. Emissions Limitation Test Result, QPSK




Graph 5. Emissions Limitation Test Result, 16 QAM




Graph 6. Emissions Limitation Test Result, 16 QAM




Conducted Spurious Emissions Test Results



Graph 7. Conducted Spurious Emissions Test Results, 1 GHz to 2.9 GHz



Graph 8. Conducted Spurious Emissions Test Results, 9 GHz to 12 GHz




Photograph 1. Conducted Spurious Emissions Test Setup




Radiated Spurious Emissions Test Results

Frequency (MHz)	EUT Azimuth (Degrees)	Antenna Polarity (H/V)	Antenna HEIGHT (m)	Uncorrected Amplitude (dBuv)	Antenna Correction Factor (dB) (+)	Cable Loss (dB) (+)	Corrected Amplitude (dBuv)	Limit (dBuv)	Margin (dB)
31.600	3.4	H	70.00	11.70	6.55	1.32	19.57	40.00	-20.43
31.600	1	V	70.00	25.56	6.18	1.32	33.07	40.00	-6.93
37.480	2.8	H	70.00	7.80	8.65	1.41	17.86	40.00	-22.14
37.480	1	V	0.00	21.59	8.10	1.41	31.10	40.00	-8.90
92.600	2.3	H	0.00	10.00	7.11	2.21	19.32	43.50	-24.18
92.600	1	V	0.00	17.04	7.24	2.21	26.50	43.50	-17.00
150.000	1.9	H	0.00	16.58	8.10	2.65	27.33	43.50	-16.18
150.000	1	V	0.00	19.49	8.20	2.65	30.34	43.50	-13.17
480.000	1.4	H	0.00	13.32	17.00	4.38	34.70	46.00	-11.30
480.000	1	V	0.00	16.91	17.50	4.38	38.79	46.00	-7.21
500.000	1.5	H	0.00	13.42	17.10	4.44	34.96	46.00	-11.04
500.000	1	V	0.00	13.32	17.50	4.44	35.26	46.00	-10.74


Table 4. Radiated Emissions Test Results




Graph 10. Radiated Spurious Emissions Test Results, 1 GHz to 2.9 GHz




Graph 11. Radiated Spurious Emissions Test Results, 2.9 GHz to 12 GHz




Graph 12. Radiated Spurious Emissions Test Results, 12 GHz to 26.5 GHz




Graph 13. Radiated Spurious Emissions Test Results, 26.5 GHz to 40 GHz



Graph 14. Radiated Spurious Emissions Test Results, 33 GHz to 50 GHz



Graph 15. Radiated Spurious Emissions Test Results, 50 GHz to 75 GHz



Graph 18. Radiated Spurious Emissions Test Results, 170 GHz to 260 GHz



Photograph 2. Radiated Spurious Emissions Test Setup



3.3 Transmitter Power Limitations

Test Requirement(s): § 101.113: The output power of a transmitter on any authorized frequency in this service may not exceed the following:

Frequency band (MHz) (EIRP)	Maximum allowable EIRP 12	
	Fixed 1 ,2 (dBW)	Mobile (dBW)
928.0–929.0(2)	+17	
932.0–932.5(2)	+17	
932.5–935.0	+40	
941.0–941.5(2)	+30	+14
941.5–944.0	+40	
952.0–960.0(2)	+40	+14
1,850–1,990	+45	
2,110–2,150	+45	
2,150–2,180 3	+45	
2,180–2,200	+45	
2,450–2,500	+45	
2,500–2,686		
2,686–2,690	+45	
3,700–4,200	+55	
5,925–6,425	+55	
6,425–6,525		+35
6,525–6,875	+55	
10,550 to 10,600 5	+55	
10,600 to 10,680 5	+40	
10,700–11,700	+55	
12,200–12,700 11	+50	
12,700–13,200 4	+50	
13,200–13,250 4	+55	
14,200–14,400	+45	
17,700–18,600	+55	
18,600–18,800 6	+35	
18,800–19,700	5 +55	
21,200–23,600 10	+55	
24,250–25,250	5 +55	
27,500–28,350 9	+55	
29,100–29,250	(7)	
31,000 to 31,075 8, 9	30 dBW/MHz	30 dBW/MHz
31,075 to 31,225 8, 9	30 dBW/MHz	30 dBW/MHz
31,225 to 31,300 8, 9	30 dBW/MHz	30 dBW/MHz
38,600–40,000	+55	



Test Procedure: As required by 47 CFR 2.1046, *RF power output measurements* were made at the RF output terminals using an attenuator and a power meter. This test was performed with carrier modulated by a continuous phase modulation signal.

The average output power level of the modulated carrier was measured at the FR output terminals of the EUT.

Test Results: The EUT was found compliant with the requirement(s) of this section. The transmitter output power was tested at 24.064 GHz. All channels selected by the EUT are symmetrical across the band of 24.997-25.445 GHz for each modulation. Therefore, the transmitter output power limits would be satisfied by the 24.064 GHz emissions centered on the 24.264 GHz frequency.

EUT	Power Meter Reading (dBm)	Frequency (GHz)
WT Low Channel QPSK/16QAM	13.54/10.92	24.064
WT Middle Channel QPSK/16QAM	13.31/11.25	24.227
WT High Channel QPSK/16QAM	13.90/11.35	24.535

Table 5. Transmission Power Limitation Test Results

Test Engineer(s): Liming Xu

Test Date(s): 04/27/2005



3.4 Modulation

Test Requirements: §101.141(a): Microwave transmitters employing digital modulation techniques.


Test Results: The EUT was found compliant with the requirement(s) of this section.

Test Engineer: Liming Xu


Test Date: 04/27/2005



Modulation Test Results



Graph 19. Modulation Test Results, QPSK



Graph 20. Modulation Test Results, 16 QAM



3.5 Frequency Stability

Frequency Stability over Temperature Variations

Test Requirements: §2.1055(a)(1)

Test Procedures: As required by §2.1055(a)(1) of CFR 407, *frequency tolerance measurements* were made over the temperature range of -30°C to +50°C. The frequency measurements were made using direct input to a spectrum analyzer. Climatic control was accomplished using an environmental simulation chamber. The temperature was first lowered to -30°C and then raised hourly in 10° increments. The unit remained in the chamber during temperature transitions and during the measurement process.

Test Results: Frequency tolerance of carrier signal: 0.001% Per Pt.101.107(a) for a temperature variation from - 30°C to + 50°C at normal supply voltage. The frequency stability was tested at 24.05008 GHz. All channels selected by the EUT are symmetrical across the band of 24.050-24.549 GHz for their frequency control circuitry. Therefore, the frequency stability limits would be satisfied by the same channel operating in the 24.264 – 24.535 GHz band.

Temperature (°C)	Carrier Frequency (GHz)	Frequency Deviation (KHz)	Deviation Limit (KHz)
-30	24.142969	31 *	241
-20	24.142969	31 *	241
-10	24.142969	31 *	241
0	24.142969	31 *	241
+10	24.142969	31 *	241
+20	24.143000	0 *	241
+30	24.143000	0 *	241
+40	24.143000	0 *	241
+50	24.143000	0 *	241

Table 6. Carrier Frequency Deviations due to Temperature Instability

- * The frequency deviation is less than 31 KHz,
- * There is no detectable frequency variation when the frequency counter was set to 1kHz resolution.
- *The unit meets the requirements of 2.1055 (a)(1)

Test Engineer: Liming Xu

Test Date: 04/19/2005



Frequency Stability over Voltage Variations

Test Requirements: §2.1055(d)(1)

Test Procedures: As required by §2.1055(d)(1) of CFR 47, *frequency tolerance measurements* were made over changes in the supply voltage to the EUT from 85% to 115% of the nominal supply voltage using a variable transformer to vary the AC supply. The frequency measurements were made using direct input to a spectrum analyzer.

Test Results: Frequency tolerance of carrier signal: 0.001% Per Pt.101.107 for a variation in primary voltage from 85% to 115% of the rated supply.

Percentage of Rated Supply	DC/AC Voltage (V)	Carrier Frequency (GHz)	Frequency Deviation (Hz)	Deviation Limit (kHz)
85%	40.0/102	24.05008	50 *	241
100%	48.0/110	24.05008	50 *	241
115%	56.0/138	24.05008	50 *	241

Table 7. Carrier Frequency Deviations Due to Voltage Variations

- * The frequency deviation is less than 50 Hz,
- * There is no detectable frequency variation when the frequency counter was set to 50Hz resolution.

The EUT meets the requirements of 2.1055 (d)(1)

Test Engineer: Liming Xu

Test Date: 04/18/2005



3.6 Directional Antenna

- Test Requirements:** § 101.517: (a) Transmitting antennas may be omnidirectional or directional, consistent with coverage and interference requirements.
- (b) The use of horizontal or vertical plane wave polarization, or right hand or left hand rotating elliptical polarization must be used to minimize harmful interference between stations.
- (c) Directive antennas must be used at all DEMS User Stations and may be elevated no higher than necessary to assure adequate service.

Test Results: The EUT is compliant with the requirement(s) of this section.

	W-TYPE
	WT
	PLANAR
POLARIZATION	V/H
FREQUENCY	24.0GHZ-27GHZ
VSWR(MAX)	1.5
GAIN(MIN)[DBI]	47.2

Table 8. Directional Antenna Test Results

Test Engineer: Liming Xu

Test Date: 05/11/2005



3.7 MPE Calculation

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

MPE Limit Calculation: EUT's operating frequencies @ **25011.0 – 252360.0MHz**; highest conducted power = 13.90dBm therefore, Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²

EUT maximum antenna gain = **47.2 dBi**.

where, S = Power Density (mW/cm²)
P = Power Input to antenna (0.024W)
G = Antenna Gain (52480.75 numeric)

$$R = (0.024 * 52480.75 / 4 * 3.14 * 1.0)^{1/2} = (1288250 / 12.56)^{1/2} = \mathbf{320.26cm}$$

Notice in the User manual

FCC Radio-Frequency Exposure Statement:

This equipment generates and radiates radio-frequency energy. In order to comply with FCC radio-frequency radiation exposure guidelines for an uncontrolled environment, this equipment has to be installed and operated while maintaining a minimum body to antenna distance of **320 cm** based on continuous exposure of 30 minutes.



4.0 Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ANSI/NCSL Z540-1-1994 and ANSI/ISO/IEC 17025:2000.

All Tests		Test Date(s): 04/22/2005-05/11/2005			
MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1T4300	SEMI-ANECHOIC CHAMBER # 1	EMC TEST SYSTEMS	NONE	03-MAY-03	03-APR-06
1T4303	ANTENNA: BILOG	SCHAFNER-CHASE EMC	CBL6140A	13-MAY-04	13-MAY-05
1T2665	ANTENNA; HORN	EMCO	3115	28-MAR-05	28-MAR-06
1T2511	ANTENNA; HORN	EMCO	3115	28-JUN-04	28-JUN-05
1T4351	SPECTRUM ANALYZER	AGILENT	E7405A	28-SEP-04	28-SEP-05
1T4302	EMI RECEIVER	HEWLETT PACKARD	85462A	18-OCT-04	18-OCT-05
1T4320	UNIVERSAL RADIO COMMUNICATION TESTER	RHODE AND SCHWARZ	CMU200	09-AUG-04	09-AUG-07
1T4453	VECTOR SIGNAL GENERATOR	RHODE & SCHWARZ	SMIQ03	23-FEB-05	23-FEB-06
1T4356	POWER SENSOR	HEWLETT PACKARD	8485D	04-OCT-04	04-OCT-05
1T4476	POWER METER	HEWLETT PACKARD	EPM-442A	05-MAR-05	05-MAR-06
1T4080	SPECTRUM ANALYZER W/ MEMORY MODULE	HEWLETT PACKARD	8563A	16-JUL-04	16-JUL-05
1T4323	HARMONIC MIXER	HEWLETT PACKARD	11970 (18-110 GHZ)	SEE NOTE	
Ø	HARMONIC MIXER	OLESON MICROWAVE LABS	M06HWD (110-170GHZ)	SEE NOTE	
Ø	HARMONIC MIXER	OLESON MICROWAVE LABS	M04HWD (170-260GHZ)	SEE NOTE	

Table 9. Test Equipment List

Note: Functionally verified test equipment is verified using calibrated instrumentation at the time of testing.