

ATTACHMENT A.

ID LABEL INFORMATION AND LOCATION PHOTOS

1.1 ID Label Information

Following is a copy of the label that will be placed on the rear side of the cabinet.

Figure 3.1 PRODUCT LABEL

Both the FCC ID and compliance statement are included in the product label

Model NO : A526
TYPE No : C15R08050
POWER : AC 100 – 240 VAC 2.0 A
FCC ID : CKLA526
Serial No :

This device complies with part 15 of the FCC Rules Operation


is subject the following two conditions :

- (1) this device may not cause harmful interference , and**
- (2) this device must accept any interference received,**
including interference that may cause undesired operation.

“ Product complies with DHHS Rules-21 CFR subchapter J-applicable
at date of manufacture

HYUNDAI ELECTRONICS AMERICA
3101 North 1st Street, San Jose,CA95134
MANUFACTURED BY HYUNDAI ELECTRONICS INDUSTRIES CO., LTD

MADE IN KOREA

 Packard Bell	See installation instructions before connecting to the supply.	* Product Complies with DHS Radiation Performance Standard 21 CFR Subchapter j *
Model No. : A526 P/N : 6811880000  POWER : 100-240V ~ 2.0A 60/50 Hz FCC ID : CKLA526 Serial No. : HNMN043 00001  Manufactured OCTOBER 2000	This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.	Apparaten skall anslutas till jordat nätuttag. Connect only to a properly grounded outlet.
NEC Computers International B. V. Nieuweweg 279 PO Box 337 Wijchen The Netherlands	This Class B digital apparatus meets all requirements of the Canadian Interference-Causing Equipment Regulations. Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.	            E142408 LISTED I.T.E 0683 LR 65701
P/N 631 6333 445 Rev.00 MADE IN KOREA	Die in diesem Gerät entstehende Röntgenstrahlung ist durch eine eigensichere Kathodenstrahlröhre nach Anlage III Röntgenverordnung ausreichend abgeschirmt. Beschleunigungsspannung : Max. 27 kV	MATERIAL : PE PRINTED ID : TFPY
WARNING : Vor öffnen des Gerätes Netzstecker ziehen. Disconnect power before opening.		

1.2 Label Location Photos



The label shown shall be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time purchase.(Labeling requirements per 2.925)