




# RF EXPOSURE REPORT



Report No.: 17071442-FCC-H2

Supersede Report No.: N/A

|  |   |   |
|--|---|---|
| Applicant  | MFOURTEL MEXICO S.A. DE C.V.  |   |
| Product Name   | Smart Phone   |   |
| Model No.  | M4 B2   |   |
| Serial No.   | N/A   |   |
| Test Standard  | FCC 2.1093:2016   |   |
| Test Date  | December 22, 2017 to January 24, 2018   |   |
| Issue Date   | January 25, 2018  |   |
| Test Result  | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail              |   |
| Equipment complied with the specification  | <input checked="" type="checkbox"/>   |   |
| Equipment did not comply with the specification  | <input type="checkbox"/>  |   |
|   |  |  |
| Aaron Liang<br>Test Engineer   | David Huang<br>Checked By   |   |
| This test report may be reproduced in full only<br>Test result presented in this test report is applicable to the tested sample only |   |   |

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

| Country/Region | Scope                              |
|----------------|------------------------------------|
| USA            | EMC, RF/Wireless, SAR, Telecom     |
| Canada         | EMC, RF/Wireless, SAR, Telecom     |
| Taiwan         | EMC, RF, Telecom, SAR, Safety      |
| Hong Kong      | RF/Wireless, SAR, Telecom          |
| Australia      | EMC, RF, Telecom, SAR, Safety      |
| Korea          | EMI, EMS, RF, SAR, Telecom, Safety |
| Japan          | EMI, RF/Wireless, SAR, Telecom     |
| Singapore      | EMC, RF, SAR, Telecom              |
| Europe         | EMC, RF, SAR, Telecom, Safety      |

|             |                 |
|-------------|-----------------|
| Test Report | 17071442-FCC-H2 |
| Page        | 3 of 9          |

This page has been left blank intentionally.

# CONTENTS

|  |   |
|--|---|
| 1. REPORT REVISION HISTORY .....   | 5 |
| 2. CUSTOMER INFORMATION.....   | 5 |
| 3. TEST SITE INFORMATION .....   | 5 |
| 4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....                                  | 6 |
| 5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES. | 8 |
| 5.1 RF EXPOSURE.....   | 8 |
| 5.2 TEST RESULT .....  | 9 |

## 1. Report Revision History

| Report No.      | Report Version | Description | Issue Date       |
|-----------------|----------------|-------------|------------------|
| 17071442-FCC-H2 | NONE           | Original    | January 25, 2018 |
|                 |                |             |                  |
|                 |                |             |                  |
|                 |                |             |                  |
|                 |                |             |                  |

## 2. Customer information

|                  |   |
|------------------|---|
| Applicant Name   | MFOURTEL MEXICO S.A. DE C.V.  |
| Applicant Add    | Av. Ejército Nacional 436 Piso 3 Chapultepec Morales Miguel Hidalgo Distrito Federal 11570. |
| Manufacturer     | CK Telecom Limited  |
| Manufacturer Add | Technology Road.High-Tech Development Zone. Heyuan, Guangdong,P.R.China.                    |

## 3. Test site information

|                      |  |
|----------------------|--|
| Lab performing tests | SIEMIC (Shenzhen-China) LABORATORIES   |
| Lab Address          | Zone A, Floor 1, Building 2 Wan Ye Long Technology Park<br>South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China<br>518108 |
| FCC Test Site No.    | 535293   |
| IC Test Site No.     | 4842E-1  |
| Test Software        | Radiated Emission Program-To Shenzhen v2.0   |

## 4. Equipment under Test (EUT) Information

|                               |   |
|-------------------------------|---|
| Description of EUT:           | Smart Phone   |
| Main Model:                   | M4 B2   |
| Serial Model:                 | N/A   |
| Date EUT received:            | December 21, 2017   |
| Test Date(s):                 | December 22, 2017 to January 24, 2018   |
| Antenna Gain:                 | GSM850: -3dBi<br>PCS1900: -1dBi<br>UMTS-FDD Band V: -3dBi<br>UMTS-FDD Band II: -1dBi<br>LTE Band II: -1dBi<br>LTE Band IV: -3dBi<br>LTE Band VII: 0 dBi<br>LTE Band XII: -4dBi<br>Bluetooth/BLE: 1dBi<br>WIFI: 1dBi<br>GPS: -1dBi |
| Antenna Type:                 | PIFA Antenna  |
| Type of Modulation:           | GSM / GPRS: GMSK<br>EGPRS: GMSK,8PSK<br>UMTS-FDD: QPSK<br>LTE Band: QPSK, 16QAM<br>802.11b/g/n: DSSS, OFDM<br>Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK<br>BLE: GFSK<br>GPS: BPSK   |
| RF Operating Frequency (ies): | GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz<br>PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz<br>UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz<br>UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;      |

RX: 1932.4 ~ 1987.6 MHz

LTE Band II TX: 1850.7 ~ 1909.3MHz; RX : 1930.7 ~ 1989.3 MHz

LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7~ 2154.3 MHz

LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz

LTE Band XII TX:699.7 ~ 715.3 MHz; RX : 729.7~ 745.3MHz

WIFI: 802.11b/g/n(20M): 2412-2462 MHz

WIFI: 802.11n(40M): 2422-2452 MHz

Bluetooth& BLE: 2402-2480 MHz

GPS: 1575.42 MHz

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V: 102CH

UMTS-FDD Band II: 277CH

Number of Channels:

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Port:

USB Port, Earphone Port

Adapter:

Model: M4

Input: AC100-240V~50/60Hz,150mA

Input Power:

Output: DC 5V, 1000mA

Battery:

Model: M2400A

Spec: 3.7V, 2400mAh, 8.88Wh

Trade Name :

M4

GPRS/EGPRS Multi-slot class

8/10/11/12

FCC ID:

CLNM4B2

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>16</sup> where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



## 5.2 Test Result

### Bluetooth Mode:

| Modulation | CH   | Frequency (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|------------|------|-----------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| GFSK       | Low  | 2402            | 4.631                 | 5±1                 | 6                       | 3.981                  | 1.23   | 3     |
|            | Mid  | 2441            | 5.955                 | 5±1                 | 6                       | 3.981                  | 1.24   | 3     |
|            | High | 2480            | 5.217                 | 5±1                 | 6                       | 3.981                  | 1.25   | 3     |
| π /4 DQPSK | Low  | 2402            | 5.550                 | 5±1                 | 6                       | 3.981                  | 1.23   | 3     |
|            | Mid  | 2441            | 5.156                 | 5±1                 | 6                       | 3.981                  | 1.24   | 3     |
|            | High | 2480            | 5.395                 | 5±1                 | 6                       | 3.981                  | 1.25   | 3     |
| 8-DPSK     | Low  | 2402            | 5.559                 | 5±1                 | 6                       | 3.981                  | 1.23   | 3     |
|            | Mid  | 2441            | 5.126                 | 5±1                 | 6                       | 3.981                  | 1.24   | 3     |
|            | High | 2480            | 5.371                 | 5±1                 | 6                       | 3.981                  | 1.25   | 3     |

### BLE Mode:

| Modulation | CH   | Freq (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|------------|------|------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| GFSK       | Low  | 2402       | -4.756                | -4±1                | -3                      | 0.501                  | 0.16   | 3     |
|            | Mid  | 2440       | -4.293                | -4±1                | -3                      | 0.501                  | 0.16   | 3     |
|            | High | 2480       | -4.280                | -4±1                | -3                      | 0.501                  | 0.16   | 3     |

**Result:** Compliance

No SAR measurement is required.