

TABLE OF CONTENTS

APPLICANT: RECOTON CORPORATION

FCC ID: CLVIC40HP-T

TEST REPORT CONTAINING:

PAGE	1.....	TEST EQUIPMENT LIST AND TEST PROCEDURE
PAGE	2.....	TEST PROCEDURE CONTINUED
PAGE	3.....	RADIATION INTERFERENCE TEST DATA
PAGE	4.....	OCCUPIED BANDWIDTH
PAGE	5.....	OCCUPIED BANDWIDTH PLOT

EXHIBIT ATTACHMENTS:

EXHIBIT	1.....	FCC ID LABEL SAMPLE
EXHIBIT	2.....	FCC ID LABEL LOCATION
EXHIBIT	3.....	BLOCK DIAGRAM
EXHIBIT	4.....	SCHEMATIC
EXHIBIT	5.....	INSTRUCTION MANUAL
EXHIBIT	6A.....	FRONT VIEW EXTERNAL PHOTO
EXHIBIT	6B.....	REAR VIEW EXTERNAL PHOTO
EXHIBIT	7A.....	COMPONENT SIDE INTERNAL PHOTOS
EXHIBIT	7B.....	COPPER SIDE INTERNAL PHOTOS
EXHIBIT	8.....	TEST SET UP PHOTO
EXHIBIT	9.....	CIRCUIT DESCRIPTION

APPLICANT: RECOTON CORPORATION

FCC ID: CLVIC40HP-T

REPORT #: T:\CUS\R\REC\643U0\643u0rpt.doc

PAGE: TABLE OF CONTENTS LIST

APPLICANT: RECOTON CORPORATION  
FCC ID: CLVIC40HP-T

#### TEST EQUIPMENT LIST

1. X Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/  
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter  
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,  
S/N 3008A00372 Cal. 10/17/99
2. X Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3.    Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
4. X Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
5.    Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
6. X Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,  
1-18 GHz, S/N 2319
7.    18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
8.    Horn 40-60GHz: ATM Part #19-443-6R
9.    Line Impedance Stabilization Network: Electro-Metrics Model  
ANS-25/2, S/N 2604 Cal. 2/9/00
10.    Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
11.    Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
12.    Peak Power Meter: HP Model 8900C, S/N 2131A00545
13. X Open Area Test Site #1-3meters Cal. 12/22/99
14.    Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
15.    Signal Generator: HP 8614A, S/N 2015A07428
16.    Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N  
9706-1211 Cal. 6/10/00
17.    Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153  
Cal. 11/24/99
18.    AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
19.    Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
20.    Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
21.    Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

#### TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC. The UUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the UUT was 74.3oF with a humidity of 69%.

APPLICANT : RECOTON CORPORATION  
FCC ID : CLVIC40HP-T  
REPORT # : T:\CUS\R\REC\643U0\643u0rpt.doc  
PAGE # : 1

APPLICANT : RECOTON CORPORATION

FCC ID : CLVIC40HP-T

TEST PROCEDURE CONTINUED

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 74.3oF with a humidity of 69%.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: RECOTON CORPORATION  
FCC ID: CLVIC40HP-T  
REPORT NO.: T:\CUS\R\REC\643U0\643u0rpt.doc  
PAGE #: 2

APPLICANT: RECOTON CORPORATION  
 FCC ID: CLVIC40HP-T  
 NAME OF TEST: RADIATION INTERFERENCE  
 RULES PART NUMBER: 15.249

REQUIREMENTS:  
 FIELD STRENGTH FIELD STRENGTH S15.209  
 of Fundamental: of Harmonics 30 - 88 MHz 40 dBuV/m @3M  
 902-928 MHZ 88 -216 MHz 43.5  
 2.4-2.4835 GHz 216 -960 MHz 46  
 94 dBuV/m @3m 54 dBuV/m @3m ABOVE 960 MHz 54dBuV/m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS,  
 EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 dB BELOW  
 THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION  
 LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

TEST RESULTS: This unit DOES meet the FCC requirements.

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
914.20	56.80	2.90	24.14	83.84	10.16	H
1828.30	14.10	1.00	27.31	42.42	11.58	V

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard  
 Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Prese-  
 lector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an  
 appropriate antenna - see the test equipment list. The bandwidth of  
 spectrum analyzer was 100 kHz with an appropriate sweep speed. When an  
 emission was found, the table was rotated to produce the maximum  
 signal strength. The antenna was placed in both the horizontal and  
 vertical planes and the worse case emissions were reported. The spec-  
 trum was searched to at least the tenth(10) harmonic of the fundamen-  
 tal.

PERFORMED BY: JOSEPH SCOGLIO

DATE: DECEMBER 27, 2000

APPLICANT: RECOTON CORPORATION  
 FCC ID: CLVIC40HP-T  
 REPORT NO.: T:\CUS\R\REC\643U0\643u0rpt.doc  
 PAGE NO.: 3

APPLICANT: RECOTON CORPORATION  
FCC ID: CLVIC40HP-T  
NAME OF TEST: Occupied Bandwidth  
RULES PART NO.: 15.249  
REQUIREMENTS: The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

THE PLOT ON THE NEXT PAGE REPRESENTS THE EMISSIONS TAKEN FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 20 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO

DECEMBER 27, 2000

APPLICANT: RECOTON CORPORATION  
FCC ID: CLVIC40HP-T  
REPORT NO.: T:\CUS\R\REC\643U0\643u0rpt.doc  
PAGE NO.: 4

hp REF 60.0 dBμV ATTEN 10 dB +0 dB

MKR 913.350 1 MHz  
59.40 dBμV


10 dB/

RECOTON CORPORATION  
FCC ID : CLVIC40HP  
JOB # : 643U0

EXHIBIT #: 5

OFFSET  
-20.0  
dB

DL  
34.0  
dBμV



CENTER 913.347 MHz

RES BW 300 Hz (i) VBW 100 kHz

SPAN 200 kHz

SWP 15.0 sec