## **Compliance with 47 CFR 15.247(b)(5)**

"Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter."

The EUT is a wireless LAN operating in the 2.4 GHz band as a 15.247 hopper. The EUT will only be used with a separation distance of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). For this Class II permissive change, three new antennas have been added. The maximum peak conducted output power is 100 mW.

Since the transmit frequency is greater than 1.5 GHz, and the output power is less than 3 W ERP, the EUT is categorically excluded from routine environmental evaluation per 47 CFR 2.1091(c).

The MPE estimates are as follows:

Table 1 in 47 CFR 1.1310 defines the maximum permissible exposure (MPE) for the general population as 1 mW/cm<sup>2</sup>. The exposure level at a 20 cm distance from the EUT's transmitting antenna is calculated using the general equation:

 $S = (PG)/4\pi R^2$ 

Where:  $S = power density (mW/cm^2)$ 

P = power input to the antenna (mW)

G = numeric power gain relative to an isotropic radiator

R = distance to the center of the radiation of the antenna (20 cm = limit for MPE estimates)

PG = EIRP

Solving for S, the maximum power density 20 cm from the transmitting antenna is summarized in the following table:

## **MPE Estimate**

## FCC ID: CM6010-0914-00

Antenna Type	Manufacturer	Antenna Part No.	Transmit Frequency	Max Peak Conducted Output Power	Antenna Gain	Minimum Antenna Cable Loss	Power Density @ 20 cm	from 1.1310
			(MHz)	(mW)	(dBi)	(dB)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
Patch	Centurion	CAF94131	2400	100	1.5	0	0.028	1
Dipole	Radiall	R380.500.117	2400	100	2	0	0.032	1
Dipole	Radiall/Larsen	R380.500.116	2400	100	2	0	0.032	1

The power density does not exceed 1 mW/cm<sup>2</sup> at 20 cm; therefore, the exposure condition is compliant with FCC rules.

The applicant's radio is compliant with the requirements of 15.247(b)(5).