Occupied Bandwidth

FCC ID: CM676A91343-600

Occupied Bandwidth

Revision 2/4/02

Justification

The individuals and/or the organization requesting the test provided the modes, configurations and settings available to evaluate. While scanning the radiated emissions, all of the EUT parameters listed below were investigated. This includes, but may not be limited to, antennas, tuned transmit frequency ranges, operating modes, and data rates.

Channels in S	pecified Band	Investigated:
---------------	---------------	---------------

Mid

Operating Modes Investigated:

Typical

Data Rates Investigated:

Maximum

Output Power Setting(s) Investigated:

Maximum

Power Input Settings Investigated:

Battery

Software\Firmware Applied During Test

on Version	Unknown
	on Version

Description

The system was tested using standard operating production software to exercise the functions of the device during the testing.

Equipment Modifications

No EMI suppression devices were added or modified. The EUT was tested as delivered.

EUT and Peripherals

Description	Manufacturer	Model/Part Number	Serial Number
EUT	SpaceLabs Medical	91343-05	001

Measurement Equipment

Description	Manufacturer	Model	Identifier	Last Cal	Interval
Spectrum Analyzer	Tektronix	2784	AAO	03/08/2001	24 mo
Near field probe	EMCO	7405	IPD	No cal required	N/A



Occupied Bandwidth

Revision 2/4/02

Test Description

Requirement: Per 47 CFR 2.1049, the 20 dB occupied bandwidth was measured.

Configuration: The antenna is integral to the EUT, so a radiated measurement was made using a spectrum analyzer and a near field probe. A 300Hz resolution bandwidth with no video filtering and a peak detector were used. The RBW was sufficiently narrow to plot the actually bandwidth of the signal and not the filter response curve of the spectrum analyzer.

Completed by:

				Rev BETA 01/30/01	
EUT: 91343-05			Work Order:		
Serial Number: 001				09/05/02	
Customer: SpaceLabs Inc.			Temperature:		
Attendees: N/A		Tested by: Greg Kiemel	Humidity:		
Customer Ref. No.: N/A		Power: N/A	Job Site:	EV09	
TEST SPECIFICATIONS					
Specification: 47 CFR 2.1049	Year: Most Current	Method: TIA/EIA - 603	Year:	1993	
SAMPLE CALCULATIONS					
COMMENTS					
EUT OPERATING MODES					
Transmitting mid band					
DEVIATIONS FROM TEST STANDARD					
None					
REQUIREMENTS					
The 20 dB bandwidth shall be measured	The 20 dB bandwidth shall be measured				
RESULTS		20 dB Bandwidth			
ss 18.54 kHz					
SIGNATURE					
Tested By:					
DESCRIPTION OF TEST					
Occupied Bandwidth					

