

MPE Calculation

Product:	WiFi/BT Module
Model no.:	STMD1
FCC ID:	CNFSTMD1
Rating:	3.6VDC
RF Transmission Frequency:	For Bluetooth Low Energy/Bluetooth: 2402-2480MHz For Wi-Fi 2.4G: 2412~2462 MHz For Wi-Fi 5GHz: 5180MHz – 5320MHz, 5500MHz – 5720MHz, 5745MHz – 5825MHz
Antenna Type:	PIFA
Max Antenna Gain:	1.64dBi Max for 2.4GHz 4.58dBi max for 5.180GHz~5.240GHz; 4.37dBi max for 5.260GHz~5.320GHz; 3.68dBi max for 5.500GHz~5.720GHz; 3.50dBi max for 5.745GHz~5.825GHz
Description of the EUT:	The equipment supports Bluetooth Low Energy/Bluetooth BR+EDR /Wi-Fi functions. The TX and RX range is 2402MHz-2480MHz for Bluetooth, 2412MHz – 2462MHz for 2.4GHzWi-Fi, 5180MHz – 5320MHz, 5500MHz – 5720MHz, 5745MHz – 5825MHz for 5GHzWi-Fi

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1,500	/	/	f/1500	30
1,500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

for 5G Wi-Fi

Maximum output power at antenna input terminal (dBm):	16.8
Maximum output power at antenna input terminal (mW):	47.86
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	4.58
Maximum Antenna Gain (numeric):	4.58
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0436
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0

For 2.4G Wi-Fi

Maximum output power at antenna input terminal (dBm):	19.5
Maximum output power at antenna input terminal (mW):	89.13
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	1.64
Maximum Antenna Gain (numeric):	1.64
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0291
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0

For Bluetooth

Maximum output power at antenna input terminal (dBm):	8.06
Maximum output power at antenna input terminal (mW):	6.40
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	1.64
Maximum Antenna Gain (numeric):	1.64
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0021
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0

For BLE

Maximum output power at antenna input terminal (dBm):	4.99
Maximum output power at antenna input terminal (mW):	3.16
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	1.64
Maximum Antenna Gain (numeric):	1.64
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0010
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0

For simultaneous transmission

Simultaneous transmission configuration	Power density(mW/cm ²)	MPE Limit (mW/cm ²)
5G Wi-Fi+BT	0.0457	1.0
5G Wi-Fi+BLE	0.0446	1.0
2.4G Wi-Fi+BT	0.0312	1.0
2.4G Wi-Fi+BLE	0.0301	1.0

Result: Compliant

TUV SUD China, Shenzhen Branch

Reviewed by:

Prepared By:



John Zhi/ Project Manager
Date: 2022-03-16

Joe Gu/Project Engineer
Date: 2022-03-16