

RF Exposure Report

Report No.: SABERD-WTW-P20110669

FCC ID: COF-WMBACAT49

Test Model: WM-BAC-AT-49

Received Date: Nov. 21, 2020

Date of Evaluation: Dec. 29, 2020

Issued Date: Dec. 31, 2020

Applicant: Universal Global Scientific Industrial Co., Ltd.

Address: 141, Lane 351, Sec. 1, Taiping Road., Tsaotuen, Nantou 54261, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SABERD-WTW-P20110669	Original Release	Dec. 31, 2020

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN <PCB Antenna>	2412-2462	18.71	3.15	20	0.031	1.00
	5180-5240	16.95	4.12	20	0.025	1.00
	5260-5320	16.93	4.12	20	0.025	1.00
	5500-5700	16.89	4.12	20	0.025	1.00
	5745-5825	16.92	4.12	20	0.025	1.00
WLAN <Dipole Antenna>	2412-2462	20.00	6.19	20	0.083	1.00
	5180-5240	16.95	5.68	20	0.036	1.00
	5260-5320	16.93	5.68	20	0.036	1.00
	5500-5700	16.89	5.68	20	0.036	1.00
	5745-5825	16.92	5.68	20	0.036	1.00
BT	2402-2480	6.17	1.23	20	0.001	1.00

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible
- For PCB Antenna**
 2.4GHz: Directional gain = 0.14 dBi + 10log(2) = 3.15 dBi
 5.0GHz: Directional gain = 1.11dBi + 10log(2) = 4.12dBi
For Dipole Antenna
 2.4GHz: Directional gain = 3.18 dBi + 10log(2) = 6.19 dBi
 5.0GHz: Directional gain = 2.67dBi + 10log(2) = 5.68dBi

Conclusion:

The formula of calculated the MPE is:
 $CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$
 CPD = Calculation power density
 LPD = Limit of power density

$$\text{WLAN 2.4GHz} + \text{BT} = 0.083/1 + 0.001/1 = 0.084$$

$$\text{WLAN 5GHz} + \text{BT} = 0.036/1 + 0.001/1 = 0.037$$

The product WiFi 2.4G and WiFi 5G will not simultaneous transmissions, but 2.4G + BT & 5G + BT can operate at the simultaneous transmissions. The emission of the simultaneous operation has been evaluated and no non-compliance was found.

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---