



# RF EXPOSURE REPORT

**REPORT NO.:** SA140123E01  
**MODEL NO.:** NFA-BAC-MR-02  
**FCC ID:** COFNFABACMR02  
**RECEIVED:** Jan. 23, 2014  
**TESTED:** Feb. 07 to 11, 2014  
**ISSUED:** Feb. 21, 2014

**APPLICANT:** UNIVERSAL GLOBAL SCIENTIFIC  
INDUSTRIAL CO., LTD.

**ADDRESS:** 141, Lane 351, Sec. 1, Taiping Road.,  
Tsaotuen, Nantou 54261, Taiwan

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS:** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,  
R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION .....	4
2. RF EXPOSURE LIMIT .....	5
3. MPE CALCULATION FORMULA .....	5
4. CLASSIFICATION .....	5
5. ANTENNA GAIN .....	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER .....	7



## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140123E01	Original release	Feb. 21, 2014



## 1. CERTIFICATION

**PRODUCT:** 802.11ac/a/b/g/n + BT Wireless Module  
**BRAND NAME:** UG  
**MODEL NO.:** NFA-BAC-MR-02  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**APPLICANT:** UNIVERSAL GLOBAL SCIENTIFIC INDUSTRIAL CO., LTD.  
**TESTED DATE:** Feb. 07 to 11, 2014  
**STANDARDS:** FCC Part 2 (Section 2.1091)  
FCC OET Bulletin 65, Supplement C (01-01)  
IEEE C95.1

The above equipment (Model: NFA-BAC-MR-02) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Midoli Peng , **DATE:** Feb. 21, 2014  
( Midoli Peng, Specialist )

**APPROVED BY :** May Chen , **DATE:** Feb. 21, 2014  
( May Chen, Manager )

## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
<b>LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE</b>				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

r = distance between observation point and center of the radiator in cm

### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Brand	Model	Antenna Gain(dBi) <Including cable loss>	Frequency range (GHz to GHz)	Antenna Type	Connector Type	Cable Loss (dB)	Cable Length (mm)
Chain (0) Ant. 1 (WLAN Ant)	High-Tek Electronics Co.,Ltd	DC33001JB20	1.5	2.4~2.4835	PIFA	i-pex(MHF)	0.65	260
			0.68	5.15~5.35	PIFA	i-pex(MHF)	1.02	260
			2.77	5.47~5.75			1.07	
			2.72	5.75~5.85			1.09	
Chain (1) Ant. 2 (WLAN+BT Ant)	High-Tek Electronics Co.,Ltd	DC33001JB30	-1.55	2.4~2.4835	PIFA	i-pex(MHF)	0.98	390
			1.57	5.15~5.35	PIFA	i-pex(MHF)	1.53	390
			2.77	5.47~5.7			1.6	
			1.70	5.75~5.85			1.64	

**Note:** For 802. 11a/b/g mode: Max. antenna gain was chosen for final test.

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For WLAN: 15.247(2.4GHz)

### 802.11b

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412 - 2462	98.401	1.5	20	0.02765	1.00

### 802.11g

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412 - 2462	470.977	1.5	20	0.13235	1.00

### 802.11n(HT20)

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412 - 2462	795.974	1.5	20	0.22368	1.00

### 802.11n(HT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2422 - 2452	531.246	1.5	20	0.14929	1.00

### BT-LE(GFSK)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2402 - 2480	17.539	-1.55	20	0.00244	1.00

**For WLAN: 15.247(5GHz)**

**802.11a**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5745 - 5825	146.555	2.72	20	0.05454	1.00

**802.11ac (VHT20)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5745 - 5825	299.047	2.72	20	0.11129	1.00

**802.11ac (VHT40)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5755 - 5795	261.060	2.72	20	0.09716	1.00

**802.11ac (VHT80)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5775	148.175	2.72	20	0.05514	1.00



**For WLAN: 15.407(5GHz, 5150MHz~5350MHz)**

**802.11a**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5180 -5240, 5260 - 5320	39.902	1.57	20	0.01140	1.00

**802.11ac (VHT20)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5180 -5240, 5260 - 5320	67.900	1.57	20	0.01939	1.00

**802.11ac (VHT40)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5190 -5230, 5270 - 5310	56.017	1.57	20	0.01600	1.00

**802.11ac (VHT80)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5210, 5290	14.724	1.57	20	0.00420	1.00

**For WLAN: 15.407(5GHz, 5470MHz ~ 5600MHz & 5650MHz ~ 5725MHz)**

**802.11a**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5500 - 5580 & 5660 - 5700	40.832	2.77	20	0.01537	1.00

**802.11ac (VHT20)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5500 - 5580 & 5660 - 5700	74.158	2.77	20	0.02792	1.00

**802.11ac (VHT40)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5510 - 5550 & 5670	54.943	2.77	20	0.02068	1.00

**802.11ac (VHT80)**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5530	14.047	2.77	20	0.00529	1.00



**For Bluetooth:**  
**GFSK**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2402-2480	12.050	-1.55	20	0.00168	1.00

**8DPSK**

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2402-2480	11.455	-1.55	20	0.00159	1.00

--- END ---