

## ALPS ELECTRIC CO., LTD

HEAD OFFICE: 1-7, YUKIGAYA OTSUKA-CHO, OTA-KU, TOKYO, 145-8501 JAPAN PHONE:(03)3726-1211 FACSIMILE:(03)3728-1812

## COMMUNICATION DEVICES DIVISION, SOMA PLANT

1-2-1, OKINOUCHI, SOMA-CITY, FUKUSHIMA-PREF., 976-8501, JAPAN PHONE:+81-244-35-1207 FACSIMILE:+81-244-35-1602

Date: November 5, 2007

Federal Communications Commission **Equipment Authorization Division Application Processing Branch** 7435 Oakland Mills Road Columbia, Maryland 21046

Subject: Modular Approval (MA) Attestation for Bluetooth<sup>TM</sup> Transceiver Module, Model LICP76 C3 FCC ID: CWTLIGP76-C3

Model UGPZ6-C3, FCC ID: CWTUGPZ6-C3		
Item	FCC Requirements	UGPZ6-C3
1	Have its own RF shielding	Device is equipped with metal shielding to cover RF section. Refer to external photos
2	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the modules are buffered through logic or microprocessor inputs.
3	Have it own power supply regulation	Internal power regulators. The regulator operates within the +3.3Vdc +/- 0.2V range. Refer to Block diagram
4	Meet the antenna requirements of Section 15.203	The external antenna with unique Hirose U.FL connector.
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device is tested external to a host on an extender board in a standalone configuration.  Refer to test set-up configuration.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	FCC ID label drawing is submitted in the filing. Instructions (User Guide Information) are provided to our customers on how to apply the exterior label. Refer to FCC ID label drawing and Assembly drawing for location.
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	Refer to "User Guide Information"
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	MPE calculation is provided to demonstrate RF compliance for mobile modular approval.

Sincerely yours,

Signature:

Mame: Masaaki Ueki

Title: Compliance Team Leader

Company: Alps Electric Co., Ltd Communication Devices Division