Lectrosonics, Inc. FCC ID: DBZIFBT447A

4 FCC §2.1091 - RF Exposure

4.1 Applicable Standards

FCC §2.1091, (a) Requirements of this section are a consequence of Commission responsibilities under the National Environmental Policy Act to evaluate the environmental significance of its actions. See subpart I of part 1 of this chapter, in particular §1.1307(b).

Limits for Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	842/f	2.19/f	$*(180/f^2)$	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1	30

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Lectrosonics, Inc. FCC ID: DBZIFBT447A

4.3 MPE Prediction

IFBT4-470

Maximum output power at antenna input terminal (dBm): 24.00 Maximum output power at antenna input terminal (mW): 250 Prediction distance (cm): <u>20</u> Prediction frequency (MHz): 495.6 Maximum Antenna Gain, typical (dBi): 2.15 Maximum Antenna Gain (numeric): 1.64 Power density of prediction frequency at 20 cm (mW/cm²): 0.082 FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 0.330

Conclusion

The device is compliant with the requirement MPE limit for uncontrolled exposure. All transceiver modules must be installed with a separation distance of no less than **20** cm from all persons.

Report Number: R1809278-74 Page 12 of 36 FCC Part 74 Test Report