

Maximum Permissible Exposure (MPE) Calculation for IFBT4L

MPE Calculator

Lectrosonics DBZIFBT4L Test 061017

MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.

dBi = dB gain compared to an isotropic radiator.

S = power density in mW/cm²

				Antenna Gain (dBi)	7
		Output Power	dBd + 2.17 = dBi	dBi to dBd	2.17
Tx Frequency (MHz)	537.6	(Watts)	0.2500	Antenna Gain (dBd)	4.83
Cable Loss (dB)	0.0	(dBm)	23.98	Antenna minus cable (dBi)	7.00

Calculated ERP (mw) 760.221

Calculated EIRP (mw) 1252.968

EIRP = Po(dBm) + Gain (dB)

Radiated (EIRP) dBm 30.979

ERP = EIRP - 2.17 dB

Radiated (ERP) dBm 28.809

Occupational Limit	Power density (S)
1.79200	EIRP
	----- = mW/cm ²
General Public Limit	4 π r ²
0.35840	r (cm) EIRP (mW)

FCC radio frequency radiation exposure limits per 1.1310		
Frequency (MHz)	Occupational Limit	Public Limit
300-1,500	f/300	f/1500
1,500-10,000	5	1

FCC radio frequency radiation exposure limits per 1.1310		
Frequency (MHz)	Occupational Limit @ Tx Freq (mW/cm ²)	Public Limit @ Tx Freq (mW/cm ²)
300-1,500	1.792	0.3584
1,500-10,000	5	1

EIRP	Distance	Distance	S
milliwatts	cm	inches	mW/cm ²
1252.968	50.00	19.69	0.03988
1252.968	40.00	15.75	0.06232
1252.968	30.00	11.81	0.11079
1252.968	25.00	9.84	0.15953
1252.968	20.00	7.87	0.24927
1252.968	16.80	6.61	0.35327
1252.968	14.00	5.51	0.50871
1252.968	13.00	5.12	0.58999
1252.968	12.00	4.72	0.69242
1252.968	11.00	4.33	0.82403
1252.968	10.00	3.94	0.99708
1252.968	9.00	3.54	1.23096
1252.968	8.00	3.15	1.55794
1252.968	7.50	2.95	1.77259
1252.968	6.00	2.36	2.76967
1252.968	5.60	2.20	3.17947
1252.968	5.50	2.17	3.29613
1252.968	5.00	1.97	3.98832
1252.968	4.00	1.57	6.23175
1252.968	3.50	1.38	8.13943
1252.968	3.00	1.18	11.07867
1252.968	2.45	0.96	16.61108
1252.968	2.40	0.94	17.31042
1252.968	2.00	0.79	24.92701
1252.968	1.00	0.39	99.70803

Frequency (MHz)	Occupational Limit minimum Distance (cm)	Public Limit minimum distance (cm)
300-1,500	7.50	16.80
1,500-10,000	N/A	N/A

ROGERS LABS, INC.
 4405 W. 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214

LectroSonics Inc.
 MODEL: IFBT4
 Test #: 061017
 Test to: FCC Parts 2 and 74

FCCID#: DBZIFBT4L
 S/N:P452