

TEST REPORT

Reference No. : WTD18S07119019W
FCC ID..... : DC9-IVPCDI
Applicant : OPTEX CO., LTD.
Address : 5-8-12, Ogoto Otsu-Shi, Shifa-Ken Japan 520-0101
Manufacturer : OPTEX CO., LTD.
Address : 5-8-12, Ogoto Otsu-Shi, Shifa-Ken Japan 520-0101
Product : Door Interface
Models. : IVPC-DI
Standards : FCC CFR47 Part 15 Section 15.249:2017
Date of Receipt sample.... : 2018-07-24
Date of Test..... : 2018-07-25 to 2018-08-07
Date of Issue : 2018-08-08
Test Result : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:

Jack Wen

Jack Wen / Test Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

2.1 Test Facility

A. Accreditations for Conformity Assessment (International)

Country/Region	Accreditation Body	Scope	Note
USA	CNAS L3110	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		International Services	WPC
Thailand	NTC		-
Singapore	IDA		-
Note: 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476. 2. IC Canada Registration No.: 7760A			

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

	Page
1 COVER PAGE.....	1
2 LABORATORIES INTRODUCTION.....	2
3 CONTENTS	4
4 REVISION HISTORY	5
5 GENERAL INFORMATION.....	6
5.1 GENERAL DESCRIPTION OF E.U.T.....	6
5.2 DETAILS OF E.U.T.....	6
5.3 STANDARDS APPLICABLE FOR TESTING	7
5.4 TEST MODE	7
6 EQUIPMENT USED DURING TEST	8
6.1 EQUIPMENTS LIST	8
6.2 MEASUREMENT UNCERTAINTY.....	9
6.3 TEST EQUIPMENT CALIBRATION.....	9
7 TEST SUMMARY	10
8 CONDUCTED EMISSION	11
8.1 E.U.T. OPERATION.....	11
8.2 EUT SETUP	11
8.3 MEASUREMENT DESCRIPTION	11
8.4 TEST RESULT	12
9 RADIATION EMISSION TEST	14
9.1 EUT OPERATION.....	14
9.2 TEST SETUP	15
9.3 SPECTRUM ANALYZER SETUP.....	16
9.4 TEST PROCEDURE.....	17
9.5 FREQUENCY RANGE OF RADIATED MEASUREMENTS.....	18
9.6 TEST RESULT	19
10 PERIODIC OPERATION	21
11 BAND EDGE	22
11.1 TEST PROCEDURE.....	22
11.2 TEST RESULT	22
12 20 DB BANDWIDTH MEASUREMENT	23
12.1 TEST PROCEDURE.....	23
12.2 TEST RESULT	23
13 ANTENNA REQUIREMENT	24
14 PHOTOGRAPHS- TEST SETUP PHOTOS	25
14.1 PHOTOGRAPH – RADIATION EMISSION	25
14.2 PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP.....	27
15 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	28
15.1 EXTERNAL PHOTOS.....	28
15.2 INTERNAL PHOTOS	32

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD18S07119019W	2018-07-24	2018-07-25 to 2018-08-07	2018-08-08	original	-	Valid

5 General Information

5.1 General Description of E.U.T

Product Name:	Door Interface
Model No.:	IVPC-DI
Model Difference:	N/A
Frequency range:	916.80MHz
Type of modulation:	FSK
Antenna Gain:	1dBi
Antenna installation:	Integrated Antenna

5.2 Details of E.U.T

Ratings:	Input: 10 to 24 VAC/DC 500mA max
----------	----------------------------------

5.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC CFR47 Part 15 Section 15.249:2017 Telecommunication-RADIO FREQUENCY DEVICES-Intentional Radiators-Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.

5.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests.

And according to FCC 47 CFR Section 15.203(m):

Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle.
1 to 10 MHz	2	1 near top and 1 near bottom.
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

So frequency range over 908.40MHz to 908.42MHz is 1MHz or less, only the Middle channel were recorded and reported.

Test mode	Lower channel	Middle channel	Upper channel
Transmitting	/	916.80MHz	/

6 Equipment Used during Test

6.1 Equipments List

Conducted Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMI Test Receiver	R&S	ESCI	101155	2017.09.11	2018.09.10
2	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017.09.11	2018.09.10
3	Limitter	York	MTS-IMP-136	261115-001-0024	2017.09.11	2018.09.10
4	Cable	LARGE	RF300	-	2018.07.18	2019.07.17
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	2017.09.11	2018.09.10
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2018.07.18	2019.07.17
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2018.05.18	2019.05.17
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017.10.14	2018.10.15
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2018.05.18	2019.05.17
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2018.05.18	2019.05.17
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2018.04.07	2019.04.06
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2018.04.07	2019.04.06
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2018.04.20	2019.04.19
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2018.04.19	2019.04.18
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	2018.04.20	2019.04.19
4	Cable	HUBER+SUHNER	CBL2	525178	2018.04.20	2019.04.19
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date

1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2017-09-14	2018-09-13
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2017-09-14	2018-09-13
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2017-09-14	2018-09-13

6.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)

6.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by GUANG ZHOU GRG METROLOGY & TEST CO., LTD. address is No.163, Pingyun Rd. West of Huangpu Ave, Tianhe District, Guangzhou, Guangdong, China.

7 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207	C
Radiated Emission	15.249(a) 15.209 15.205(a)	C
Periodic Operation	15.35(c)	C
Band Edge	15.249 15.205 15.209	C
20dB Bandwidth	15:215(c)	C
Antenna Requirement	15.203	C
Note: C=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

8 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013;ANSI C63.4:2014
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)
Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> not applicable (Remark)

8.1 E.U.T. Operation

Operating Environment :


Temperature:	25.5 °C
Humidity:	51 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.




8.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


8.4 Test Result

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	26.17	10.26	36.43	65.99	-29.56	QP	
2	0.1500	8.61	10.26	18.87	55.99	-37.12	AVG	
3	0.3660	22.47	10.42	32.89	58.59	-25.70	QP	
4	0.3660	11.66	10.42	22.08	48.59	-26.51	AVG	
5	0.4220	25.87	10.42	36.29	57.41	-21.12	QP	
6	0.4220	14.62	10.42	25.04	47.41	-22.37	AVG	
7	0.6740	18.51	10.45	28.96	56.00	-27.04	QP	
8	0.6740	8.43	10.45	18.88	46.00	-27.12	AVG	
9	1.6100	18.61	10.50	29.11	56.00	-26.89	QP	
10	1.6100	10.74	10.50	21.24	46.00	-24.76	AVG	
11	1.9020	19.85	10.54	30.39	56.00	-25.61	QP	
12	1.9020	13.58	10.54	24.12	46.00	-21.88	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	26.46	10.26	36.72	65.99	-29.27	QP	
2	0.1500	7.48	10.26	17.74	55.99	-38.25	AVG	
3	0.2860	17.02	10.40	27.42	60.64	-33.22	QP	
4	0.2860	6.11	10.40	16.51	50.64	-34.13	AVG	
5	0.3700	18.95	10.42	29.37	58.50	-29.13	QP	
6	0.3700	8.80	10.42	19.22	48.50	-29.28	AVG	
7	0.4260	21.93	10.42	32.35	57.33	-24.98	QP	
8	0.4260	11.75	10.42	22.17	47.33	-25.16	AVG	
9	0.7380	13.61	10.44	24.05	56.00	-31.95	QP	
10	0.7380	4.51	10.44	14.95	46.00	-31.05	AVG	
11	3.6020	7.82	10.74	18.56	56.00	-37.44	QP	
12	3.6020	0.21	10.74	10.95	46.00	-35.05	AVG	

9 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249&15.209&15.205

Test Method: ANSI 63.10: 2013;ANSI C63.4:2014

Measurement Distance: 3m

Test Result: Pass Fail

15.249(a)Limit:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

15.209 Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40(29.54+40)$
30 ~ 88	100	3	100	$20\log^{(100)} = (40)$
88 ~ 216	150	3	150	$20\log^{(150)} = (43.5)$
216 ~ 960	200	3	200	$20\log^{(200)} = (46)$
Above 960	500	3	500	$20\log^{(500)} = (54)$

Note: RF Voltage(dBuV)=20 log₁₀ RF Voltage(uV)

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth 10kHz
 Resolution Bandwidth 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth 10Hz

Video Bandwidth 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane; For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

9.5 Frequency range of radiated measurements.

According to FCC 47 CFR Section 15.33:

(a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

(1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

(3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.

(4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1) through (a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

Result: So the Frequency range of radiated form: 16MHz to 10GHz.

9.6 Test Result

Test Frequency: 12.8MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 10GHz

Frequency	Receiver Reading	Detector	Turntable Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.249/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP)	Degree	(m)	(H/V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)
35.94	40.45	QP	180	1.5	V	-14.19	26.26	40.00	-13.74
916.8	88.63	QP	51	1.5	H	2.02	90.65	114.00	-23.35
916.8	84.26	QP	342	1.6	V	2.02	86.28	114.00	-27.72
1833.6	53.04	QP	135	1.2	H	-14.26	38.78	74.00	-35.22
1833.6	55.04	QP	218	1.1	V	-14.26	40.78	74.00	-33.22
2750.4	49.27	QP	239	1.6	H	-12.54	36.73	74.00	-37.27
2750.4	51.72	QP	234	1.6	V	-12.54	39.18	74.00	-34.82
3667.2	46.17	QP	134	1.1	H	-8.04	38.13	74.00	-35.87
3667.2	47.01	QP	175	1.6	V	-8.04	38.97	74.00	-35.03

AV = Peak +20Log10(duty cycle) =PK+(-0.55) [refer to section 9 for more detail]

Frequency	PK	RX Antenna Polar	Duty cycle Factor	AV	FCC Part 15.249/209/205	
					Limit	Margin
(MHz)	(dBμV/m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
916.80	90.65	H	-0.55	90.10	94.00	-3.90
916.80	86.28	V	-0.55	85.73	94.00	-8.27
1833.60	38.78	H	-0.55	38.23	54.00	-15.77
1833.60	40.78	V	-0.55	40.23	54.00	-13.77
2750.40	36.73	H	-0.55	36.18	54.00	-17.82
2750.40	39.18	V	-0.55	38.63	54.00	-15.37
3667.20	38.13	H	-0.55	37.58	54.00	-16.42
3667.20	38.97	V	-0.55	38.42	54.00	-15.58

10 Periodic Operation

The duty cycle was determined by the following equation:


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

$$\text{Duty Cycle(\%)} = \text{Total On interval in a complete pulse train} / \text{Length of a complete pulse train} * \%$$

$$\text{Duty Cycle Correction Factor(dB)} = 20 * \text{Log}_{10}(\text{Duty Cycle})$$

Total transmission time(ms)	15.40
Length of a complete transmission period(ms)	16.40
Duty Cycle(%)	93.90
Duty Cycle Correction Factor(dB)	-0.55

Refer to the duty cycle plot (as below)



Date: 6.AUG.2018 23:01:17


11 Band Edge

Test Requirement:	15.249(d):Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.
Test Method:	ANSI C63.10:2013
Test Mode:	Transmitting

11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

11.2 Test Result



12 20 dB Bandwidth Measurement


Test Requirement:	FCC CFR47 Part 15 Section 15.215(c)
Test Method:	ANSI C63.10:2013
Test Mode:	Transmitting

12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 3kHz, VBW = 10kHz

12.2 Test Result

Frequency (MHz)	Bandwidth Emission (kHz)
916.80	98.00




13 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:


The EUT has Integrated Antenna. meets the requirements of FCC 15.203.



14 Photographs- Test Setup Photos

14.1 Photograph – Radiation Emission

Test frequency below 30MHz




Test frequency from 30MHz to 1GHz





Test frequency above 1GHz







14.2 Photograph – Conducted Emission Test Setup




15 Photographs - Constructional Details

15.1 External Photos














15.2 Internal Photos











ANT











====End of Report====