




RF Exposure Evaluation Declaration

FCC ID: DD4GLXD6Z3
APPLICANT: Shure Incorporated
Product: Wireless Guitar Pedal Receiver
Model No.: GLXD6+ Z3
Brand Name: 
FCC Rule Part(s): FCC Part 2 (Section 2.1091)

Reviewed By:

Jame Yuan

Jame Yuan

Approved By:

Robin Wu

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2107RSU040-U3	Rev. 01	Initial Report	08-21-2021	Valid

1. Product Information

1.1. Equipment Description

Product Name	Wireless Guitar Pedal Receiver
Model No.	GLXD6+ Z3
Serial No.	3AE12002409
Radio Specification	2.4GHz & 5.8GHz
Antenna Specification	Refer to clause 1.7
Power Type	AC/DC Adapter
Accessories	
AC/DC Adapter	Model No.: PS24US Input: 100 ~ 240V, 50/60Hz, 0.15A Output: 12.0V=0.4A

Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.

1.2. RF Specification under test

Frequency Range	2404 ~ 2478MHz 5729 ~ 5846MHz
Declared Channel Bandwidth	Full Bandwidth Mode: 2 MHz Half Bandwidth Mode: 1 MHz
Channel Number	2.4GHz: 36 5.8GHz: 55
Channel Spacing	1MHz
Type of Modulation	2-level CPM with Gaussian shaping (basically GFSK)
Antenna Number	2

Note 1: Total working frequencies refer to operation description.

Note 2: Two RF paths and antenna are the same and only one antenna can work during normal operation, it is switchable.

1.3. Antenna Details

Antenna Type	Frequency Band (MHz)	Max Peak Gain (dBi)
PIFA Antenna	2404	-0.76
	2442	0.65
	2478	0.08
	5729	3.10
	5788	4.45
	5846	4.79

1.4. Applied Standards

KDB 447498 D01v06

2. RF Exposure Evaluation

2.1. Test Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result

Product	Wireless Guitar Pedal Receiver
Test Item	RF Exposure Evaluation

Frequency Band (MHz)	Maximum Turn-up E.I.R.P (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
2404 ~ 2478	10	0.0020	1
5729 ~ 5846	10	0.0020	1

Note: 2.4GHz band and 5.8GHz band can't work simultaneously.

Conclusion:

The Max Power Density at R (20 cm) = $0.0020\text{mW/cm}^2 < 1\text{mW/cm}^2$.

So the EUT complies with the requirement.

_____ The End _____

Appendix - EUT Photograph

Refer to "2107RSU040-UE" file.