

# RF Exposure Statement

FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

**(A) Limits for Occupational/Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

**(B) Limits for General Population/Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz \*Plane-wave equivalent power density

NOTE 1: See Section 1 for discussion of exposure categories.

NOTE 2: The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirements for mobile and portable transmitters.

## 1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a portable device.

## 2. Measurement Result:

Using the formula:

$$S = (P \times G) / (4 \times \pi \times d^2)$$

where:

S = power density

P = transmitter conducted power in (W)

G = antenna numeric gain

d = distance to radiation center (cm<sup>2</sup>)

This is a portable device and the max peak output power is 14.72 dBm (29.65 mW)

$$(29.65 \times 1) / (4 \times \pi \times 20^2) = .005902 \text{ mW/cm}^2$$

The limit for uncontrolled f/1500 is .629 @ 944 MHz

THRESHOLD

Lower than the low threshold  $60/f \text{ GHz} = (63.03 \text{ mW})$ , this was measured at 951.875 MHz.  
d < 2.5 cm general population category.

The SAR measurement is not necessary.

NOTE:

To determine the worst case level to be used for the RF exposure statement, when possible we will make RF conducted at the antenna terminal measurements and EIRP measurements. The higher of the two measurements will be used. If using the RF conducted method, the antenna gain is added.