



## MEASUREMENT REPORT

### FCC PART 74 / RSS-210

---

**FCC ID:** DD4ULXD6G50  
**IC:** 616A-ULXD6G50  
**APPLICANT:** Shure Incorporated

**Product:** Wireless Boundary Transmitter  
**Model No.:** ULXD6/C G50, ULXD6/O G50  
**Brand Name:** SHURE  
**FCC Classification:** Licensed Non-Broadcast Station Transmitter (TNB)  
**FCC Rule Part(s):** Part 2, Part 74.861  
**IC Rule Part(s):** RSS-210 Issue 9, RSS-GEN Issue 4  
**Test Procedure(s):** ANSI C63.4-2014, ANSI/TIA-603-D 2010,  
KDB 971168 D01v02r02  
**Test Date:** September 22 ~ October 30, 2016

Reviewed By :

*Robin Wu*

( Robin Wu )

Approved By :

*Marlin Chen*

( Marlin Chen )



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI/TIA-603-D 2010. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

Report No.	Version	Description	Issue Date	Note
1609RSU01705	Rev. 01	Initial report	10-31-2016	Invalid
1609RSU01705	Rev. 02	Add the frequency deviation item	11-24-2016	Valid

---

## CONTENTS

Description	Page
<b>1. INTRODUCTION .....</b>	<b>6</b>
1.1. Scope .....	6
1.2. MRT Test Location .....	6
<b>2. PRODUCT INFORMATION .....</b>	<b>7</b>
2.1. Equipment Description.....	7
2.2. Operation Frequency / Channel List .....	7
2.3. Test Mode .....	7
2.4. EMI Suppression Device(s)/Modifications.....	7
<b>3. TEST EQUIPMENT CALIBRATION DATE .....</b>	<b>8</b>
<b>4. MEASUREMENT UNCERTAINTY.....</b>	<b>9</b>
<b>5. TEST RESULT .....</b>	<b>10</b>
5.1. Summary .....	10
5.2. RF Output Power .....	11
5.2.1. Test Limit .....	11
5.2.2. Test Procedure Used .....	11
5.2.3. Test Setting.....	11
5.2.4. Test Setup.....	11
5.2.5. Test Result.....	12
5.3. Frequency Stability .....	13
5.3.1. Test Limit .....	13
5.3.2. Test Procedure Used .....	13
5.3.3. Test Setting.....	13
5.3.4. Test Setup.....	14
5.3.5. Test Result.....	15
5.4. Occupied Bandwidth and Emission Mask .....	16
5.4.1. Test Limit .....	16
5.4.2. Test Procedure Used .....	16
5.4.3. Test Setting.....	16
5.4.4. Test Setup.....	17
5.4.5. Test Result.....	18
5.5. Frequency Deviation.....	30
5.5.1. Test Limit .....	30
5.5.2. Test Procedure Used .....	30
5.5.3. Test Setting.....	30
5.5.4. Test Setup.....	31
5.5.5. Test Result.....	31
5.6. Radiated Spurious Emission.....	32
5.6.1. Test Limit .....	32

5.6.2. Test Procedure Used ..... 32

5.6.3. Test Setting..... 32

5.6.4. Test Setup..... 33

5.6.5. Test Result..... 34

**6. CONCLUSION..... 36**

## §2.1033 General Information

<b>Applicant:</b>	Shure Incorporated
<b>Applicant Address:</b>	5800 West Touhy Avenue, Niles, IL, USA
<b>Manufacturer:</b>	Shure Incorporated
<b>Manufacturer Address:</b>	5800 West Touhy Avenue, Niles, IL, USA
<b>Test Site:</b>	MRT Technology (Suzhou) Co., Ltd
<b>Test Site Address:</b>	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
<b>MRT FCC Registration No.:</b>	809388
<b>MRT IC Registration No.:</b>	11384A
<b>FCC Rule Part(s):</b>	Part 74.861
<b>IC Rule Part(s):</b>	RSS-210 Issue 9, RSS-GEN Issue 4
<b>Model No.:</b>	ULXD6/C G50, ULXD6/O G50
<b>Test Device Serial No.:</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering

### Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.





## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	Wireless Boundary Transmitter
Model No.	ULXD6/C G50, ULXD6/O G50 (Note 1)
Frequency Range	470 ~ 534MHz
Conducted Power Levels	1mW & 10mW & 20mW (Note 2)
Type of Modulation	8PSK
Data Rate	468.75kbps
Channel Spacing	25kHz
Antenna Type	PIFA
Antenna Gain	-8.8dBi
<b>Components (Note 3)</b>	
Rechargeable Li-ion Battery	Model: SB900A OUTPUT: 3.7Vdc, 1320mAh,4.88Wh

Note 1: The difference between ULXD6/C and ULXD6/O is that the EUT has different built-in MIC.

Note 2: EUT has three power levels (1mW & 10mW & 20mW). Power levels are switchable among these power levels.

Note 3: The EUT is capable of operating with AA alkaline batteries or with the Shure SB900A rechargeable battery pack.

### 2.2. Operation Frequency / Channel List

G50 band

Channel	Frequency
LOW	470.125 MHz
...	...
MID	502.000 MHz
...	...
HIG	534.000 MHz

### 2.3. Test Mode

Test Mode	Mode 1: Transmit
-----------	------------------

### 2.4. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

### 3. TEST EQUIPMENT CALIBRATION DATE

#### Radiated Emission - AC1

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
MXE EMI Receiver	Agilent	N9038A	MY51210182	1 year	2017/08/03
Preamplifier	Agilent	83017A	MY52090106	1 year	2017/03/28
Loop Antenna	Schwarzbeck	FMZB1519	1519-041	1 year	2016/12/14
TRILOG Antenna	Schwarzbeck	VULB9162	9162-047	1 year	2016/11/07
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1167	1 year	2016/11/07
Digital Thermometer & Hygrometer	Yuhuaze	HTC-2	N/A	1 year	2016/12/20
Anechoic Chamber	TDK	Chamber-AC1	N/A	1 year	2017/05/10

#### Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MY52090106	1 year	2017/05/08
DC Power Supply	APECC	DPS-336030D	00002016	N/A	N/A
Audio Analyzer	Agilent	U8903B	MY55280009	1 year	2017/08/18
USB Wideband Power Sensor	Boonton	55006	8911	1 year	2017/05/08
Audio Analyzer	Agilent	U8903B	MY55280009	1 year	2017/08/19
Modulation Analyzer	HP	8901A	1205A01034	1 year	2017/05/19
Temperature/Humidity Meter	Yuhuaze	HTC-2	N/A	1 year	2016/12/20

Software	Version	Function
e3	V8.3.5	EMI Test Software



#### 4. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>Radiated Emission Measurement - AC1</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB
<b>Output Power - TR3</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.13dB
<b>Occupied Bandwidth - TR3</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.28%

## 5. TEST RESULT

### 5.1. Summary

**Company Name:** Shure Incorporated  
**FCC Classification:** Licensed Non-Broadcast Station Transmitter (TNB)  
**Tested Channel:** G50 Band (470.125MHz, 502.000MHz, 534.000MHz)

FCC Part Section(s)	IC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
74.861(e) (1)(ii)	RSS-210 [G.3.1]	RF Output Power	$\leq 250\text{mW}$ Conducted, $\leq 250\text{mW}$ EIRP	Conducted	Pass	Section 5.2
74.861(e) (4)	RSS-210 [G.3.3]	Frequency Stability	$\leq \pm 50\text{Hz}$		Pass	Section 5.3
74.861(e) (5), (6)	RSS-210 [G.3.2], [G.3.4]	Occupied Bandwidth	Operating Bandwidth $\leq 200\text{kHz}$ The mean power of emissions shall be attenuated below the mean output power of the transmitter as below: $(50\% \sim 100\%)*\text{OBW} \geq 25\text{dB}$ $(100\% \sim 250\%)*\text{OBW} \geq 35\text{dB}$ More than $250\%*\text{OBW}$ $\geq 43 + 10*\log(P)\text{dB}$ ETSI EN 300 422 Clause 8.3.2.2		Pass	Section 5.4
74.861(e) (3)	RSS-210 [G.3.5]	Frequency Deviation	$\leq \pm 75\text{kHz}$		N/A	Section 5.5
74.861(e) (6)	RSS-210 [G.3.4]	Radiated Spurious Emission	More than $250\%*\text{OBW} \geq 43 + 10*\log(P)\text{dB}$ ETSI EN 300 422 Clause 8.4.3	Radiated	Pass	Section 5.6

#### Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- For RF Output Power, we evaluated three power settings (1mW/10mW/20mW). For the other test items, we tested the lowest power setting 1mW and the maximum power setting 20mW.

## 5.2. RF Output Power

### 5.2.1. Test Limit

For FCC

The conducted power may not exceed 250mW in 470 ~ 608 and 614 ~ 698 MHz band.

For IC

The transmit E.I.R.P may not exceed 250mW in 470 ~ 608 and 614 ~ 698 MHz band.

### 5.2.2. Test Procedure Used


KDB 971168 D01v02r02 - Section 5.2.3

### 5.2.3. Test Setting

Average power measurement with average power meter

If the EUT can be configured to transmit continuously and at all times the EUT is transmitting at its maximum output power level, then a conventional wide-band RF power meter can be used.

### 5.2.4. Test Setup



### 5.2.5. Test Result

For Power Level - 1.0mW

Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	Limit (dBm)	Result
470.125	0.11	≤ 24.0	-8.69	≤ 24.0	Pass
502.000	0.20	≤ 24.0	-8.60	≤ 24.0	Pass
534.000	0.16	≤ 24.0	-8.64	≤ 24.0	Pass

For Power Level - 10.0mW

Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	Limit (dBm)	Result
470.125	10.00	≤ 24.0	1.20	≤ 24.0	Pass
502.000	10.08	≤ 24.0	1.28	≤ 24.0	Pass
534.000	10.03	≤ 24.0	1.23	≤ 24.0	Pass

For Power Level - 20.0mW

Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	Limit (dBm)	Result
470.125	12.89	≤ 24.0	4.09	≤ 24.0	Pass
502.000	12.94	≤ 24.0	4.14	≤ 24.0	Pass
534.000	12.95	≤ 24.0	4.15	≤ 24.0	Pass

Note: E.I.R.P (dBm) = Average Output Power (dBm) + Antenna Gain (dBi).

### **5.3. Frequency Stability**

#### **5.3.1. Test Limit**

The frequency tolerance of the transmitter shall be 0.005 percent.

#### **5.3.2. Test Procedure Used**


KDB 971168 D01v02r02 - Section 9

#### **5.3.3. Test Setting**

The EUT was connected to a frequency counter or spectrum analyzer through the antenna output of each transmitter. The EUT was then placed in a temperature chamber.

- a) The nominal frequency of the transmitter was measured and recorded.
- b) The temperature chamber was then set to  $-30^{\circ}\text{C}$ .
- c) Once the temperature had reached  $-30^{\circ}\text{C}$  the EUT was allowed to soak for 30 minutes.
- d) After soaking at  $-30^{\circ}\text{C}$  for thirty minutes the EUT was turned on and the transmit frequency was measured and recorded.
- e) Steps (b) through (d) were repeated for each temperature in  $10^{\circ}\text{C}$  steps from  $-20^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ .
- f) The EUT was then removed from the temperature chamber and allowed to adjust to nominal room temperature ( $22^{\circ}\text{C}$ ).
- g) The input voltage was checked and adjusted to the nominal level. The frequency was measured and recorded.
- h) The input voltage was then varied to 85% of its nominal level. The frequency was measured and recorded.
- i) The input voltage was then varied to 115% of its nominal level. The frequency was measured and recorded.

### 5.3.4. Test Setup



**5.3.5. Test Result**

Voltage (%)	Power (V <sub>DC</sub> )	Temp (°C)	Nominal Frequency (MHz)	Measured Frequency (MHz)	Deviation (%)	Limit (%)	Result
100%	3.7	-30	470.125	470.124993	-0.000001	0.005	Pass
			502.000	501.999920	-0.000016	0.005	Pass
			534.000	533.999852	-0.000028	0.005	Pass
		-20	470.125	470.124845	-0.000033	0.005	Pass
			502.000	502.000292	0.000058	0.005	Pass
			534.000	533.999961	-0.000007	0.005	Pass
		-10	470.125	470.124954	-0.000010	0.005	Pass
			502.000	502.000168	0.000033	0.005	Pass
			534.000	533.999532	-0.000088	0.005	Pass
		0	470.125	470.125052	0.000011	0.005	Pass
			502.000	502.000164	0.000033	0.005	Pass
			534.000	533.999775	-0.000042	0.005	Pass
		+10	470.125	470.125085	0.000018	0.005	Pass
			502.000	502.000891	0.000177	0.005	Pass
			534.000	534.000537	0.000101	0.005	Pass
		+20 (Ref)	470.125	470.125109	0.000023	0.005	Pass
			502.000	501.999891	-0.000022	0.005	Pass
			534.000	534.000172	0.000032	0.005	Pass
		+30	470.125	470.125242	0.000051	0.005	Pass
			502.000	501.999985	-0.000003	0.005	Pass
			534.000	534.000335	0.000063	0.005	Pass
		+40	470.125	470.125122	0.000026	0.005	Pass
			502.000	502.000085	0.000017	0.005	Pass
			534.000	533.999835	-0.000031	0.005	Pass
+50	470.125	470.125321	0.000068	0.005	Pass		
	502.000	502.000057	0.000011	0.005	Pass		
	534.000	534.000352	0.000066	0.005	Pass		
115%	3.45	+20	470.125	470.125466	0.000099	0.005	Pass
			502.000	502.000535	0.000107	0.005	Pass
			534.000	533.999697	-0.000057	0.005	Pass
85%	3.145	+20	470.125	470.125093	0.000020	0.005	Pass
			502.000	502.000199	0.000040	0.005	Pass
			534.000	534.000465	0.000087	0.005	Pass

## 5.4. Occupied Bandwidth and Emission Mask

### 5.4.1. Test Limit

#### For FCC:

The operating bandwidth shall not exceed 200 kHz.

The mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (i) On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB;
- (ii) On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB;
- (iii) On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth: at least  $43+10\log_{10}$  (mean output power in watts) dB.

#### For IC:

The occupied bandwidth for low-power radio apparatus shall not exceed the authorized bandwidth 200 kHz.

The transmitter output spectrum shall be within the mask defined in EN 300 422 Clause 8.3.2.2.

### 5.4.2. Test Procedure Used

KDB 971168 D01v02r02 - Section 4

### 5.4.3. Test Setting

#### Occupied Bandwidth

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least  $10\log$  (OBW / RBW) below the reference level.
- e) Set the detection mode to peak, and the trace mode to max hold.
- f) Use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the




measured bandwidth.

### **Emission Mask**

- a) The EUT was connected to a spectrum analyzer. The un-modulated carrier signal level was measured and recorded.
- b) The EUT was modulated with typical digital modulation.
- c) The spectrum analyzer center frequency was set to the EUT operating frequency; span was set to 2 MHz; resolution bandwidth was set to 1 MHz; video bandwidth set to 3 MHz; sweep time set to 3 s; after clear/write, max-hold was set; Marker 1 was set to Peak, then Marker 1 was set to reference value.
- d) The peak output power was recorded and used to set the reference level on the spectrum analyzer.
- e) The spectrum analyzer span was then set to 1.5 MHz; resolution bandwidth set to 2 kHz, video bandwidth set to 5 kHz, sweep time to Auto; trace set to Max Hold.

#### **5.4.4. Test Setup**




### 5.4.5. Test Result


Power Level (mW)	Frequency (MHz)	99% Occupied Bandwidth (kHz)	Result	FCC Emission Mask	IC Necessary Bandwidth
1	470.125	163.85	Pass	Pass	Pass
	502.000	162.88	Pass	Pass	Pass
	534.000	164.06	Pass	Pass	Pass
20	470.125	164.72	Pass	Pass	Pass
	502.000	164.20	Pass	Pass	Pass
	534.000	163.62	Pass	Pass	Pass

#### G50 Band 1mW - 99% Occupied Bandwidth


##### Channel 470.125MHz



##### Channel 502.000 MHz




##### Channel 534.000 MHz




### G50 Band 20mW - 99% Occupied Bandwidth


#### Channel 470.125MHz



#### Channel 502.000 MHz




#### Channel 534.000 MHz




### G50 Band 1mW - Emission Mask

#### Channel 470.125MHz

##### Reference Level




##### Occupied Bandwidth





#### Channel 502.000 MHz

##### Reference Level



##### Occupied Bandwidth







### G50 Band 20mW - Emission Mask

#### Channel 470.125MHz

##### Reference Level




##### Occupied Bandwidth





#### Channel 502.000 MHz

##### Reference Level



##### Occupied Bandwidth






### G50 Band 1mW - Necessary Bandwidth


#### Step 1 - 470.125MHz



#### Step 2 - 470.125MHz



#### Step 3 - 470.125MHz






### G50 Band 1mW - Necessary Bandwidth


#### Step 1 - 502.000MHz



#### Step 2 - 502.000MHz




#### Step 3 - 502.000MHz




### G50 Band 1mW - Necessary Bandwidth


#### Step 1 - 534.00MHz



#### Step 2 - 534.00MHz



#### Step 3 - 534.00MHz




### G50 Band 20mW - Necessary Bandwidth


#### Step 1 - 470.125MHz



#### Step 2 - 470.125MHz



#### Step 3 - 470.125MHz




### G50 Band 20mW - Necessary Bandwidth


#### Step 1 - 502.000MHz



#### Step 2 - 502.000MHz



#### Step 3 - 502.000MHz




### G50 Band 20mW - Necessary Bandwidth


#### Step 1 - 534.00MHz



#### Step 2 - 534.00MHz



#### Step 3 - 534.00MHz



## 5.5. Frequency Deviation

### 5.5.1. Test Limit

#### For FCC

Any form of modulation may be used. A maximum deviation of  $\pm 75$  kHz is permitted when frequency modulation is employed.

#### For IC

##### Amplitude Modulation

Equipment employing amplitude modulation (AM) shall have a modulation index that does not exceed 100%.

##### Frequency Modulation

Equipment employing frequency measurement (FM) modulation shall have a frequency deviation that does not exceed  $\pm 75$  kHz.

### 5.5.2. Test Procedure Used

KDB 971168 D01v02r02 - Section 3

### 5.5.3. Test Setting


Make the antenna port connect to a modulation analyzer. An audio signal generator was connected to the audio input port of the EUT.

- a) The EUT was modulated with a 1000 Hz modulating signal at 60% of the EUT's rated frequency deviation.
- b) With input level held constant the audio signal generator was varied from 20 Hz to 20 kHz.
- c) The positive and negative peak deviations were recorded and plotted.

The output of the antenna port of the EUT was connected to a modulation analyzer. An audio signal generator was connected to the audio input port of the EUT.

- a) The modulation response was measured separately for each of five frequencies (100Hz, 500Hz, 2500Hz, 10000Hz and 15000Hz).
- b) The input voltage of the audio signal generator was varied and frequency deviation was observed on the modulation analyzer.
- c) The frequency deviations were recorded and plotted.

#### 5.5.4. Test Setup



#### 5.5.5. Test Result

This test item is not applicable due to the EUT adopt digital modulation.

## 5.6. Radiated Spurious Emission

### 5.6.1. Test Limit

#### For FCC:

The mean power of emissions shall be attenuated below the mean output power of the transmitter. On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth: at least  $43+10\log_{10}$  (mean output power in watts) dB.

#### For IC:

The transmitter unwanted emissions shall meet the requirements in sections 8.4 of ETSI EN 300 422-1 v1.4.2 (2011-08).

### 5.6.2. Test Procedure Used

KDB 971168 D01v02r02 – Section 7

### 5.6.3. Test Setting

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurement and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 80cm high PVC support structure is placed on top of the turntable. The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized.

Per the guidance of ANSI/TIA-603-B-2002, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to




obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$


Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

#### 5.6.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



### 5.6.5. Test Result

For Power Level – 1mW

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Substitute Antenna Gain (dBi)	ERP (dBm)	FCC Limit (dBm)	IC Limit (dBm)	Result
<b>Channel 470.125 MHz</b>								
262.3	V	-77.4	0.2	1.5	-76.1	-13.0	-36.0	Pass
940.3	V	-64.6	0.5	0.9	-64.2	-13.0	-36.0	Pass
607.2	H	-67.4	0.4	0.9	-66.9	-13.0	-54.0	Pass
940.3	H	-64.2	0.5	0.9	-63.8	-13.0	-36.0	Pass
1410.4	V	-84.1	0.6	25.4	-59.3	-13.0	-30.0	Pass
1880.5	V	-84.6	0.7	25.7	-59.6	-13.0	-30.0	Pass
1410.4	H	-85.4	0.6	25.4	-60.6	-13.0	-30.0	Pass
1880.5	H	-87.0	0.7	25.7	-62.0	-13.0	-30.0	Pass
<b>Channel 502.000 MHz</b>								
262.3	V	-77.1	0.2	1.5	-75.8	-13.0	-36.0	Pass
820.6	V	-63.4	0.5	0.9	-63.0	-13.0	-54.0	Pass
238.1	H	-75.2	0.2	1.4	-74.0	-13.0	-36.0	Pass
813.8	H	-65.5	0.5	0.9	-65.1	-13.0	-54.0	Pass
1004.0	V	-89.2	0.5	24.5	-65.2	-13.0	-30.0	Pass
1506.0	V	-84.8	0.6	25.2	-60.2	-13.0	-30.0	Pass
1004.0	H	-89.0	0.5	24.5	-65.0	-13.0	-30.0	Pass
1506.0	H	-84.4	0.6	25.2	-59.8	-13.0	-30.0	Pass
<b>Channel 534.000 MHz</b>								
262.8	V	-78.6	0.2	1.5	-77.3	-13.0	-36.0	Pass
860.8	V	-63.7	0.5	0.9	-63.3	-13.0	-54.0	Pass
229.8	H	-74.3	0.2	1.5	-73.0	-13.0	-54.0	Pass
765.3	H	-63.3	0.4	0.9	-62.8	-13.0	-54.0	Pass
1068.0	V	-88.9	0.5	24.3	-65.1	-13.0	-30.0	Pass
1602.0	V	-86.7	0.7	26.6	-60.8	-13.0	-30.0	Pass
1068.0	H	-87.9	0.5	24.3	-64.1	-13.0	-30.0	Pass
1602.0	H	-87.4	0.7	26.6	-61.5	-13.0	-30.0	Pass

Note: ERP (dBm) = SG Reading (dBm) - Cable Loss (dB) + Substitute Antenna Gain (dBi).

For Power Level – 20mW

Frequency (MHz)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Substitute Antenna Gain (dBi)	ERP (dBm)	FCC Limit (dBm)	IC Limit (dBm)	Result
Channel 470.125 MHz								
773.0	V	-64.3	0.4	1.0	-63.7	-13.0	-54.0	Pass
940.3	V	-57.9	0.5	0.9	-57.5	-13.0	-36.0	Pass
756.0	H	-63.8	0.4	0.9	-63.3	-13.0	-54.0	Pass
940.3	H	-60.7	0.5	0.9	-60.3	-13.0	-36.0	Pass
1410.4	V	-85.2	0.6	25.4	-60.4	-13.0	-30.0	Pass
1880.5	V	-86.0	0.7	25.7	-61.0	-13.0	-30.0	Pass
1410.4	H	-86.5	0.6	25.4	-61.7	-13.0	-30.0	Pass
1880.5	H	-85.7	0.7	25.7	-60.7	-13.0	-30.0	Pass
Channel 502.000 MHz								
264.3	V	-77.5	0.2	1.3	-76.4	-13.0	-36.0	Pass
745.4	V	-66.1	0.4	0.8	-65.7	-13.0	-54.0	Pass
232.2	H	-73.8	0.2	1.3	-72.7	-13.0	-36.0	Pass
819.1	H	-62.9	0.5	0.9	-62.5	-13.0	-54.0	Pass
1004.0	V	-88.7	0.5	24.5	-64.7	-13.0	-30.0	Pass
1506.0	V	-84.2	0.6	25.2	-59.6	-13.0	-30.0	Pass
1004.0	H	-89.5	0.5	24.5	-65.5	-13.0	-30.0	Pass
1506.0	H	-85.1	0.6	25.2	-60.5	-13.0	-30.0	Pass
Channel 534.000 MHz								
265.7	V	-76.9	0.2	1.2	-75.9	-13.0	-36.0	Pass
768.7	V	-64.5	0.4	0.9	-64.0	-13.0	-54.0	Pass
235.6	H	-73.4	0.2	1.1	-72.5	-13.0	-36.0	Pass
753.6	H	-63.4	0.4	0.8	-63.0	-13.0	-54.0	Pass
1068.0	V	-89.3	0.5	24.3	-65.5	-13.0	-30.0	Pass
1602.0	V	-87.5	0.7	26.6	-61.6	-13.0	-30.0	Pass
1068.0	H	-88.4	0.5	24.3	-64.6	-13.0	-30.0	Pass
1602.0	H	-88.2	0.7	26.6	-62.3	-13.0	-30.0	Pass

Note: ERP (dBm) = SG Reading (dBm) - Cable Loss (dB) + Substitute Antenna Gain (dBi).

## 6. CONCLUSION

The data collected relate only the item(s) tested and show that the **Wireless Boundary Transmitter** is in compliance with Part 74 of the FCC Rules and RSS-210 Rules.

————— The End —————