
MT BCMDE 02

PRODUCT SPECIFICATION AND

MANUAL

Title	Certification Request Document		
Project Name	KORANDO C	Drawn	2012-03-08
		Released	2012-03-08
		Made by	B.S.Choi

Table of Contents

1. CONTENTS.....	3
2. ELECTRONIC SPEC.....	3
3. SPECIFICATION	4
4. CIRCUIT EXPLANATION.....	4

Title	Certification Request Document		
Project Name	KORANDO C	Drawn	2012-03-08
		Released	2012-03-08
		Made by	B.S.Choi

1. Contents

Type	Weak Signal Equip.
Name	Unit Assy - Body Control
Use	Utilizing the frequency of 134.2kHz RFID vehicle anti-theft device
Summary	<ol style="list-style-type: none"> 1. This Equip is designed to prevent car theft. 2. This Equip & Transponder communicate encryption algorithm mutually for User Authentication. 3. This equipment uses semiconductors and integrated circuits that are designed to have a high reliability. 4. Main Power use Regulator VCC of BCM.
Composition	<ol style="list-style-type: none"> 1. LF Base Station 2. Bobbin Antenna

2. ELECTRONIC SPEC

item	UNIT	Unit Assy - Body Control
Rated Voltage		DC 13.5V (TMS3705 DC 5.0V)
Operating Voltage Range		DC 9.0V ~ 16.0V (TMS3705 DC 4.5V~5.5V)
Operating Temp. Range		-30°C ~ +80°C
Storage Temp. Range		-40°C ~ +85°C
COIL INDUCTANCE		420uH ± 20(WITH KEY LOCK BODY)
COIL TURNS		95T

Title	Certification Request Document		
Project Name	KORANDO C	Drawn	2012-03-08
		Released	2012-03-08
		Made by	B.S.Choi

3. SPECIFICATION

Name	Unit Assy - Body Control
Type	Weak Signal Equip.
Equipment List	LF Transmitter-Receiver
Frequency	134.2 kHz
Antenna Type	Type : BOBBIN COIL ANTENNA
Oscillation Method	Crystal oscillation
Local clock frequency	4 MHz
Modulation Method	FSK
Communication Scheme	Two-Way Communication
Equipment use	Vehicle Antitheft Equip.
Operating Voltage	DC 13.5V (TMS3705 DC 5.0V)
Operating Temp.	-30°C ~ +80°C
Weight	BCM : 580g, IMMO ANTENNA : 37g
Dimension	Antenna : External diameter 45mm

4. CIRCUIT EXPLANATION

- 1) After IGNITION, When EMS Data transmitted to the receiver, the received Data is analyzed.
- 2) After data analyzing, When EMS need to order Write key or Challenge service, U1 send data to U5.
- 3) U5 what are transmitted data by U1 modulate FSK way, and then it transmit transponder via Antenna.
- 4) Transponder what receive data from U5 reply information what U5 is ordered after processing data.
- 5) Data received from the transponder to reply with U1 and U5 after the demodulation. U1 verify data from U5, and then the results are sent back to EMS.

Title		Certification Request Document	
Project Name	KORANDO C	Drawn	2012-03-08
		Released	2012-03-08
		Made by	B.S.Choi

FCC (Federal Communications Commission)

WARNING: This equipment may generate or use radio frequency energy.

Changes or modifications to this equipment may cause harmful interference unless the modifications are expressly approved in the instruction manual.

The user could lose the authority to operate this equipment if an unauthorized change or modification is made.

This device complies with Part 15 of the FCC's Rules. Operation is subject to the following two

Conditions:

1. This device may not cause harmful interference, and
2. This device must accept ant interference received, including interference that may cause undesirable operation

Title	Certification Request Document		
Project Name	KORANDO C	Drawn	2012-03-08
		Released	2012-03-08
		Made by	B.S.Choi