



## Certificate of Compliance

The Laboratory certifies that the device complies with the following specifications

**CFR 47 part 15.247**

Test report No.: 221FCC15.247-2001 dated 2002-01-08

**ETS 300 328 :Nov. 1996**

**EN 300 328-1 :2000-07**

**EN 300 328-2 :2000-07**

Test report No.: 221ETS328-2001 dated 2002-01-08

Product description: Wireless LAN Access point

Model No.: **WL-306**

Manufacturer: **3COM Corporation  
5400 Bayfront Plaza  
Santa Clara, CA 95052**


Test laboratory: CETECOM Inc.  
411 Dixon Landing Road  
Milpitas, CA 95035

FCC registration No.: 101450

Industry Canada Registration: IC-3925

The wireless LAN was tested with different antenna configurations. The different antennas and power settings to be used are described in annex 1 of this certificate

Milpitas, 16 January 2002  
Place, date

  
.....  
Technical Manager EMC/Radio

## Annex1

### WL-306 EIRP measurements

The WL 306 was tested with a combination of power settings and antennas. Some of the antennas were identical except the length of the cable (cable has a fix connection to the antenna).

The device will be delivered with cable length of 6, 20, and 50 ft. (2, 6 and 15 m). The measurements were done with the antenna with the highest gain and the maximum power setting for the different cable lengths.

The device will be manufactured with two different amplifiers. The amplifiers have slightly different amplification over the frequency range. The amplifier with the highest amplification was chosen for the final full test measurement and checks were performed for all applicable tests to ensure that the alternative power amplifier was also fully compliant.

The following tables show the max combination of antenna, cable length and power settings. It includes also the max values for the different power amplifiers RFMD and Infineon).

The power level will be set by the manufacturer and is not accessible for the user.

The following antenna, cable and power setting were determined to be compliant with the specifications:

### FCC requirements

Power Level Setting	Antenna cable/ft	Antenna gain/ dBi	“pc” value	Power Amp	Result
High	20	18	160	RFMD	Pass
	20	18	160	Infineon	Pass
	50	18	160	RFMD	Pass
	50	18	160	Infineon	Pass
	6	13	160	RFMD	Pass
	6	13	160	Infineon	Pass
	20	13	160	RFMD	Pass
	20	13	160	Infineon	Pass
	50	13	160	RFMD	Pass
	50	13	160	Infineon	Pass
	6	8	160	RFMD	Pass
	6	8	160	Infineon	Pass
	20	8	160	RFMD	Pass
	20	8	160	Infineon	Pass
	50	8	160	RFMD	Pass
	50	8	160	Infineon	Pass
Medium	6	18	110	RFMD	Pass
	6	18	110	Infineon	Pass
Low power (1)	6	18	76	RFMD	Pass
	6	18	76	Infineon	Pass
Low power (2)	6	18	66	RFMD	Pass
	6	18	66	Infineon	Pass
Note: All lower gain antennas and cable combinations not detailed above (4dBi, 2dBi etc) are covered by the above worst case measurements for FCC.					

## Annex1

### *ETS/EN Requirements*

Power Level Setting	Antenna cable/ft	Antenna gain/ dBi	“pc” value	Power Amp	Result
High	50	18	160	Infineon	Pass
	50	13	160	RFMD	Pass
	50	13	160	Infineon	Pass
	50	8	160	RFMD	Pass
	50	8	160	Infineon	Pass
	50	4	160	RFMD	Pass
	50	4	160	Infineon	Pass
	20	2.5/ 2	160	RFMD	Pass
	20	2.5/ 2	160	Infineon	Pass
	6	1	160	RFMD	Pass
	6	1	160	Infineon	Pass
Medium	50	13	110	RFMD	Pass
	50	13	110	Infineon	Pass
	6	8	110	RFMD	Pass
	6	8	110	Infineon	Pass
Low (1)	6	18	76	RFMD	Pass
	6	18	76	Infineon	Pass
Low (2)	6	18	66	RFMD	Pass
	6	18	66	Infineon	Pass

Note: All lower gain antennas and cable combinations not detailed above (4dBi, 2dBi etc) are covered by the above worst case measurements for the EU.