

TEST REPORT

Report No.: HK10060857-1

Computime Ltd.

Application
For
Certification
(Original Grant)
(FCC ID: D12GES2181)
(IC: 1700A-GES2181)

Transceiver

Prepared and Checked by:

Approved by:

Signed On File
Lau Chin Yu, Benny
Engineer

Chan Chi Hung, Terry
Senior Lead Engineer
Date: July 19, 2010

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

INTERTEK TESTING SERVICES

GENERAL INFORMATION

Computime Ltd.

**FCC: BRAND NAME: Computime, MODEL: GES2181
BRAND NAME: General Electric (GE), MODEL: PCT1*100*#****

**IC: BRAND NAME: Computime, MODEL: GES2181
BRAND NAME: General Electric (GE), MODEL: PCT1**

FCC ID: DI2GES2181

IC: 1700A-GES2181

Grantee:	Computime Ltd.
Grantee Address:	17/F, Great Eagle Centre, 23 Harbour Road, Wanchai, Hong Kong
Contact Person:	Philip Chung
Tel:	(852) 2260 0300
Fax:	(852) 2790 3996
e-mail:	N/A
Manufacturer:	Computime Ltd.
Manufacturer Address:	17/F, Great Eagle Centre, 23 Harbour Road, Wanchai, Hong Kong
Brand Name:	Computime / General Electric (GE)
FCC Model:	GES2181 / PCT1*100*#**
IC Model:	GES2181 / PCT1
Type of EUT:	Transceiver
Description of EUT:	Energy Saving Thermostat
Serial Number:	N/A
FCC ID / IC:	DI2GES2181 / 1700A-GES2181
Date of Sample Submitted:	June 15, 2010
Date of Test:	June 22, 2010
Report No.:	HK10060857-1
Report Date:	July 19, 2010
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

Report No.: HK10060857-1

FCC ID: DI2GES2181

IC: 1700A-GES2181

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

Computime Ltd.

**FCC: BRAND NAME: Computime, MODEL: GES2181
BRAND NAME: General Electric (GE), MODEL: PCT1*100*#****

**IC: BRAND NAME: Computime, MODEL: GES2181
BRAND NAME: General Electric (GE), MODEL: PCT1**

**FCC ID: DI2GES2181
IC: 1700A-GES2181**

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	Pass
6 dB Bandwidth	15.247(a)(2) / RSS-210 A8.2	Pass
Maximum Power Density	15.247(e) / RSS-210 A8.2	Pass
Out of Band Antenna Conducted Emission	15.247(d) / RSS-210 A8.5	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	Pass
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	Pass
Antenna Requirement	15.203	Pass (See Note 1)
Receiver Radiated Spurious Emissions	RSS-210 2.3	Pass
Digital Device Radiated Emissions	15.109 / ICES-003	Pass
Digital Device Conducted Emissions	15.107 / ICES-003	Pass

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology.....	1
1.4	Test Facility	2
2.0	<u>System Test Configuration</u>	3
2.1	Justification	3
2.2	EUT Exercising Software.....	3
2.3	Special Accessories	4
2.4	Equipment Modification	4
2.5	Measurement Uncertainty.....	4
2.6	Support Equipment List and Description	4
3.0	<u>Emission Results</u>	5
3.1	Field Strength Calculation.....	5
3.2	Radiated Emission Configuration Photograph.....	6
3.3	Radiated Emission Data	6
3.4	Worst Case RF Output Level Emission.....	6
3.4	Conducted Emission Configuration Photograph.....	6
3.5	Conducted Emission Data	6
3.6	RF Output Level Data	6
3.7	Worst Case Spurious Emission.....	6
3.8	Spurious Emission Data	6
4.0	<u>Measurement Results</u>	7
4.1	Maximum Conducted Output Power at Antenna Terminals	7
4.2	Minimum 6 dB RF Bandwidth	7
4.3	Maximum Power Density Reading.....	8
4.4	Out of Band Conducted Emissions	8
4.5	Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier).....	9
4.6	Transmitter Radiated Emissions in Restricted Bands	9
4.7	Radiated Spurious Emissions.....	10
5.0	<u>Equipment Photographs</u>	15
6.0	<u>Product Labelling</u>	15
7.0	<u>Technical Specifications</u>	15
8.0	<u>Instruction Manual</u>	15
9.0	<u>Miscellaneous Information</u>	16
9.1	Discussion Pulse Desensitivity	16
9.2	Calculation of Average Factor.....	16
9.3	Emissions Test Procedures	16
10.0	<u>Equipment List</u>	18

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a IEEE802.15.4 ZigBee transceiver operating at 2405 to 2480MHz with 5MHz channel spacing. The EUT is powered by 24VAC. The EUT is an Energy Saving Thermostat which can connect to 3 Heat/ 2 Cool conventional Heat Pump HVAC systems. It can communicate with In-Home Display in the same ZigBee network and the Utility Company. It will receive the message about the energy saving event and price reduction from the Utility Company.

The FCC Model: PCT1*100*#** is the same as the Model: GES2181 in hardware aspect. The different in model number represents different brand name. And the 5th digit represents CBKE or non-CBKE encryption method. The 9th digit represents model year. The “#” represents software version of CBKE or non-CBKE encryption method. The last two “**” represents different color.

The IC Model: PCT1 is the same as the Model: GES2181 in hardware aspect. The different model number represents different brand name.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

The Certification procedure of the transceiver for this transceiver (with FCC ID: DI2GES2181) is being processed as the same time of this application.

The receiver for this transmitter is exempted from the Part 15 technical rules 15.101(b).

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

INTERTEK TESTING SERVICES

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC and IC.

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The device was powered from 24VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

A Software called <Insight Desktop> is provided by the applicant for controlling the testing channel and power. The RF output power selection is for the setting of RF output power expected by the applicant. And it is going to be fixed on the firmware of the final end product power parameters of the RF module:

Channel	CH11	CH12	CH13	CH14	CH15	CH16	CH17	CH18
Frequency (MHZ)	2405	2410	2415	2420	2425	2430	2435	2440
RF Power Setting	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)

Channel	CH19	CH20	CH21	CH22	CH23	CH24	CH25	CH26
Frequency (MHZ)	2445	2450	2455	2460	2465	2470	2475	2480
RF Power Setting	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	5dBm (boost)	-5dBm	-10dBm

INTERTEK TESTING SERVICES

2.3 Special Accessories

There are no special software accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by Computime Ltd. will be incorporated in each production model sold/leased in the United States and Canada.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

N/A

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB μ V/m
- RR = RA - AG - AV in dB μ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V/m	
AF = 7.4 dB	RR = 18.0 dB μ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB μ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 7320 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 9.2 dB

3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.3885 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photos.pdf.

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Passed by 9.44 dB

3.6 Worst Case RF Output Level Emission

The worst case RF output level emission was found at 2440MHz.

3.7 RF Output Level Data

Judgment: Passed by 11.93dB.

3.8 Worst Case Spurious Emission

The worst case spurious emission on RF output port was found at 2483.9MHz.

3.9 Spurious Emission Data

Judgment: Passed by 0.24dB.

INTERTEK TESTING SERVICES

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

Test Setup:

The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

Frequency (MHz)	Maximum Antenna Gain = 0dBi	
	Output in dBm	Output in mWatt
Lowest Channel: 2405	17.61	57.68
Middle Channel: 2440	18.07	64.12
Highest Channel: 2480	6.46	4.43

EUT dBm max. output level = 18.07 dBm (+30 dBm or less)

Limit: ≤ 30 dBm

For RF Safety, the information is saved with filename: RF exposure.pdf.

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Frequency (MHz)	6 dB Bandwidth (kHz)
2405	1650
2440	1620
2480	1630

Limit: at least 500kHz

For electronic filing, the above plots are saved with filename: 6db.pdf

INTERTEK TESTING SERVICES

4.3 Maximum Power Density Reading, FCC Rule 15.247(e) :

The spectrum analyzer RES BW was set to 3kHz. In order to look for a peak, the START and STOP frequencies were set to the band edges of the maximum output passband. If there is no clear maximum amplitude in any given portion of the band, it may be necessary to make measurements at a number of bands defined by several START and STOP frequency pairs.

Cable loss: 1.0 dB

External Attenuation: 0 dB

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are added to the analyzer raw readings.

Frequency (MHz)	Power Density (dBm/3kHz)
2405	3.95
2440	4.57
2480	-7.39

Peak Power Density = 4.57 dBm/3kHz

Limit: 8dBm/ 3kHz

For electronic filing, the above plots are saved with filename: psd.pdf

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

The plots showed all spurious emission up to the tenth harmonic. They were found to be at least 20 dB below the highest level of the desired power in the passband.

For the electronic filing, the above plots are saved with filename: oob.pdf

INTERTEK TESTING SERVICES

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The following data list the significant emission frequencies, the limit and the margin of compliance.

Frequency (MHz)	OATS radiated field strength at carrier frequency measured at 3m (dB μ V/m)		Attenuation (dBc)	Calculated radiated field strength at the bandedge (dB μ V/m)	
	Peak	Average		Peak	Average
2483.5	109.6	79.1	35.84	73.76	43.26

Limit:

The average radiated field strength at bandedge should be smaller than 54 dB μ V/m and the peak radiated field strength at bandedge should be smaller than 74 dB μ V/m.

INTERTEK TESTING SERVICES

4.7 Radiated Spurious Emissions

Applicant: Computime Ltd.

Date of Test: June 20, 2010

Model: GES2181

Worst-Case Operating Mode: TX mode (Lowest Channel)

Table 1

**Radiated Emissions
Pursuant to FCC Part 15 Section 15.247: Emissions Requirement**

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	4810.000 *	27.2	33	34.9	59.6	30.5	29.1	54.0	-24.9
H	7215.000	29.1	33	37.9	64.5	30.5	34.0	54.0	-20.0
H	9620.000	20.9	33	40.4	58.8	30.5	28.3	54.0	-25.7
H	12025.000 *	23.6	33	40.5	61.6	30.5	31.1	54.0	-22.9
H	14430.000	25.0	33	40.0	62.5	30.5	32.0	54.0	-22.0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	4810.000 *	57.7	33	34.9	59.6	74.0	-14.4
H	7215.000	59.6	33	37.9	64.5	74.0	-9.5
H	9620.000	51.4	33	40.4	58.8	74.0	-15.2
H	12025.000 *	54.1	33	40.5	61.6	74.0	-12.4
H	14430.000	55.5	33	40.0	62.5	74.0	-11.5

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000MHz and average limit for frequencies over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Computime Ltd.

Date of Test: June 20, 2010

Model: GES2181

Worst-Case Operating Mode: TX mode (Middle Channel)

Table 2

**Radiated Emissions
Pursuant to FCC Part 15 Section 15.247: Emissions Requirement**

Polari- zation	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	4880.000 *	28.6	33	34.9	61.0	30.5	30.5	54.0	-23.5
H	7320.000 *	29.4	33	37.9	64.8	30.5	34.3	54.0	-19.7
H	9760.000	23.2	33	40.4	61.1	30.5	30.6	54.0	-23.4
H	12200.000 *	23.4	33	40.5	61.4	30.5	30.9	54.0	-23.1
H	14640.000	26.7	33	38.4	62.6	30.5	32.1	54.0	-21.9

Polari- zation	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	4880.000 *	59.1	33	34.9	61.0	74.0	-13.0
H	7320.000 *	59.9	33	37.9	64.8	74.0	-9.2
H	9760.000	53.7	33	40.4	61.1	74.0	-12.9
H	12200.000 *	53.9	33	40.5	61.4	74.0	-12.6
H	14640.000	57.2	33	38.4	62.6	74.0	-11.4

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000MHz and average limit for frequencies over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Computime Ltd.

Date of Test: June 20, 2010

Model: GES2181

Worst-Case Operating Mode: TX mode (Highest Channel)

Table 3

**Radiated Emissions
Pursuant to FCC Part 15 Section 15.247: Emissions Requirement**

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	4960.000 *	19.4	33	34.9	51.8	30.5	21.3	54.0	-32.7
H	7440.000 *	15.6	33	37.9	51.0	30.5	20.5	54.0	-33.5
H	9920.000	13.8	33	40.4	51.7	30.5	21.2	54.0	-32.8
H	12400.000 *	16.4	33	40.5	54.4	30.5	23.9	54.0	-30.1
H	14880.000	19.7	33	38.4	55.6	30.5	25.1	54.0	-28.9

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	4960.000 *	49.9	33	34.9	51.8	74.0	-22.2
H	7440.000 *	46.1	33	37.9	51.0	74.0	-23.0
H	9920.000	44.3	33	40.4	51.7	74.0	-22.3
H	12400.000 *	46.9	33	40.5	54.4	74.0	-19.6
H	14880.000	50.2	33	38.4	55.6	74.0	-18.4

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000MHz and average limit for frequencies over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Computime Ltd.
 Model: GES2181
 Operating mode: RX mode

Date of Test: June 20, 2010

Data Table 4 – 6
Radiated Emission Test Pursuant to RSS-210 Requirement

Channel Low

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	2405.000	43.2	33	29.4	39.6	54.0	-14.4
H	4810.000	39.2	33	34.9	41.1	54.0	-12.9
H	7215.000	37.9	33	37.9	42.8	54.0	-11.2
H	9620.000	36.6	33	40.4	44.0	54.0	-10.0
H	12025.000	37.9	33	40.5	45.4	54.0	-8.6

Channel Middle

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	2440.000	43.4	33	29.4	39.8	54.0	-14.2
H	4880.000	39.7	33	34.9	41.6	54.0	-12.4
H	7320.000	38.0	33	37.9	42.9	54.0	-11.1
H	9760.000	37.2	33	40.4	44.6	54.0	-9.4
H	12200.000	37.8	33	40.5	45.3	54.0	-8.7

Channel High

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	43.0	33	29.4	39.4	54.0	-14.6
H	4960.000	39.8	33	34.9	41.7	54.0	-12.3
H	7440.000	37.5	33	37.9	42.4	54.0	-11.6
H	9920.000	37.4	33	40.4	44.8	54.0	-9.2
H	12400.000	38.1	33	40.5	45.6	54.0	-8.4

- Notes:
1. Peak Detector Data unless otherwise stated.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative sign in the column shows value below limit.
 4. Horn antenna is used for the emission over 1000MHz.

Report No.: HK10060857-1
 FCC ID: DI2GES2181
 IC: 1700A-GES2181

INTERTEK TESTING SERVICES

Applicant: Computime Ltd.
Model: GES2181
Operating mode: On mode

Date of Test: June 20, 2010

Data Table 7

**Radiated Emissions
Pursuant to FCC Part 15 Section 15.109: Emissions Requirement**

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	32.431	37.1	16	10.0	31.1	40.0	-8.9
V	33.420	37.2	16	10.0	31.2	40.0	-8.8
H	35.760	36.8	16	10.0	30.8	40.0	-9.2
H	42.055	36.4	16	10.0	30.4	40.0	-9.6
H	47.105	35.0	16	11.0	30.0	40.0	-10.0
H	48.600	34.6	16	11.0	29.6	40.0	-10.4

Notes: 1. Negative sign (-) in the margin column signify levels below the limit.

INTERTEK TESTING SERVICES

5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

6.0 **Product Labelling**

For electronics filing, the FCC ID and IC label artwork and the label location are saved with filename: label.pdf.

7.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States and Canada.

INTERTEK TESTING SERVICES

9.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and calculation of factor such as averaging factor (calculation and timing diagram).

9.1 **Discussion Pulse Desensitivity**

Pulse desensitivity is not applicable for this device. The effective period (T_{eff}) is approximately $740\mu s$ for a digital "1" bit which is illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

9.2 **Calculation of Average Factor**

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100ms

Effective period of the cycle = 2.96ms

DC = $(2.96/100)ms$

Therefore, the averaging factor is found by $20\log 0.0296 = -30.5dB$.

9.3 **Emissions Test Procedures**

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003. A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

INTERTEK TESTING SERVICES

9.3 Emissions Test Procedures (cont'd)

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

10.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-0016	EW-0571	EW-0446
Manufacturer	R&S	EMCO	EMCO
Model No.	ESVS30	3104C	3146
Calibration Date	Apr 21, 2010	Nov 12, 2008	Apr 26, 2010
Calibration Due Date	Apr 21, 2011	Aug 13, 2010	Oct 26, 2011

Equipment	Spectrum Analyzer	Double Ridged Guide Antenna
Registration No.	EW-2188	EW-0194
Manufacturer	AGILENTTECH	EMCO
Model No.	E4407B	3115
Calibration Date	Dec 25, 2009	Dec 24, 2008
Calibration Due Date	Dec 31, 2010	Jun 24, 2010

2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN
Registration No.	EW-2500	EW-2501
Manufacturer	R&S	R&S
Model No.	ESCI	ENV-216
Calibration Date	Sep 20, 2009	Sep 09, 2009
Calibration Due Date	Sep 20, 2010	Sep 09, 2010

3) Measurement Test

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	R&S
Model No.	FSP30
Calibration Date	Jun 25, 2009
Calibration Due Date	Jun 25, 2010