

**Produkte**  
*Products*
**RF Exposure Statement: JP21R26X 002**

Page 1 of 2

**Client:** **NEC Corporation**  
 1753 Shimonumabe, Nakahara-ku, Kawasaki City, Kanagawa, 211-8666  
 Japan

**Test item:** **5G NR FR1 Base Station Sub6 Massive MIMO RU**

**Identification:** **MB5420-m5770-62**

**FCC Requirement**

According to FCC 1.1307(b), fixed RF source must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:

Equipment Use	Frequency Range	Power Density [mW/cm <sup>2</sup> ]	Average Time [min]
General Population / Uncontrolled Exposure	1.5 – 100GHz	1	30
Occupational / Controlled Exposure	1.5 – 100GHz	5	30

**Assessment Result**

The distance where the MPE limit for General Population / Uncontrolled Exposure is met is given in the following table:

Maximum EIRP [dBm]	Maximum EIRP [mW]	Distance [cm] Power Density = 1mW/cm <sup>2</sup>	Proposed Minimum RF Safety Distance [cm]
68.44	6982324.041	745.41	746

Note:

The distance [cm] is calculated according to the Friis formula:  $D = \sqrt{EIRP / (4\pi \cdot S)}$ , where

S = power density in mW/cm<sup>2</sup>

EIRP = Effective Isotropically Radiated Power in mW

The distance where the MPE limit for Occupational / Controlled Exposure is met is given in the following table:

Maximum EIRP [dBm]	Maximum EIRP [mW]	Distance [cm] Power Density = 5mW/cm <sup>2</sup>	Proposed Minimum RF Safety Distance [cm]
68.44	6982324.041	333.36	334

Note:

The distance [cm] is calculated according to the Friis formula:  $D = \sqrt{EIRP / (4\pi \cdot S)}$ , where

S = power density in mW/cm<sup>2</sup>

EIRP = Effective Isotropically Radiated Power in mW

**Prüfbericht - Nr.: 12603897 001**  
*Test Report No.:*

**Seite 2 von 2**  
*Page 2 of 2*

### **Conclusion**

The device complies with the FCC RF exposure requirements with minimum RF safety distance of 746cm for General Population / Uncontrolled Exposure and 334cm for Occupational / Controlled Exposure.

Refer to test report JP21R26X 001 for more details.