



Dish Technologies Battery Charger User Guide.

Model: NHGBC

The battery charger is design to be commercially installed.

Installation Steps:

1. Remove cover
2. Professionally install supply and load side wiring
3. Mount to Dish approved location
4. Install batteries and route cables to mainboard
5. Plug all mainboard connections in (supply, load and batteries)
6. Close cover

BLE Operation:

The BLE radio in the product will send beacons with encrypted status information.

Nearby Dish BLE sensors will receive the beacons and be able to decrypt the status information.

There are no installation steps necessary to configure the BLE radio for its intended functionality.

FCC Statements:

This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions:

(1) this device may not cause interference, and

(2) this device must accept any interference, including interference that may cause undesired operation of the device.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

The antenna must be installed and operated with a minimum distance of 20 cm between the radiator and typical nearby person locations.

Do not make any modifications to the product or its antenna.

Doing so will void your authority to operate the product.

This product has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.