



RF EXPOSURE REPORT

REPORT NO.: SA981102L25

MODEL NO.: BTD 300 Audio

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Sennheiser electronic GmbH & Co.KG

ADDRESS: Am Labor 1, D-30900 Wedemark Postfach 100
264, D-30892 Wedemark, Germany

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	2.8	1.91
EIRP Power	2.7	1.86

***Note:** The antenna is PCB antenna with -0.1dBi gain

Threshold for no SAR evaluation is 24.58mW
Transmitter power is 1.91mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold