



# RF EXPOSURE REPORT

**REPORT NO.:** SA980409L06

**MODEL NO.:** BTD 300i

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Sennheiser electronic GmbH & Co.KG

**ADDRESS:** Am Labor 1, D-30900 Wedemark Postfach 100  
264, D-30892 Wedemark, Germany

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	2.490	1.774
EIRP Power	2.490	1.774

**\*Note:** The antenna is PCB printing wire antenna with 0dBi gain

Threshold for no SAR evaluation is 24.580mW  
Transmitter power is 1.774mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold