

Report No. 264013-8

Test Report

Product UPCS Base Station

Name and address of the

applicant

Sennheiser Communications A/S Industriparken 27, 2750 Ballerup

Denmark

Name and address of the

manufacturer

Same as above

Model D10 BS PHONE

Rating 5.9V DC (External AC Adaptor) or 5.0V DC (Power from USB)

Trademark Sennheiser

Serial number /

Additional information DECT 6.0

Tested according to FCC Part 15, subpart D

Isochronous UPCS Device, 1920 – 1930 MHz

Industry Canada RSS 213, Issue 2

2 GHz License-exempt Personal Communications Service Devices (LE-PCS)

Order number 264013

Tested in period 2014.07.01 to 2014.10.07

Issue date 2015.01.13

Name and address of the testing laboratory

Nemko

FCC No: 994405 IC OATS: 2040D-1

Instituttveien 6 Kjeller, Norway

TEL: (+47) 22 96 03 30 FAX: (+47) 22 96 05 50

Prepared by [Frode Sveinsen]

Approved by [G. Suhanthakumar]

This report shall not be reproduced except in full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the current accreditation. This report was originally distributed electronically with digital signatures. For more information contact Nemko.



CONTENTS

1	INFORMATION	
1.1	Tested Item	
1.2	Description of Tested Device	
1.3	Exposure Evaluation	
1.4	Test Environment	
1.5	Test Engineer(s)	
1.6	Test Equipment	
1.7	Other Comments	4
2	TEST REPORT SUMMARY	5
2.1	General	5
2.2	Test Summary	
•	TEST RESULTS	-
3 3.1	Power Line Conducted Emissions	
3.1	Digital Modulation Techniques	
3.3	Labeling Requirements	
3.4	Channel Frequencies	
3.5	Antenna Requirement	
3.6	Automatic Discontinuation of Transmission	
3.7	Peak Power Output	
3.8	Emission Bandwidth B	
3.9	Power Spectral Density	17
3.10	In-Band Unwanted Emissions, Conducted	
3.11	Out-of-band Emissions, Conducted	
3.12	Carrier Frequency Stability	
3.13	Frame Repetition Stability	
3.14	Frame Period and Jitter	31
3.15	Monitoring Threshold, Least Interfered Channel	
3.16	Threshold Monitoring Bandwidth	35
3.17	Reaction Time and Monitoring Interval	
3.18 3.19	Time and Spectrum Window Access Procedure	38
3.19	Dual Access Criteria Check	42 12
3.21	Alternative Monitoring Interval	
3.21	•	
4	MEASUREMENT UNCERTAINTY	44
5	TEST SETUPS	
5.1	Frequency Measurements	
5.2	Timing Measurements	
5.3	Conducted Emission Test	
5.4	Power Line Conducted Emissions Test	
5.5	Monitoring Tests	46
6	TEST FOUIPMENT USED	47



TEST REPORT FCC part 15D Report no.: 264013-8

FCC ID: DMOCBDDGG

INFORMATION 1

1.1 **Tested Item**

Name :	Sennheiser
Model name :	D10 BS PHONE
FCC ID:	DMOCBDDGG
Industry Canada ID :	2099A-D10BSPHONE
Serial number :	1
Hardware identity and/or version:	IFB V4D, WCB V2C
Software identity and/or version :	V0122
Tested to IC Radio Standard (RSS):	RSS-213 Issue 2, RSS-GEN Issue 4
Test Site IC Reg. Number :	IC 2040D-1
Frequency Range :	1921.536 – 1928.448 MHz
Number of Channels :	5 RF Channels, 5x12 = 60 TDMA Duplex Channels
Type of Modulation :	Digital (Gaussian Frequency Shift Keying)
Conducted Output Power :	106 mW (Peak)
Antenna Connector :	None
Number of Antennas :	2
Antenna Diversity Supported :	Yes
Power Supply :	AC Adaptor Model: PSAA05U-060 or Power from USB port

1.2 **Description of Tested Device**

The EUT is a DECT Base Station and is a responding device as described in ANSI C63.17 and is designed to operate together with a DECT portable part (i.e. a handset), which is the initiating device.

1.3 **Exposure Evaluation**

The EUT is designed to be used on top of a table and the user manual contains text that it shall be used with a separation distance of at least 20cm from any persons. For the purposes of exposure evaluation this EUT is a mobile device. MPE Calculation at 20cm satisfying FCC requirements is submitted as a separate document.

The EUT is exempted from RF Exposure Evaluation to Industry Canada requirements since the output power complies with the power levels of section 2.5.2 of RSS-102 Issue 4.



1.4 Test Environment

Temperature: 20.5 - 24.3 °C

Relative humidity: 36 – 58 % Normal test voltage: 120 V DC

The values are the limit registered during the test period.

1.5 Test Engineer(s)

Frode Sveinsen

1.6 Test Equipment

See list of test equipment in clause 6.

1.7 Other Comments

The Monitoring and Time and Spectrum Window Access tests were performed with Test Set-Up 6 (Ref. clause 5). A clock signal from the companion device was used to synchronize the Pulse Pattern Generator and the Spectrum Analyzer to the start of the DECT time window. The EUT was limited by administrative commands to operate on only two frequency carriers. For the tests where the EUT was required to operate on only one frequency carrier, one carrier was blocked by applying a CW interfering signal from RF Generator 3. The Pulse Pattern Generator was used to apply time synchronized interference to time windows where this was required.

Since the EUT was programmed to operate on only two RF carriers, it was only necessary with two RF generators for the monitoring tests, however a third generator was applied for the tests that required specific time slots to be blocked.

This EUT supports Least Interfered Channel procedure (LIC), the Monitoring and Time and Spectrum Window Access tests were conducted as specified for EUTs that support LIC procedure.

All tests except Power-Line Conducted Emissions were performed in conducted mode with a temporary antenna connector.



2 TEST REPORT SUMMARY

2.1 General

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15D for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 2 / RSS-GEN Issue 4 / RSP-100 Issue 10.

All tests were conducted is accordance with ANSI C63.4-2009 and ANSI C63.17-2013. Antenna Gain tests were made in a 3m fully-anechoic chamber.

A description of the test facility is on file with the FCC and Industry Canada.

⊠ New Submission	□ Production Unit
Class II Permissive Change	☐ Pre-production Unit
PUB Equipment Code	☐ Family Listing



THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.



2.2 Test Summary

Name of test	FCC CFR 47 Paragraph #	IC RSS-213 Paragraph #	Verdict
Power Line Conducted Emission	15.107(a) 15.207(a)	6.3 RSS-GEN 8.8	Complies
Digital Modulation Techniques	15.319(b)	6.1	Complies
Labeling requirements	15.19(a)(3)	3 RSP-100 3.1	Complies
Antenna Requirement	15.317, 15.203	RSS-GEN 8.3	Complies
Channel Frequencies	15.303	1	Complies
Automatic discontinuation of transmission	15.319(f)	4.3.4(a)	Complies
Emission Bandwidth	15.323(a)	6.4 RSS-GEN 6.6	Complies
In-band emissions	15.323(d)	6.7.2	Complies
Out-of-band emissions	15.323(d)	6.7.1	Complies
Output Power and Antenna Gain	15.319(c)(e), 15.31(e)	6.5 and 4.1(e) RSS-GEN 8.3	Complies
Power Spectral Density	15.319(d)	4.3.2.1	Complies
Carrier frequency stability	15.323(f)	6.2	Complies
Frame repetition stability	15.323(e)	4.3.4(c)	Complies
Frame period and jitter	15.323(e)	4.3.4(c)	Complies
Monitoring threshold, Least interfered channel	15.323(c)(2);(5); (9)	4.3.4(b)	Complies
Monitoring of intended transmit window and maximum reaction time	15.323(c)(1)	4.3.4(b)	Complies
Threshold monitoring bandwidth	15.323(c)(7)	4.3.4(b)	Complies
Reaction time and monitoring interval	15.323(c)(1);(5); (7)	4.3.4(b)	Complies
Access criteria test interval	15.323(c)(4);(6)	4.3.4(b)	Complies
Access Criteria functional test	15.323(c)(4);(6)	4.3.4(b)	Complies
Acknowledgements	15.323(c)(4)	4.3.4(b)	Complies
Transmission duration	15.323(c)(3)	4.3.4(b)	N/A ¹
Dual access criteria	15.323(c)(10)	4.3.4(b)	N/A ¹
Alterative monitoring interval	15.323(c)(10);(11)	4.3.4(b)	N/A ²
Spurious Emissions (Radiated)	15.319(g) 15.109(a) 15.209(a)	4.3.3 RSS-GEN 8.9	N/A ³

 $^{^{\}rm 1}$ Only applies for equipment that transmits unacknowledged control and signaling information

¹ Only applies for EUT that can be initiating device

 $^{^{\}rm 2}$ The client declares that the tested equipment does not implement this provision

³ Not required if the Conducted Out-of-Band Emissions test is Passed



3 TEST RESULTS

3.1 Power Line Conducted Emissions

FCC Part 15.207(a)

RSS-213 Clause 6.3, RSS-GEN Clause 8.8

Test Performed By: Tore Løvlien Date of Test: 16-Jul-2014

Measurement procedure: ANSI C63.4-2009 using 50 μ H/50 ohms LISN.


Test Results: Complies


Measurement Data: See attached graph, (Peak detector).

Highest measured value (L1 and N):

120V AC 60Hz


Frequency	Level	Af	Limit	Margin	Det	Position	Verdict
[MHz]	[dBuV]	[dB]	[dBuV]	[dB]			[Pass/Fail]
0.415000	34.40	10.20	57.50	23.10	QP	N	Pass
0.480000	27.60	10.20	56.30	28.70	QP	N	Pass
0.180000	15.40	10.10	54.50	39.10	AV	N	Pass
0.210000	14.70	10.10	53.20	38.50	AV	L1	Pass
0.275000	18.10	10.10	51.00	32.90	AV	L1	Pass
0.415000	21.90	10.20	47.50	25.60	AV	N	Pass
0.480000	17.70	10.20	46.30	28.60	AV	N	Pass
0.690000	11.80	10.20	46.00	34.20	AV	N	Pass
0.875000	7.70	10.20	46.00	38.30	AV	N	Pass
1.230000	11.10	10.20	46.00	34.90	AV	L1	Pass
1.420000	9.70	10.20	46.00	36.30	AV	L1	Pass
2.015000	14.80	10.20	46.00	31.20	AV	N	Pass
2.245000	15.00	10.30	46.00	31.00	AV	N	Pass
2.820000	13.80	10.30	46.00	32.20	AV	N	Pass
4.530000	15.20	10.40	46.00	30.80	AV	N	Pass
4.760000	12.70	10.40	46.00	33.30	AV	N	Pass
7.765000	20.30	10.50	50.00	29.70	AV	N	Pass
8.120000	20.70	10.60	50.00	29.30	AV	N	Pass







120V AC 60Hz:





3.2 Digital Modulation Techniques

The EUT uses Multi Carrier / Time Division Multiple Access / Time Division Duplex and Digital GFSK modulation. For further details see the operational description provided by the applicant.

Requirement, FCC 15.319(b):

All transmissions must use only digital modulation techniques.

3.3 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

Requirements FCC 15.19

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

3.4 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
Upper Band Edge	1930.000
0 (Highest)	1928.448
1	1926.720
2	1924.992
3	1923.264
4 (Lowest)	1921.536
Lower Band Edge	1920.000

Requirement: FCC 15.303

Within 1920 -1930 MHz band for isochronous devices.



3.5 Antenna Requirement

Does the EUT have detachable antenna(s)? If detachable, is the antenna connector(s) nor	n-standard?	☐ Yes	⊠ No □ No		
The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.					
Requirement: FCC 15.203, 15.204, 15.317.					
3.6 Automatic Discontinuation of Transmission					
3.6 Automatic Discontinuation	of Transmission				
3.6 Automatic Discontinuation Does the EUT transmit Control and Signal		ES [] NO		

The following tests simulate the reaction of the EUT in case of either absence of information to transmit or operational failure after a connection with the companion device is established.

Number	Test	EUT Reaction	Verdict
1	Power removed from EUT	A	Pass
2	Switch Off EUT	N/A	Pass
3	Hook-On by EUT	N/A	Pass
4	Power Removed from Companion Device	В	Pass
5	Switch Off Companion Device	В	Pass
6	Hook-On by Companion Device	В	Pass

- A Connection breakdown, Cease of all transmissions
- B Connection breakdown, EUT transmits control and signaling information
- C Connection breakdown, Companion Device transmits control and signaling information
- N/A Not Applicable (EUT does not have On/Off switch and cannot perform Hook-On)

Requirements, FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.



TEST REPORT FCC part 15D Report no.: 264013-8

FCC ID: DMOCBDDGG

3.7 **Peak Power Output**

Test Method:

ANSI C63.17, clause 6.1.2.

Test Results: Complies

Measurement Data:

Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Antenna Gain (dBi)	Maximum Radiated Output Power (dBm)
4	1921.536	20.2	2.0*	22.2
2	1924.992	20.3	2.0*	22.3
0	1928.448	20.3	2.0*	22.3

^{*}Antenna Gain is value declared by manufacturer

For this test it was also checked that input voltage variation of 85 and 115% of nominal value did not have any effect on the measured output power.

Limit:

Conducted: 100 μ W x SQRT(B) where B is the measured Emission Bandwidth in Hz


FCC 15.319(c)(e): 20.72 dBm (118 mW) RSS-213, Issue 2: 20.48 dBm (112 mW)

The antenna gain is below 3 dBi, no reduction in transmit power is necessary.

Requirements, FCC 15.319(c)(e); RSS-213, Issue 2; RSS-GEN, Issue 4


Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.







Conducted Peak Output Power




Lower Channel





Report no.: 264013-8 FCC ID: DMOCBDDGG





Middle Channel



TEST REPORT FCC part 15D Report no.: 264013-8

FCC ID: DMOCBDDGG

3.8 Emission Bandwidth B

Test Method:

ANSI C63.17, clause 6.1.3.

Test Results: Complies

Measurement Data:

Channel No.	Frequency (MHz)	26 dB Bandwidth <i>B</i> (kHz)
4	1921.536	1390
0	1928.448	1390

Channel No.	Frequency (MHz)	99% Bandwidth (kHz)
2	1924.992	1248

Channel No.	Frequency (MHz)	6 dB Bandwidth (kHz)
4	1921.536	N/A
0	1928.448	N/A
Channel No.	Frequency (MHz)	12 dB Bandwidth (kHz)
4	1921.536	N/A
0	1928.448	N/A

Requirements, FCC 15.323(a)

The 26 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.


Requirements, RSS-213 Issue 2, clause 6.4

The 99% Bandwidth shall be larger than 50 kHz and less than 2.5 MHz.


No requirements for 6 and 12 dB Bandwidth, these values are only used for testing Monitoring Bandwidth if the Simple Compliance test fails (ANSI C63.17, clause 7.4).

99% BW is measured according to RSS-GEN Issue 4, clause 6.6.






Emission Bandwidth B, Lower Channel



Emission Bandwidth B, Upper Channel





99% Bandwidth, Middle Channel



3.9 Power Spectral Density

Test Method:

ANSI C63.17, clause 6.1.5.

Test Results: Complies


Measurement Data:

Channel No.	Frequency (MHz)	Power Spectral Density (dBm)
4	1921.536	2.9
0	1928.448	2.7

Averaged over 1000 sweeps.

Requirements, FCC 15.319(d)


The Power Spectral Density shall be less than 3 mW (4.77 dBm) when averaged over at least 100 sweeps.





Power Spectral Density


Lower Channel:



Overview




Averaged, 1000 Sweeps




Nemko

Upper Channel:



Overview



Averaged, 1000 Sweeps



TEST REPORT FCC part 15D

Report no.: 264013-8 FCC ID: DMOCBDDGG

In-Band Unwanted Emissions, Conducted 3.10

Test Method:

ANSI C63.17, clause 6.1.6.1.

Test Results: Complies


Measurement Data:

See plots.


Requirements, FCC 15.323(d):

 $B < f \le 2B$: at least 30 dB below max. permitted peak power 2B < f ≤ 3B: at least 50 dB below max. permitted peak power

 $3B < f \le UPCS$ Band Edge: at least 60 dB below max. permitted peak power




Middle Channel




Nemko

In-Band Unwanted Emissions, Conducted



Lower Channel



Upper Channel



3.11 Out-of-band Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.2.

Test Results: Complies

Measurement Data:


See plots.

Requirements, FCC 15.323(d):

 $f \le 1.25 \text{MHz}$ outside UPCS band : $\le -9.5 \text{dBm}$ 1.25MHz $\le f \le 2.5 \text{MHz}$ outside UPCS band : $\le -29.5 \text{dBm}$ $f \ge 2.5 \text{MHz}$ outside UPCS band : $\le -39.5 \text{dBm}$

Out-of-Band Emissions, Conducted


Lower Channel:






Out-of-Band Emissions, Conducted


Lower Channel:









Out-of-Band Emissions, Conducted









Out-of-Band Emissions, Conducted









Out-of-Band Emissions, Conducted









Out-of-Band Emissions, Conducted






Out-of-Band Emissions, Conducted







Out-of-Band Emissions, Conducted





TEST REPORT FCC part 15D

Report no.: 264013-8 FCC ID: DMOCBDDGG

3.12 **Carrier Frequency Stability**

Test Method:

ANSI C63.17, clause 6.2.1.

Test Results: Complies

Measurement Data:

The Frequency Stability is measured with the CMD60. The CMD60 was logged by a computer programmed to get new readings as fast as possible (about 3 readings per second) over the noted time period or number of readings. The peak-to-peak difference was recorded and the mean value and deviation in ppm was calculated.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

Carrier Frequency Stability over Time at Nominal Temperature

Average Mean Carrier	Max. Diff.	Min. Diff.	Max. Dev.	Limit
Frequency (MHz)	(kHz)	(kHz)	(ppm)	
1924.983379	0.8	-16.6	-4.1	±10 ppm

Deviation ppm = ((Diff. - Mean Diff) / Mean Carrier Freq.) x 106

Deviation (ppm) is calculated from 3000 readings.

Frequency Stability over Power Supply Voltage at Nominal Temperature

Voltage	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
V _{nom}	1924.991906	0	0	
85% of V _{nom}	1924.991509	-0.4	-0.2	±10 ppm
115% of V _{nom}	1924.991698	-0.2	-0.1	

Deviation ppm = ((Mean - Measured Frequency) / Mean) x 10⁶

Frequency Stability over Temperature

Temperature	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
T = +20 °C	1924.991906	0	0	
T = -20 °C	1925.01000	18.1	9.4	±10 ppm
T = +50 °C	1924.997737	5.8	3.0	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10⁶



TEST REPORT FCC part 15D Report no.: 264013-8

Report no.: 264013-8 FCC ID: DMOCBDDGG

3.13 Frame Repetition Stability

Test Method:

ANSI C63.17, clause 6.2.2.

Test Results: Complies

Measurement Data:

The envelope of the RF signal from the EUT is detected with a Crystal Detector and the mean and standard deviation of the frame repetition frequency is then gated over 100 frames and measured with a Frequency Domain Analyzer. The frame repetition stability is 3 times the standard deviation.

Carrier Frequency	Mean	Standard Deviation	Frame Repetition
(MHz)	(Hz)	(Hz)	Stability (ppm)
1924.992	100.000	0.000111	3.323

Limit:

Frame Repetition Stability	±10 ppm (TDMA)
----------------------------	----------------

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.2

3.14 Frame Period and Jitter

Test Method:

ANSI C63.17, clause 6.2.3.

Test Results: Complies

Measurement Data:

Carrier Frequency (MHz)	Frame Period (ms)	Max Jitter (μs)	3xStandard Deviation of Jitter (μs)
1924.992	10.000	-0.021	-0.012

Max Jitter = $(1/(Frame \, Period + Pk-Pk/2)) - (1/Frame \, Period)$, when Pk-Pk and Frame Period are in Hz $3xSt.Dev.Jitter = 3x \, (1/(Frame \, Period + St.Dev) - 1/St.Dev) \, x \, 10^6$

Limit:


Frame Period	20 or 10 ms
Max Jitter	25 μs
3 times St.Dev of Jitter	12.5 µs

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.3

TEST REPORT


FCC part 15D Report no.: 264013-8 FCC ID: DMOCBDDGG





100.000001925 1/Mean 10.000ms Mean Pk-Pk 323րե Std Dev 110.76pg

Frame Repetition Stability, Gated over 100 Frames



100.00000185975 1/Mean 10.000ms Mean Pk-Pk 418.7րե Std Dev 39.6978µ4

Frame Period and Jitter



TEST REPORT FCC part 15D Report no.: 264013-8

Report no.: 264013-8 FCC ID: DMOCBDDGG

3.15 Monitoring Threshold, Least Interfered Channel

Monitoring Threshold Limits:

Lower Threshold:

$$T_L = 15 \log B - 184 + 30 - P_{EUT}$$
 (dBm)

Upper Threshold:

$$T_U = 15 \log B - 184 + 50 - P_{EUT}$$
 (dBm)

B is measured Emission Bandwidth in Hz P_{EUT} is measured Transmitter Power in dBm

Calculated values:

	FCC 15.323	RSS-213, Issue 2
Lower Threshold	-82.1 dBm	-82.8 dBm
Upper Threshold	N/A	-62.8 dBm

Least Interfered Channel Procedure (LIC) may only be used by systems with more than 20 duplex system access channels. Systems with less than 20 duplex system access channels are not allowed to transmit when interferer level is above Lower Threshold.

Upper Threshold has been removed from FCC 15D but still exists in Industry Canada RSS-213.

Measurement Procedure:

The Upper or Lower Threshold is found by the procedure defined in ANSI C63.17 clause 7.3.1 or 7.3.2.

Least Interfered Channel Procedure NOT used:			
Lower Threshold N/A dBm			
Least Interfered Channel Procedure:			
Upper Threshold	-61.4 dBm		

Least Interfered Channel (LIC) Procedure Test, FCC 15.323(b), (c)(2) and (c)(5)

ANSI C63.17 clause 7.3.3 ref.	Observation	Verdict
b) $f_1 T_L + 13 \text{ dB}$, $f_2 \text{ at } T_L + 6 \text{ dB}$	Transmission always on f_2	Pass
c) $f_1 T_L + 6 \text{ dB}$, $f_2 \text{ at } T_L + 13 \text{ dB}$	Transmission always on f_I	Pass
d) $f_1 T_L + 7 dB$, f_2 at T_L	Transmission always on f_2	Pass
e) f_1 T _L , f_2 at T _L + 7 dB	Transmission always on f_I	Pass




Selected Channel Confirmation, FCC 15.323(c)(1) and (5)

ANSI C63.17 clause 7.3.4	Observation	Verdict
b) Shall not transmit on f_I	EUT transmits on f ₂	Pass
d) Shall not transmit on f ₂	EUT transmits on f_I	Pass

Limits:

	FCC 15.323	RSS-213, Issue 2
Lower Threshold + 6 dB margin	-76.1 dBm	-76.8 dBm
Upper Threshold + 6 dB margin	N/A	-56.8 dBm



7.3.4 Selected Channel Confirmation, Connection 3.6s After Interferer Removed



TEST REPORT FCC part 15D Report no.: 264013-8

FCC ID: DMOCBDDGG

3.16 **Threshold Monitoring Bandwidth**

This test is only required if a dedicated monitoring receiver is used. However, if the test is not carried out the manufacturer shall declare and provide proper evidence that the monitoring is made through the radio receiver used for communication.

Measurement Procedure:

Simple Compliance Test, ANSI C63.17, clause 7.4.1

More Detailed Test, ANSI C63.17, clause 7.4.2

The test is passed if either the Simple Compliance Test or the More Detailed test is passed.

During this test the spectrum analyzer is observed visually to see if the EUT transmits or not.

Test Results:

Test performed	Observation	Verdict
Simple Compliance test, at ±30% of B	N/A	N/A
More Detailed Test, at -6 dB points	N/A	N/A
More Detailed Test, at -12 dB points	N/A	N/A

The more detailed test must be pass at both the -6 and -12 dB points if the Simple Compliance test fails.

Comment: The manufacturer declares that the tested EUT uses the same receiver for monitoring and communication, this test is therefore not required.

Limits, FCC 15.323(c)(7):

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission.



TEST REPORT FCC part 15D

Report no.: 264013-8 FCC ID: DMOCBDDGG

3.17 **Reaction Time and Monitoring Interval**

Measurement Procedure

ANSI C63.17, clause 7.5

Test results:

By administrative commands and out-of-operating region interference, the EUT is restricted to operate on two RF carrier frequencies.

A CW interferer signal at a level $T_U + U_M$ is applied on f_I and time-synchronized pulsed interference at a level TU + UM +7 dB is applied on f_2 . The level on f_2 was raised 6 dB for part d) with 35 µs pulses.

The pulses are synchronized with the EUT timeslots and applied centered within all timeslots.

For both tests the test is passed if the EUT transmits on f_I .


Pulse Width, ref. to ANSI C63.17 clause 7.5	Observation	Verdict
c) > largest of 50 μs and 50*SQRT(1.25/ <i>B</i>)	EUT transmits on f_I	Pass
d) > largest of 35 μs and 35*SQRT(1.25/ <i>B</i>), and with interference level raised 6 dB	EUT transmits on f_I	Pass

Comment: Since B is larger than 1.25 MHz the test was performed with pulse lengths of 50 µs and 35 µs.


Limits, FCC 15.323(c)(1), (5) and (7)

The maximum reaction time must be less than 50xSQRT (1.25/emission bandwidth in MHz) microseconds for signals at the applicable threshold level but shall not be required to be less than 50 µs.


If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be 35xSQRT (1.25/emission bandwidth in MHz) microseconds but shall not be required to be less than 35 µs.







50 µs Pulses



35 µs Pulses



TEST REPORT FCC part 15D Report no.: 264013-8

FCC ID: DMOCBDDGG

3.18 **Time and Spectrum Window Access Procedure**

This requirement is only for EUTs which transmit unacknowledged control and signaling information.

Measurement Procedure:

Timing for EUTs using control and signaling channel type transmissions: ANSI C63.17, clause 8.1

Test results:

Access Criteria, ref. to ANSI C63.17 clause 8.1.1	Observation	Verdict
b) Check that the EUT transmits on the interference free time-slot	EUT transmits on the interference free time-slot	Pass
b) The EUT must terminate or pause in its repetitive transmission of the control and signalling channel on the open channel to repeat the access criteria not less frequently than every 30 s	Transmission paused every 1.28 s	Pass

If FCC 15.323(c)(6) option, If Random Waiting Interval is NOT implemented

Access Criteria, ref. to ANSI C63.17 clause 8.1.2	Observation	Verdict
b) Check that the EUT changes to an interference-free slot when interference is introduced on the time slot in use	EUT changes to the interference-free time-slot, and stays there	Pass

If FCC 15.323(c)(6) option, Only if Random Waiting Interval is implemented

Access Criteria, ref. to ANSI C63.17 clause 8.1.3	Observation	Verdict
b-d) Check that the EUT uses random waiting interval before continuing transmission on an interfered time slot	N/A	N/A

Comment: The tested EUT does not support the Random Waiting Interval option.

Limits:

FCC 15.323(c)(4):


Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

FCC 15.323(c)(6):


If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available



Access Criteria Check





8.1.1a) EUT Transmits on Unblocked Slot






Access Criteria Check






8.1.1b) Access Criteria check Interval



Nemko



8.1.2b) Access Criteria Functional Test, Before and After



TEST REPORT FCC part 15D Report no.: 264013-8

FCC ID: DMOCBDDGG

3.19 **Acknowledgements and Transmission Duration**

Measurement Procedure:

Acknowledgements: ANSI C63.17, clause 8.2.1

Transmission Duration: ANSI C63.17, clause 8.2.2

During the test Initial transmission without acknowledgements the signal from the EUT to the companion device is blocked by circulators in addition to the tunable attenuator.

The test Transmission time after loss of acknowledgements is performed by cutting-off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

The Transmission Duration test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

Test Results:

Acknowledgements

Test ref. to ANSI C63.17 clause 8.2.1	Observation	Verdict
a) Initial transmission without acknowledgements	Not applicable for EUT that transmits control and signaling information	N/A
c) Transmission time after loss of acknowledgements	5 sec	Pass

Transmission Duration

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict	
b) Transmission duration on same time and frequency window	Only for initiating device that controls which time slot is used	N/A	

Comment: /

Limits, FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.



3.20 Dual Access Criteria Check

Measurement Procedure:

EUTs that does not implement LIC Procedure: ANSI C63.17, clause 8.3.1

EUTs that implement LIC Procedure: ANSI C63.17, clause 8.3.2

This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

Test Results:

EUTs that Implements the Upper Threshold:

Test ref. to ANSI C63.17 clause 8.3.2	Observation	Verdict
b) EUT is restricted to a single carrier f_l for TDMA systems. The Test is Pass if EUT can transmit	N/A	N/A
c) d) Transmission on interference-free receive time/spectrum window	N/A	N/A
e) f) Transmission on interference-free transmit time/spectrum window	N/A	N/A
g) Transmission not possible on any time/spectrum window	N/A	N/A

Comment: This test is only applicable for EUT that can be initiating device.

Limits, FCC 15.323(c)(10)

An initiating device may attempt to establish a duplex connection by monitoring both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

3.21 Alternative Monitoring Interval

Test procedure described in ANSI C63.17 clause 8.4.

This test is required if the EUT implements the provisions of FCC 15.323(c)(11).

Test result:

Not Tested. The tested EUT does not implement this provision. See manufacturers' declaration.





Measurement Uncertainty

Measurement Uncertainty Values			
Test Item		Uncertainty	
Output Power		±0.5 dB	
Power Spectral Density		±0.5 dB	
Out of Band Emissions, Conducted (RBW < 100 kHz)	< 3.6 GHz	±0.6 dB	
	> 3.6 GHz	±0.9 dB	
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB	
	> 1 GHz	±2.2 dB	
Emission Bandwidth		±4 %	
Power Line Conducted Emissions		+2.9 / -4.1 dB	
Spectrum Mask Measurements	Frequency	±5 %	
	Amplitude	±1.0 dB	
Frequency Error		±0.6 ppm	
Timing and Jitter Measurements		±2.0 ns	
Frame Timing Measurements		±1.4 ppm	
Receiver Blocking Levels		±1.0 dB	
Temperature Uncertainty		±1 °C	

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2



5 Test Setups

5.1 Frequency Measurements




Test equipment included: 5, 9, 28

Test Set-up 1

This setup is used for measuring Carrier frequency stability at normal and extreme temperatures.

5.2 Timing Measurements




Test equipment included: 5, 7, 9, 28

Test Set-up 2

This setup is used for measuring Frame repetition stability, Frame period and Jitter.

5.3 Conducted Emission Test




Test equipment included: 1, 2, 9, 26

Test Set-up 3

This setup is used for all conducted emission tests.

5.4 Power Line Conducted Emissions Test




Test equipment: 8, 17, 18, 22, 27

Test Set-Up 5



5.5 Monitoring Tests



Test equipment: 1, 2, 3, 4, 6, 9, 10, 11, 12, 13, 14, 15, 19, 23, 24, 25, 26

Test Set-Up 6

This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generators to the EUT is measured with a power meter before the testing is started.

The CLK100 is used to synchronize the Pulse-/ Pattern generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the CLK100 signal will come form the Companion Device.

The sync signal to the Spectrum Analyzer is the CLK100 signal that is regenerated in the Pulse-/ Pattern Generator, this is used to synchronize the Spectrum Analyzer to the DECT frame when in zero span. The Pulse-/ Pattern Generator is used for tests that require time synchronized pulses or blocking of specific time slots.



6 Test Equipment Used

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Testhouse.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSW26	Spectrum Analyzer	Rohde & Schwarz	LR 1640	2014.09.22	2015.09.22
2	SME03	Signal generator	Rohde & Schwarz	LR 1238	2013.03.19	2015.03.19
3	SMIQ03B	Signal generator	Rohde & Schwarz	LR 1516	Cal b4 use	
4	SMHU52	Signal generator	Rohde & Schwarz	LR 1240	Cal b4 use	
5	53310A	Modulation Domain Analyzer	Hewlett Packard	LR 1483	2013.08.14	2015.08.14
6	81104A	Pulse-/ Pattern Generator	Agilent	LR 1502	2013.03.19	2015.03.19
7	8470B	Crystal Detector	Hewlett Packard	LR 1207	N/A	
8	ESHS10	Measuring Receiver	Rohde & Schwarz	N- 3528	2014.09.15	2015.09.15
9	4768-10	Attenuator	Narda	LR1356	Cal b4 use	
10	745-69	Step Attenuator	Narda	LR 1442	N/A	
11	WE 1506A	Power Splitter	Weinchel	LR 244	Cal b4 use	
12	WE 1506A	Power Splitter	Weinchel	LR 245	Cal b4 use	
13	H-9	Hybrid	Anzac	LR 86	Cal b4 use	
14	H-9	Hybrid	Anzac	LR 257	Cal b4 use	
15	S212DS	RF Switch	Narda	LR 1244	N/A	
16	ESH3-Z5	Two Line V-Network	Rohde & Schwarz	LR 1076	Cal b4 use	
17	ESH3-Z2	Pulse Limiter	Rohde & Schwarz	LR 1074	N/A	
18	6812B	AC Power Source	Agilent	LR 1515	2013.10.28	2014.10.28
19	Model 87 V	Multimeter	Fluke	N-4672	2014.09.17	2015.09
20	87H35-1	Circulator	Racal-MESL	s.no.: 140	N/A	
21	87H35-1	Circulator	Racal-MESL	s.no.: 141	N/A	
22	87H35-1	Circulator	Racal-MESL	s.no.: 142	N/A	
23	U2000A	Average Power Sensor	Agilent	LR 1523	2013.10.24	2015.10.24
24	RTX2011	DECT Tester	RTX Telecom	LR 1587	Cal b4 use	