



A D T

# FCC TEST REPORT

**REPORT NO.:** RF120928C03

**MODEL NO.:** PRESENCE

**FCC ID:** DMOCBMSKE

**RECEIVED:** Sep. 28, 2012

**TESTED:** Oct. 15, 2012 ~ Jan. 08, 2013

**ISSUED:** Jan. 09, 2013

**APPLICANT:** Sennheiser Electronic Corp (NY)

**ADDRESS:** 1 Enterprise Drive Old Lyme, Connecticut 06371  
United States

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,  
New Taipei City, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim  
product certification, approval, or endorsement by  
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

## Table of Contents

RELEASE CONTROL RECORD .....	6
1. CERTIFICATION.....	7
2. SUMMARY OF TEST RESULTS .....	8
2.1 MEASUREMENT UNCERTAINTY .....	9
3. GENERAL INFORMATION.....	10
3.1 GENERAL DESCRIPTION OF EUT.....	10
3.2 DESCRIPTION OF TEST MODES.....	11
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	12
3.3 DESCRIPTION OF SUPPORT UNITS.....	16
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST .....	16
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	18
4. TEST TYPES AND RESULTS (FOR BLUETOOTH EDR).....	19
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	19
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	19
4.1.2 TEST INSTRUMENTS .....	20
4.1.3 TEST PROCEDURES .....	21
4.1.4 DEVIATION FROM TEST STANDARD .....	21
4.1.5 TEST SETUP .....	22
4.1.6 EUT OPERATING CONDITIONS .....	22
4.1.7 TEST RESULTS .....	23
4.2 CONDUCTED EMISSION MEASUREMENT .....	33
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	33
4.2.2 TEST INSTRUMENTS .....	33
4.2.3 TEST PROCEDURES .....	34
4.2.4 DEVIATION FROM TEST STANDARD .....	34
4.2.5 TEST SETUP .....	35
4.2.6 EUT OPERATING CONDITIONS .....	35
4.2.7 TEST RESULTS .....	36
4.3 NUMBER OF HOPPING FREQUENCY USED .....	40
4.3.1 LIMIT OF HOPPING FREQUENCY USED .....	40
4.3.2 TEST SETUP .....	40
4.3.3 TEST INSTRUMENTS .....	40
4.3.4 TEST PROCEDURES .....	40
4.3.5 DEVIATION FROM TEST STANDARD .....	40
4.3.6 TEST RESULTS .....	40
4.4 DWELL TIME ON EACH CHANNEL .....	42
4.4.1 LIMIT OF DWELL TIME USED.....	42
4.4.2 TEST SETUP .....	42



A D T

4.4.3 TEST INSTRUMENTS .....	42
4.4.4 TEST PROCEDURES .....	42
4.4.5 DEVIATION FROM TEST STANDARD .....	42
4.4.6 TEST RESULTS .....	43
4.5 CHANNEL BANDWIDTH.....	45
4.5.1 LIMITS OF CHANNEL BANDWIDTH.....	45
4.5.2 TEST SETUP .....	45
4.5.3 TEST INSTRUMENTS .....	45
4.5.4 TEST PROCEDURE .....	45
4.5.5 DEVIATION FROM TEST STANDARD .....	45
4.5.6 EUT OPERATING CONDITION .....	45
4.5.7 TEST RESULTS .....	46
4.6 HOPPING CHANNEL SEPARATION .....	47
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION .....	47
4.6.2 TEST SETUP .....	47
4.6.3 TEST INSTRUMENTS .....	47
4.6.4 TEST PROCEDURES .....	47
4.6.5 DEVIATION FROM TEST STANDARD .....	47
4.6.6 TEST RESULTS .....	48
4.7 MAXIMUM OUTPUT POWER.....	49
4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT .....	49
4.7.2 TEST SETUP .....	49
4.7.3 TEST INSTRUMENTS .....	49
4.7.4 TEST PROCEDURES .....	49
4.7.5 DEVIATION FROM TEST STANDARD .....	49
4.7.6 EUT OPERATING CONDITION .....	49
4.7.7 TEST RESULTS .....	50
4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	51
4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	51
4.8.2 TEST INSTRUMENTS .....	51
4.8.3 TEST PROCEDURE .....	51
4.8.4 DEVIATION FROM TEST STANDARD .....	51
4.8.5 EUT OPERATING CONDITION .....	51
4.8.6 TEST RESULTS .....	51
5. TEST TYPES AND RESULTS (FOR BLUETOOTH LE 4.0).....	54
5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	54
5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	54
5.1.2 TEST INSTRUMENTS .....	54
5.1.3 TEST PROCEDURES .....	54
5.1.4 DEVIATION FROM TEST STANDARD .....	54
5.1.5 TEST SETUP .....	54
5.1.6 EUT OPERATING CONDITIONS .....	54



A D T

5.1.7 TEST RESULTS .....	55
5.2 CONDUCTED EMISSION MEASUREMENT .....	62
5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	62
5.2.2 TEST INSTRUMENTS .....	62
5.2.3 TEST PROCEDURES .....	62
5.2.4 DEVIATION FROM TEST STANDARD .....	62
5.2.5 TEST SETUP .....	62
5.2.6 EUT OPERATING CONDITIONS .....	62
5.2.7 TEST RESULTS .....	63
5.3 6dB BANDWIDTH MEASUREMENT .....	67
5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	67
5.3.2 TEST SETUP .....	67
5.3.3 TEST INSTRUMENTS .....	67
5.3.4 TEST PROCEDURE .....	67
5.3.5 DEVIATION FROM TEST STANDARD .....	67
5.3.6 EUT OPERATING CONDITIONS .....	67
5.3.7 TEST RESULTS .....	68
5.4 CONDUCTED OUTPUT POWER .....	69
5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	69
5.4.2 TEST SETUP .....	69
5.4.3 TEST INSTRUMENTS .....	69
5.4.4 TEST PROCEDURES .....	69
5.4.5 DEVIATION FROM TEST STANDARD .....	69
5.4.6 EUT OPERATING CONDITIONS .....	69
5.4.7 TEST RESULTS .....	69
5.5 POWER SPECTRAL DENSITY MEASUREMENT.....	70
5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	70
5.5.2 TEST SETUP .....	70
5.5.3 TEST INSTRUMENTS .....	70
5.5.4 TEST PROCEDURE .....	70
5.5.5 DEVIATION FROM TEST STANDARD .....	70
5.5.6 EUT OPERATING CONDITION .....	70
5.5.7 TEST RESULTS .....	70
5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	71
5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	71
5.6.2 TEST SETUP .....	71
5.6.3 TEST INSTRUMENTS .....	71
5.6.4 TEST PROCEDURE .....	71
5.6.5 DEVIATION FROM TEST STANDARD .....	72
5.6.6 EUT OPERATING CONDITION .....	72
5.6.7 TEST RESULTS .....	72
5.6.8 TEST RESULTS .....	73



A D T

6. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	74
7. INFORMATION ON THE TESTING LABORATORIES .....	75
8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	76



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120928C03	Original release.	Jan. 09, 2013



A D T

## 1. CERTIFICATION

**PRODUCT:** Bluetooth mono headset  
**MODEL NO.:** PRESENCE  
**BRAND:** SENNHEISER  
**APPLICANT:** Sennheiser Electronic Corp (NY)  
**TESTED:** Oct. 15, 2012 ~ Jan. 08, 2013  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**STANDARDS:** FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10-2009

The above equipment (model: PRESENCE) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Sunee Liu , DATE : Jan. 09, 2013  
Suntee Liu / Specialist

APPROVED BY : Ken Liu , DATE : Jan. 09, 2013  
Ken Liu / Manager



A D T

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Bluetooth EDR)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.04dB at 0.49324MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.0dB at 31.35MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

**NOTE:** If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) (Bluetooth LE 4.0)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.57dB at 0.49324MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.1dB at 7320.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



A D T

## 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

EUT	Bluetooth mono headset	
MODEL NO.	PRESENCE	
POWER SUPPLY	5Vdc (adapter / host equipment / car charger) 3.7Vdc (Li-ion battery)	
MODULATION TYPE	Bluetooth EDR	GFSK, $\pi/4$ -DQPSK, 8DPSK
	Bluetooth LE 4.0	GFSK
TRANSFER RATE	Bluetooth EDR	1/2/3Mbps
	Bluetooth LE 4.0	3Mbps
OPERATING FREQUENCY	2402~2480MHz	
NUMBER OF CHANNEL	Bluetooth EDR	79
	Bluetooth LE 4.0	40
CHANNEL SPACING	Bluetooth EDR	1MHz
	Bluetooth LE 4.0	2MHz
OUTPUT POWER	Bluetooth EDR	6.653mW
	Bluetooth LE 4.0	4.819mW
ANTENNA TYPE	Printed antenna with 1.7dBi gain	
ANTENNA CONNECTOR	N/A	
DATA CABLE	0.1m non-shielded USB cable without core 1m non-shielded USB cable without core	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Adapter, Car charger	

#### NOTE:

1. The EUT is powered by the following adapter.

Brand	SIL Switching Adapter
Model	SSA-3P 050015US
Input Power	100-240Vac, 50/60Hz, 0.2A
Output Power	5.0Vdc, 150mA

2. The EUT is powered by the following car charger.

Model	SIL-C05050A
Input Power	12-24dc, 0.5A
Output Power	5Vdc, 500mA

3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

### 3.2 DESCRIPTION OF TEST MODES

#### Bluetooth EDR:

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

#### Bluetooth LE 4.0:

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



A D T

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

#### Bluetooth EDR:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
A	✓	✓	✓	✓	EUT power from adapter
B	-	✓	✓	-	EUT power from host equipment
C	-	✓	-	-	EUT power from Li-ion battery
D	-	✓	-	-	EUT power from car charger

Where RE $\geq$ 1G: Radiated Emission above 1GHz

RE&lt;1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Y-plane.

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	GFSK	DH5
A	0 to 78	0, 39, 78	8DPSK	DH5

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A, B, C, D	0 to 78	0	GFSK	DH5

#### POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A, B	0 to 78	0	GFSK	DH5



A D T

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	GFSK	DH5
A	0 to 78	0, 39, 78	8DPSK	DH5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	24deg. C, 67%RH	120Vac, 60Hz	Martin Lee
RE<1G	24deg. C, 67%RH	120Vac, 60Hz 3.7Vdc	Martin Lee
PLC	26deg. C, 65%RH	120Vac, 60Hz	Cedric Wu
APCM	24deg. C, 64%RH	120Vac, 60Hz	Match Tsui



A D T

### FOR Bluetooth LE 4.0:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	✓	✓	✓	✓	EUT power from adapter
B	-	✓	✓	-	EUT power from host equipment
C	-	✓	-	-	EUT power from Li-ion battery
D	-	✓	-	-	EUT power from car charger

Where RE≥1G: Radiated Emission above 1GHz

RE&lt;1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Y-plane.

### RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A	0 to 39	0, 19, 39	GFSK	3

### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A, B, C, D	0 to 39	0	GFSK	3

### POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A, B	0 to 39	0	GFSK	3



A D T

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A	0 to 39	0, 19, 39	GFSK	3

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	24deg. C, 67%RH	120Vac, 60Hz	Martin Lee
RE<1G	25deg. C, 65%RH	120Vac, 60Hz 3.7Vdc	Chris Lin
PLC	26deg. C, 65%RH	120Vac, 60Hz	Cedric Wu
APCM	24deg. C, 64%RH	120Vac, 60Hz	Match Tsui



A D T

### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	D531	CN-0XM006-48643-8 1U-2610	QDS-BRCM1020
2	DC Power Supply	R&S	NGSM 32/10	4237	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA


**NOTE:** All power cords of the above support units are non-shielded (1.8m).

#### 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST

##### TEST MODE A




##### TEST MODE B






A D T

## TEST MODE C



## TEST MODE D





A D T

### **3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v02**

**FCC Public Notice DA 00-705**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.



A D T

## 4. TEST TYPES AND RESULTS (FOR BLUETOOTH EDR)

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>uV</sub>/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUe DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	Aug. 06, 2012	Aug. 05, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Feb. 03, 2012	Feb. 02, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Apr. 06, 2012	Apr. 05, 2013
HORN Antenna SCHWARZBECK	9120D	209	Sep. 03, 2012	Sep. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8447D	2944A10633	Oct. 25, 2012	Oct. 24, 2013
Preamplifier Agilent	8449B	3008A01964	Oct. 25, 2012	Oct. 24, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250723/4	Aug. 28, 2012	Aug. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6+309224/4	Aug. 28, 2012	Aug. 27, 2013
Software ADT.	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table ADT.	TT100	TT93021703	NA	NA
Turn Table Controller ADT.	SC100	SC93021703	NA	NA
High Speed Peak Power Meter	ML2495A	0842014	Apr. 28, 2012	Apr. 27, 2013
Power Sensor	MA2411B	0738404	Apr. 28, 2012	Apr. 27, 2013

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. The test was performed in HwaYa Chamber 3.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The FCC Site Registration No. is 988962.
  6. The IC Site Registration No. is IC 7450F-3.



A D T

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

##### TEST MODE A, C, D

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

##### TEST MODE B

- Connected the EUT with notebook via USB cable on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.



A D T

#### 4.1.7 TEST RESULTS

##### ABOVE 1GHz WORST-CASE DATA :

GFSK

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 0		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		120Vac, 60Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		24deg. C, 67%RH		TESTED BY Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	41.5 PK	74.0	-32.5	1.09 H	214	10.70	30.80
2	2390.00	30.1 AV	54.0	-23.9	1.09 H	214	-0.70	30.80
3	#2400.00	64.6 PK	83.6	-19.0	1.09 H	186	33.70	30.90
4	#2400.00	34.5 AV	53.5	-19.0	1.09 H	186	3.60	30.90
5	*2402.00	103.6 PK			1.09 H	186	72.70	30.90
6	*2402.00	73.5 AV			1.09 H	186	42.60	30.90
7	4804.00	61.4 PK	74.0	-12.6	1.03 H	121	24.50	36.90
8	4804.00	31.3 AV	54.0	-22.7	1.03 H	121	-5.60	36.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	39.8 PK	74.0	-34.2	1.22 V	45	9.00	30.80
2	2390.00	30.1 AV	54.0	-23.9	1.22 V	45	-0.70	30.80
3	#2400.00	59.0 PK	78.0	-19.0	1.02 V	196	28.10	30.90
4	#2400.00	28.9 AV	47.9	-19.0	1.02 V	196	-2.00	30.90
5	*2402.00	98.0 PK			1.02 V	196	67.10	30.90
6	*2402.00	67.9 AV			1.02 V	196	37.00	30.90
7	4804.00	58.5 PK	74.0	-15.5	1.00 V	163	21.60	36.90
8	4804.00	28.4 AV	54.0	-25.6	1.00 V	163	-8.50	36.90

##### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on  $0.625 * 5$  per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	106.2 PK			1.06 H	138	75.20	31.00
2	*2441.00	76.1 AV			1.06 H	138	45.10	31.00
3	4882.00	51.4 PK	74.0	-22.6	1.24 H	148	14.30	37.10
4	4882.00	21.3 AV	54.0	-32.7	1.24 H	148	-15.80	37.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	98.2 PK			1.63 V	141	67.20	31.00
2	*2441.00	68.1 AV			1.63 V	141	37.10	31.00
3	4882.00	48.2 PK	74.0	-25.8	1.00 V	156	11.10	37.10
4	4882.00	18.1 AV	54.0	-35.9	1.00 V	156	-19.00	37.10

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	106.8 PK			1.04 H	185	75.60	31.20
2	*2480.00	76.7 AV			1.04 H	185	45.50	31.20
3	2483.50	45.9 PK	74.0	-28.1	1.04 H	185	14.70	31.20
4	2483.50	15.8 AV	54.0	-38.2	1.04 H	185	-15.40	31.20
5	4960.00	57.4 PK	74.0	-16.6	1.07 H	126	20.10	37.30
6	4960.00	27.3 AV	54.0	-26.7	1.07 H	126	-10.00	37.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	100.5 PK			1.16 V	79	69.30	31.20
2	*2480.00	70.4 AV			1.16 V	79	39.20	31.20
3	2483.50	39.6 PK	74.0	-34.4	1.16 V	79	8.40	31.20
4	2483.50	9.5 AV	54.0	-44.5	1.16 V	79	-21.70	31.20
5	4960.00	56.1 PK	74.0	-17.9	1.21 V	148	18.80	37.30
6	4960.00	26.0 AV	54.0	-28.0	1.21 V	148	-11.30	37.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

## 8DPSK

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 0		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		120Vac, 60Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		24deg. C, 67%RH		TESTED BY Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.5 PK	74.0	-26.5	1.00 H	102	16.70	30.80
2	2390.00	36.2 AV	54.0	-17.8	1.00 H	102	5.40	30.80
3	#2400.00	63.2 PK	82.5	-19.3	1.39 H	13	32.30	30.90
4	#2400.00	33.1 AV	52.4	-19.3	1.39 H	13	2.20	30.90
5	*2402.00	102.5 PK			1.39 H	13	71.60	30.90
6	*2402.00	72.4 AV			1.39 H	13	41.50	30.90
7	4804.00	54.3 PK	74.0	-19.7	1.14 H	65	17.40	36.90
8	4804.00	24.2 AV	54.0	-29.8	1.14 H	65	-12.70	36.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.5 PK	74.0	-29.5	1.01 V	80	13.70	30.80
2	2390.00	31.6 AV	54.0	-22.4	1.01 V	80	0.80	30.80
3	#2400.00	59.0 PK	78.3	-19.3	1.01 V	88	28.10	30.90
4	#2400.00	28.9 AV	48.2	-19.3	1.01 V	88	-2.00	30.90
5	*2402.00	98.3 PK			1.01 V	80	67.40	30.90
6	*2402.00	68.2 AV			1.01 V	80	37.30	30.90
7	4804.00	56.1 PK	74.0	-17.9	1.02 V	151	19.20	36.90
8	4804.00	26.0 AV	54.0	-28.0	1.02 V	151	-10.90	36.90

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* ”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on  $0.625 \times 5$  per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	104.4 PK			1.36 H	21	73.40	31.00
2	*2441.00	74.3 AV			1.36 H	21	43.30	31.00
3	4882.00	50.6 PK	74.0	-23.4	1.28 H	110	13.50	37.10
4	4882.00	20.5 AV	54.0	-33.5	1.28 H	110	-16.60	37.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	97.8 PK			1.18 V	317	66.80	31.00
2	*2441.00	67.7 AV			1.18 V	317	36.70	31.00
3	4882.00	51.9 PK	74.0	-22.1	1.14 V	145	14.80	37.10
4	4882.00	21.8 AV	54.0	-32.2	1.14 V	145	-15.30	37.10

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	104.3 PK			1.21 H	101	73.10	31.20
2	*2480.00	74.2 AV			1.21 H	101	43.00	31.20
3	2483.50	46.5 PK	74.0	-27.5	1.21 H	101	15.30	31.20
4	2483.50	16.4 AV	54.0	-37.6	1.21 H	101	-14.80	31.20
5	4960.00	55.0 PK	74.0	-19.0	1.12 H	114	17.70	37.30
6	4960.00	24.9 AV	54.0	-29.1	1.12 H	114	-12.40	37.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	98.9 PK			1.02 V	33	67.70	31.20
2	*2480.00	68.8 AV			1.02 V	33	37.60	31.20
3	2483.50	41.1 PK	74.0	-32.9	1.41 V	5	9.90	31.20
4	2483.50	11.0 AV	54.0	-43.0	1.41 V	5	-20.20	31.20
5	4960.00	53.4 PK	74.0	-20.6	1.20 V	333	16.10	37.30
6	4960.00	23.3 AV	54.0	-30.7	1.20 V	333	-14.00	37.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$ .
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

## BELOW 1GHz WORST-CASE DATA : GFSK

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 0		FREQUENCY RANGE
INPUT POWER		120Vac, 60Hz		DETECTOR FUNCTION
ENVIRONMENTAL CONDITIONS		24deg. C, 67%RH		TESTED BY
TEST MODE		A		Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	61.01	17.7 QP	40.0	-22.3	1.36 H	248	4.30	13.40
2	154.33	18.6 QP	43.5	-24.9	1.00 H	265	4.50	14.10
3	243.77	22.3 QP	46.0	-23.7	1.14 H	161	9.50	12.80
4	319.60	19.6 QP	46.0	-26.4	1.58 H	168	4.10	15.50
5	648.18	24.1 QP	46.0	-21.9	1.24 H	208	1.60	22.50
6	774.56	29.3 QP	46.0	-16.7	1.74 H	19	4.30	25.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.35	37.0 QP	40.0	-3.0	1.00 V	151	24.50	12.50
2	59.06	33.1 QP	40.0	-6.9	1.33 V	19	19.60	13.50
3	99.89	20.0 QP	43.5	-23.5	1.54 V	106	10.60	9.40
4	129.06	15.4 QP	43.5	-28.1	1.57 V	71	2.80	12.60
5	232.11	15.6 QP	46.0	-30.4	1.16 V	294	3.30	12.30
6	344.87	17.0 QP	46.0	-29.0	1.20 V	159	0.90	16.10

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	177.67	33.5 QP	43.5	-10.0	1.36 H	75	20.60	12.90
2	247.66	36.5 QP	46.0	-9.5	1.00 H	67	23.60	12.90
3	364.32	31.3 QP	46.0	-14.7	1.25 H	128	14.70	16.60
4	432.37	34.4 QP	46.0	-11.6	1.00 H	9	16.10	18.30
5	724.01	32.4 QP	46.0	-13.6	1.50 H	109	8.80	23.60
6	836.78	39.7 QP	46.0	-6.3	1.13 H	326	13.60	26.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.84	31.8 QP	40.0	-8.2	2.11 V	242	19.30	12.50
2	97.95	34.4 QP	43.5	-9.1	1.00 V	188	25.20	9.20
3	179.61	31.4 QP	43.5	-12.1	1.45 V	173	18.80	12.60
4	226.27	37.2 QP	46.0	-8.8	1.65 V	101	25.10	12.10
5	432.37	25.5 QP	46.0	-20.5	1.12 V	215	7.20	18.30
6	667.63	29.7 QP	46.0	-16.3	1.02 V	350	7.00	22.70

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.68	18.6 QP	40.0	-21.4	1.32 H	55	5.30	13.30
2	70.73	16.9 QP	40.0	-23.1	1.01 H	82	4.80	12.10
3	129.06	13.9 QP	43.5	-29.6	1.63 H	159	1.30	12.60
4	286.55	15.0 QP	46.0	-31.0	1.85 H	254	0.60	14.40
5	329.32	16.3 QP	46.0	-29.7	1.63 H	236	0.60	15.70
6	479.03	19.8 QP	46.0	-26.2	1.14 H	82	0.40	19.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.84	24.1 QP	40.0	-15.9	1.44 V	128	11.60	12.50
2	70.73	20.7 QP	40.0	-19.3	1.65 V	229	8.60	12.10
3	99.89	22.5 QP	43.5	-21.0	1.78 V	56	13.10	9.40
4	129.06	17.3 QP	43.5	-26.2	1.00 V	8	4.70	12.60
5	162.11	15.4 QP	43.5	-28.1	1.36 V	205	1.40	14.00
6	255.44	14.2 QP	46.0	-31.8	1.00 V	357	1.00	13.20

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang
TEST MODE	D		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.5 QP	40.0	-9.5	2.00 H	4	16.90	13.60
2	144.61	22.0 QP	43.5	-21.5	1.50 H	249	8.40	13.60
3	274.88	27.0 QP	46.0	-19.0	1.00 H	71	12.90	14.10
4	552.91	25.5 QP	46.0	-20.5	1.25 H	130	4.10	21.40
5	712.35	28.8 QP	46.0	-17.2	1.00 H	123	4.90	23.90
6	823.17	25.6 QP	46.0	-20.4	2.00 H	4	-0.30	25.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	26.0 QP	40.0	-14.0	1.00 V	130	12.40	13.60
2	282.66	24.5 QP	46.0	-21.5	1.24 V	154	10.10	14.40
3	444.03	20.1 QP	46.0	-25.9	1.00 V	182	1.50	18.60
4	605.41	21.6 QP	46.0	-24.4	1.24 V	62	-1.00	22.60
5	706.51	24.9 QP	46.0	-21.1	1.24 V	144	1.10	23.80
6	827.06	25.2 QP	46.0	-20.8	1.50 V	249	-0.80	26.00

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 23, 2011	Nov. 22, 2012
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 29, 2011	Dec. 28, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 02, 2012	Jul. 01, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 07, 2012	Feb. 06, 2013
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Shielded Room 1.
  3. The VCCI Site Registration No. is C-2040.



A D T

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

#### 4.2.7 TEST RESULTS


##### CONDUCTED WORST CASE DATA: GFSK

<b>PHASE</b>	Line 1	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>A</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
	0.21282	0.22	18.16	0.65	18.38	0.87	63.09	53.09	-44.71	-52.22
1	0.39739	0.24	28.56	8.54	28.80	8.78	57.91	47.91	-29.11	-39.13
2	1.59323	0.33	16.97	1.95	17.30	2.28	56.00	46.00	-38.70	-43.72
3	3.10596	0.40	16.38	2.01	16.78	2.41	56.00	46.00	-39.22	-43.59
4	5.11179	0.45	21.33	7.60	21.78	8.05	60.00	50.00	-38.22	-41.95
5	12.09896	0.58	12.83	0.77	13.41	1.35	60.00	50.00	-46.59	-48.65
6										

##### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




<b>PHASE</b>	Line 2	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>A</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17374	0.20	22.16	3.25	22.36	3.45	64.78	54.78	-42.42	-51.33
2	0.25458	0.21	20.81	0.79	21.02	1.00	61.61	51.61	-40.59	-50.61
3	0.40024	0.22	25.92	6.70	26.14	6.92	57.85	47.85	-31.71	-40.93
4	0.93076	0.26	12.77	1.30	13.03	1.56	56.00	46.00	-42.97	-44.44
5	5.22909	0.47	20.34	8.73	20.81	9.20	60.00	50.00	-39.19	-40.80
6	9.77251	0.60	13.34	2.72	13.94	3.32	60.00	50.00	-46.06	-46.68

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




<b>PHASE</b>	Line 1	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>B</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17737	0.21	51.13	33.49	51.34	33.70	64.61	54.61	-13.26	-20.90
2	0.22429	0.22	44.99	30.28	45.21	30.50	62.66	52.66	-17.45	-22.16
<b>3</b>	<b>0.49324</b>	<b>0.25</b>	<b>39.72</b>	<b>38.82</b>	<b>39.97</b>	<b>39.07</b>	<b>56.11</b>	<b>46.11</b>	<b>-16.14</b>	<b>-7.04</b>
4	1.62717	0.33	35.81	32.07	36.14	32.40	56.00	46.00	-19.86	-13.60
5	2.74162	0.38	28.52	22.34	28.90	22.72	56.00	46.00	-27.10	-23.28
6	12.29055	0.58	35.71	30.40	36.29	30.98	60.00	50.00	-23.71	-19.02

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




<b>PHASE</b>	Line 2	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>B</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16096	0.20	56.44	43.53	56.64	43.73	65.41	55.41	-8.77	-11.68
2	0.22434	0.20	44.32	27.70	44.52	27.90	62.66	52.66	-18.13	-24.75
3	0.49408	0.23	38.64	36.76	38.87	36.99	56.10	46.10	-17.23	-9.11
4	2.04244	0.31	34.75	29.66	35.06	29.97	56.00	46.00	-20.94	-16.03
5	5.87105	0.49	29.54	24.10	30.03	24.59	60.00	50.00	-29.97	-25.41
6	12.31032	0.67	35.35	30.19	36.02	30.86	60.00	50.00	-23.98	-19.14

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



### 4.3 NUMBER OF HOPPING FREQUENCY USED

#### 4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.


#### 4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.




A D T

## GFSK



## 8DPSK






## 4.4 DWELL TIME ON EACH CHANNEL

### 4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.



A D T


#### 4.4.6 TEST RESULTS

##### GFSK


Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) * 6.32 = 332.32 times	0.456	146.978	400
DH3	25 (times / 5 sec) * 6.32 = 158.00 times	1.710	270.180	400
DH5	17 (times / 5 sec) * 6.32 = 107.44 times	3.000	322.320	400

NOTE: Test plots of the transmitting time slot are shown as below.


##### DH1



##### DH3



##### DH5






A D T

### 8DPSK


Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) * 6.32 = 332.32 times	0.498	160.515	400
DH3	25 (times / 5 sec) * 6.32 = 158.00 times	1.740	274.920	400
DH5	17 (times / 5 sec) * 6.32 = 107.44 times	3.050	327.692	400

NOTE: Test plots of the transmitting time slot are shown as below.


#### DH1



#### DH3



#### DH5






A D T

## 4.5 CHANNEL BANDWIDTH

### 4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



A D T

#### 4.5.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	
		GFSK	8DPSK
0	2402	0.875	1.220
39	2441	0.871	1.210
78	2480	0.846	1.220






## 4.6 HOPPING CHANNEL SEPARATION

### 4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.




A D T

#### 4.6.6 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)		20dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)		PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.000	1.010	0.875	1.220	0.583	0.813	PASS
39	2441	1.010	1.010	0.871	1.210	0.581	0.807	PASS
78	2480	1.000	1.000	0.846	1.220	0.564	0.813	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth.






A D T

## 4.7 MAXIMUM OUTPUT POWER

### 4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

### 4.7.2 TEST SETUP



### 4.7.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.7.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

### 4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.7.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



A D T

#### 4.7.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)		OUTPUT POWER (dBm)		POWER LIMIT (mW)	PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	6.653	5.420	8.23	7.34	125	PASS
39	2441	6.653	5.508	8.23	7.41	125	PASS
78	2480	6.561	5.346	8.17	7.28	125	PASS





A D T

## 4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

### 4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

### 4.8.2 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.8.3 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set VBW =300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit continuously.

### 4.8.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

## GFSK


### Hopping disabled\_ Low Channel




### Hopping disabled\_ High Channel



### Hopping enabled\_ Low Channel



### Hopping enabled\_ High Channel







A D T

## 8DPSK


### Hopping disabled\_ Low Channel




### Hopping disabled\_ High Channel



### Hopping enabled\_ Low Channel



### Hopping enabled\_ High Channel





A D T

## 5. TEST TYPES AND RESULTS (FOR BLUETOOTH LE 4.0)

### 5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Same as 4.1.1.

#### 5.1.2 TEST INSTRUMENTS

Same as 4.1.2.

#### 5.1.3 TEST PROCEDURES

Same as 4.1.3.

#### 5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 5.1.5 TEST SETUP

Same as 4.1.5.

#### 5.1.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



A D T

### 5.1.7 TEST RESULTS

#### ABOVE 1GHz DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 0		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		120Vac, 60Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		24deg. C, 67%RH		TESTED BY Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.3 PK	74.0	-17.7	1.38 H	330	25.50	30.80
2	2390.00	43.8 AV	54.0	-10.2	1.38 H	330	13.00	30.80
3	*2402.00	102.1 PK			1.38 H	330	71.20	30.90
4	*2402.00	98.9 AV			1.38 H	330	68.00	30.90
5	4804.00	55.4 PK	74.0	-18.6	1.43 H	37	18.50	36.90
6	4804.00	50.5 AV	54.0	-3.5	1.43 H	37	13.60	36.90
7	#7206.00	57.2 PK	82.1	-24.9	1.00 H	328	13.90	43.30
8	#7206.00	49.8 AV	78.9	-29.1	1.00 H	328	6.50	43.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.7 PK	74.0	-19.3	1.00 V	192	23.90	30.80
2	2390.00	43.8 AV	54.0	-10.2	1.00 V	192	13.00	30.80
3	*2402.00	98.5 PK			1.00 V	192	67.60	30.90
4	*2402.00	95.0 AV			1.00 V	192	64.10	30.90
5	4804.00	55.9 PK	74.0	-18.1	1.05 V	151	19.00	36.90
6	4804.00	51.7 AV	54.0	-2.3	1.05 V	151	14.80	36.90
7	#7206.00	57.0 PK	78.5	-21.5	1.12 V	218	13.70	43.30
8	#7206.00	49.7 AV	75.0	-25.3	1.12 V	218	6.40	43.30

#### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 19		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		120Vac, 60Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		24deg. C, 67%RH		TESTED BY Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	103.6 PK			1.34 H	7	72.60	31.00
2	*2440.00	99.7 AV			1.34 H	7	68.70	31.00
3	4880.00	50.5 PK	74.0	-23.5	1.29 H	181	13.40	37.10
4	4880.00	45.4 AV	54.0	-8.6	1.29 H	181	8.30	37.10
5	7320.00	60.2 PK	74.0	-13.8	1.55 H	136	16.50	43.70
6	7320.00	52.9 AV	54.0	-1.1	1.55 H	136	9.20	43.70

## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	99.2 PK			1.01 V	191	68.20	31.00
2	*2440.00	95.7 AV			1.01 V	191	64.70	31.00
3	4880.00	50.5 PK	74.0	-23.5	1.14 V	168	13.40	37.10
4	4880.00	42.9 AV	54.0	-11.1	1.14 V	168	5.80	37.10
5	7320.00	56.0 PK	74.0	-18.0	1.04 V	226	12.30	43.70
6	7320.00	47.6 AV	54.0	-6.4	1.04 V	226	3.90	43.70

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		FREQUENCY RANGE		1 ~ 25GHz
INPUT POWER		DETECTOR FUNCTION		Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		TESTED BY		Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.4 PK			1.33 H	325	72.20	31.20
2	*2480.00	99.7 AV			1.33 H	325	68.50	31.20
3	2483.50	51.8 PK	74.0	-22.2	1.33 H	325	20.60	31.20
4	2483.50	48.1 AV	54.0	-5.9	1.33 H	325	16.90	31.20
5	4960.00	55.2 PK	74.0	-18.8	1.37 H	20	17.90	37.30
6	4960.00	50.8 AV	54.0	-3.2	1.37 H	20	13.50	37.30
7	7440.00	56.7 PK	74.0	-17.3	1.56 H	139	12.70	44.00
8	7440.00	48.5 AV	54.0	-5.5	1.56 H	139	4.50	44.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	98.6 PK			1.25 V	192	67.40	31.20
2	*2480.00	95.0 AV			1.25 V	192	63.80	31.20
3	2483.50	49.0 PK	74.0	-25.0	1.25 V	192	17.80	31.20
4	2483.50	45.4 AV	54.0	-8.6	1.25 V	192	14.20	31.20
5	4960.00	56.1 PK	74.0	-17.9	1.42 V	150	18.80	37.30
6	4960.00	50.4 AV	54.0	-3.6	1.42 V	150	13.10	37.30
7	7440.00	55.1 PK	74.0	-18.9	1.53 V	210	11.10	44.00
8	7440.00	43.4 AV	54.0	-10.6	1.53 V	210	-0.60	44.00

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.



A D T

**BELow 1GHz WORST-CASE DATA**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Chris Lin
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	107.67	16.5 QP	43.5	-27.0	1.99 H	153	6.10	10.40
2	239.88	27.7 QP	46.0	-18.3	1.24 H	119	15.10	12.60
3	356.54	21.8 QP	46.0	-24.2	1.50 H	6	5.40	16.40
4	617.08	24.2 QP	46.0	-21.8	1.24 H	15	1.90	22.30
5	731.79	25.1 QP	46.0	-20.9	1.00 H	162	1.30	23.80
6	887.33	25.8 QP	46.0	-20.2	1.00 H	104	-0.90	26.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	66.84	22.4 QP	40.0	-17.6	1.24 V	15	9.70	12.70
2	234.05	19.3 QP	46.0	-26.7	1.50 V	329	6.90	12.40
3	467.36	19.1 QP	46.0	-26.9	1.99 V	33	-0.10	19.20
4	706.51	23.2 QP	46.0	-22.8	1.99 V	117	0.00	23.20
5	834.84	34.3 QP	46.0	-11.7	1.50 V	339	8.30	26.00
6	939.83	26.7 QP	46.0	-19.3	1.50 V	226	-0.50	27.20

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	175.72	33.3 QP	43.5	-10.2	1.32 H	91	20.20	13.10
2	255.44	37.1 QP	46.0	-8.9	1.00 H	76	23.90	13.20
3	335.15	29.8 QP	46.0	-16.2	1.05 H	29	13.90	15.90
4	364.32	31.7 QP	46.0	-14.3	1.65 H	126	15.10	16.60
5	663.74	29.7 QP	46.0	-16.3	1.85 H	4	7.00	22.70
6	840.67	35.5 QP	46.0	-10.5	1.12 H	46	9.40	26.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	99.89	34.8 QP	43.5	-8.7	1.45 V	157	25.40	9.40
2	177.67	31.0 QP	43.5	-12.5	1.36 V	186	18.10	12.90
3	230.16	35.4 QP	46.0	-10.6	1.14 V	157	23.20	12.20
4	432.37	24.5 QP	46.0	-21.5	1.85 V	271	6.20	18.30
5	663.74	27.4 QP	46.0	-18.6	1.36 V	358	4.70	22.70
6	840.67	30.5 QP	46.0	-15.5	1.00 V	246	4.40	26.10

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Martin Lee
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	41.22	19.3 QP	40.0	-20.7	1.32 H	241	5.60	13.70
2	111.24	18.4 QP	43.5	-25.1	1.32 H	52	7.60	10.80
3	133.23	17.2 QP	43.5	-26.3	1.12 H	157	4.20	13.00
4	275.55	18.0 QP	46.0	-28.0	1.32 H	254	4.00	14.00
5	365.22	19.7 QP	46.0	-26.3	1.00 H	0	3.10	16.60
6	482.22	24.6 QP	46.0	-21.4	1.37 H	78	5.10	19.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	32.25	20.6 QP	40.0	-19.4	1.14 V	256	8.00	12.60
2	105.66	18.3 QP	43.5	-25.2	1.20 V	142	8.20	10.10
3	128.47	16.7 QP	43.5	-26.8	1.04 V	14	4.10	12.60
4	274.22	16.5 QP	46.0	-29.5	1.63 V	333	2.50	14.00
5	364.22	18.4 QP	46.0	-27.6	1.25 V	5	1.80	16.60
6	502.33	23.0 QP	46.0	-23.0	2.10 V	44	3.00	20.00

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 0		FREQUENCY RANGE Below 1000MHz
INPUT POWER		120Vac, 60Hz		DETECTOR FUNCTION Quasi-Peak
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY Chris Lin
TEST MODE		D		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.8 QP	40.0	-9.2	2.00 H	195	17.20	13.60
2	251.55	24.1 QP	46.0	-21.9	1.00 H	285	10.90	13.20
3	436.26	20.0 QP	46.0	-26.0	2.00 H	33	1.50	18.50
4	531.53	24.0 QP	46.0	-22.0	1.50 H	217	3.10	20.90
5	654.02	28.2 QP	46.0	-17.8	1.24 H	216	5.10	23.10
6	832.89	25.9 QP	46.0	-20.1	1.00 H	193	-0.10	26.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	25.1 QP	40.0	-14.9	1.00 V	120	11.50	13.60
2	251.55	22.0 QP	46.0	-24.0	2.00 V	175	8.80	13.20
3	444.03	18.4 QP	46.0	-27.6	2.00 V	173	-0.20	18.60
4	648.18	24.3 QP	46.0	-21.7	1.50 V	159	1.30	23.00
5	755.12	24.9 QP	46.0	-21.1	1.25 V	189	0.20	24.70
6	883.44	26.1 QP	46.0	-19.9	1.00 V	220	-0.60	26.70

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

## 5.2 CONDUCTED EMISSION MEASUREMENT

### 5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

Same as 4.2.1.

### 5.2.2 TEST INSTRUMENTS

Same as 4.2.2.

### 5.2.3 TEST PROCEDURES

Same as 4.2.3.

### 5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

### 5.2.5 TEST SETUP

Same as 4.2.5.

### 5.2.6 EUT OPERATING CONDITIONS

Same as 4.2.6.



A D T

## 5.2.7 TEST RESULTS


### CONDUCTED WORST CASE DATA:

PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17605	0.21	17.58	1.02	17.79	1.23	64.67	54.67	-46.88	-53.44
2	0.39219	0.24	29.51	9.24	29.75	9.48	58.02	48.02	-28.27	-38.54
3	0.80945	0.29	15.30	0.46	15.59	0.75	56.00	46.00	-40.41	-45.25
4	1.39657	0.32	15.68	1.16	16.00	1.48	56.00	46.00	-40.00	-44.52
5	2.63285	0.37	16.55	1.34	16.92	1.71	56.00	46.00	-39.08	-44.29
6	5.80386	0.46	20.83	7.10	21.29	7.56	60.00	50.00	-38.71	-42.44

### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




<b>PHASE</b>	Line 2	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>A</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17374	0.20	21.76	2.46	21.96	2.66	64.78	54.78	-42.82	-52.12
2	0.23586	0.20	21.40	1.77	21.60	1.97	62.24	52.24	-40.64	-50.27
3	0.37304	0.22	24.03	5.43	24.25	5.65	58.43	48.43	-34.19	-42.79
4	0.88531	0.26	12.16	1.17	12.42	1.43	56.00	46.00	-43.58	-44.57
5	5.79421	0.48	20.21	8.33	20.69	8.81	60.00	50.00	-39.31	-41.19
6	10.95333	0.64	11.83	1.64	12.47	2.28	60.00	50.00	-47.53	-47.72

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




<b>PHASE</b>	Line 1	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>B</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17374	0.21	54.10	40.42	54.31	40.63	64.78	54.78	-10.47	-14.15
2	0.21059	0.22	46.88	32.50	47.10	32.72	63.18	53.18	-16.08	-20.46
<b>3</b>	<b>0.49324</b>	<b>0.25</b>	<b>39.95</b>	<b>39.29</b>	<b>40.20</b>	<b>39.54</b>	<b>56.11</b>	<b>46.11</b>	<b>-15.91</b>	<b>-6.57</b>
4	0.99065	0.31	34.08	30.60	34.39	30.91	56.00	46.00	-21.61	-15.09
5	5.30338	0.46	29.62	24.25	30.08	24.71	60.00	50.00	-29.92	-25.29
6	12.10287	0.58	35.81	30.49	36.39	31.07	60.00	50.00	-23.61	-18.93

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




<b>PHASE</b>	Line 2	<b>6dB BANDWIDTH</b>	9kHz
<b>TEST MODE</b>	<b>B</b>		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16967	0.20	54.51	41.35	54.71	41.55	64.98	54.98	-10.26	-13.42
2	0.19510	0.20	47.42	33.14	47.62	33.34	63.82	53.82	-16.20	-20.48
3	0.48678	0.23	35.16	30.40	35.39	30.63	56.22	46.22	-20.84	-15.60
4	2.12329	0.32	34.53	30.28	34.85	30.60	56.00	46.00	-21.15	-15.40
5	5.43914	0.47	29.18	23.84	29.65	24.31	60.00	50.00	-30.35	-25.69
6	12.13806	0.67	35.32	29.96	35.99	30.63	60.00	50.00	-24.01	-19.37

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### 5.3 6dB BANDWIDTH MEASUREMENT

#### 5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 5.3.2 TEST SETUP



#### 5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 5.3.4 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

### 5.3.7 TEST RESULTS


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.70	0.5	PASS
19	2440	0.70	0.5	PASS
39	2480	0.69	0.5	PASS

## 5.4 CONDUCTED OUTPUT POWER

### 5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz: 1 Watt (30dBm)

### 5.4.2 TEST SETUP



### 5.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 5.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

### 5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

### 5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

### 5.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	4.786	6.80	30	PASS
19	2440	<b>4.819</b>	6.83	30	PASS
39	2480	4.613	6.64	30	PASS




A D T

## 5.5 POWER SPECTRAL DENSITY MEASUREMENT

### 5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 5.5.2 TEST SETUP



### 5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 5.5.4 TEST PROCEDURE

- a. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- d. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(3 \text{ kHz}/100\text{kHz})$

### 5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 5.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

### 5.5.7 TEST RESULTS

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	6.41	-8.82	8	PASS
19	2440	6.44	-8.79	8	PASS
39	2480	6.20	-9.03	8	PASS




A D T

## 5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

### 5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 5.6.2 TEST SETUP



### 5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 5.6.4 TEST PROCEDURE

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



A D T

## MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

### 5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

### 5.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6




### 5.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



A D T

## 5.6.8 TEST RESULTS

**CH 0****CH 19****CH 39**



A D T

## 6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## **8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No modifications were made to the EUT by the lab during the test.

**--- END ---**