



Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-4298/17-02-28

Certification numbers and labeling requirements	
FCC ID	DMOG4SR
IC number	2099A-G4SR
Model name:	SR IEM G4
HVIN (Hardware Version Identification Number)	SR IEM G4
PMN (Product Marketing Name)	ewG4
FVIN (Firmware Version Identification Number)	1.1.0
HMN (Host Marketing Name)	-/-
Antenna:	6602-DVBT-BNC(Male) 470-860 MHz

This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:



Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. power conducted: (peak)	Max. antenna gain:	Min. pathloss:
Analog FM 470-608MHz	Declared 16.6 dBm +/-1 dB)*	Measured : 1.75 dBi	-- (if applicable)

) * worst case result see CTC advanced test report 1-4298/17-02-12

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

	Technology	WLAN
	Frequency	470 MHz
P	Declared max power input to the antenna	17.6 dBm
R	Distance	20 cm
G	Antenna gain	1.75 dBi
S	MPE limit for uncontrolled exposure	0.3133 mW/cm ²
	Calculated Power density:	0.0171 mW/cm ²
	Calculated percentage of limit:	5.47%

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - IC

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		0.3 - 6 GHz
	Technology - WLAN	470 MHz
P	Max power input to the antenna	17.6 dBm
R	Distance	20 cm
G	Antenna gain	1.75 dBi
	Maximum EIRP	86.1 mW
	Exclusion Limit from above:	0.88 W

Conclusion: RF exposure evaluation is not required.

For applications where minimum distance to radiating element is 20cm Annex C of RSS-102 should be filled out.