



RF EXPOSURE REPORT

REPORT NO.: SA980717L11

MODEL NO.: HDR160

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Sennheiser electronic GmbH & Co.KG

ADDRESS: Am Labor 1, D-30900 Wedemark Postfach 100
264, D-30892 Wedemark, Germany

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.



No evaluation required if power is below this threshold:

| F(GHz) | | mW |
|--------|-------|-------|
| Low | 2.403 | 24.59 |
| High | 2.478 | |

Maximum measured transmitter power:

| Pout (dBm) | Pout (mW) | |
|-----------------|-----------|------|
| Conducted Power | 2.330 | 1.71 |
| EIRP Power | 6.300 | 4.27 |

***Note:** The antenna is Inverted F antenna with 3.97dBi gain

Threshold for no SAR evaluation is 24.59mW

Transmitter power is 4.27mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold