

RF Exposure Evaluation

of

E.U.T. : XS WIRELESS
FCC ID. : DMOSKXSW
Model No. : SK-XSW
Working Frequency : 548 MHz ~ 572 MHz

for

APPLICANT : Sennheiser Electric Corp.
ADDRESS : 1 Enterprise Drive, Old Lyme, CT 06371, USA

Test Performed by

TAIWAN TESTING AND CERTIFICATION CENTER

NO. 34. LIN 5, DINGFU VIL., LINKOU DIST.,
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.
TEL : (02)26023052 FAX : (02)26010910
[http:// www.etc.org.tw](http://www.etc.org.tw) ; e-mail:emc@etc.org.tw

Report Number : 22-12-RBF-009-03-MPE

1.Report Version History :

The following revisions have been made to ETC report No. 18-11-RBF-013-02-MPE

<u>Report No.</u>	<u>Date of issue</u>	<u>Description</u>
18-11-RBF-013-02-MPE	Dec.27, 2018	First Version.
22-12-RBF-009-03-MPE	Jul. 03, 2023	1.Reference Test Report (Data from ETC Report No.: 18-11-RBF-013-02-MPE) Class II Change description: To change the PIN with the same VCO as following the KDB Publication 178919 D01 (C2PC) which describes general permissive change policies.

TEST REPORT CERTIFICATION

Applicant : Sennheiser Electric Corp.
 1 Enterprise Drive, Old Lyme, CT 06371, USA

Manufacturer : MASCOT ELECTRIC CO., LTD
 NO. 85, CHANGXING 1ST ST., RENDE DIST., TAINAN CITY
 717, TAIWAN

Description of EUT :

a) Type of EUT : XS WIRELESS
 b) Trade Name : SENNHEISER
 c) Model No. : SK-XSW
 d) FCC ID : DMOSKXSW
 e) Working Frequency : 548 MHz ~ 572 MHz
 f) Power Supply : DC 3V Battery

Regulation Applied: FCC KDB447498 D01. The equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.

Note:

1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC

Issued Date : Jul. 03, 2023

Test Engineer : Brian Huang
 (Brian Huang, Engineer)



Approve & Authorized : Kevin Lee
 Kevin Lee, Section Manager
 EMC Dept. II of TAIWAN
 TESTING AND CERTIFICATION
 CENTER

Product Information:

Type of EUT: XS WIRELESS
FCC ID: DMOSKXSW
Model: SK-XSW

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

The max. average power of channel, including tune-up tolerance(mW) is 10.0mW @ 571.650MHz (With Tune-up tolerance),

The min. test separation distance (mm) is 5 mm,

So, $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 1.51 < 3.0$ (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.

.