



RF EXPOSURE REPORT

REPORT NO.: SA980717L12

MODEL NO.: TR170, TR180

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Sennheiser electronic GmbH & Co.KG

ADDRESS: Am Labor 1, D-30900 Wedemark Postfach 100
264, D-30892 Wedemark, Germany

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.403	24.585
High	2.473	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	6.42	4.385
EIRP Power	8.57	7.194

***Note:** The antenna is Inverted F antenna with 2.15dBi gain

Threshold for no SAR evaluation is 24.585mW
 Transmitter power is 7.194mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold