

# FCC Part 24E Transmitter Certification

# **Test Report**

FCC ID: DNY008MCELL1900

FCC Rule Part: CFR 47 Part 24 Subpart E

ACS Report Number: 06-0458-24E

Manufacturer: EMS Wireless

Equipment Type: PCS Bi-Directional Repeater Tradename: MirrorCell<sup>®</sup> II Model: CDM1912-739

**RF Exposure** 

## **General Information:**

Applicant: EMS Technologies, Inc.

ACS Project: 06-0458

FCC ID: DNY008MCELL1900

Device Category: Fixed

Exposure Conditions: Uncontrolled/General Population

# **Technical Information:**

## **UPLINK:**

Antenna Type: Yagi Antenna Gain Maximum: 15.1dBi Max Transmitter Output Power: 26.39dBm

Max System EIRP: 41.49dBm / 14.1W

Operating Configuration: Fixed

#### DOWNLINK:

Antenna Type: Panel
Antenna Gain Maximum: 7.5dBi
Max Transmitter Output Power: 42.39dBm

Max System EIRP: 49.89dBm / 97.5W

Operating Configuration: Fixed

**NOTE:** Multiple antennas are available for both the uplink and downlink applications. Listed above are antennas with the highest gain.

#### **MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

#### Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Calculations were performed at the frequencies with the highest output power as determined during testing.

Maximum Permissible Exposure (MPE) General Population/Uncontrolled Exposure								
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)	Configuaration
1880	26.39	1.00	435.51	15.1	32.359	34	0.970	Uplink
1960	42.39	1.00	17338.04	7.5	5.623	89	0.980	Downlink

## **Installation Guidelines**

End-users and installers must be provided with antenna installation instructions and transmitter operating conditions for satisfying RF exposure compliance.