

ATTACHMENT B to File No.: T42115-00-00HU

Maximum permissible exposure (MPE) Model: WRTZ1500

1.1

For test instruments and accessories used see section 6 Part **CPC 2**.

1.1.1 Description of the test location

Test location: AREA4

1.1.2 Applicable standard

According to FCC Part 15, Section 15.247(i):

Systems operating under the provisions of this section shall be operated in a manner that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

The test methods used comply with ANSI/IEEE C95.1, "IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz".

This test report shows the compliance with the limits for Maximum Permissible Exposure (MPE) specified in FCC Part 1, Section 1.1310 and the criteria to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in FCC Part 1, Section 1.1307(b).

1.1.3 Description of Measurement

The maximum total power input to the antenna has been measured conducted as described in clause 5.3 of this document. Through the Friis transmission formula, the known maximum gain of the antenna and the maximum power, the MPE can be calculated in a defined distance away from the product.

Friis transmission formula:
$$P_d = \frac{P_{out} * G}{4 * \pi * r^2}$$

where

P_d = power density (mW/cm²)

P_{out} = output power to antenna (mW)

G = gain of antenna (linear scale)

r = distance between antenna and observation point (cm)

ATTACHMENT B to File No.: T42115-00-00HU

1.1.4 Test result

Power setting 29.0 dBm

Antenna BEAM SWITCH ANTENNA: antenna gain: 7.0 dBic

| Channel No. | Frequency | Max power output to antenna | | Antenna gain | Power density | Limit of power density |
|-------------|-----------|-----------------------------|---------|--------------|-----------------------|------------------------|
| | (MHz) | (dBm) | (mW) | (dBi) | (mW/cm ²) | (mW/cm ²) |
| 1 | 902.75 | 29.0 | 794.328 | 7.0 | 0.5989 | 0.602 |

Power setting 27.7 dBm

Antenna 520 10079: antenna gain: 8.3 dBi

| Channel No. | Frequency | Max power output to antenna | | Antenna gain | Power density | Limit of power density |
|-------------|-----------|-----------------------------|---------|--------------|-----------------------|------------------------|
| | (MHz) | (dBm) | (mW) | (dBi) | (mW/cm ²) | (mW/cm ²) |
| 1 | 902.75 | 27.7 | 588.844 | 8.3 | 0.5989 | 0.602 |

Limits for maximum permissible exposure (MPE):

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (B) Limits for General Population / Uncontrolled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | 100 | 30 |
| 3.0 – 30 | 824/f | 2.19/f | 180/ f ² | 30 |
| 30 - 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | --- | --- | f/1500 | 30 |
| 1500-100000 | --- | --- | 1.0 | 30 |

f = Frequency (MHz)

According to FCC Rules 47CFR 2.1093(b) the EUT is not a portable device. The EUT is designed to be used that radiating structures are more than **23 cm outside of the body of the user**. ($r = 23$ cm).

This distance must be stated in the user's manual.

Note: The manufacturer shall state in the manual the minimum cable length for each antenna. Additionally this shall be stated on the label of the EUT.

The requirements are **FULFILLED**.

Remarks:
