

Table of Contents

Report Cover Page.....	1
Table of Contents	2
Figures.....	3
1. GENERAL INFORMATION	4
1.1 Verification of Compliance.....	4
1.2 Equipment Modifications	5
1.3 Product Information	6
1.4 Test Methodology	6
1.5 Test Facility	6
1.6 Test Equipment	6
1.7 Statement for the Document Use	7
2. PRODUCT LABELING	8
3. SYSTEM TEST CONFIGURATION	9
3.1 Justification	9
3.2 Special Accessories.....	9
3.3 Configuration of Tested System	9
4. SYSTEM SCHEMATICS	14
5. RADIATED EMISSION DATA	15
5.1 Field Strength Calculation	15
5.2 Test Methods and Conditions	15
5.3 Test Data	15
6. EUT RECEIVING MODE VERIFICATION.....	20
7. PHOTOS OF TESTED EUT	22

Figures

Figure 2.1 FCC/IC ID Label	8
Figure 2.2 Location of Label	8
Figure 3.1 Radiated Test Setup	10
Figure 4.1 EUT Schematics.....	12
Figure 7.1 Front View.....	23
Figure 7.2 Back View.....	24
Figure 7.3 Inside View	25
Figure 7.4 PCB Component Side View	26
Figure 7.5 PCB Foil Side View.....	27

1. GENERAL INFORMATION

1.1 Verification of Compliance

EUT: SWF Basic Remote Control ZWave

Model: BRZ1

Applicant: SOMFY SYSTEMS INC.

Test Type: FCC Part 15.249 &
 IC RSS-210 (Issue 8) A2.9 & RSS-Gen (Issue 4)

Result: PASS

Tested by: ADVANCED COMPLIANCE LABORATORY


Test Date: April 18, 2016

Report Number: 0048-160405-01

The above equipment was tested by Compliance Laboratory, Advanced Technologies, Inc. for compliance with the requirement set forth in the FCC rules and regulations Part 15 subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
 Lab Manager
 Advanced Compliance Lab

Date April 18, 2016

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC/IC ID	CABLE
Product	SWF Basic Remote Control ZWave, Model: BRZ1	DWNBRZ (1) 12049A-BRZ	
Housing	PLASTICS		
Power Supply	3V DC Battery		
Operation Freq.	908.42MHz, 916MHz		
Receiver	BRZ1(Rx)	Verification	

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2014 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Hillsborough, New Jersey, USA. This site is accepted by FCC to perform measurements under Part 15 or 18 (Registration # 90601) and also designated by IC as “**site IC 3130**”. This site The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Cal Due dd/mm/y
Hewlett-Packard	HP8546A	3448A00290	EMI Receiver	25/09/16
Agilent	E4440A	US40420700	3Hz-26.5GHz Spectrum Analyzer	17/06/16
Electro-Meterics	ALR-25M/30	289	10KHz-30MHz Active Loop Antenna	28/05/16
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	12/11/17
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	13/11/17
EMCO	3115	49225	Double Ridge Guide Horn Antenna	28/11/17

All Test Equipment Used are Calibrated Traceable to NIST Standards. Calibration interval: 2 year.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. & Canada Government.

2. PRODUCT LABELING




Figure 2.1 FCC/IC ID Label
(Only ID show on the EUT)




Figure 2.2 Location of the Label

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). Customized antenna on PCB was used. Testing was performed as EUT was continuously operated at the following frequency channels: Low=908.4MHz, High=916MHz

Fresh external battery was used for extended operating time. However, EUT was checked with the internal battery and it was confirmed that the readings obtained with the fresh external battery remain representative of the device as marketed.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 illustrate this system, which is tested standing along.









Figure 3.1 Radiated Test Setup

4. SYSTEM SCHEMATICS

See Attachment.

Figure 4.1 System Schematics

5. RADIATED EMISSION DATA

5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in dB μ V/m

RA: Amplitude of EMI Receiver before correction in dB μ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

5.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 100KHz IF bandwidth / 100KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. The frequency range from 9KHz up to 10th harmonics were investigated.

5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel:



Typed/Printed Name: Edward Lee

Date: April 18, 2016

Radiated Test Data (CH-908.4/916MHz)

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak /QP Reading at 3m (2) (dBuV/m)	FCC/IC 3m Peak Limit (3) (dBuV/m)	Difference To Peak Limit (dBuV/m)	Average Reading with Correction (>1GHz) (dBuV/m)	FCC/IC 3m QP/Average Limit (1) (dBuV/m)	Difference To AVG Limit (dBuV/m)
908.4	V/X	1.1	080	70.1				94	-23.9
1816.8	V/X	1.1	180	39.8	74			54	-14.2
2725.2	V/X	1.1	180	43.5	74			54	-10.5
908.4	H/X	1.1	090	82.4				94	-11.6
1816.9	H/X	1.0	230	44.3	74			54	-9.7
2725.5	H/X	1.0	135	42.9	74			54	-11.1
916	V/X	1.1	235	68.7				94	-25.3
1832	V/X	1.1	090	38.5	74			54	-15.5
2748	V/X	1.1	080	42.8	74			54	-11.2
916	H/X	1.0	270	80.7				94	-13.3
1832	H/X	1.1	045	43.0	74			54	-11.0
2748	H/X	1.1	045	42.7	74			54	-11.3
908.4	V/Y	1.1	180	72.3				94	-21.7
1816.8	V/Y	1.1	135	42.6	74			54	-11.4
2725.2	V/Y	1.1	080	43.7	74			54	-10.3
908.4	H/Y	1.0	000	81.1				94	-12.9
1816.9	H/Y	1.1	045	39.9	74			54	-14.1
2725.5	H/Y	1.1	270	42.5	74			54	-11.5
916	V/Y	1.1	090	71.8				94	-22.2
1832	V/Y	1.1	135	41.6	74			54	-12.4
2748	V/Y	1.1	135	43.0	74			54	-11.0
916	H/Y	1.0	180	81.3				94	-12.7
1832	H/Y	1.1	000	38.6	74			54	-15.4
2748	H/Y	1.1	000	41.7	74			54	-12.3
908.4	V/Z	1.1	180	84.0				94	-10.0
1816.8	V/Z	1.1	090	39.5	74			54	-14.5
2725.2	V/Z	1.1	080	44.1	74			54	-9.9
908.4	H/Z	1.0	330	77.8				94	-16.2
1816.9	H/Z	1.1	080	38.9	74			54	-15.1
2725.5	H/Z	1.1	235	43.5	74			54	-10.5
916	V/Z	1.1	045	82.7				94	-11.3
1832	V/Z	1.1	000	39.7	74			54	-14.3
2748	V/Z	1.1	000	43.4	74			54	-10.6
916	H/Z	1.0	090	73.6				94	-20.4
1832	H/Z	1.1	180	39.0	74			54	-15.0
2748	H/Z	1.1	135	43.1	74			54	-10.9

(1) The limit for emissions within the 902-928MHz band is 50mV(94dB) per FCC Sec. 15.249 & IC RSS-210 Annex 2.9. The limit for its harmonics is 500uV (54dB). Other spurious emissions shall be lower than either its fundamental by 50dB or the limit defined in Sec. 15.209, whichever is higher.

(2) If the peak reading is less than the FCC/IC quasi-peak or average limit, it'll be not necessary to show the measured/ calculated quasi-peak or average reading.



(3) For above 1GHz range, peak reading shall meet the limit: average Limit+20dB.

Other Spurious outside of the band 902-928MHz



Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC/IC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
350	H/Y	1.1	135	35.2		46.5	-11.3
568	H/Y	1.1	135	34.7		46.5	-11.8
640	H/Y	1.0	180	38.1		46.5	-8.4
810	H/Y	1.0	330	40.7		46.5	-5.8
350	V/Z	1.2	045	34.6		46.5	-11.9
568	V/Z	1.1	080	33.4		46.5	-13.1
640	V/Z	1.1	270	36.1		46.5	-10.4
810	V/Z	1.1	270	41.8		46.5	-4.7

Comparing to the limit defined in FCC Sec. 15.209/IC RSS-Gen, emissions below the limit by 20dB were not recorded.

Frequency: 908MHz



Frequency: 916MHz



6. EUT RECEIVING MODE VERIFICATION

Radiated Test Data for Receiving Mode (worst case: Z&Y-position)

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC/IC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
250	H/Y	1.1	090	33.5		46.5	-13.0
300	H/Y	1.1	045	34.3		46.5	-12.2
480	H/Y	1.0	090	36.7		46.5	-9.8
850	H/Y	1.0	000	40.0		46.5	-6.5
250	V/Z	1.2	135	35.6		46.5	-10.9
300	V/Z	1.1	180	34.9		46.5	-11.6
480	V/Z	1.1	180	36.5		46.5	-10.0
850	V/Z	1.1	090	41.5		46.5	-5.0

(1) Receiving mode spurious emissions shall be lower than the limit defined in FCC Sec. 15.209 & IC RSS-GEN.

(2) If the peak reading is less than the FCC/IC quasi-peak or average limit, it'll be not necessary to show the measured/ calculated quasi-peak or average reading.