

MODEL: J400 LINE 1 (HOT SIDE)

WYSE TECHNOLOGY

1 May 2003 14:42:26

2. CONDUCTED no Preselector

2.3 EN 55022 (1995)

Class B

20 highest Avg Peaks above -25 dB of Limit Line #2
peak criteria = 6 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	.3098	33	-16.9
2	.54	28.7	-17.3
3	.2728	33.5	-17.5
4	.6099	27	-19.0
5	.1996	34.2	-19.4
6	.3462	29.3	-19.7
7	.9265	26.3	-19.7
8	4.369	26	-20.0
9	.2207	32.2	-20.5
10	.6744	25.2	-20.8
11	1.08	25	-21.0
12	1.008	24.8	-21.2
13	3.498	24.8	-21.2
14	3.972	24.8	-21.2
15	3.767	24.6	-21.4
16	.4731	24.9	-21.5
17	4.78	24.5	-21.5
18	3.097	24.1	-21.9
19	1.145	24	-22.0
20	4.582	23.8	-22.2

MODEL: J400 LINE 2 (NEUTRAL SIDE)

WYSE TECHNOLOGY

1 May 2003 15:52:46

2. CONDUCTED no Preselector

2.3 EN 55022 (1995) Class B

20 highest Avg Peaks above -25 dB of Limit Line #2
peak criteria = 6 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	4.036	28.6	-17.4
2	20.17	32.1	-17.9
3	.3098	31.8	-18.1
4	3.016	27.6	-18.4
5	2.938	27.5	-18.5
6	1.934	27.4	-18.6
7	2.441	27	-19.0
8	1.075	26.9	-19.1
9	3.517	26.9	-19.1
10	3.554	26.9	-19.1
11	2.876	26.6	-19.4
12	1.873	26.4	-19.6
13	3.443	26.4	-19.6
14	3.592	26.4	-19.6
15	.9265	26.1	-19.9
16	1.408	26.1	-19.9
17	2.364	26.1	-19.9
18	2.52	26.1	-19.9
19	.5343	26	-20.0
20	.9413	26	-20.0