

=====

WYSE TECHNOLOGY

20 Sep 2002 14:01:44

=====

2. CONDUCTED no Preselector

2.3 EN 55022 (1995)

Class B

WT9450XE - LINE 1 (HOT SIDE)

=====

25 highest Avg Peaks above -15 dB of Limit Line #2
peak criteria = 6 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	.4393	38.1	-8.9
2	.9168	36.6	-9.4
3	.3081	38.9	-11.1
4	1.524	33.7	-12.3
5	3.669	33.5	-12.5
6	.4857	33.4	-12.8
7	.7863	32.4	-13.6
8	1.052	32.4	-13.6
9	4.277	32.4	-13.6
10	.3972	33.6	-14.3

=====

WYSE TECHNOLOGY

20 Sep 2002 14:41:40

=====

2. CONDUCTED no Preselector
2.3 EN 55022 (1995)

Class B

WT9450XE - LINE 2 (NEUTRAL SIDE)

=====

25 highest Avg Peaks above -15 dB of Limit Line #2
peak criteria = 6 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	.9216	36.4	-9.6
2	.3065	38.4	-11.6
3	1.041	34.3	-11.7
4	.437	35.2	-11.9
5	1.532	32.3	-13.7
6	3.669	31.9	-14.1
7	4.277	31.8	-14.2
8	.4806	31.5	-14.8
9	1.109	31.1	-14.9