

FCC LISTED,  
REGISTRATION  
NUMBER: 905266

IC LISTED,  
REGISTRATION  
NUMBER: IC 4621

**CENTRO DE  
TECNOLOGÍA DE LAS  
COMUNICACIONES, S.A.**

Parque Tecnológico de Andalucía,  
c/Severo Ochoa nº 2  
29590 Campanillas/ Málaga/ España  
Tel. 952 61 91 00 - Fax 952 61 91 13  
MÁLAGA, C.I.F. A29 507 456  
Registro Mercantil Tomo 1169 Libro 82  
Folio 133 Hoja MA3729

## TEST REPORT




**Report No.: 18605RET.102**

**TEST NAME:** FCC PART 15.247 TESTING FOR BLUETOOTH RADIO DEVICE

**Product** : MediaPad (Bluetooth remote commander)  
**Trade Mark** : Logitech  
**Model/type Ref.** : Y-RN43  
**Manufacturer** : SUZHOU LOGITECH ELECTRONIC Co. LTD  
**Requested by** : LOGITECH INC.  
**Other identification of the product** : PB2-007  
PB2-009  
**Standard(s)** : USA FCC Part 15.247, 15.205, 15.209, 15.109  
CANADA RSS-210

This test report includes 2 annexes and therefore the total number of pages is 59.

**IMPORTANT: No parts of this report may be reproduced or quoted out of context, and must not be reproduced except in full without the written approval of Centro de Tecnología de las Comunicaciones, S.A. (CETECOM).**

Date: 2003-07-29	Test operator A. Llamas 	Revised by: Date: 2003-08-04 A. Rojas 	Approved by: Date: AG-05 <sup>th</sup> , 2003 F. Broissin Area Director 	Page: 1 of 8 AGY-733865-0000.A0
------------------	---	--	--	------------------------------------

**INDEX**

1. COMPETENCE AND GUARANTEES .....	3
2. GENERAL CONDITIONS .....	3
3. CHARACTERISTICS OF THE TEST .....	3
3.1 TEST REQUESTED .....	3
3.2 REQUIREMENTS AND METHOD .....	3
4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT .....	5
4.1 APPLICANT .....	5
4.2 REPRESENTATIVE .....	5
4.3 TEST SAMPLES SUPPLIER .....	5
4.4 IDENTIFICATION OF ITEM/ITEMS TESTED .....	5
5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS .....	6
5.1 USAGE OF SAMPLES .....	6
5.2 PERIOD OF TESTING .....	6
5.3 ENVIROMENTAL CONDITIONS .....	6
6. TEST RESULTS .....	8
7. REMARKS AND COMMENTS .....	8
8. SUMMARY .....	8

## ANNEXES

ANNEX A. TEST RESULTS

ANNEX B. PHOTOGRAPHS

## 1. COMPETENCE AND GUARANTEES

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

In order to assure the traceability to other national and international laboratories, CETECOM has a calibration and maintenance programme for its measuring equipment.

CETECOM guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at CETECOM at the time of execution of the test.

CETECOM is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

## 2. GENERAL CONDITIONS

1. This report only refers to the item that has undergone the test.
2. This report does not constitute or imply by its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without written approval of CETECOM.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of CETECOM and the Accreditation Bodies.

## 3. CHARACTERISTICS OF THE TEST

### 3.1 TEST REQUESTED

Measurements for frequency hopping spread spectrum equipment (Bluetooth) operating in the 2400 MHz -2483.5 MHz band and using, according to FCC Part 15.247.

### 3.2 REQUIREMENTS AND METHOD

The test has been carried out according to FCC parts 15.33, 15.35, 15.109, 15.205, 15.209, 15.247 and the document DA 00-705:"Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems".

The testing was performed according to the procedure in ANSI C63.4 (1992). Radiated testing was performed in Cetecom's semi-anechoic chamber. This site has been fully described in a report submitted to the FCC and was accepted in a letter dated July 25, 2002.

Report No.:  
18605RET.102

Date: 2003-08-07

Page: 3 of 3

AGY-733865-0000.A0

The instrumentation used to perform the testing is listed below:

1. Semianechoic Absorber Lined Chamber IR 11. BS.
2. Control Chamber IR 12.BC.
3. Spectrum Analyzer HP 8566 B.
4. RF Preselector HP 85685A.
5. Quasi-peak adaptor HP 85650A.
6. RF linear amplifier HP 8447.F
7. Antenna mast EM 1072 NMT.
8. Rotating table EM 1084-4. ON.
9. Mast controller EM 1053-22.
10. Rotating table controller EM 1064-4023.
11. Process controller HP 98581C.
12. Harddisk HP 9153.
13. Peripheral unit HP 9153 C.
14. Measurement software HP 85879A.
15. 3 dB attenuator HP 8491A.
16. Bilog antenna CHASE CBL6111.
17. Bilog antenna CHASE CBL6111.
18. Antenna tripod EMCO 11968C.
19. Double-ridge Guide Horn antenna 1-18 GHz HP 11966E.
20. Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J.
21. Switch Unit with RF pre-amplifiers R&S TS8930SU.
22. RF pre-amplifier Miteq JS4-12002600-30-5A.
23. EMI Test Receiver R&S ESIB26.

#### 4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data in this section has been supplied by the client.

##### 4.1 APPLICANT

**Name or Company:** Logitech INC.

**V.A.T.:** -----

**Address:** 6505 kaiser Drive

**City:** Fremont (California)

**Postal code:** 94555

**Country:** USA

**Telephone:** +1 510 713 4777

**Fax:** +1 510 713 4790

##### 4.2 REPRESENTATIVE

**Name:** Bharatkumar Shah

##### 4.3 TEST SAMPLES SUPPLIER

**Name or Company:** Logitech Europe, S.A.

**V.A.T.:** -----

**Address:** ZI Moulin du Choc

**City:** Romanel Sur Morges

**Postal code:** 1122

**Country:** Switzerland

**Telephone:** +41 (0)21 863 50 67

**Fax:** +41 (0)21 863 53 33

Samples undergoing test have been selected by: [the client](#).

##### 4.4 IDENTIFICATION OF ITEM/ITEMS TESTED

**Product:** Cordless Elite Keyboard for Bluetooth

**Trade mark:** Logitech

**Model:** Y-RP20

**Manufacturer:** Suzhou Logitech Electronic Co., LTD

**Country of manufacture:** P.R.C.

**Manufacture site:** No. 168, Bin He Rd, Standard Plant, 215011, Suzhou City

**Description:** Cordless keyboard for PCs, using Bluetooth technology and combines three common devices all together: Numpad, Remote control and Calculator

Report No.:  
18605RET.102

Date: 2003-08-07

Page: 5 of 5

AGY-733865-0000.A0

## 5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS

### 5.1 USAGE OF SAMPLES

Sample M/01 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
18605/14	MediaPad (Bluetooth remote commander)	Y-RN43	PB2-007	30/06/03

Sample M/02 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
18605/17	MediaPad (Bluetooth remote commander)	Y-RN43	PB2-009	30/06/03

1. Sample M/01 has undergone following test(s).  
Radiated measurements indicated in annex A.
2. Sample M/02 has undergone following test(s).  
Conducted measurements indicated in annex A.

### 5.2 PERIOD OF TESTING

The performed test started on 2003-07-03 and finished on 2003-07-07.

The tests as detailed in this report have been performed at CETECOM.

### 5.3 ENVIROMENTAL CONDITIONS

In the control chamber the following limits were not exceeded during the test:

Temperature	Min. = 24 °C Max. = 25 °C
Relative humidity	Min. = 55 % Max. = 56 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

In the semianechoic chamber (21 meters x 11 meters x 8 meters) the following limits were not exceeded during the test.

Temperature	Min. = 25 °C Max. = 25 °C
Relative humidity	Min. = 51 % Max. = 51 %
Air pressure	Min. = 1017 mbar Max. = 1018 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k $\Omega$
Reference resistance to earth	< 0,5 $\Omega$
Normal site attenuation (NSA)	< $\pm$ 4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements the following limits were not exceeded during the test:

Temperature	Min. = 25 °C Max. = 26 °C
Relative humidity	Min. = 52 % Max. = 53 %
Air pressure	Min. = 1017 mbar Max. = 1018 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k $\Omega$
Reference resistance to earth	< 0,5 $\Omega$



## 6. TEST RESULTS

Abbreviations used in the VERDICT column of the following tables are:

- P** Pass
- F** Fail
- NA** not applicable
- NM** not measured

FCC PART 15 PARAGRAPH	VERDICT			
	NA	P	F	NM
15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation		P		
15.247 Subclause (a) (1) (iii). Number of hopping channels		P		
15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)		P		
15.247 Subclause (b). Maximum peak output power and antenna gain		P		
15.247 Subclause (c). Band-edge of conducted emissions (Transmitter)		P		
15.247 Subclause (c). Emission limitations conducted (Transmitter)		P		
15.247 Subclause (c). Emission limitations radiated (Transmitter)		P		
15.207. Conducted limits	NA			
15.109. Receiver spurious radiation		P		

## 7. REMARKS AND COMMENTS

None.

## 8. SUMMARY

Based on the results of the performed test, stated in annex A the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 "TEST REQUESTED".

NOTE: The results presented in this Test Report apply only to the particular item under test declared in section 4.4 "IDENTIFICATION OF ITEM/ITEMS TESTED" of this document, as presented for test on the date(s) declared in section 5, "USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS".

Report No.: 18605RET.102		Page: 8 of 8
Date: 2003-08-07		AGY-733865-0000.A0



**ANNEX A  
TEST RESULTS**

**Report No: 18605RET.102**

Report No:  
18605RET.102

Date: 2003-08-07

Page: 1 of 1

Annex A  
AGY-733865-0000.A0

## INDEX

	Page
TEST CONDITIONS .....	3
Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation .....	4
Section 15.247 Subclause (a) (1) (iii). Number of hopping channels .....	9
Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time).....	11
Section 15.247 Subclause (b). Maximum peak output power and antenna gain.....	14
Section 15.247 Subclause (c). Band-edge of conducted emissions (Transmitter) .....	21
Section 15.247 Subclause (c). Emission limitations conducted (Transmitter).....	25
Section 15.247 Subclause (c). Emission limitations radiated (Transmitter) .....	28
Section 15.109. Receiver spurious radiation .....	39

**TEST CONDITIONS**

Power supply (V):

$$V_{\text{nominal}} = 3.0 \text{ Vdc}$$

Type of power supply = DC Voltage from batteries

Type of antenna = Integral antenna

Maximum Declared Gain for antenna= 0 dB

Operating Temperature Range (°C):

$$T_n = -15 \text{ to } +55$$

**TEST FREQUENCIES:**

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

The test set-up was made in accordance to the general provisions of ANSI C63.4-1992.

**CONDUCTED MEASUREMENTS**

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyzer via the antenna connector (sma type) provided with the test sample. No coaxial low-loss connecting cable was necessary for such connection so no cable attenuation correction was made.

**RADIATED MEASUREMENTS**

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

**Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation**SPECIFICATION

Frequency hopping system shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


RESULTS

20 dB Bandwidth (see next 3 plots).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	881.76	825.65	873.75
Measurement uncertainty (kHz)	±11		


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH.

Middle Channel: 2441 MHz.




Date: 9.JUL.2003 09:11:44

20 dB BANDWIDTH.  
 Highest Channel: 2480 MHz.





Carrier frequency separation (see next plot).



The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS


**Section 15.247 Subclause (a) (1) (iii). Number of hopping channels**

SPECIFICATION


Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels.

RESULTS

The number of hopping channels is 79 (see next two plots).



Number of hopping frequencies: 39



Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

**Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)**

SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed =  $0.4 \times 79 = 31.6$  seconds.

RESULTS


The equipment only supports 1 slot packet (DH1).

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of  $625\mu s$  with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/2 = 800$  hops per second with 79 channels. So you have each channel  $800/79 = 10.13$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $10.13 \times 31.6 = 320.11$  times of appearance .

Each Tx-time per appearance is  $424.8 \mu s$  (see next plot).

So we have  $320.11 \times 424.8 \mu s = 135.98$  ms per 31.6 seconds.




Verdict: PASS

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet need 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/4 = 400$  hops per second with 79 channels. So you have each channel  $400/79 = 5.1$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $5.1 \times 31.6 = 161.16$  times of appearance .

Each Tx-time per appearance is 1.68 ms (see next plot).

So we have  $161.16 \times 1.68 \text{ ms} = 270.75 \text{ ms}$  per 31.6 seconds.



Verdict: PASS