

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM141000557601
Page: 1 of 45
FCC ID: DZO-IQHOME

TEST REPORT

Application No.:	GZEM1410005576CR
Applicant:	OSRAM SYLVANIA INC
Manufacturer:	Same as the applicant.
FCC ID:	DZO-IQHOME
Product Name:	IQ-H product Zigbee module
Product Description:	Zigbee/ IEEE 802.15.4
Model No.:	IQ Home
Product Name of Host:	LIGHTIFY Flex RGBW
Product Description of Host:	LIGHTIFY Flex RGBW with Zigbee Technology
Model No. of Host:	73661
Trade Mark:	OSRAM
Standards:	CFR 47 FCC PART 15 SUBPART C:2013 section 15.247
Date of Receipt:	2014-10-27
Date of Test:	2014-10-29 to 2014-11-03
Date of Issue:	2015-01-08
Test Result :	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.
Please refer to section 3 of this report for further detail.

Authorized Signature:


Jerry Chan
Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-01-08		Original

Authorized for issue by:			
Tested By		 (Sangdi Huang) / Project Engineer	2014-10-29 to 2014-11-03
Prepared By		 (June Chen) / Clerk	2014-11-11
Checked By		 (Jerry Chan) / Reviewer	2014-11-14

3 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 6.9.1	N/A
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	FCC/KDB-558074 D01 v03r01 Clause 9.1.2	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 6. 11. 2. 3	N/A
Conducted Spurious Emission (30MHz to 25GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.7	PASS
Radiated Spurious Emission 30 MHz to 25 GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	FCC/KDB-558074 D01 v03r01 Clause 13.3.1	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS
Remark:			
EUT: In this whole report EUT means Equipment Under Test.			
Tx: In this whole report Tx (or tx) means Transmitter.			
Rx: In this whole report Rx (or rx) means Receiver.			
RF: In this whole report RF means Radio Frequency.			
ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.			
N/A: not applicable. It means that the change of this class II permissive change and the change does not affect the test result. The result refers to report EESZG09150013 of FCC ID: DZO-IQHOME			

4 Contents

1 Cover Page	1
2 Version.....	2
3 Test Summary.....	3
4 Contents	4
5 General Information.....	5
5.1 Client Information.....	5
5.2 General Description of E.U.T.....	5
5.3 Details of E.U.T	5
5.4 Description of Support Units.....	6
5.5 Deviation from Standards	6
5.6 Abnormalities from Standard Conditions	6
5.7 Other Information Requested by the Customer.....	6
5.8 Test Location.....	6
5.9 Test Facility	7
6 Equipment Used during Test.....	8
7 Test Results	10
7.1 E.U.T. test conditions	10
7.2 Antenna Requirement.....	13
7.3 Maximum Peak Output Power.....	14
7.4 Conducted Spurious Emissions.....	18
7.5 Radiated Spurious Emissions.....	24
7.6 Conducted Emissions at Mains Terminals 150 kHz to 30MHz	42

5 General Information

5.1 Client Information

Applicant: OSRAM SYLVANIA INC
Address of Applicant: 54 Cherry Hill Dr. DANVERS MA 01923 USA
Manufacturer: Same as the applicant.
Address of Manufacturer: Same as the applicant.

5.2 General Description of E.U.T.

Product Name: IQ-H product Zigbee module
Model No.: IQ Home
Product Name of Host: LIGHTIFY Flex RGBW
Model No. of Host: 73661

5.3 Details of E.U.T.

Operating Frequency 2405 MHz to 2480 MHz
Type of Modulation: BPSK/O-QPSK
Number of Channels 16 Channels
Channel Separation: 5 MHz
Antenna Type Integral
Antenna gain: 0 dBi
Function: Zigbee function to transmit and receive signal
Power Supply: Working voltage: AC 100-240V 50/60Hz 1.0A
Adapter: Model: GM36-120300-1
Input: AC 100-240V 50/60Hz 1.0A
Output: DC 12V 3.0A
Power cord: 1.2m x 2 wires unscreened power cable

5.4 Description of Support Units

The EUT has been tested as an independent unit

5.5 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.6 Abnormalities from Standard Conditions

None.

5.7 Other Information Requested by the Customer

None.

5.8 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663
Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

5.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.

6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2013-12-5	2014-12-5
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-04-19	2015-04-19
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2014-03-03	2015-03-03
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2014-05-09	2015-05-09
EMC2025	Trilog Broadband Antenna 30-1000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9160	9160-3372	2014-07-14	2017-07-14
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2013-08-31	2016-08-31
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-05-04	2017-05-04
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2013-08-31	2016-08-31
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2012-07-01	2015-07-01
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2014-03-03	2015-03-03
EMC2065	Amplifier	HP	8447F	N/A	2014-08-25	2015-08-25
EMC0075	310N Amplifier	Sonama	310N	272683	2014-03-03	2015-03-03
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-03-03	2016-03-03
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-05-26	2017-05-26
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2014-04-19	2015-04-19
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2014-05-03	2016-05-03

Conducted Emission						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date (YYYY-MM-DD)	Cal.Due date (YYYY-MM-DD)
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m ³	N/A	N/A	N/A
EMC0118	Two-line v-netwok	R&S	ENV216	100359	2014-03-03	2015-03-03
EMC0102	LISN	SCHAFFNER CHASE	MN2050D/1	1421	2014-09-14	2015-09-14
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2014-03-03	2015-03-03
EMC0107	Coaxial Cable	SGS	2m	N/A	2014-07-25	2016-07-25
EMC0106	Voltage Probe	SGS	N/A	N/A	2014-4-19	2015-4-19
EMC0120	8 Line ISN	Fischer Custom Communications	FCC-TLISN-T8-02	20550	2014-08-30	2015-08-30
EMC0121	4 Line ISN	Fischer Custom Communications	FCC-TLISN-T4-02	20549	2014-08-30	2015-08-30
EMC0122	2 Line ISN	Fischer Custom Communications	FCC-TLISN-T2-02	20548	2014-08-30	2015-08-30
EMC2047	CDN	Elektronik-Feinmechanik	L-801:AF2	2793	2011-11-11	2014-11-11
EMC2048	CDN	Elektronik-Feinmechanik	L-801:M2/M3	2738	2011-11-11	2014-11-11
EMC2062	6dB Attenuator	HP	8491A	24487	2014-04-19	2015-04-19
EMC167	Conical metal housing	SGS-EMC	N/A	N/A	2014-02-16	2016-02-16

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date (YYYY-MM-DD)	Cal.Due date (YYYY-MM-DD)
EMC0006	DMM	Fluke	73	70681569	2014-09-15	2015-09-15
EMC0007	DMM	Fluke	73	70671122	2014-09-15	2015-09-15

7 Test Results

7.1 E.U.T. test conditions

Test Voltage: AC 120V, 60 Hz

Temperature: 20.0 -25.0 °C

Humidity: 38-50 % RH

Atmospheric Pressure: 1000 -1010 mbar

Requirements: **15.31(e):** For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.

Test frequencies and frequency range: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

EUT channels and frequencies list:

1. Test frequencies are lowest channel: 2405 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	12	2460
2	2410	13	2465
3	2415	14	2470
4	2420	15	2475
5	2425	16	2480
6	2430	/	/
7	2435	/	/
8	2440	/	/
9	2445	/	/
10	2450	/	/
11	2455	/	/

7.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed.

Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is an integral and no consideration of replacement. The best case gain of the antenna is 0 dBi.



Test result: The unit does meet the FCC requirements.


7.3 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247
(b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Method: FCC/KDB-558074 D01 v03r01 9.1.1 RBW \geq DTS bandwidth

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:





Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =1.5dB) from the antenna port to the spectrum.
2. Set the $RBW \geq DTS$ bandwidth
3. Set the $VBW \geq 3 \times RBW$
4. Set the span $\geq 3 \times RBW$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Use peak marker function to determine the peak amplitude level.
9. Report the worse case.


Test result:

Channel No.	Frequency (MHz)	Measured Channel Power (dBm)	Limit	Result
1	2405	-8.76	1W(30dBm)	Pass
8	2440	-9.07		Pass
16	2480	-10.18		Pass

Remark: Level = Read Level + Cable Loss.**The unit does meet the FCC requirements.**

Result plot as follows:
Channel 1: 2.405GHz:

Channel 8: 2.440GHz:


Channel 16: 2.480GHz:



7.4 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.7

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:




Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.


Result plot as follows:



Channel 1: 2.405GHz:



30 MHz to 1 GHz





1 G to 5 GHz




5 G to 25 GHz

Channel 8: 2.440GHz:
30 MHz to 1 GHz


1 G to 5 GHz

5 G to 25 GHz


Channel 16:2.480 GHz
30 MHz to 1 GHz

1 G to 5 GHz


5 G to 25 GHz




7.5 Radiated Spurious Emissions


Test Requirement:	FCC Part 15 C section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
Detector:	For PK value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW \geq RBW Sweep = auto Detector function = peak Trace = max hold For AV value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW = 10Hz Sweep = auto Detector function = peak Trace = max hold
15.209 Limit:	40.0 dB μ V/m between 30MHz & 88MHz 43.5 dB μ V/m between 88MHz & 216MHz 46.0 dB μ V/m between 216MHz & 960MHz 54.0 dB μ V/m above 960MHz

Test Configuration:

- 1) 30 MHz to 1 GHz emissions:



- 2) 1 GHz to 40 GHz emissions:



Test Procedure:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting;

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

7.5.1 Harmonic and other spurious emissions & Band Edge


Test at Channel 1 (2.405 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq MHz	ReadAntenna		Cable		Preamp Level	Limit Line dB μ V/m	Over Limit dB	Over Limit Remark
	Level dB μ V	Factor dB/m	Loss dB	Factor dB				
46.995	29.12	12.68	0.00	31.00	10.80	40.00	-29.20	QP
73.617	34.14	10.18	0.00	31.00	13.32	40.00	-26.68	QP
144.842	38.90	13.63	0.00	31.06	21.47	43.50	-22.03	QP
185.138	38.82	11.65	0.00	31.09	19.38	43.50	-24.12	QP
245.090	37.21	11.81	0.00	31.05	17.97	46.00	-28.03	QP
311.087	27.73	13.46	0.00	30.99	10.20	46.00	-35.80	QP

Horizontal:

Peak scan

Level (dB μ V/m)**Quasi-peak measurement**

Freq MHz	Read	Antenna	Cable	Preamp	Limit Line dB	Over Line dB	Over Limit Remark
	Level dBuV	Factor	Loss dB	Factor			
39.162	37.22	12.64	0.00	31.01	18.85	40.00	-21.15 QP
70.090	45.57	10.99	0.00	31.00	25.56	40.00	-14.44 QP
84.999	44.89	8.68	0.00	31.00	22.57	40.00	-17.43 QP
123.266	40.46	12.21	0.00	31.02	21.65	43.50	-21.85 QP
217.544	35.01	10.73	0.00	31.08	14.66	46.00	-31.34 QP
266.609	34.54	12.36	0.00	31.02	15.88	46.00	-30.12 QP

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4810.00	48.17	31.53	11.11	38.57	52.24	74.00	V
7215.00	42.45	36.47	12.96	38.85	53.03	74.00	V
9620.00	42.08	38.08	15.16	39.71	55.61	74.00	V
4810.00	50.13	31.53	11.11	38.57	54.20	74.00	H
7215.00	43.03	36.47	12.96	38.85	53.61	74.00	H
9620.00	44.88	38.08	15.16	39.71	58.41	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4810.00	43.67	31.53	11.11	38.57	47.74	54.00	V
7215.00	37.06	36.47	12.96	38.85	47.64	54.00	V
9620.00	36.30	38.08	15.16	39.71	49.83	54.00	V
4810.00	43.66	31.53	11.11	38.57	47.73	54.00	H
7215.00	39.64	36.47	12.96	38.85	50.22	54.00	H
9620.00	35.84	38.08	15.16	39.71	49.37	54.00	H


Test at Channel 8 (2.440 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq MHz	Read	Antenna Level	Cable Loss	Preamp Factor	Level dB	Limit dBuV/m	Line dBuV/m	Over Line dB	Over Limit Remark
	MHz	dB μ V	dB/m		dB	dB μ V/m	dB μ V/m	dB	
49.014	23.72	12.59	0.00	31.00	5.31	40.00	40.00	-34.69	QP
65.803	25.40	12.13	0.00	31.00	6.53	40.00	40.00	-33.47	QP
128.563	31.37	12.58	0.00	31.03	12.92	43.50	43.50	-30.58	QP
154.279	34.36	13.89	0.00	31.07	17.18	43.50	43.50	-26.32	QP
246.815	33.49	11.86	0.00	31.04	14.31	46.00	46.00	-31.69	QP
368.112	25.78	14.59	0.00	30.92	9.45	46.00	46.00	-36.55	QP

Horizontal:

Peak scan

Level (dB μ V/m)**Quasi-peak measurement**

Freq MHz	Read	Antenna Level	Cable Loss	Preamp Factor	Level dB	dBuV/m	dBuV/m	dBuV/m	dB	Over Line Limit	Over Limit Remark
	dBuV	dB/m	dB	Factor							
39.162	33.22	12.64	0.00	31.01	14.85	40.00	40.00	40.00	-25.15	QP	
70.090	39.57	10.99	0.00	31.00	19.56	40.00	40.00	40.00	-20.44	QP	
85.598	40.45	8.75	0.00	31.00	18.20	40.00	40.00	40.00	-21.80	QP	
123.266	36.46	12.21	0.00	31.02	17.65	43.50	43.50	43.50	-25.85	QP	
217.544	32.01	10.73	0.00	31.08	11.66	46.00	46.00	46.00	-34.34	QP	
266.609	31.54	12.36	0.00	31.02	12.88	46.00	46.00	46.00	-33.12	QP	

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4880.00	44.89	31.57	11.24	38.56	49.14	74.00	V
7320.00	42.75	36.50	13.28	38.88	53.65	74.00	V
9760.00	43.99	38.46	15.05	39.74	57.76	74.00	V
4880.00	45.86	31.57	11.24	38.56	50.11	74.00	H
7320.00	44.03	36.50	13.28	38.88	54.93	74.00	H
9760.00	45.40	38.46	15.05	39.74	59.17	74.00	H

Average Measurement:


Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4880.00	40.60	31.57	11.24	38.56	44.85	54.00	V
7320.00	37.65	36.50	13.28	38.88	48.55	54.00	V
9760.00	35.99	38.46	15.05	39.74	49.76	54.00	V
4880.00	42.63	31.57	11.24	38.56	46.88	54.00	H
7320.00	39.89	36.50	13.28	38.88	50.79	54.00	H
9760.00	35.63	38.46	15.05	39.74	49.40	54.00	H

Test at Channel 16 (2.480 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan


Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	Read Level dB μ V	Antenna Factor dB/m	Cable Loss Factor dB	Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Over Limit Remark
38.888	24.93	12.63	0.00	31.01	6.55	40.00	-33.45	QP
54.261	25.32	12.42	0.00	31.00	6.74	40.00	-33.26	QP
85.598	32.91	8.75	0.00	31.00	10.66	40.00	-29.34	QP
146.888	37.03	13.75	0.00	31.06	19.72	43.50	-23.78	QP
238.310	36.54	11.67	0.00	31.05	17.16	46.00	-28.84	QP
365.539	27.16	14.50	0.00	30.93	10.73	46.00	-35.27	QP

Horizontal:

Peak scan

Level (dB μ V/m)**Quasi-peak measurement**

Freq MHz	Read		Antenna		Cable		Preamp Level dB	Limit Line dBuV/m	Over Line dB	Over Limit Remark
	Level dBuV	Factor dB/m	Loss Factor dB	Level dBuV/m						
38.752	36.47	12.61	0.00	31.01	18.07	40.00	-21.93	QP		
71.330	40.82	10.75	0.00	31.00	20.57	40.00	-19.43	QP		
85.298	40.66	8.72	0.00	31.00	18.38	40.00	-21.62	QP		
124.133	34.15	12.29	0.00	31.02	15.42	43.50	-28.08	QP		
138.387	33.77	13.26	0.00	31.04	15.99	43.50	-27.51	QP		
263.819	31.66	12.28	0.00	31.02	12.92	46.00	-33.08	QP		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4960.00	48.86	31.70	11.39	38.56	53.39	74.00	V
7440.00	43.32	36.60	13.60	38.91	54.61	74.00	V
9920.00	43.61	38.65	14.92	39.78	57.40	74.00	V
4960.00	47.49	31.70	11.39	38.56	52.02	74.00	H
7440.00	43.80	36.60	13.60	38.91	55.09	74.00	H
9920.00	44.31	38.65	14.92	39.78	58.10	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4960.00	42.00	31.70	11.39	38.56	46.53	54.00	V
7440.00	37.73	36.60	13.60	38.91	49.02	54.00	V
9920.00	35.66	38.65	14.92	39.78	49.45	54.00	V
4960.00	41.31	31.70	11.39	38.56	45.84	54.00	H
7440.00	36.10	36.60	13.60	38.91	47.39	54.00	H
9920.00	36.49	38.65	14.92	39.78	50.28	54.00	H

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Band Edges:

Lowest 2405MHz

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.0	27.58	6.56	38.25	46.37	42.26	74.00	V
2483.5	27.55	6.99	38.26	46.97	43.25	74.00	V
2400.0	27.58	6.56	38.25	46.71	42.60	74.00	H
2483.5	27.55	6.99	38.26	47.63	43.91	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.0	27.58	6.56	38.25	42.62	38.51	54.00	V
2483.5	27.55	6.99	38.26	42.83	39.11	54.00	V
2400.0	27.58	6.56	38.25	42.98	38.87	54.00	H
2483.5	27.55	6.99	38.26	43.23	39.51	54.00	H

Highest 2480MHz

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.0	27.58	6.56	38.25	45.43	41.32	74.00	V
2483.5	27.55	6.99	38.26	47.18	43.46	74.00	V
2400.0	27.58	6.56	38.25	45.57	41.46	74.00	H
2483.5	27.55	6.99	38.26	45.60	41.88	74.00	H

Average Measurement:

Frequency (MHz)	Frequen cy (MHz)	Frequency (MHz)	Frequenc y (MHz)	Frequen cy (MHz)	Frequency (MHz)	Frequenc y (MHz)	Frequency (MHz)
2400.0	27.58	6.56	38.25	42.61	38.50	54.00	V
2483.5	27.55	6.99	38.26	43.29	39.57	54.00	V
2400.0	27.58	6.56	38.25	41.35	37.24	54.00	H
2483.5	27.55	6.99	38.26	40.51	36.79	54.00	H

Remark:

- 1). The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

Test result: The unit does meet the FCC requirements.

7.5.2 Radiated Emissions which fall in the restricted bands

Test Requirement:	FCC Part 15 C section 15.247
	(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Limit:	40.0 dB μ V/m between 30MHz & 88MHz; 43.5 dB μ V/m between 88MHz & 216MHz; 46.0 dB μ V/m between 216MHz & 960MHz; 54.0 dB μ V/m above 960MHz.
Detector:	For PK value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW \geq RBW Sweep = auto Detector function = peak Trace = max hold
	For AV value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW = 10Hz Sweep = auto Detector function = peak Trace = max hold

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

Test Result:

Test at Channel 1 (2.405 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	57.46	27.93	4.74	35.09	55.04	74.00	Vertical
2390.000	56.12	27.63	4.96	35.05	53.66	74.00	V
2483.500	57.38	27.55	4.9	34.99	54.84	74.00	V
2500.000	53.59	27.55	5.00	34.98	51.16	74.00	V
2310.000	55.27	27.93	4.74	35.09	52.85	74.00	Horizontal
2390.000	57.68	27.63	4.96	35.05	55.22	74.00	H
2483.500	56.54	27.55	4.9	34.99	54.00	74.00	H
2500.000	55.74	27.55	5.00	34.98	53.31	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	47.31	27.93	4.74	35.09	44.89	54.00	Vertical
2390.000	46.58	27.63	4.96	35.05	44.12	54.00	V
2483.500	49.77	27.55	4.9	34.99	47.23	54.00	V
2500.000	46.58	27.55	5.00	34.98	44.15	54.00	V
2310.000	43.76	27.93	4.74	35.09	41.34	54.00	Horizontal
2390.000	47.51	27.63	4.96	35.05	45.05	54.00	H
2483.500	47.33	27.55	4.9	34.99	44.79	54.00	H
2500.000	46.54	27.55	5.00	34.98	44.11	54.00	H

Test at Channel 8 (2.440 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna actors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	54.69	27.93	4.74	35.09	52.27	74.00	Vertical
2390.000	55.72	27.63	4.96	35.05	53.26	74.00	V
2483.500	54.28	27.55	4.90	34.99	51.74	74.00	V
2500.000	55.96	27.55	5.00	34.98	53.53	74.00	V
2310.000	54.38	27.93	4.74	35.09	51.96	74.00	Horizontal
2390.000	55.75	27.63	4.96	35.05	53.29	74.00	H
2483.500	53.89	27.55	4.90	34.99	51.35	74.00	H
2500.000	54.36	27.55	5.00	34.98	51.93	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	44.66	27.93	4.74	35.09	42.24	54.00	Vertical
2390.000	46.37	27.63	4.96	35.05	43.91	54.00	V
2483.500	45.29	27.55	4.90	34.99	42.75	54.00	V
2500.000	44.38	27.93	4.74	35.09	41.96	54.00	V
2310.000	42.65	27.93	4.74	35.09	40.23	54.00	Horizontal
2390.000	42.74	27.63	4.96	35.05	40.28	54.00	H
2483.500	44.35	27.55	4.90	34.99	41.81	54.00	H
2500.000	45.68	27.93	4.74	35.09	43.26	54.00	H

Test at Channel 16 (2.480 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	53.12	27.93	4.74	35.09	50.70	74.00	Vertical
2390.000	54.55	27.63	4.96	35.05	52.09	74.00	V
2483.500	53.79	27.55	4.90	34.99	51.25	74.00	V
2500.000	54.62	27.93	4.74	35.09	52.20	74.00	V
2310.000	53.41	27.93	4.74	35.09	50.99	74.00	Horizontal
2390.000	53.56	27.63	4.96	35.05	51.10	74.00	H
2483.500	52.75	27.55	4.90	34.99	50.21	74.00	H
2500.000	52.60	27.93	4.74	35.09	50.18	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	42.43	27.93	4.74	35.09	40.01	54.00	Vertical
2390.000	43.86	27.63	4.96	35.05	41.40	54.00	V
2483.500	45.78	27.55	4.90	34.99	43.24	54.00	V
2500.000	46.14	27.93	4.74	35.09	43.72	54.00	V
2310.000	45.96	27.93	4.74	35.09	43.54	54.00	Horizontal
2390.000	46.73	27.63	4.96	35.05	44.27	54.00	H
2483.500	45.86	27.55	4.90	34.99	43.32	54.00	H
2500.000	44.89	27.93	4.74	35.09	42.47	54.00	H

7.6 Conducted Emissions at Mains Terminals 150 kHz to 30MHz

Test Requirement: FCC Part 15 C section 15.207
Test Method: ANSI C63.10: Clause 6.2
Frequency Range: 150 kHz to 30 MHz
Detector: Peak for pre-scan (9kHz Resolution Bandwidth)
Test Limit


Limits for conducted disturbance at the mains ports of class B

Frequency Range (MHz)	Class B Limit (dBuV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.
Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Pre-test the EUT in 2405MHz, 2440MHz, and 2480MHz, find worst case in 2405 MHz.

Test Configuration:



Test procedure:

1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

7.6.1 Measurement Data


An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT:

Neutral Line


Level(dB μ V)



Measure data:

Freq	Read Level	Cable Loss	LISN Factor	Level	Limit Line	Over Limit	Remark
MHz	dB μ V	dB	dB	dB μ V	dB μ V	dB	
0.164	35,26	0,10	9,66	45,02	65,25	-20,24	QP
0.164	24,68	0,10	9,66	34,44	55,25	-20,82	AVERAGE
0.234	27,74	0,08	9,66	37,48	62,30	-24,83	QP
0.234	16,45	0,08	9,66	26,19	52,30	-26,12	AVERAGE
0.611	24,06	0,03	9,67	33,76	56,00	-22,24	QP
0.611	13,57	0,03	9,67	23,27	46,00	-22,73	AVERAGE
0.918	23,10	0,00	9,67	32,78	56,00	-23,22	QP
0.918	13,08	0,00	9,67	22,76	46,00	-23,24	AVERAGE
3,364	21,66	0,16	9,70	31,52	56,00	-24,48	QP
3,364	11,39	0,16	9,70	21,25	46,00	-24,75	AVERAGE
7,175	16,62	0,26	9,74	26,62	60,00	-33,38	QP
7,175	9,45	0,26	9,74	19,45	50,00	-30,55	AVERAGE

Live Line

Level(dB μ V)

Measure result:

Freq MHz	Read Level dB μ V	Cable Loss dB	LISN Factor dB	Level dB μ V	Limit Line dB μ V	Over Limit dB	Over Limit	Remark
							Line	QP
0.163	36.54	0.10	9.60	46.24	65.30	-19.06		QP
0.163	23.68	0.10	9.60	33.38	55.30	-21.92		AVERAGE
0.259	28.84	0.07	9.62	38.53	61.47	-22.94		QP
0.259	19.51	0.07	9.62	29.20	51.47	-22.27		AVERAGE
0.943	12.08	0.00	9.70	21.78	46.00	-24.22		AVERAGE
0.943	19.88	0.00	9.70	29.58	56.00	-26.42		QP
1.535	24.78	0.06	9.70	34.54	56.00	-21.46		QP
1.535	16.51	0.06	9.70	26.27	46.00	-19.73		AVERAGE
3.417	9.45	0.16	9.70	19.31	46.00	-26.69		AVERAGE
3.417	22.48	0.16	9.70	32.34	56.00	-23.66		QP
16.398	9.39	0.37	9.99	19.76	50.00	-30.24		AVERAGE
16.398	18.70	0.37	9.99	29.07	60.00	-30.93		QP

--End of Report--