Applicant/Grantee Dell Computer Corporation						
FCC ID: E2KDWBT3						
Section 15.212 Modular Transmitters						
Request	for Modular Approval Requ	est for Limited Modular Approval				
	Requirements	EUT Conditions	Comply (Y/N)			
	Single Modular Approval Requirements					
1	The radio elements of the modular	Device is equipped with Metal shielding	Y			
	transmitter must have their own	to cover RF section.				
	shielding. The physical crystal and	Refer to external photos.				
	tuning capacitors may be located	1				
	external to the shielded radio elements.					
2	The modular transmitter must have	All inputs to the modules are buffered	Y			
	buffered modulation/data inputs (if such	through logic or microprocessor inputs.				
	inputs are provided) to ensure that the					
	module will comply with Part 15					
	requirements under conditions of					
	excessive data rates or over-modulation.					
3	The modular transmitter must have its	The mini-pci interface provides 3.3VDC,	Y			
	own power supply regulation.	so there are rgulator in fron to these				
		chips.				
4	The modular transmitter must comply	Refer to antenna specification and test	Y			
	with the antenna and transmission	report.				
	system requirements of Sections 15.203,					
	15.204(b) and 15.204(c). The antenna					
	must either be permanently attached or					
	employ a "unique" antenna coupler (at					
	all connections between the module and					
	the antenna, including the cable). The					
	"professional installation" provision of					
	Section 15.203 is not applicable to					
	modules but can apply to limited					
	modular approvals under paragraph (b)					
	of this section.					
5	The modular transmitter must be tested	The EUT was test in Notebook	Y			
	in a stand-alone configuration, <i>i.e.</i> , the	Computer (Brand name: DELL; Model:				
	module must not be inside another	P05G). Please see section Photographs				
	device during testing for compliance	of Test Configuration in the test report.				
	with Part 15 requirements. Unless the					
	transmitter module will be battery					
	powered, it must comply with the AC					
	line conducted requirements found in					
	Section 15.207. AC or DC power lines					
	and data input/output lines connected to					
	the module must not contain ferrites,					
	unless they will be marketed with the					
	module (see Section 15.27(a)). The					
	length of these lines shall be the length					
	typical of actual use or, if that length is					
	unknown, at least 10 centimeters to					
	insure that there is no coupling between					

	1 01 11 1		1
	the case of the module and supporting		
	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	Refer to label format and location file.	Y
	equipped with either a permanently	110101 00 100 01 10111100 0110 10 00011011	
	affixed label or must be capable of		
	electronically displaying its FCC		
	identification number.		
	(A) If using a permanently affixed label, the modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC		
	identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains		
	Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which explain		
	this requirement. In the latter case, a copy of these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same		
	meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for equipment authorization.		
7	The modular transmitter must comply	Detail instructions for maintaining	Y
,	with any specific rules or operating	compliance are given in the Users	•
	requirements that ordinarily apply to a	Manual.	
	complete transmitter and the	ividitidat.	
	manufacturer must provide adequate		
	instructions along with the module to		
	explain any such requirements. A copy		
	of these instructions must be included in		
	the application for equipment		

	authorization.			
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The EUT is compliant with all applicable RF exposure requirements. RF Exposure is addressed in the RF exposure exhibition.	Y	
· ·				

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Signature:

NAME: Steven Wang

TITLE: Section Manager

Date: March 10, 2010

TESTING LABORATORY: Compliance Certification Services Inc.