

FCC RF Test Report


APPLICANT : DELL Inc.
EQUIPMENT : Tablet PC
BRAND NAME : Dell
MODEL NAME : T01C
TYPE NAME : T01C001
FCC ID : E2K-T01C001
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Aug. 12, 2013 and testing was completed on Sep. 11, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 6

 1.6 Testing Site 7

 1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Carrier Frequency Channel 8

 2.2 Pre-Scanned RF Power 9

 2.3 Test Mode 10

 2.4 Connection Diagram of Test System 11

 2.5 Support Unit used in test configuration and system 12

 2.6 Description of RF Function Operation Test Setup 12

 2.7 Measurement Results Explanation Example 13

3 TEST RESULT 14

 3.1 6dB and 99% Bandwidth Measurement 14

 3.2 Output Power Measurement 17

 3.3 Power Spectral Density Measurement 20

 3.4 Conducted Band Edges and Spurious Emission Measurement 23

 3.5 Radiated Band Edges and Spurious Emission Measurement 33

 3.6 AC Conducted Emission Measurement 61

 3.7 Antenna Requirements 65

4 LIST OF MEASURING EQUIPMENT 66

5 UNCERTAINTY OF EVALUATION 67

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR381201B	Rev. 01	Initial issue of report	Sep. 24, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	RSS-Gen 4.6.1	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-210 A8.4	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.92 dB at 50.370 MHz
3.6	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 17.13 dB at 0.390 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

DELL Inc.
One Dell Way, Round Rock, Texas 78682, United States

1.2 Manufacturer

DELL Inc.
One Dell Way, Round Rock, Texas 78682, United States

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	Dell
Model Name	T01C
Type Name	T01C001
FCC ID	E2K-T01C001
EUT supports Radios application	WLAN 2.4GHz 802.11bgn HT20/Bluetooth v3.0 + EDR/ Bluetooth v4.0
HW Version	B1.1
SW Version	V01.19
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum Output Power to Antenna	802.11b : 17.22 dBm (0.0527 W) 802.11g : 22.62 dBm (0.1828 W) 802.11n HT20 : 21.70 dBm (0.1479 W)
99% Occupied Bandwidth	802.11b : 12.20MHz 802.11g : 17.05MHz 802.11n HT20 : 17.90MHz
Antenna Type	FPC Antenna with gain 3.25 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC/IC Registration No.
	TH01-KS	CO01-KS	03CH01-KS	149928/4086E-1

Note: The test site complies with ANSI C63.4 2003 requirement.

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8
- ♦ IC RSS-Gen Issue 3
- ♦ NOTICE 2012-DRS0126

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. Per the section 2.2.3 of Notice of 2012-DRS0126, " Receivers Excluded from Industry Canada Requirements", only radiocommunication receivers operating in stand-alone mode within the band 30-960 MHz and scanner receivers are subject to Industry Canada requirements.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and the highest data rates of peak power were chosen for full test shown in the following tables.

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412 MHz	17.22	16.96	16.83	17.20
CH 06	2437 MHz	16.29	16.45	16.52	16.32
CH 11	2462 MHz	16.77	16.78	16.79	17.02

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412 MHz	22.58	22.32	21.81	22.05	22.17	22.05	22.21	21.87
CH 06	2437 MHz	21.96	21.97	21.98	21.82	21.43	21.57	21.93	21.89
CH 11	2462 MHz	22.62	22.58	22.56	22.37	22.39	22.34	22.32	22.01

Channel	Frequency	2.4GHz 802.11n HT20 RF Power (dBm)							
		OFDM Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412 MHz	20.42	20.33	20.30	20.52	20.84	20.52	20.81	20.74
CH 06	2437 MHz	21.13	21.16	20.89	20.94	21.23	20.93	21.13	21.12
CH 11	2462 MHz	21.70	21.48	21.69	21.56	21.66	21.40	21.64	21.69



2.3 Test Mode


Final results of test modes, data rates and test channels are shown as following table.

Test Cases				
	Test Items	Mode	Data Rate	Test Channel
Conducted TCs	6dB and 99% BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
Conducted Spurious Emission	802.11b	1 Mbps	1/6/11	
	802.11g	6 Mbps	1/6/11	
	802.11n HT20	MCS0	1/6/11	
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11


Test Cases	
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GWINSTEK	GPS-3030D	FCC DoC	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m
4.	Earphone	Lenovo	SH100	FCC DoC	N/A	N/A
5.	Bluetooth Earphone	Lenovo	LBH301	FCC DoC	N/A	N/A

2.6 Description of RF Function Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.6 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5.6 + 10 = 15.6 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Test Band :	2.4GHz	Temperature :	20~23°C
Test Engineer :	Neil Zhu	Relative Humidity :	45~46%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	99% Bandwidth (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.20	7.04	0.5	Pass
11b	1Mbps	1	6	2437	12.05	7.00	0.5	Pass
11b	1Mbps	1	11	2462	12.00	7.04	0.5	Pass
11g	6Mbps	1	1	2412	17.00	15.08	0.5	Pass
11g	6Mbps	1	6	2437	17.05	15.08	0.5	Pass
11g	6Mbps	1	11	2462	17.00	15.08	0.5	Pass
HT20	MCS0	1	1	2412	17.90	15.08	0.5	Pass
HT20	MCS0	1	6	2437	17.90	15.08	0.5	Pass
HT20	MCS0	1	11	2462	17.90	15.08	0.5	Pass



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test Mode :	2.4GHz	Temperature :	20~23°C
Test Engineer :	Neil Zhu	Relative Humidity :	45~46%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	17.22	30	3.25	Pass
11b	1Mbps	1	6	2437	16.29	30	3.25	Pass
11b	1Mbps	1	11	2462	16.77	30	3.25	Pass
11g	6Mbps	1	1	2412	22.58	30	3.25	Pass
11g	6Mbps	1	6	2437	21.96	30	3.25	Pass
11g	6Mbps	1	11	2462	22.62	30	3.25	Pass
HT20	MCS0	1	1	2412	20.42	30	3.25	Pass
HT20	MCS0	1	6	2437	21.13	30	3.25	Pass
HT20	MCS0	1	11	2462	21.70	30	3.25	Pass

Note: Measured power (dBm) has offset with cable loss.



3.2.6 Test Result of Average output Power (Reporting Only)

Test Mode :	2.4GHz	Temperature :	20~23°C
Test Engineer :	Neil Zhu	Relative Humidity :	45~46%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.32	14.02	30	3.25	Pass
11b	1Mbps	1	6	2437	0.32	13.14	30	3.25	Pass
11b	1Mbps	1	11	2462	0.32	13.84	30	3.25	Pass
11g	6Mbps	1	1	2412	0.23	12.81	30	3.25	Pass
11g	6Mbps	1	6	2437	0.23	12.86	30	3.25	Pass
11g	6Mbps	1	11	2462	0.23	13.13	30	3.25	Pass
HT20	MCS0	1	1	2412	0.25	10.73	30	3.25	Pass
HT20	MCS0	1	6	2437	0.25	11.46	30	3.25	Pass
HT20	MCS0	1	11	2462	0.25	12.18	30	3.25	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Test Mode :	2.4GHz	Temperature :	20~23°C
Test Engineer :	Neil Zhu	Relative Humidity :	45~46%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-7.78	8	3.25	Pass
11b	1Mbps	1	6	2437	-7.82	8	3.25	Pass
11b	1Mbps	1	11	2462	-7.29	8	3.25	Pass
11g	6Mbps	1	1	2412	-11.37	8	3.25	Pass
11g	6Mbps	1	6	2437	-11.20	8	3.25	Pass
11g	6Mbps	1	11	2462	-10.71	8	3.25	Pass
HT20	MCS0	1	1	2412	-12.28	8	3.25	Pass
HT20	MCS0	1	6	2437	-12.28	8	3.25	Pass
HT20	MCS0	1	11	2462	-11.54	8	3.25	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval.
5. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
6. Measure and record the results in the test report.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	20~23°C
Test Band :	2.4GHz Low	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Neil Zhu






Test Mode :	802.11b	Temperature :	20~23°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~46%
Test Channel :	06	Test Engineer :	Neil Zhu


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 17.AUG.2013 10:51:38

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 10:52:00

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 10:52:20



Test Mode :	802.11b	Temperature :	20~23°C
Test Band :	2.4GHz High	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Neil Zhu


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 17.AUG.2013 10:43:17

High Channel Plot




Date: 17.AUG.2013 10:43:37

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 10:44:09

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 10:44:28



Test Mode :	802.11g	Temperature :	20~23°C
Test Band :	2.4GHz Low	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Neil Zhu


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 17.AUG.2013 10:57:46

Low Channel Plot




Date: 17.AUG.2013 10:58:06

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 10:58:31

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 10:58:51



Test Mode :	802.11g	Temperature :	20~23°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~46%
Test Channel :	06	Test Engineer :	Neil Zhu


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 17.AUG.2013 09:53:15

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 09:53:54

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 09:54:13



Test Mode :	802.11g	Temperature :	20~23°C
Test Band :	2.4GHz High	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Neil Zhu


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 17.AUG.2013 09:57:14

High Channel Plot




Date: 17.AUG.2013 09:58:05

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 09:58:55

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 09:59:14



Test Mode :	802.11n HT20	Temperature :	20~23°C
Test Band :	2.4GHz Low	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Neil Zhu


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 17.AUG.2013 10:02:46

Low Channel Plot




Date: 17.AUG.2013 10:03:13

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 10:03:56

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 10:04:16



Test Mode :	802.11n HT20	Temperature :	20~23°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~46%
Test Channel :	06	Test Engineer :	Neil Zhu


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 17.AUG.2013 10:07:47

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2013 10:08:27

Spurious Emission 2GHz~25GHz




Date: 17.AUG.2013 10:08:47




Test Mode :	802.11n HT20	Temperature :	20~23°C
Test Band :	2.4GHz High	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Neil Zhu

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.


3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
 For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100.00	-	-	10Hz
802.11g	94.931	2.06	0.485	1KHz
2.4GHz 802.11n HT20	94.488	1.92	0.521	1KHz



802.11b Duty Cycle




Date: 15.AUG.2013 11:00:57

Note:

The total loss is 15.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



802.11g Duty Cycle




Date: 15.AUG.2013 11:04:47

Note:

The total loss is 15.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



2.4GHz 802.11n HT20 Duty Cycle




Date: 15.AUG.2013 11:12:22

Note:


The total loss is 15.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2368.86	50.86	-23.14	74	45.57	32.83	3.16	30.7	100	360	Peak
2387.13	36.5	-17.5	54	31.15	32.86	3.17	30.68	100	360	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2386.68	50.79	-23.21	74	45.44	32.86	3.17	30.68	100	0	Peak
2385.96	36.7	-17.3	54	31.35	32.86	3.17	30.68	100	0	Average

Test Mode :	802.11b	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2487.73	50.43	-23.57	74	44.74	33.05	3.23	30.59	100	0	Peak
2488.54	37.36	-16.64	54	31.67	33.05	3.23	30.59	100	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.89	52.71	-21.29	74	47.08	33.01	3.22	30.6	168	18	Peak
2484.67	39.93	-14.07	54	34.3	33.01	3.22	30.6	168	18	Average



Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.29	50.6	-23.4	74	45.25	32.86	3.17	30.68	106	159	Peak
2389.83	37.36	-16.64	54	32.01	32.86	3.17	30.68	106	159	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.74	52.77	-21.23	74	47.42	32.86	3.17	30.68	180	47	Peak
2389.02	37.23	-16.77	54	31.88	32.86	3.17	30.68	180	47	Average

Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.77	54.28	-19.72	74	48.65	33.01	3.22	30.6	189	353	Peak
2496.64	36.39	-17.61	54	30.7	33.05	3.23	30.59	189	353	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.62	54.95	-19.05	74	49.32	33.01	3.22	30.6	125	96	Peak
2483.56	36.87	-17.13	54	31.24	33.01	3.22	30.6	124	96	Average



Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2373.72	50.14	-23.86	74	44.85	32.83	3.16	30.7	100	0	Peak
2389.47	37.26	-16.74	54	31.91	32.86	3.17	30.68	100	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.47	50.97	-23.03	74	45.62	32.86	3.17	30.68	179	30	Peak
2385.6	37.56	-16.44	54	32.21	32.86	3.17	30.68	179	30	Average

Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	53.59	-20.41	74	47.96	33.01	3.22	30.6	157	360	Peak
2485.18	37.71	-16.29	54	32.08	33.01	3.22	30.6	157	360	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2485.81	57.45	-16.55	74	51.82	33.01	3.22	30.6	173	59	Peak
2484.76	37.83	-16.17	54	32.2	33.01	3.22	30.6	173	59	Average

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	<ol style="list-style-type: none"> 1. 2412 MHz is fundamental signal which can be ignored. 2. 7236 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. For example, 89.52dBμV/m - 20dB = 69.52dBμV/m. 3. Average measurement was not performed if peak level went lower than the average limit. 		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	89.52	-	-	84.11	32.89	3.18	30.66	194	0	Peak
2412	84.62	-	-	79.21	32.89	3.18	30.66	194	0	Average
4824	49.88	-24.12	74	39.45	35.17	4.58	29.32	100	125	Peak
7236	50.36	-19.16	69.52	38.71	36.18	5.62	30.15	100	36	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. 7236 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	95.09	-	-	89.68	32.89	3.18	30.66	200	348	Peak
2412	90.2	-	-	84.79	32.89	3.18	30.66	200	348	Average
4824	50.43	-23.57	74	40	35.17	4.58	29.32	100	235	Peak
7236	49.15	-25.94	75.09	37.5	36.18	5.62	30.15	100	236	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	90.82	-	-	85.3	32.95	3.2	30.63	158	0	Peak
2437	85.57	-	-	80.05	32.95	3.2	30.63	158	0	Average
4874	49.02	-24.98	74	38.56	35.18	4.6	29.32	100	126	Peak
7312	48.48	-25.52	74	36.82	36.2	5.64	30.18	100	25	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	94.42	-	-	88.9	32.95	3.2	30.63	173	22	Peak
2437	89.43	-	-	83.91	32.95	3.2	30.63	173	22	Average
4874	50.18	-23.82	74	39.72	35.18	4.6	29.32	100	45	Peak
7312	47.53	-26.47	74	35.87	36.2	5.64	30.18	100	126	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	19.72	-20.28	40	35.77	18	-0.48	33.57	-	-	Peak
112.45	21.22	-22.28	43.5	42.04	11.8	0.99	33.61	-	-	Peak
170.65	26.76	-16.74	43.5	49.99	9.14	1.2	33.57	-	-	Peak
382.11	25.24	-20.76	46	41.26	15.53	1.78	33.33	-	-	Peak
423.82	24.14	-21.86	46	39.38	16.14	1.88	33.26	-	-	Peak
939.86	31.35	-14.65	46	40.29	20.69	2.81	32.44	100	26	Peak
2462	91.9	-	-	86.33	32.98	3.21	30.62	100	360	Peak
2462	87.45	-	-	81.88	32.98	3.21	30.62	100	360	Average
4924	50.57	-23.43	74	40.08	35.19	4.61	29.31	100	263	Peak
7386	47.92	-26.08	74	36.24	36.24	5.66	30.22	100	245	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
50.37	29.08	-10.92	40	54.6	7.4	0.66	33.58	100	13	Peak
172.59	26.22	-17.28	43.5	49.57	9.01	1.21	33.57	-	-	Peak
466.5	27.17	-18.83	46	41.83	16.55	1.97	33.18	-	-	Peak
509.18	30.02	-15.98	46	43.73	17.38	2.02	33.11	-	-	Peak
593.57	29.73	-16.27	46	41.87	18.59	2.23	32.96	-	-	Peak
946.65	32.12	-13.88	46	41.03	20.72	2.81	32.44	-	-	Peak
2462	95.55	-	-	89.98	32.98	3.21	30.62	196	76	Peak
2462	86.02	-	-	80.45	32.98	3.21	30.62	196	76	Average
4924	50.67	-23.33	74	40.18	35.19	4.61	29.31	100	124	Peak
7386	48.61	-25.39	74	36.93	36.24	5.66	30.22	100	45	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. 7236 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	93.51	-	-	88.1	32.89	3.18	30.66	106	161	Peak
2412	81.35	-	-	75.94	32.89	3.18	30.66	106	161	Average
4824	48.97	-25.03	74	38.54	35.17	4.58	29.32	100	26	Peak
7236	49.97	-23.54	73.51	38.32	36.18	5.62	30.15	100	36	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. 7236 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	95.52	-	-	90.11	32.89	3.18	30.66	167	45	Peak
2412	86.7	-	-	81.29	32.89	3.18	30.66	167	45	Average
4824	49.24	-24.76	74	38.81	35.17	4.58	29.32	100	26	Peak
7236	48.59	-26.93	75.52	36.94	36.18	5.62	30.15	100	58	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	91.21	-	-	85.69	32.95	3.2	30.63	100	0	Peak
2437	79.53	-	-	74.01	32.95	3.2	30.63	100	0	Average
4874	49.69	-24.31	74	39.23	35.18	4.6	29.32	100	45	Peak
7312	49.5	-24.5	74	37.84	36.2	5.64	30.18	100	123	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	96.52	-	-	91	32.95	3.2	30.63	177	31	Peak
2437	84.94	-	-	79.42	32.95	3.2	30.63	177	31	Average
4874	48.98	-25.02	74	38.52	35.18	4.6	29.32	100	36	Peak
7312	49.98	-24.02	74	38.32	36.2	5.64	30.18	100	98	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	91.11	-	-	85.54	32.98	3.21	30.62	100	356	Peak
2462	82.1	-	-	76.53	32.98	3.21	30.62	100	356	Average
4924	50.27	-23.73	74	39.78	35.19	4.61	29.31	100	254	Peak
7386	48.76	-25.24	74	37.08	36.24	5.66	30.22	100	123	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	97.53	-	-	91.96	32.98	3.21	30.62	100	96	Peak
2462	82.57	-	-	77	32.98	3.21	30.62	100	96	Average
4924	49.81	-24.19	74	39.32	35.19	4.61	29.31	100	34	Peak
7386	48.88	-25.12	74	37.2	36.24	5.66	30.22	100	46	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. 7236 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	89.31	-	-	83.9	32.89	3.18	30.66	156	0	Peak
2412	75.18	-	-	69.77	32.89	3.18	30.66	156	0	Average
4824	49.55	-24.45	74	39.12	35.17	4.58	29.32	100	25	Peak
7236	47.27	-22.04	69.31	35.62	36.18	5.62	30.15	125	30	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. 7236 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	94.48	-	-	89.07	32.89	3.18	30.66	144	10	Peak
2412	84.05	-	-	78.64	32.89	3.18	30.66	144	10	Average
4824	49.45	-24.55	74	39.02	35.17	4.58	29.32	142	100	Peak
7236	48.24	-26.24	74.48	36.59	36.18	5.62	30.15	156	135	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	91.07	-	-	85.55	32.95	3.2	30.63	129	0	Peak
2437	79.32	-	-	73.8	32.95	3.2	30.63	129	0	Average
4874	47.36	-26.64	74	36.9	35.18	4.6	29.32	100	224	Peak
7311	48.18	-25.82	74	36.52	36.2	5.64	30.18	110	135	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	93.65	-	-	88.13	32.95	3.2	30.63	178	51	Peak
2437	81.6	-	-	76.08	32.95	3.2	30.63	178	51	Average
4874	49.99	-24.01	74	39.53	35.18	4.6	29.32	100	125	Peak
7311	48.31	-25.69	74	36.65	36.2	5.64	30.18	100	325	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	90.24	-	-	84.67	32.98	3.21	30.62	100	360	Peak
2462	80.57	-	-	75	32.98	3.21	30.62	100	360	Average
4924	49.51	-24.49	74	39.02	35.19	4.61	29.31	100	200	Peak
7386	48.66	-25.34	74	36.98	36.24	5.66	30.22	100	360	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	94.73	-	-	89.16	32.98	3.21	30.62	101	76	Peak
2462	81.54	-	-	75.97	32.98	3.21	30.62	101	76	Average
4924	49.06	-24.94	74	38.57	35.19	4.61	29.31	100	250	Peak
7386	48.59	-25.41	74	36.91	36.24	5.66	30.22	100	45	Peak

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Harry Tang	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		




Site : C001-KS
 Condition: FCC PART15C LISN-L20130306 LINE

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	39.05	-26.91	65.96	26.39	1.94	10.72	QP
2	0.15	30.15	-25.81	55.96	17.49	1.94	10.72	Average
3	0.20	26.11	-27.60	53.71	14.51	1.02	10.58	Average
4	0.20	33.41	-30.30	63.71	21.81	1.02	10.58	QP
5	0.39	27.53	-20.55	48.08	16.90	0.34	10.29	Average
6	0.39	36.33	-21.75	58.08	25.70	0.34	10.29	QP
7	0.45	32.18	-24.71	56.89	21.66	0.25	10.27	QP
8	0.45	24.32	-22.57	46.89	13.80	0.25	10.27	Average
9	1.25	19.98	-26.02	46.00	9.70	0.10	10.18	Average
10	1.25	27.18	-28.82	56.00	16.90	0.10	10.18	QP
11	5.71	24.78	-25.22	50.00	14.30	0.20	10.28	Average
12	5.71	32.08	-27.92	60.00	21.60	0.20	10.28	QP



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Harry Tang	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		



Site : C001-KS
 Condition: FCC PART15C LISN-N20130306 NEUTRAL

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	34.97	-30.90	65.87	22.40	1.87	10.70	QP
2	0.15	27.17	-28.70	55.87	14.60	1.87	10.70	Average
3	0.28	32.46	-28.44	60.90	21.20	0.82	10.44	QP
4	0.28	24.46	-26.44	50.90	13.20	0.82	10.44	Average
5	0.39	30.90	-17.13	48.03	20.19	0.42	10.29	Average
6	0.39	40.10	-17.93	58.03	29.39	0.42	10.29	QP
7	0.45	37.02	-19.87	56.89	26.41	0.34	10.27	QP
8	0.45	28.12	-18.77	46.89	17.51	0.34	10.27	Average
9	0.80	32.27	-23.73	56.00	21.90	0.17	10.20	QP
10	0.80	23.77	-22.23	46.00	13.40	0.17	10.20	Average
11	2.41	31.81	-24.19	56.00	21.50	0.11	10.20	QP
12	2.41	23.11	-22.89	46.00	12.80	0.11	10.20	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

Non-standard antenna connector is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Aug. 17, 2013~ Sep. 11, 2013	Dec. 28, 2013	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	N/A	Feb. 28, 2013	Aug. 17, 2013~ Sep. 11, 2013	Feb. 27, 2014	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	N/A	Feb. 28, 2013	Aug. 17, 2013~ Sep. 11, 2013	Feb. 27, 2014	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Aug. 15, 2013~ Aug. 28, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 23, 2013	Aug. 15, 2013~ Aug. 28, 2013	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Aug. 15, 2013~ Aug. 28, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 22, 2012	Aug. 15, 2013~ Aug. 28, 2013	Oct. 21, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Aug. 15, 2013~ Aug. 28, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	N/A	Aug. 15, 2013~ Aug. 28, 2013	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	N/A	Aug. 15, 2013~ Aug. 28, 2013	N/A	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Aug. 15, 2013~ Aug. 28, 2013	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Aug. 15, 2013~ Aug. 28, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 07, 2012	Aug. 15, 2013~ Aug. 28, 2013	Nov. 06, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Aug. 15, 2013~ Aug. 28, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	May 23, 2013	Aug. 28, 2013	May 22, 2014	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 29, 2012	Aug. 28, 2013	Dec. 28, 2013	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	60105	9kHz~30MHz	Dec. 29, 2012	Aug. 28, 2013	Dec. 28, 2013	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	N/A	Nov. 15, 2012	Aug. 28, 2013	Nov. 14, 2013	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------