

# FCC Test Report

**Equipment** : Tablet PC  
**Brand Name** : DELL  
**Regulatory model name (RMN)** : T03H  
**Regulatory type name (RTN)** : T03H001  
**FCC ID** : E2K-T03H001  
**Standard** : 47 CFR FCC Part 15.225  
**Operating Band** : 13.110 – 14.010 MHz (channel freq. 13.56 MHz)  
**FCC Classification** : DXX  
**Applicant** : Dell Inc.  
**Manufacturer** : One Dell Way, Round Rock, Texas 78682, USA

The product sample received on Jun. 01, 2015 and completely tested on Jun. 12, 2015. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

  
Kevin Liang / Assistant Manager





## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Accessories and Support Equipment .....	6
1.3	Testing Applied Standards .....	6
1.4	Testing Location Information .....	6
1.5	Measurement Uncertainty .....	7
<b>2</b>	<b>TEST CONFIGURATION OF EUT.....</b>	<b>8</b>
2.1	The Worst Case Modulation Configuration .....	8
2.2	Test Channel Frequencies Configuration.....	8
2.3	The Worst Case Measurement Configuration.....	9
2.4	Test Setup Diagram .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULT .....</b>	<b>12</b>
3.1	AC Power-line Conducted Emissions .....	12
3.2	Emission Bandwidth .....	16
3.3	Field Strength of Fundamental Emissions and Spectrum Mask .....	18
3.4	Transmitter Radiated Unwanted Emissions .....	20
3.5	Frequency Stability.....	30
<b>4</b>	<b>TEST EQUIPMENT AND CALIBRATION DATA .....</b>	<b>32</b>
<b>APPENDIX A. TEST PHOTOS</b>		
<b>APPENDIX B. PHOTOGRAPHS OF EUT</b>		
<b>APPENDIX C. DISTANCE FACTOR CALCULATION</b>		

## Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 13.56MHz 50.10 (Margin 9.90dB) - QP 49.77 (Margin 0.23dB) - AV	FCC 15.207	Complied
3.2	15.215(c)	Emission Bandwidth	20dB Bandwidth: 2.72 [kHz] F <sub>L</sub> :13.55836 MHz F <sub>H</sub> :13.56108 MHz	Fall in band F <sub>L</sub> ≥ 13.553 MHz F <sub>H</sub> ≤ 13.567 MHz	Complied
3.3	15.225 (a)~(d)	Field Strength of Fundamental Emissions and Spectrum Mask	Fundamental Emissions peak:60.69 dBuV/m at 3m Device complies with spectrum mask – refer to test data	124 dBuV/m at 3	Complied
3.4	15.225(d)	Transmitter Radiated Unwanted Emissions	[dBuV/m at 3m]: 31.940MHz 33.88 (Margin 6.12dB) - Peak	FCC 15.209	Complied
3.5	15.225(e)	Frequency Stability	22.12 ppm	± 0.01% (100ppm)	Complied



# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

RF General Information				
Frequency Range	Modulation	Ch. Frequency (MHz)	Channel Number	Field Strength (dBuV/m)
13.110 – 14.010 MHz	ISO 14443-2 (ASK)	13.56	1	60.69
Note 1: Field strength performed peak level at 3m.				

### 1.1.2 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	External antenna (dedicated antennas)

### 1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input checked="" type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:
<input type="checkbox"/>	Other:

### 1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Voltage Duty Factor [dB] – (20 log 1/x)
<input checked="" type="checkbox"/> 100%	0

### 1.1.5 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> From Host System	<input checked="" type="checkbox"/> External AC adapter	<input checked="" type="checkbox"/> Li-ion Battery

## 1.2 Accessories and Support Equipment

Accessories Information				
AC Adapter	Brand Name	DELL	Model Name	HK45NM140
	Power Rating	I/P: 100 - 240Vac, 1.3A, O/P: 19.5Vdc, 2.31A		
Li-ion Battery	Brand Name	DELL	Model Name	7XNTR
	Power Rating	7.4Vdc, 26Wh		
Wifi/BT Module	Brand Name	Intel	Model Name	7265NGW

Reminder: Regarding to more detail and other information, please refer to user manual.

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Identity Badge	-	-	-

## 1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2009
- ◆ ANSI C63.10-2013 (KDB requirement)
- ◆ FCC KDB 174176
- ◆ FCC KDB 937606

## 1.4 Testing Location Information

Testing Location					
<input checked="" type="checkbox"/>	HWA YA	ADD	: No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.		
		TEL	: 886-3-327-3456	FAX	: 886-3-327-0973
<b>Test Site Registration Number: FCC 636805</b>					
Test Condition	Test Site No.	Test Engineer	Test Environment		
AC Conduction	CO04-HY	Zeus	22°C / 62%		
RF Conducted	TH06-HY	Rory	22.4°C / 61%		
Radiated Emission	03CH03-HY	Daniel	22.5°C / 56%		



### 1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty		
Test Item		Uncertainty
AC power-line conducted emissions		±2.2 dB
Emission bandwidth		±1.4 %
Unwanted emissions, conducted	9 – 150 kHz	±0.3 dB
	0.15 – 30 MHz	±0.4 dB
	30 – 1000 MHz	±0.5 dB
All emissions, radiated	9 – 150 kHz	±2.4 dB
	0.15 – 30 MHz	±2.2 dB
	30 – 1000 MHz	±2.5 dB
Temperature		±0.8 °C
Humidity		±3 %
DC and low frequency voltages		±3 %
Time		±1.4 %
Duty Cycle		±1.4 %



## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration

Modulation Used for Conformance Testing	
Modulation Mode	Field Strength (dBuV/m at 3 m)
ASK	60.69




### 2.2 Test Channel Frequencies Configuration

Test Channel Frequencies Configuration	
Modulation Mode	Test Channel Frequencies (MHz)
ASK	13.56




### 2.3 The Worst Case Measurement Configuration


The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
<b>Operating Mode</b>	Operating Mode Description
1	EUT with AC Adapter

The Worst Case Mode for Following Conformance Tests			
<b>Tests Item</b>	Emission Bandwidth, Field Strength of Fundamental Emissions Spectrum Mask, Transmitter Radiated Unwanted Emissions Frequency Stability		
<b>Test Condition</b>	Radiated measurement		
<b>User Position</b>	<input type="checkbox"/> EUT will be placed in fixed position.		
	<input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two orthogonal planes.		
	<input checked="" type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed three orthogonal planes.		
<b>Operating Mode</b>	1. EUT Built in NFC A type		
	2. EUT Built in NFC B type		
	3. EUT Built in NFC F type		
	4. EUT Built in NFC V type		
	The Pretest Mode 3 is the worst case with the following test modes.		
	1. EUT with AC Adapter		
<b>Modulation Mode</b>	ASK		
<b>Orthogonal Planes of EUT</b>	<b>X Plane</b>	<b>Y Plane</b>	<b>Z Plane</b>
			
<b>Worst Planes of EUT</b>		V	


## 2.4 Test Setup Diagram



Test Setup Diagram - Radiated 9kHz~30MHz Test



Test Setup Diagram - Radiated 30MHz~1GHz Test



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.
<input checked="" type="checkbox"/>	If AC conducted emissions fall in operating band, then following below test method confirm final result.
<input type="checkbox"/>	Accept measurements done with a suitable dummy load replacing the antenna under the following conditions: (1) Perform the AC line conducted tests with the antenna connected to determine compliance with FCC 15.207 limits outside the transmitter's fundamental emission band; (2) Retest with a dummy load to determine compliance with FCC 15.207 limits within the transmitter's fundamental emission band.
<input checked="" type="checkbox"/>	For a device with a permanent antenna operating at or below 30 MHz, accept measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) Perform the AC line conducted tests with the permanent antenna to determine compliance with the FCC 15.207 limits outside the transmitter's fundamental emission band; (2) Retest with a dummy load in lieu of the permanent antenna to determine compliance with the FCC 15.207 limits within the transmitter's fundamental emission band.

### 3.1.4 Test Setup






3.1.5 Test Result of AC Power-line Conducted Emissions





AC Power-line Conducted Emissions Result			
Operating Mode	1	Power Phase	Line
Operating Function	EUT with AC Adapter		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1540270	39.11	-16.67	55.78	38.71	0.05	0.35	Average
2	0.1540270	54.97	-10.81	65.78	54.57	0.05	0.35	QP
3	0.1694400	54.71	-10.28	64.99	54.25	0.05	0.41	QP
4	0.1694400	35.98	-19.01	54.99	35.52	0.05	0.41	Average
5	0.1965370	48.48	-15.28	63.76	47.93	0.06	0.49	QP
6	0.1965370	31.83	-21.93	53.76	31.28	0.06	0.49	Average
7	0.2416480	31.86	-20.18	52.04	31.27	0.06	0.53	Average
8	0.2416480	43.72	-18.32	62.04	43.13	0.06	0.53	QP
9	0.5551950	27.94	-18.06	46.00	27.20	0.07	0.67	Average
10	0.5551950	35.11	-20.89	56.00	34.37	0.07	0.67	QP
11	2.240	24.72	-31.28	56.00	23.84	0.10	0.78	QP
12	2.240	15.78	-30.22	46.00	14.90	0.10	0.78	Average
13	13.560	50.71	-9.29	60.00	49.62	0.29	0.80	QP
14	13.560	49.71	-0.29	50.00	48.62	0.29	0.80	Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)  
 Note 3: Frequency 13.56 MHz is NFC signal.

### 3.2 Emission Bandwidth

#### 3.2.1 Emission Bandwidth Limit

20dB Bandwidth Limit	
<input checked="" type="checkbox"/>	Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band (13.110 – 14.010 MHz).


#### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	For the emission bandwidth refer ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/>	For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.

#### 3.2.4 Test Setup








3.2.5 Test Result of Emission Bandwidth

Occupied Channel Bandwidth Result					
Modulation Mode	Frequency (MHz)	20dB Bandwidth (kHz)	F <sub>L</sub> at 20dB BW (MHz)	F <sub>H</sub> at 20dB BW (MHz)	99% Bandwidth (kHz)
ASK	13.56	2.72	13.55836	13.56108	2.32
Limit		N/A	13.553	13.567	N/A
Result		Complied			



### 3.3 Field Strength of Fundamental Emissions and Spectrum Mask

#### 3.3.1 Field Strength of Fundamental Emissions and Spectrum Mask Limit

Field Strength of Fundamental Emissions					
Emissions	(uV/m)@30m	(dBuV/m)@30m	(dBuV/m)@10m	(dBuV/m)@3m	(dBuV/m)@1m
Fundamental	15848	84.0	103.1	124.0	143.1
Quasi peak measurement of the fundamental.					

Spectrum Mask					
Freq. of Emission (MHz)	(uV/m)@30m	(dBuV/m)@30m	(dBuV/m)@10m	(dBuV/m)@3m	(dBuV/m)@1m
1.705~13.110	30	29.5	48.6	69.5	88.6
13.110~13.410	106	40.5	59.6	80.5	99.6
13.410~13.553	334	50.5	69.6	90.5	109.6
13.553~13.567	15848	84.0	103.1	124.0	143.1
13.567~13.710	334	50.5	69.6	90.5	109.6
13.710~14.010	106	40.5	59.6	80.5	99.6
14.010~30.000	30	29.5	48.6	69.5	88.6

#### 3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

#### 3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/>	At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the requirements; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be following below methods.
<input type="checkbox"/>	The results shall be extrapolated to the specified distance by making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor.
<input checked="" type="checkbox"/>	The results shall be by using the square of an inverse linear distance extrapolation factor (40 dB/decade).
<input checked="" type="checkbox"/>	For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.

Note : The field strength calculation with different distance refer to appendix C.


### 3.3.4 Test Setup



### 3.3.5 Test Result of Field Strength of Fundamental Emissions and Spectrum Mask

Field Strength of Fundamental Emissions Result					
Modulation Mode	Frequency (MHz)	Fundamental (dBuV/m)@3m	Polarization	Margin (dB)	Limit (dBuV/m)@3m
ASK	13.56	60.69	H	-63.31	124.00
<b>Result</b>		<b>Complied</b>			

Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal).



### 3.4 Transmitter Radiated Unwanted Emissions

#### 3.4.1 Transmitter Radiated Unwanted Emissions Limit

Transmitter Radiated Unwanted Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

#### 3.4.2 Measuring Instruments



Refer a test equipment and calibration data table in this test report.




3.4.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/>	At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the requirements; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be following below methods.
<input type="checkbox"/>	The results shall be extrapolated to the specified distance by making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor.
<input checked="" type="checkbox"/>	The results shall be by using the square of an inverse linear distance extrapolation factor (40 dB/decade).
<input checked="" type="checkbox"/>	For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.
<input checked="" type="checkbox"/>	The any unwanted emissions level shall not exceed the fundamental emission level.
<input checked="" type="checkbox"/>	All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

### 3.4.4 Test Setup




3.4.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)





Transmitter Radiated Unwanted Emissions (150 kHz – 2 MHz)

Modulation Mode	ASK	Polarization	H
Operating Mode	1		



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	0.934	45.28	-22.92	68.20	24.39	20.79	0.10	0.00	Peak
2	1.538	45.94	-17.93	63.87	25.23	20.61	0.10	0.00	Peak
3	1.575	46.23	-17.43	63.66	25.53	20.60	0.10	0.00	Peak


Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.





Transmitter Radiated Unwanted Emissions (2 MHz – 8 MHz)

Modulation Mode	ASK	Polarization	H
Operating Mode	1		




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	2.468	51.96	-17.58	69.54	31.52	20.29	0.15	0.00	Peak
2	3.284	40.98	-28.56	69.54	20.58	20.21	0.19	0.00	Peak
3	3.884	37.57	-31.97	69.54	16.88	20.45	0.24	0.00	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.



Transmitter Radiated Unwanted Emissions (8 MHz – 25 MHz)

Modulation Mode	ASK	Polarization	H
Operating Mode	1		




	Freq	Level	Over Limit	Limit	ReadAntenna	Cable	Preamp	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8.170	39.50	-30.04	69.54	18.01	21.15	0.34	0.00 Peak
2	13.746	35.92	-33.62	69.54	14.07	21.37	0.48	0.00 Peak
3	18.030	34.13	-35.41	69.54	12.10	21.46	0.57	0.00 Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.




Transmitter Radiated Unwanted Emissions (25 MHz – 30 MHz)			
Modulation Mode	ASK	Polarization	H
Operating Mode	1		



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	26.390	32.84	-36.70	69.54	10.52	21.63	0.69	0.00	Peak
2	28.750	32.93	-36.61	69.54	10.54	21.67	0.72	0.00	Peak
3	29.550	33.67	-35.87	69.54	11.25	21.69	0.73	0.00	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.


3.4.6 Transmitter Radiated Unwanted Emissions (Above 30MHz)





Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation Mode	ASK	Polarization	H
Operating Mode	1		



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	30.000	30.53	-9.47	40.00	40.00	17.67	0.75	27.89	Peak
2	90.140	23.09	-20.41	43.50	40.88	8.59	1.34	27.72	Peak
3	187.140	27.11	-16.39	43.50	43.76	8.79	1.97	27.41	Peak
4	340.400	22.70	-23.30	46.00	33.82	13.56	2.74	27.42	Peak
5	749.740	28.26	-17.74	46.00	32.89	19.36	4.16	28.15	Peak
6	800.180	27.08	-18.92	46.00	31.28	19.48	4.33	28.01	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.

### 3.5 Frequency Stability

#### 3.5.1 Frequency Stability Limit

Frequency Stability Limit	
<input checked="" type="checkbox"/>	Carrier frequency stability shall be maintained to $\pm 0.01\%$ ( $\pm 100$ ppm).


#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.8 for frequency stability tests
<input checked="" type="checkbox"/>	Frequency stability with respect to ambient temperature
<input checked="" type="checkbox"/>	Frequency stability when varying supply voltage
<input checked="" type="checkbox"/>	For conducted measurement.
<input type="checkbox"/>	For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

#### 3.5.4 Test Setup





3.5.5 Test Result of Frequency Stability

Test date: Jun. 08, 2015		Frequency Stability Result
Power Level	1	Frequency Stability Max. Deviation Limit < 100 ppm
Condition	Freq. (MHz)	10 min
T <sub>20°C</sub> V <sub>max</sub>	13.55977	-16.96
T <sub>20°C</sub> V <sub>min</sub>	13.55979	-15.49
T <sub>50°C</sub> V <sub>nom</sub>	13.55970	-22.12
T <sub>40°C</sub> V <sub>nom</sub>	13.55974	-19.17
T <sub>30°C</sub> V <sub>nom</sub>	13.55974	-19.17
T <sub>20°C</sub> V <sub>nom</sub>	13.55978	-16.22
T <sub>10°C</sub> V <sub>nom</sub>	13.55980	-14.75
T <sub>0°C</sub> V <sub>nom</sub>	13.55982	-13.27
T <sub>-10°C</sub> V <sub>nom</sub>	13.55984	-11.80
T <sub>-20°C</sub> V <sub>nom</sub>	13.55984	-11.80
<b>Result</b>		<b>Complied</b>
Note 1: Measure at 85 % [V <sub>min</sub> ] and 115 % [V <sub>max</sub> ] of the nominal voltage [V <sub>nom</sub> ]. The nominal voltage refer test report clause 1.1.2 for EUT operational condition.		



## 4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Apr. 15, 2015	AC Conduction
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 22, 2015	AC Conduction
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	Oct. 31, 2014	AC Conduction
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	AC Conduction

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	G.W	APS-9102	EL920581	AC 0V ~ 300V	Jul. 15, 2014	RF Conducted
Spectrum Analyzer	R&S	FSP 40	100305	9KHz~40GHz	Jul. 14, 2014	RF Conducted
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	-20 ~ 100°C	Nov. 25, 2014	RF Conducted

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9kHz ~ 40GHz	Oct. 02, 2014	Radiation Emission
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	May 03, 2015	Radiation Emission
Amplifier	Agilent	8447D	2944A11149	100kHz ~ 1.3GHz	Jul. 22, 2014	Radiation Emission
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Nov. 08, 2014	Radiation Emission
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Sep. 20, 2014	Radiation Emission
Turn Table	Chaintek Instruments	3000	MF7802058	0~ 360 degree	N/A	Radiation Emission
Antenna Mast	MF	MF7802	MF780208205	1 ~ 4 m	N/A	Radiation Emission

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz~30 MHz	Feb. 02, 2015	Radiation Emission

Note: Calibration Interval of instruments listed above is two years.